NOT MEASUREMENT SENSITIVE


MIL-B-3476/26B
10 May 1991
SUPERSEDING
MIL-B-3476/26A
30 March 1973

MILITARY SPECIFICATION SHEET

BRASSARD; SECURITY POLICE, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3476.



MATERIAL:
BASE: Facing cloth
LETTERING: Felt

COLOR:
BASE: Ultramarine blue (Cable 65010)
LETTERING: Silver gray (Cable 65008)

CONSTRUCTION DETAILS:
1. Lettering shall be appliqued to the base in the position shown using Stitch Type 301 having 16 stitches to the inch.
2. The brassard shall have a 3/8 inch hem on all sides. Hemming shall be accomplished using Stitch Type EFa-1 with 12 stitches to the inch.
3. Thread for hemming and appliqueing shall conform to Type IC2, 3 Ply, Ticket No. A of V-T-276. The color of the thread for hemming shall be ultramarine blue conforming to Cable No. 67118. The color of the thread for appliqueing shall be silver gray conforming to Cable No. 67137.
4. Base and letters shall be cut from a single ply of the material specified.
5. Unless otherwise indicated, all letters shall be 3/4 inch wide with 1/4 inch spacing between letters.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activities:
Air Force - 82
DLA - CT

(Project No. 8455-0119)

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:58Z
Check the source to verify that this is the current version before use.