[METRIC]

A-A-2810A
December 27, 1996
SUPERSEDING
A-A-2810, dated
February 1, 1993

COMMERCIAL ITEM DESCRIPTION

BINDER, LOOSE-LEAF, COATED CLOTH BOUND, STIFF COVERS (FOR TABULATING MACHINE PAPER AND ACCESSORIES).

The General Services Administration has authorized the use of this commercial item description.

1. Scope. This commercial item description covers requirements for flexible-post binders for containing unburst marginal punched tabulating machine paper and accessories. Covers are separable and have a binding mechanism with locking devices for containment of contents.

2. Classification. The binders shall be of the following classes and styles, as specified (see 8.1.2).

Class 1 - Top and bottom loading
Class 2 - Top loading.

Style A - Inside locking mechanism.
Style B - Outside locking mechanism.

3. SALIENT CHARACTERISTICS:

3.1. Design. Binders shall be designed for containing continuous, unburst, marginal punched tabulating sheets by means of flexible posts secured by a locking device in the binding mechanism. Binders, and Sheets filed in all binders, shall lay flat so there will be no hidden entries when in use. Binders shall be designed for satisfactory performance, including loading and unloading of binders and for proper retention and performance of posts. Sheet size, capacity and color of the binder shall be as specified (see 8.1.2). The first dimension cited for the sheet size shall be the binding side. Not less than two flexible posts shall be furnished with each binder, and shall be of sufficient length to meet the capacity requirements specified.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document, should be sent to: General Services Administration, Federal Supply Service, 26 Federal Plaza, New York N.Y. 10278 ATTN: Engineering Branch (2FYEE).

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.

Class 1. Class 1 binders shall be designed for loading or withdrawal of sheets from the top and bottom of the binder.

Class 2. Class 2 binders shall be designed for loading or withdrawal of the sheets from the top of the binder only.

Style A. Style A binders shall be designed so that the cover stubs turn into the binder and have an inside locking mechanism.

Style B. Style B binder shall be of a mechanical hinge, piano style, with an outside locking mechanism in the top hinge plate, and be designed for loading from top only.

3.2. Construction (general). Each binder shall consist of two separable covers, hinged to cover stubs or plates, as applicable, for containment of a binding mechanism. Construction shall be such that no parts of the binders will mar smooth surfaces. Metal hinge components shall be properly secured and aligned. Hinges shall be recessed into plates in accordance with normal commercial practice, and plates and covers shall lay flat on smooth, even surfaces. Covers shall have round corners on the side of the binder, parallel to the binding side.

3.2.1. Covers. Covers shall be paperboard, as specified in 3.3.3, securely glued over the entire area of contact with the covers. The coated-cloth binding for each cover, including hinge and stub, shall be of one-piece construction (without splices), and shall conform to 3.3.1. The binding material shall be carried over the inside surfaces of the covers, except the binding edge, at least 9.5 mm (3/8"). On the binding side, the coated cloth shall extend beyond the edge to fabricate the hinge and fold back on the inside of the binder cover in a manner to completely cover the stub and reinforcing material, overlapping the binding edge of the cover at least 31.8 mm (1-1/4"). The overlap at the top and bottom edges of covers shall extend to overlap the top and bottom edges of the hinges and stubs for the same distance as on the covers. The overlapping binding material shall be secured to the covers and hinge in a manner that the edges are neatly and securely turned in, and there are no frayed or loose ends which will tear or pull out when the binder is in normal use. Each cover hinge shall be glued together and stubs shall be reinforced with black fiberboard, or equivalent, 0.76 ± 0.05 mm (0.030 ± 0.002)" in thickness and the approximate width of the binding mechanism. A paper lining, as specified in 3.3.4, shall be securely glued over the entire area of contact with the inner surfaces of the covers and with the binding material. The lining shall overlap the turned under edges of the binding material.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:26Z
Check the source to verify that this is the currentversion before use.

3.2.2. Style B. Covers shall be paperboard, as specified in 3.3.3, bound with coated cloth as specified in 3.3.1. Binding shall be securely glued over the entire area of contact with the covers. It shall be carried over the inside surfaces of the covers at least 9.5 mm (3/8"). A paper lining, as specified in 3.3.4, shall be securely glued over the entire area of contact with the inner surfaces of the covers and with the binding material. Lining on inside of each cover shall overlap the turned under edge of the binding material, and shall overlap and be secured to each metal hinge plate, attached to the cover, in accordance with standard commercial practice.

3.2.3. Binding Mechanism. Post holes shall be provided in both top and bottom covers to receive and securely retain flexible posts. All binders shall have two post holes spaced on proper centers to utilize sprockets feed holes of the sheet size specified. Requirements for additional post holes (multiple spacing) shall be as specified (see 8.1.5).

3.2.3.1. Class 1, Style A. The binding mechanisms shall consist of two channel bars fabricated from cold-rolled steel 0.46 ± 0.05 mm (0.018 ± 0.002)" in thickness. One channel bar shall be attached to each cover stub by at least three metal rivets or grommets. One rivet or grommet shall be positioned in the center and one near each end of the binding mechanism. The rivets or grommets shall have sufficient upset to permanently secure the channel bars to the cover stub. Each channel bar shall have post holes in the number and with center spacing specified, and shall be fitted with two slide locks to secure the flexible posts. Stops for slide locks shall be provided in each channel bar. The slide locks shall be made of steel or plastic material. Plastic slide locks shall conform to 1-2-1 of ASTM D 1788. Slide locks shall be of sufficient thickness and design to withstand repeated opening and closing. When covers are attached to the binding mechanism, post holes shall be in alignment.

3.2.3.2. Class 2, Style A. The binding mechanism shall be as specified in (a) above except that the bottom channel bar shall be without slide locks and shall have post holes to accept the flexible posts. Alternately, at the option of the manufacturer, a steel bar or bar with post holes to accept the flexible posts may be furnished in place of the bottom channel bar, provided it is equal or greater in thickness to the channel bar specified above.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.

3.2.3.3. Class 2, Style B. The binding mechanism shall be of the hinged type combination of metal and plastic. One part of the hinge shall be permanently attached to each cover and is identified hereinafter as the hinge plate. A second part shall receive the flexible posts and is identified hereinafter as the post housing. The hinge plate and post housing shall be joined by a piano style hinge with a steel pin. The pin shall be fitted in a manner that the pin will not protrude from the hinge or fall out during use. The hinge plate shall be made from cold-rolled steel, not less than 0.84 mm (0.033") in thickness, and shall overlap the inner surface of the respective cover at least 30.16 mm (1-3/16") and the length shall be the designated sheet size with the tolerance of ± 6.4 mm (± 1/4"). Each post housing shall have post holes in the number and with center to center spacing specified, and shall be made of plastic conforming to 1-2-1 of ASTM D 1788. The top cover post housing shall have two sliding or latch type locking devices, one on or near end of the housing to secure flexible posts. The bottom cover post housing shall have post holes to accept the flexible posts. The sliding locking device shall be made of cold-rolled steel, not less than 0.58 mm (0.023") in thickness and of sufficient width to slide over and cover the flexible posts, or plastic material conforming to 1-2-1 of ASTM D 1788. A pull device and a slide stop shall be provided on each sliding locking devices.

3.2.4. Posts. Posts for Class 1 binders (top and bottom loading) shall be nylon or wire fully encased in plastic, at the option of the manufacturer (see 3.2.4.1 & 3.2.4.2). Nylon posts for the Class 1 binder shall have both ends tapered. Nylon posts for the Class 2 binder (top loading) shall be nylon with one end tapered and a slotted head on the opposite end. The diameter of the head shall be larger than that of the post in accordance with good commercial practice. When heads of the posts are recessed in the binder, slot shall be designed and construed in a manner to permit tightening or removal of posts. Tightening or removal of posts shall be interpreted to mean by means of a small screwdriver or other applicable device. Posts shall be flexible and sufficiently stable so as not to loosen in the binding mechanism nor break or take a permanent set when compressed by the locking device(s). Replacement posts shall be furnished, as specified (see 8.1.5).

3.2.4.1. Nylon posts. Nylon posts shall be 3.18 ± 0.10 mm (0.125 ± 0.004)" in diameter, and shall conform to ASTM D 789.

3.2.4.2. Wire posts. The posts shall consist of at least seven strands of No. 22 annealed, galvanized wire encased in plastic in accordance with normal commercial practice. The plastic shall completely encase the wire, including the ends. The posts shall be not less than 2.84 mm (0.112") nor more than 3.30 mm (0.130") in outside diameter.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:26Z
Check the source to verify that this is the current version before use.

3.2.5. Suspension (Hanger) Bars. Suspension (hanger) bars shall be designed for use with binders racks or cabinets. Bars shall be compatible for use with the binder rack or cabinet specified (see 8.1.4).

3.2.6. Label Holder and Label. When specified, a label holder and label shall be provided in accordance with normal commercial practice, except that label holders shall not be of the cellulose nitrate type. Label holders shall be of the size and location on the binder as specified (see 8.1.6). Unless otherwise specified, the label holder shall be built into, or otherwise, securely attached to the binder and shall be nonremovable. The label holder shall be constructed so that the label can be readily inserted, removed and in the manner that the label will be retained and not fall out when binder is in normal use.

3.2.7. Identification Marking. The manufacturer's name or trademark of such known character as to be readily identifiable, shall be permanently marked by any acceptable commercial method on the inside of one cover of the binder. When specified, the words "Property of U.S. Government" shall be included in the marking.

3.3. Materials.

3.3.1. Coated cloth.

3.3.1.1. Base cloth (Binding material). The base cloth, used as binding material, shall be a balanced woven cotton cloth weighing not less than 82.2 grams (2.9 oz) per square yard and shall have not more than 3 percent nonfibrous material.

3.3.1.2. Coating compound. The coating compound shall be virgin plastic formulated from any of the following materials: ethyl cellulose, cellulose acetate, polyvinyl chloride, or polyvinyl chloride-acetate. Plasticizer shall be adequate to provide flexibility for resistance to drying and cracking of the finished coated cloth when binders are in use. The coating shall not flake or crack through to the base cloth. The weight shall not be less than 170.1 grams (6.0 oz) per square yard.

3.3.1.3. Finished coated cloth. The finished coated cloth shall consist of the base cloth and the coating compound. The base cloth shall be evenly and smoothly coated with coating compound on the face side. The finished cloth shall have a minimum breaking strength of 200 Newtons (45 lb_f) in the warp direction, and 178 Newtons (40 lb_f) in the filling direction, when tested in accordance with Fed.Std.191/5100. The weight of the finished cloth shall be not less than 252.3 grams (8.9 oz) per square yard, when tested in accordance with Fed.Std.191/5041. The finished coated cloth shall have a colorfastness to crocking rating of at least "good" when tested in accordance with Fed.Std.191/5651. Unless otherwise specified, the coated cloth shall have a shallow grain finish.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.

3.3.2. Metal components. Metal Surfaces shall be in accordance with good commercial quality for the purpose intended. Exposed metal surfaces shall have a polished finish and shall be corrosion resistant or treated to resist corrosion, except binding mechanisms for Style B binders may be painted. Unless otherwise specified, cold-rolled steel shall have a minimum Rockwell hardness of B40, when tested in accordance with ASTM E 18.

3.3.3. Paperboard. The paperboard shall have a minimum thickness of 3.0 mm (0.120") when tested in accordance with TAPPI T 411, and shall have a minimum bursting strength of 700 points when tested in accordance with TAPPI T 807.

3.3.4. Lining material. The paper lining material for inside faces of covers, when required, shall have a basis weight of not less than 8.88 g/m^2 (60 pounds based on 25" x 38" - 500 sheets), when tested in accordance with TAPPI T 410. The color of the lining shall harmonize with the binding material.

3.4. Workmanship. The binders shall be well finished, clean and all edges shall be smooth. Metal parts of the binders shall be free from burrs and rough or sharp edges. Posts shall be designed and constructed for easy and ready flexing and passage through eyelets and contents of the binder without binding, fraying, spreading, or otherwise being deformed. There shall be no unfinished edges around the label holder and the construction shall be such that the binding material will not tear, fray or pull out under normal use. Binders furnished with label holders shall be designed and fabricated in a manner that the holders will not weaken the structure of the binder nor mar smooth surfaces. The paperboard shall be free from surface lumps, indentation and mechanical imperfections, and be reasonably smooth and flat. The binder shall be free from defects that adversely affect appearance and serviceability or present a hazard to the user.

4. REGULATORY REQUIREMENTS:

4.1 Certification (paperboard). The contractor shall certify that the paperboard used in the manufacture of this item contains a minimum of 80 % Post Consumer Recovered Material (PCRM), in accordance with Code 40 of the Federal Regulations Part 247, Comprehensive Guideline for Procurement of Products Containing Recovered Materials; Final Rule. The Government reserves the right to require proof of such conformance prior to first delivery, and thereafter as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.

5. QUALITY ASSURANCE:

5.1. Product conformance. The product provided shall meet the salient characteristics of this commercial item description, conform to producer's own drawings, specifications, standards, and quality assurance practices and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

6. PACKAGING, PACKING AND MARKING: Packing, packing and marking shall be as specified in the contract or purchase order.

7. REFERENCED DOCUMENTS: The issue of the referenced documents in effect on the date of the solicitation for offers or request for proposals shall be used to determine conformance with the requirements of this Commercial Item Description.

7.1. CFR, Title 40, Code of Federal Regulations, Protection of the Environment, Part 247. Copies may be purchased with a VISA, Master Card or prepaid check through: Government Printing Office, Washington DC; Phone 202-783-3238. When ordering ask for: Title 40, Parts 190-250; Stock Number: 869-013-00-146-0.

7.2. Federal Standards & Specifications may be obtained from the General Services Administration Specifications Section (3FBO-W) in Suite 8100 at L'Enfant Plaza, SW, Washington DC 20407.

7.3. American Society for Testing and Materials (ASTM) methods, can be obtained from: American Society for Testing and Materials; 1916 Race Street; Philadelphia, PA 19103.

7.4. Technical Association of the Pulp and Paper Industry (TAPPI) methods, can be obtained from: Technical Association of the Pulp and Paper Industry; Technology Park/ Atlanta; P.O. Box 105113; Atlanta, GA 30348.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:26Z
Check the source to verify that this is the current version before use.

8. NOTES.

8.1. Ordering data. Purchasers shall specify the following in the contract or purchase order:

8.1.1. Title, number, and date of this Commercial Item Description.
8.1.2. Class, style, sheet size, capacity and color of the binder.
8.1.3. Specify when paperboard requirements (for cover construction) are other than that specified.
8.1.4. Accessories required. Suspension (hangar bars). When suspension bars are required, include manufacturer and model of rack or cabinet within which binders will be used.
8.1.5. Replacement posts, (if required). Post hole spacing required.
8.1.6. Labels, label holders, label holder's size and location.
8.1.7. Packaging, Packing and Marking required. Any special marking.

8.2. NATIONAL STOCK NUMBER LISTING (NSN'S). The following is a list of nsn's assigned which correspond to this CID. The list may not be indicative of all possible nsn's associated with the CID.

7510-00-735-0732
7510-00-128-0064
7510-00-132-4444

8.3. Item Identification/Reference Part Number System (for cataloging use only)

A-A-2810A 2 A

This example describes a coated cloth bound binder with the inside locking mechanism, designed for loading or withdrawal of sheets from the top.

A-Style A: Inside locking mechanism
B-Style B Outside locking mechanism

1-Class 1: Top and bottom loading
2-Class 2: Top loading

MILITARY INTEREST:

ARMY - GL

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:26Z
Check the source to verify that this is the current version before use.