AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

BRUSHES, DUSTING

This amendment was developed by General Services Administration, Federal Supply Service, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this amendment as a valid exception to Interim Federal Specification H-B-00190a (GSA-FSS), dated August 19, 1966.

PAGE 1

Paragraph 1.2.1: Under line 7, "Class 2 - Horsetail hair." - indent three spaces and insert the following:

A - Compound set.
B - Staple set.

PAGE 2

Paragraph 2.1: Add under "Federal Specifications:"

NN-H-104 - Handles, Wood, Acme Threaded and Circular Tapered End.

PAGE 3

Paragraph 3.4.2.3: Delete and substitute:

3.4.2.3 Staple wire. Staple wire shall be not less than 0.034 inch diameter for types I, II, III, and IV brushes and not less than 0.027 inch diameter for type V brushes. The staple wire shall be corrosion resisting steel wire or steel wire coated to resist corrosion. The wire shall show no evidence of corrosion when tested as specified in 4.3.5.

PAGE 4

Paragraph 3.9.1.2: Delete second sentence and substitute:

"Class 2 brush-filler material shall be staple set in accordance with 3.5.2.1, or compound set in accordance with 3.5.2.2, as specified (see 1.2.1)."

PAGE 5

Paragraph 3.9.2.2: Delete last sentence.

PAGE 6

Paragraph 3.9.2.3: Delete and substitute:

3.9.2.3 Handle hole. In the center of the block there shall be a 3/4-5 Acme thread tapped handle hole which shall be machined to accommodate the type I, size 1, handles specified in NN-H-104. The effective thread depth in the handle hole shall be sufficient to permit the thread shoulder of the handle to be torqued up against the brush block. The depth of the handle hole shall conform to the requirements of table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.

PAGE 6

Table II:

Line 14: In columns 3 and 4, size 1 and 2, respectively, add a tolerance of "+ 0, - 1/8" to the values for depth of handles.

Lines 15 and 16: Delete requirements for diameter of handle in their entirety.

PAGE 8

Table VI:

Line 2: In column 3, delete the tolerance on overall length "± 1/4" and substitute "± 1/2".

Line 16: In column 2, delete the plural unit of measure "ounces" and substitute "ounce".

Last line: In column 3, delete the value for length clear of block "1-1/4" and substitute "1".

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:06Z
Check the source to verify that this is the currenversion before use.