NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/218B
27 September 1996
SUPERSEDING
MIL-L-11484/218A
14 January 1994

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, LENGTH OF SERVICE (10, 20, 30, 40, AND 50 YEARS), CIVILIAN PERSONNEL, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11484 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

DASH NO.
-1: 10 Years
-2: 20 Years
-3: 30 Years
-4: 40 Years with Ruby
-5: 50 Years with Diamond

MATERIAL:
-1: Gilding Metal
-2, -3, -4, -5: Red Brass

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:26Z
Check the source to verify that this is the current version before use.

FINISH:
-1: Oxidized, Relieved, Matte Finish, Polished Highlights

-2: Nickel Plated, Silver Plated, Oxidized, Relieved, Polished Highlights and shall match TIOH Metal Finish Chip Number 15.

-3, -4, -5: Gold Plated, Rose Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 20.

DIMENSIONS:
HEIGHT (Overall): 3/4 inch (1.91 cm) (REF)
WIDTH (Overall): 21/32 inch (1.67 cm) (REF)
THICKNESS (At Thickest Point): 0.075 inch ± 0.005 inch (0.191 cm ± 0.012 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. All stones shall be 3 points and set in the lapel button with a 3 bead setting. The location of the stone shall be centered in the eagle's neck above the words "AIR FORCE" as indicated. The stones shall be synthetic and of the color specified for the corresponding year as indicated.

3. Manufacturer shall add the specified number representing the length of service to the working die in the style and location indicated on TIOH Drawing number A-9-32. Numbers shall be 0.155 inch ± 0.002 inch (0.394 cm ± 0.005 cm) in height.

4. All lapel buttons shall be lacquered.

5. Attaching devise shall be prong with pick and flat ball type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

6. Each lapel button shall be mounted and centered on a polyethylene pad and placed in a rigid hinged plastic box having a transparent lid and opaque bottom section. The box shall have two plastic hinges and catches and shall be approximately 1-1/8 inches (2.86 cm) square and 5/8 inch (1.59 cm) in overall depth. The pad shall be of sufficient depth to restrict movement of the lapel button when the lid is closed.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
DLA - CT

(Project No. 8455-0858)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:26Z
Check the source to verify that this is the current version before use.