NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/218D
17 September 2020
SUPERSEDING
MIL-DTL-11484/218C
12 November 2015

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, LENGTH OF SERVICE (10, 20, 30, 40, AND 50 YEARS) CIVILIAN PERSONNEL, U.S. AIR FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.



DASH NO.
-1: 10 Years
-2: 20 Years
-3: 30 Years
-4: 40 Years with Ruby
-5: 50 Years with Diamond

MATERIAL: -1, -2, -3, -4 and -5: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
-1: Oxidized, Buffed Relieved, Polished Highlights and shall match the Institute of Heraldry (TIOH) Metal Finish Chip Number 5.

-2: Nickel Plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match (TIOH) Metal Finish Chip Number 15.

-3, -4,-5: 24K Gold Plated, Matte Finish, Polished Highlights and shall match (TIOH) Metal Finish Chip Number 8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:26Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
HEIGHT (Overall): 3/4 inch (REF)
WIDTH (Overall): 21/32 (REF)
THICKNESS (At thickest point): 0.075 inch ± 0.010 inch

ATACHING DEVICE:
1. Attaching device shall be prong with pick and flat ball type clutch.

2. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. All stones shall be 3 points and set in the lapel button with a 3 bead setting. The location of the stone shall be centered in the eagle's neck above the words "AIR FORCE" as indicated. The stones shall be synthetic and of the color specified for the corresponding year as indicated.

3. Manufacturer shall add the specified number representing the length of service to the working die in the style and location indicated on TIOH Drawing number A-9-32. Numbers shall be 0.155 inch ± 0.002 inch in height.

4. All lapel buttons shall be lacquered.

5. Each lapel button shall be mounted and centered on a polyethylene pad and placed in a rigid hinged plastic box having a transparent lid and opaque bottom section. The box shall have two plastic hinges and catches and shall be approximately 1-1/8 inches square and 5/8 inch in overall depth. The pad shall be of sufficient depth to restrict movement of the lapel button when the lid is closed.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2020-513)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:26Z
Check the source to verify that this is the current version before use.