MIL-S-55041/10(USAF)
AMENDMENT 1
4 September 1979

MILITARY SPECIFICATION

SWITCH, WAVEGUIDE, ELECTROMECHANICAL, LATCHING
FREQUENCY RANGE 8.6 - 10.3 GH_z

This amendment is approved for use by the Air Force Acquisition Logistics Division, Directorate of Electronic Support (AFALD/PTS), Wright-Patterson AFB, Ohio 45433, Department of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Add: "Material: Lubricants shall comply, as a minimum, to the requirements of MIL-G-83261."

Delete: "Connector: The power connector shall be M83723-02R1006N (flange mount type) or M83723-06R1006N (jam nut type)." and add: "Connector: The power connector shall mate with connector MS3116E10-6S."

Add: "The test set-ups specified in Figures 2, 3, and 4 of MIL-S-55041 may be modified to reflect current industry practice."

Add: "Explosion: Applicable. The test need not be done with full RF power applied if the switch is designed so that the switching mechanism is completely isolated from the RF energy path."

PAGE 4

Delete: "Switching time: The switch shall be mounted in position shown." and add: "Switching time: The switch shall be mounted in the position shown; the long axis of the switch shall be vertical."

Custodian:
Air Force - 85

Review Activity:
Air Force - 99

Preparing Activity:
Air Force - 85

(Project 5985-F483)

FSC 5985

* U.S GOVERNMENT PRINTING OFFICE: 1979-603-022/ 3772

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:19Z
Check the source to verify that this is the current version before use.