MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6U8A

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Triode-pentode, miniature

Outline	---	6-2 (EIA)
Base	---	E9-1
Envelope	---	T6-1/2
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7	8	9
Element	---	2a	1g1	1g2	h	h	1a	1k, 1g3	2k	2g

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	E1b	E1c2	E1c1	E2b	E2c1	P1p	P1g2	P2p	Ehk	Alt
Unit:	V	Vdc	Vdc	Vdc	Vdc	Vdc	W	W	W	v	ft
Maximum:	6.9	330	165	---	330	---	3.15	0.55	2.95	180	(See note 1)
Minimum:	5.7	---	---	---	---	---	---	---	---	---	---

TEST CONDITIONS:

Pentode:	6.3	250	110	0	---	---	---	---	---	---	---
Triode:	6.3	---	---	---	150	0	---	---	---	---	---

GENERAL:

Qualification - Not required

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:14Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:14Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 3							
1501	Intermittent life	Group A: Ef = 6.3 V; E1bb = 300 Vdc; E2bb = 180 Vdc; E1cc2 = 135 Vdc; R1k = 125 ohms; R2k = 150 ohms; R1g1 = R2g1 = 0.5 Meg; E1hk = +180 Vdc; E2hk = +180 Vdc; R1g2 = 2,700 ohms	---	---	---	---	---	---
(C) ---	Intermittent life-test end points (500 hours)	Transconductance (1) (pentode)	---	---	Sm	3,700	---	µmhos
		Transconductance (1) (triode)	---	---	Sm	5,525	---	µmhos

NOTES:

1. See "Reduced pressure (altitude) rating", and altitude, maximum peak voltage.
2. Total grid current shall be read for both units.
3. This test to be performed at the conclusion of the holding period.
4. Unit not under test shall be grounded.
5. Test each section separately.
6. Tie 1a and 1g2 to 2a; tie 1g1 to 2g; tie 1k to 2k. Ebb = 250 V; Rb = 10,000 ohms; Rk = 150 ohms; Rg1 = 0.1 Meg. Esig = 60 mVac.

Custodians:
Army - EL
Navy - EC
Air Force - 80

Review activities:
Army - EL, MI
Navy -
Air Force - 11, 85
DSA - ES

User activities:
Army - WC
Navy - AS, OS, MC, CG, SH
Air Force - 19

Preparing activity: Navy - EC

Agent: DSA - ES

(Project 5960-2401-84)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:14Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:14Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:14Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

S/N 0102-014-1801 C-25254

Source: https://assist.dla.mil -- Downloaded: 202610-15T14:14Z
Check the source to verify that this is the current version before use.