MILITARY SPECIFICATION SHEET

ELECTRON TUBE, TYPE 8361

This amendment forms a part of Military Specification Sheet MIL-E-1/1228C(NAVY), dated 13 January 1967.

Page 2

Qualification, Requirement or Test column: Delete "Vibration" and substitute "Low frequency (25 Hz) vibration".

Delete "Qualification - required (Note 21)" and substitute "Qualification - Not required."

Delete "Qualification" test methods and their associated columnar data. Add these test methods after Quality conformance inspection, part 3, life tests, as "Periodic-check tests."

Page 3

Quality conformance inspection, part 2, Power output (3), Conditions column: Delete "(frequency shall not vary more than 100 Mc)", and substitute "ΔF = 50 MHz".

Quality conformance inspection, part 3, Life-test provisions, Conditions column: Add "Group S".

Page 5

Note 6(b): Delete first sentence.

Note 7: Delete second and third sentences.

Page 6

* Note 15: Delete and substitute the following:

"15. Two thermal safety switches shall be provided and shall monitor the metal temperature of the collector and drift tubes. The switches shall open when the tube temperature exceeds a safe operating value.

*NOTE: The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:17Z
Check the source to verify that this is the current version before use.

The rating of the switches shall be three amperes at 115 volts a.c. Under no condition shall the tube be operated with an external short applied between the interlock terminals or with complete stoppage of coolant flow."

Page 7

Note 21: Delete.

Page 11

Notes: Add the following as notes 6 and 7:

"6. With 12.5 amperes d.c. field current applied, the axial gauss level measured on the coil axis 8 inches from the top surface of the structure shall be 1245 ±95 gausses.

7. A 0.25 inch minimum thickness lead cylinder shall be placed between the inner core of the structure and the field winding. This lead cylinder shall not be any portion of the 9.200 inner diameter."

User activities
Navy - AS, OS, MC, CG, SH

Preparing activity:
Navy - EC

(Project 5960-N994)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:17Z
Check the source to verify that this is the current version before use.