INCH-POUND

MIL-PRF-1/1225D
2 July 1999
SUPERSEDING
MIL-E-1/1225C
10 February 1981

PERFORMANCE SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING
TYPE 6688

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the electron tube described herein shall consist of this document and the latest issue of MIL-PRF-1.

DESCRIPTION: Pentode, miniature, rf, sharp cutoff.

Outline	---	6-1 (EIA)
Base	---	E9-1
Envelope	---	T6-1/2
Cathode	---	Coated unipotential

Base connections:

Pin No.	1	2	3	4	5	6	7	8	9
Element	k	g1	k	h	h	int con	a	g3	g2

ABSOLUTE RATINGS:

Parameter: Unit:	Ef V	Eb V dc	Ec1 V dc	Ec2 V dc	Ec3 V dc	Ehk v	ec1 v
Maximum:	6.6	210	0	175	0	60	---
Minimum:	6.0	---	-50	---	---	---	-100
Test conditions:	6.3	190	+9	160	0	0	---

ABSOLUTE RATINGS:

Parameter: Unit:	Rk Ohms	Rg1 Meg	Ik mA dc	Pp W	Pg2 W	TE °C	Alt ft
Maximum:	---	0.1	25	2.7	0.6	+155	1/
Minimum:	---	---	---	---	---	---	---
Test conditions:	630	---	---	---		---	---

See footnotes at end of table I.

GENERAL: Qualification - Required.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:17Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection.

Inspection	Method	Conditions	Acceptance level	Inspection level or code	Symbol	Limits		Unit
						Min	Max	
Conformance inspection, part 1								
Heater current	1301		0.4	II	If	285	315	mA
Heater-cathode leakage	1336		0.4	II	Ihk	---	15	µA dc
Total grid current	1266	2/	0.4	II	Ic1	0	-0.5	µA dc
Anode current (1)	1256	Ebb = 180 V dc; Ecc1 = 0; Ecc2 = 150 V dc; Ecc3 = 0; Rk = 78 ohms 2/	0.4	II	Ib	8.0	18.0	mA dc
Anode current (2)	1256	Ec1 = -6.0 V dc; Ebb = 180 V dc; Ecc2 = 150 V dc; Ecc3 = 0; Rk = 78 ohms	0.4	II	Ib	---	100	µA dc
Screen-grid current	1256		0.4	II	Ic2	2.9	3.7	mA dc
Transconductance (1)	1306		0.4	II	Sm	14,200	18,800	µmhos
Short and discontinuity detection	1201		0.4	II	---	---	---	---
Conformance inspection, part 2								
Insulation of electrodes	1211		2.5	I	R	20	---	Meg
Transconductance (2)	1306	Ef = 5.7 V	2.5	I	$\frac{\Delta Sm}{Ef}$	---	15	%
Grid emission	1266	Ef = 7.5 V; Ec1 = -6.0 V dc; Rk = 0 3/	2.5	I	Ic1	0	-0.5	µA dc
Noise and microphonics	2201	Ef = 6.3 V; Ehk = 0; Ebb = Ecc2 = 200 V dc; Ec1 = 0; Ecal = 600 mV ac; Rk = 1,000 ohms; Rp = 0.1 Meg; Rg2 = 0.5 Meg; Cg2 = 2 µF 4/	2.5	I	---	---	---	---
Direct-interelectrode capacitance	1331	Shield No. 315 5/	6.5	Code E	Cg1p Cin Cout	--- 6.7 2.50	0.030 8.5 3.50	pF pF pF
Low-frequency vibration	1031	Rp = 2,000 ohms	6.5	Code E	Ep	---	300	mV dc
Shock	1041	450 G; Ehk = +100 V dc 7/	---	6/	---	---	---	---
Vibration fatigue	1031	2.5 G; F = 25 min, 60 max; fixed frequency	6.5	6/	---	---	---	---

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:17Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection - Continued.

Inspection	Method	Conditions	Acceptance level	Inspection level or code	Symbol	Limits		Unit
						Min	Max	
Conformance inspection, part 2 - Continued								
Post-shock and vibration fatigue end points	---							
Low-frequency vibration	1031		---	---	Ep	---	400	mV ac
Heater-cathode leakage	1336		---	---	Ihk	---	30	µA dc
Transconductance (1)	1306		---	---	Sm	12,500	---	µmhos
Total grid current	1266		---	---	Ic1	0	-1.0	µA dc
Base strain	1121		---	---	---	---	---	---
Glass strain	2126		6.5	I	---	---	---	---
Permanence of marking	1105		---	---	---	---	---	---
Conformance inspection, part 3								
Heater-cycling life	1506	Ef = 7.5 V; Ehk = 60 V dc; Eb = Ec1 = Ec2 = 0	---	---	---	---	---	---
Life-test end points (heater-cycling)	---							
Heater-cathode leakage	1336		---	---	Ihk	---	30	µA dc
Stability life	1516	Eb = 200 V dc; Ec1 = +9 V dc; Ec2 = 170 V dc; Ec3 = 0; Rk = 680 ohms; Rg1 = 0.5 Meg; TA = room temperature	---	---	---	---	---	---
Life test end point (stability)	---							
Change in transconductance (1) of individual tubes	1306		---	---	ΔSm t	---	10	%
Intermittent life	1501	Stability life-test conditions; TE = +155°C (min) 8/ 9/	---	---	---	---	---	---

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:17Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection - Continued.

Inspection	Method	Conditions	Acceptance level	Inspection level or code	Symbol	Limits		Unit
						Min	Max	
Conformance inspection, part 3 - Continued								
Life-test end points (intermittent) (500 hours)	---							
Inoperatives	---		---	---	---	---	---	---
Total grid current	1266		---	---	Ic1	0	-0.9	µA dc
Heater current	1301		---	---	If	285	315	mA
Change in transconductance (1) of individual tubes	1306		---	---	$\frac{\Delta Sm}{t}$	---	20	%
Transconductance (2)	1306		---	---	$\frac{\Delta Sm}{Ef}$	---	15	%
Heater-cathode leakage	1336		---	---	Ihk	---	30	µA dc
Insulation of electrodes	1211		---	---	R	10	---	Meg
Transconductance (1) average change	1306		---	---	Avg $\frac{\Delta Sm}{t}$	---	15	%
Total defectives	---		---	---	---	---	---	---
Life-test end points (Intermittent) (1,000 hours)	---							
Inoperatives	---		---	---	---	---	---	---
Total grid current	1266		---	---	Ic1	0	-0.9	µA dc
Heater current	1301		---	---	If	285	315	mA
Change in transconductance (1) of individual tubes	1306		---	---	$\frac{\Delta Sm}{t}$	---	25	%
Heater-cathode leakage	1336		---	---	Ihk	---	30	µA dc
Insulation of electrodes	1211		---	---	R	10	---	Meg
Total defectives	---		---	---	---	---	---	---

1/ See "Reduced pressure (altitude) rating", and altitude, maximum peak voltage.

2/ This test to be performed at the conclusion of the holding period.

3/ Prior to this test, tubes shall be preheated a minimum of 5 minutes at the conditions indicated below. The 3-minute test is not permitted. Test at specified conditions within 3 seconds after preheating. Grid emission shall be the last test performed on the sample selected for the grid-emission test.

Ef	Ec1	Ec2	Eb	Rk
V dc	V dc	V dc	V dc	Ohms
7.5	+9	160	190	630

4/ The rejection level shall be set at the VU meter reading obtained during calibration.

5/ Pin 6 floating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:17Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection - Continued.

6/ This test shall be conducted on the initial lot and thereafter on a lot approximately every 12-months. In the event of lot failure, the lot shall be rejected and the succeeding lots shall be subjected to this test until a lot passes. When one lot has passed, the 12-month rule shall apply. Sample size of 13, shall apply.

7/ A grid resistor of 0.1 megohm shall be added; however, this resistor will not be used when a thyratron-type short indicator is employed.

8/ Envelope temperature (TE) requirements, when measured in accordance with the temperature by conduction-band measurement (method 1226), will be satisfied if a tube having bogey Ib (± 5 percent) under normal test conditions, is determined to operate at or above minimum specified temperature at any position in the life-test rack.

9/ The life-test sample shall consist of 20 tubes per lot and not 1 tube failure shall be permitted. In the event of rejection of the first sample, due to failure of 1 tube or more, a second sample of 40 tubes shall be selected from the lot, and not 1 tube failure from the second sample of tubes shall be permitted.

10/ Revision letters are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, CR4, MI
Navy - AS, CG, MC, OS
Air Force - 99

Preparing activity:
DLA - CC

(Project 5960-3535)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:17Z
Check the source to verify that this is the current version before use.