INCH-POUND

MS51817G
30 March 2022
SUPERSEDING
MS51817F
W/ AMENDEMNT 1
26 April 2019

DETAIL SPECIFICATION SHEET

ELBOW, PIPE TO TUBE, 45 DEGREE
MALE PIPE END, FLARELESS TYPE, HYDRAULIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

Reactivated after 3 April 2018 and may be used for new and existing designs and acquisitions.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-18866.




FIGURE 1. Elbow 45°, pipe to tube.

AMSC N/A
FSC 4730

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:08Z
Check the source to verify that this is the current version before use.

Dash number Standard sizes	(see note 5)	Tube OD Nom inches (mm)	A Thread NPTF	B (see note 7)
Assembly	Body			
-1	-21	.1250 (3.18)	.125 -27	.3125 - 24UNF
-2	-22	.1875 (4.78)	.125 -27	.3750 - 24UNF
-3	-23	.2500 (6.35)	.125 -27	.4375 - 20UNF
-4	-24	.3125 (7.95)	.125 -27	.5000 - 20UNF
-5	-25	.3750 (9.53)	.250 - 18	.5625 - 18UNF
-6	-26	.5000 (12.70)	.375 - 18	.7500 - 16UNF
-7	-27	.6250 (15.88)	.500 - 14	.8750 - 14UNF
-8	-28	.7500 (19.05)	.750 - 14	1.0625 - 12UN
-9	-29	.8750 (22.23)	.750 - 14	1.1875 - 12UN
-10	-30	1.0000 (25.40)	1.000 - 11 1/2	1.3125 - 12UN
-11	-31	1.2500 (31.75)	1.250 - 11 1/2	1.6250 - 12UN
-12	-32	1.5000 (38.10)	1.500 - 11 1/2	1.8750 - 12UN
-13	-33	2.0000 (50.80)	2.000 - 11 1/2	2.5000 - 12UN

Dash number	(see note 5)	D dia. Drill inches (mm)	D_1 dia. Drill	M_2 Inches (mm) ±.03 (0.76)	N_2 Drill dia. inches (mm) ±.03 (0.76)
Assembly	Body				
-1	-21	.093 (2.36)	.188 (4.78)	.64 (16.26)	.52 (13.21)
-2	-22	.125 (3.18)	.188 (4.78)	.64 (16.26)	.52 (13.21)
-3	-23	.203 (5.16)	.188 (4.78)	.70 (17.78)	.64 (16.26)
-4	-24	.234 (5.94)	.188 (4.78)	.73 (18.54)	.64 (16.26)
-5	-25	.281 (7.14)	.281 (7.14)	.83 (21.08)	.86 (21.84)
-6	-26	.422 (10.72)	.406 (10.31)	.98 (24.89)	.95 (24.13)
-7	-27	.500 (12.70)	.531 (13.49)	1.08 (27.43)	1.17 (29.72)
-8	-28	.656 (16.66)	.719 (18.26)	1.27 (32.26)	1.20 (30.48)
-9	-29	.718 (18.24)	.719 (18.26)	1.27 (32.26)	1.27 (32.26)
-10	-30	.875 (22.23)	.938 (23.83)	1.36 (34.54)	1.48 (37.59)
-11	-31	1.093 (27.76)	1.250 (31.75)	1.45 (36.83)	1.67 (42.42)
-12	-32	1.344 (34.14)	1.500 (38.10)	1.52 (38.61)	1.77 (44.96)
-13	-33	1.813 (46.05)	1.938 (49.23)	1.83 (46.48)	2.11 (53.59)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Remove all burrs and slivers.
4. Dimensions and tolerances not shown shall be in accordance with SAE-J514.
5. Assemblies are only furnished to this specification (body, nut, and sleeve). Bodies are not to be stocked, stored, or issued.
6. The drawing is for identification purposes only and is not intended to restrict designs and shapes not dimensioned.
7. ASME B1.1 - Unified Inch Screw Threads (UN and UNR Thread Forms)

FIGURE 1. Elbow 45°, pipe to tube - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:08Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:


Elbow 45° pipe to tube shall be as specified on figure 1.

Materials and finish designators shall be in accordance with MIL-DTL-18866.

Unless otherwise specified in MIL-DTL-18866, all platings shall be capable of meeting a minimum of 96 hours salt spray test in accordance with ASTM B117. The fittings shall show no evidence of red corrosion after 96 hours of salt spray. Fluid passages, other openings and internal threads shall not be subject to the plating thickness requirement and may have bare areas provided they are protected with a light film of oil.

Maximum operating pressure. Maximum operating pressure shall be in accordance with SAE-J514.

PIN: The PIN consists of the letters “MS”, the specification number, a dash, number for an elbow 45° pipe to tube assembly/body size, and a letter for material finish designator.



PIN example: MS51817-10TFB indicates an elbow 45° pipe to tube assembly, 1.000 inch (225.40 mm) tube OD, 1 inch NPTF pipe threads and 1.3125 - 12UN threads, titanium, fluoride phosphate finish, and B style sleeve.

Marking shall be in accordance with MIL-DTL-18866.

Class I and II ozone depleting substances (ODS) shall not be used in MS51817 or any referenced procedures.

Tapered pipe thread connections are generally prohibited in high shock applications.

Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Referenced documents shall be of the issue in effect on date of invitations for bid

NOTE: The following restrictions do not apply to manufacturers of the fittings and is applicable only to OEM’s and users.

Cadmium is not recommended. To the users of this document, it is recommended that the use of carbon steel material with cadmium plating be used only when other materials and finishes specified in this document cannot meet performance requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:08Z
Check the source to verify that this is the current version before use.

Army and Marine ground vehicle applications using zinc plating. PIN codes FC, FD, Z, and ZC finishes have a chromate conversion coating which includes hexavalent chromium and are not recommended for Army and Marine ground systems. The use of coatings depositing hexavalent chromium for Army vehicles is prohibited unless otherwise explicitly stated in the contract as a requirement. For new designs PIN codes FC, FD, Z, and ZC are not to be supplied to Army and Marine ground forces. PIN code KA (MIL- PRF- 32647 Type K20) is intended as a hazardous free plating material and is a direct replacement for zinc plating with a hexavalent chromium conversion coating. PIN code KA has equivalent torque/tension behavior as the zinc plating it replaces.

Army and Marine ground vehicles. The use of cadmium plating for Army and Marine ground vehicles is prohibited unless otherwise explicitly stated in the contract as a requirement.

Army and Marine ground vehicle applications using cadmium plating. Pin code J or KB may be substituted for cadmium ("Blank" PIN code) for Army ground vehicle applications. PIN code KB (MIL-PRF-32647 Type K16) is intended as a hazardous free plating material and is a direct replacement for cadmium plating ("Blank" PIN code). PIN code KB has an equivalent torque/tension behavior as the cadmium plating it replaces.

NAVSEA shipboard owned equipment. Cadmium is prohibited from use in NAVSEA-owned shipboard systems in accordance with the requirements of T9070-AL-DPC-020/077-2, unless otherwise approved by NAVSEA.

Table II provides a detail reference data listing for MS39204 to MS51817. This table contains coordination of equivalent tube sizes, in both compression and hydraulic type elbows. Assembly replacement is authorized.

TABLE II. Assembly equivalency (for information only).

Compression MS39204	Hydraulic MS51817	Compression MS39204	Hydraulic MS51817	Compression MS39204	Hydraulic MS51817
-1	-1	-5	-5	-9	-9
-2	-2	-6	-6	-10	-10
-3	-3	-7	-7	-11	-11
-4	-4	-8	-8	-12	-12

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-18866, this document references the following:

MIL-PRF-32647
MS39204
MS51823
MS51825
ASTM B117
ASME B1.1
SAE-J514
T9070-AL-DPC-020/077-2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:08Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - AT
Navy - SH
Air Force - 71
DLA - CC

Preparing activity:
DLA - CC

(Project 4730-2022-009)

Review activities:
Army - AR, MI
Navy - AS, CG, SA

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:08Z
Check the source to verify that this is the current version before use.