


FED SUP CLASS
5306





SECTION THRU THREAD PROFILE



OPTIONAL SHAPE OF HEAD

TABLE I. DASH NUMBERS AND DIMENSIONS

DASH NUMBER	L	K +.000 -.060	APPROX WEIGHT LBS/100
-06	.750	1/	3 74
-07	812	1/	3.90
-08	.875	1/	4.07
-09	.938	1/	4.24
-10	1.000	1/	4.41
-11	1.062	1/	4.58
-12	1.125	.125	4.75
-13	1.188	.188	4.91
-14	1.250	.250	5.08
-15	1.312	.312	5.25
-16	1.375	.375	5.43
-17	1.438	.438	5.60
-18	1.500	.500	5.76
-19	1.562	.562	5.93
-20	1.625	.625	6.10
-21	1.688	.688	6.27
-22	1.750	.750	6.44
-23	1.875	.875	6.77
-24	2 000	1.000	7.11
-25	2.125	1.125	7.44
-26	2.250	1.250	7.78
-27	2.375	1.375	8.11
-28	2 500	1.500	8.44
-29	2.625	1.625	8.78
-30	2.750	1.750	9.12
-31	2 875	1.875	9.46
-32	3.000	2.000	9.80
-33	3.125	2.125	10.13
-34	3.250	2.250	10.47
-35	3.375	2.375	10.80
-36	3.500	2.500	11.14
-37	3.625	2.625	11.47
-38	3.750	2.750	11.80
-39	3.875	2.875	12.14
-40	4.000	3.000	12.47
-41	4.125	3.125	12.80
-42	4.250	3.250	13.13
-43	4.375	3.375	13.46
-44	4.500	3.500	13.89
-45	4.625	3.625	14.23
-46	4.750	3.750	14.56
-47	4.875	3.875	14.89
-48	5.000	4.000	15.23
-49	5.125	4.125	15.57
-50	5.250	4.250	15.90
-51	5.375	4.375	16.23
-52	5.500	4 500	16.56
-53	5.625	4.625	16.89
-54	5.750	4.750	17.23
-55	5.875	4.875	17.57
-56	6.000	5.000	17.91

1/ THREAD TO HEAD, MAXIMUM TWO INCOMPLETE THREADS

INACTIVE FOR NEW DESIGN
AFTER 31 DEC 1963

Ⓑ ENTIRE STANDARD REVISED

APPROVED 15 AUG 60 REVISED Ⓑ 8 AUG 86

USER ACTIVITIES

REVIEWER ACTIVITIES
AIR FORCE - 82
DLA - IS

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited
This military standard is approved for use by all Departments and Agencies of the Department of Defense
Selection for all new engineering and design applications and for repetitive use shall be made from this document

P A NAVY-AS Other Cust ARMY-AV	INTERNATIONAL INTEREST	TITLE BOLT, MACHINE-DOUBLE HEXAGON, EXTENDED WASHER HEAD, CORROSION AND HEAT RESISTANT STEEL, DRILLED, .375-24 NS	MILITARY STANDARD MS 9063
PROCUREMENT SPECIFICATION AMS7478	SUPERSEDES:		PAGE 1 OF 2

MSC N/A


DD FORM 1 MAY 73 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5306-1111

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:10Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. MATERIAL: CORROSION AND HEAT RESISTANT STEEL AMS 5732.
2. THREADS: THREADS IN ACCORDANCE WITH MIL-S-7742. INCOMPLETE THREADS NOT TO ENTER FILLET.
3. DIMENSIONING AND TOLERANCING: DIMENSIONING AND TOLERANCING SHALL BE IN ACCORDANCE WITH ANSI Y14.5M.
4. FLUORESCENT PENETRANT INSPECTION: FLUORESCENT PENETRANT INSPECTION SHALL BE IN ACCORDANCE WITH AMS 2645-83.
5. SURFACE TEXTURE: SURFACE TEXTURE, UNLESS OTHERWISE SPECIFIED, SHALL BE 125 MICROINCHES, EXCEPT UPSET HEAD, IN ACCORDANCE WITH ANSI B46.1.
6. TOLERANCE: UNLESS OTHERWISE SPECIFIED, TOLERANCES SHALL BE FOR LINEAR DIMENSIONS $\pm$ .010, ANGULAR DIMENSIONS $\pm$ 5°.
7. EDGES: BREAK SHARP EDGES .003 - .015, UNLESS OTHERWISE SPECIFIED.
8. PART NUMBER: THE PART NUMBER SHALL CONSIST OF THE BASIC MS NUMBER FOLLOWED BY A DASH NUMBER FROM TABLE I.

EXAMPLE: MS9063-06



MS9063-06 INDICATES: BOLT, MACHINE, CRES, DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED; .375-24 NS; LENGTH .750.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. DO NOT USE UNASSIGNED PART NUMBERS
3. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
4. REFERENCED GOVERNMENT (OR NONGOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.
5. THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE SAE AEROSPACE PROPULSION DIVISION.
6. AS AND AMS ARE SAE PUBLICATIONS

APPROVED 15 AUG 60 REVISED (B) FOR CHANGES SEE PAGES 1 AND 2

USER ACTIVITIES:

REVIEWER ACTIVITIES:
AIR FORCE - 82
DLA - IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document

P A NAVY - AS Other Cust ARMY - AV	INTERNATIONAL INTEREST	TITLE BOLT, MACHINE - DOUBLE HEXAGON, EXTENDED WASHER HEAD, CORROSION AND HEAT RESISTANT STEEL, DRILLED, .375-24 NS	MILITARY STANDARD MS 9063
PROCUREMENT SPECIFICATION AMS 7478	SUPERSEDES:		PAGE 2 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:10Z
Check the source to verify that this is the current version before use.

INCH-POUND

MS9063B
AMENDMENT 1
29 April 1996

MILITARY STANDARD

BOLT, MACHINE-DOUBLE HEXAGON, EXTENDED WASHER HEAD,
CORROSION AND HEAT RESISTANT STEEL, DRILLED, .375-24 NS

This amendment forms a part of MS9063B, dated 8 August 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

DELETE

4. Fluorescent penetrant inspection per AMS 2645.

SUBSTITUTE

4. Fluorescent penetrant inspection per ASTM E1417.

Custodians:
Army - AV
Navy - AS

Preparing Activity:
DLA-IS

(Project 5306-1933)

Review activity:
Air Force - 99

AMSC N/A FSC 5306

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:10Z
Check the source to verify that this is the current version before use.