MIL-E-1/1560B
27 January 1972
SUPERSEDING
MIL-E-1/1560A
21 June 1966

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6DK6

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Pentode, miniature

Outline --- 5-2 (EIA)

Base --- E7-1

Envelope --- T5-1/2

Cathode --- Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7
Element	---	g1	k	h	h	a	g^2	g3, int sd

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ecc2	Ec2	Ec3	Ec1	Ehk
Unit:	V	Vdc	Vdc	Vdc	Vdc	Vdc	v
Maximum:	6.9	330	330	165	0	0, -55	200
Minimum:	5.7	---	---	---	---	---	--- (Note 1)
TEST CONDITIONS:	6.3	125	---	125	Note 3	0	---

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Rk	Rg1	Pp	Pg2	TE	Alt
Unit:	Ohms	Meg	W	W	°C	ft
Maximum:	---	0.25	2.3	0.55	140	Note 4
Minimum:	---	--- (Note 2)	---	---	---	---
TEST CONDITIONS:	56	---	---	---	---	---

GENERAL:

Qualification - Required

(B) denotes changes

Source: https://assist.dla.mil -- Downloaded: 202610-15T14:58Z
Check the source to verify that this is the currentversion before use.

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1								
1266	Total grid current	5	Eb = 200 Vdc; Ec2 = 150 Vdc; Rk = 100 ohms	0.65	II	Ic1	---	-1.0	µAdc
1256	Electrode current (1) (anode)	-		0.65	II	Ib	9.0	16.5	mAdc
1306	Transconductance (1)	-		0.65	II	Gm	7,600	12,000	µmhos
1256	Electrode current (2) (anode)	-	Ec1 = -6.5 Vdc; Rk = 0	0.65	II	Ib	---	250	µAdc
1201	Short and discontinuity detection	-		0.4	II	---	---	---	---
	Quality conformance inspection, part 2								
1256	Electrode current (screen)	-		2.5	I	Ic2	---	5	mAdc
(B) 1246	Audio frequency noise	-	Ebb = 300 Vdc; Ec2 = 150 Vdc; Rk = 180 ohms; Rb = 10,000 ohms; Rg1 = 0.1 Meg; Esig = 100 mVac	2.5	I	EB	---	17	vu
1211	Insulation of electrodes	-		---	---	---	---	---	---
1301	Heater current	-		---	---	If	275	325	mAdc
1336	Heater-cathode leakage	-		---	---	Ihk	---	20	µAdc
1306	Transconductance (2)	-	Ef = 5.7 V	---	---	ΔGm / Ef	---	15	%
1331	Direct-interelectrode capacitance	-	No external shield	6.5	Code E	Cin	5.0	7.6	pF
						Cout	1.4	2.4	pF
						Cg1p	---	0.024	pF
1121	Base strain	-		---	---	---	---	---	---
2126	Glass strain	-		2.5	I	---	---	---	---
1105	Permanence of marking	-		---	---	---	---	---	---
	Quality conformance inspection, part 3								
1501	Intermittent life	-	Group A; Eb = 200 Vdc; Ec2 = 150 Vdc; Rk = 150 ohms; Ehk = +180 Vdc; Rg1 = 1.0 Meg	---	---	---	---	---	---
---	Intermittent life-test end points (500 hours):								
1306	Transconductance (1)	-		---	---	Gm	5,800	---	µmhos
1266	Total grid current	-		---	---	Ic1	---	-1.5	µAdc

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:58Z
Check the source to verify that this is the current version before use.

NOTES:

1. The absolute value of the positive dc heater-cathode voltage shall not exceed 100 volts.
2. This value is for operation under fixed-bias conditions. With cathode bias Rg1 may be 1.0 megohm maximum.
3. Tie grid No. 3 to positive terminal of cathode resistor.
4. See "Reduced pressure (altitude) rating", and altitude, maximum peak voltage in the basic document.
5. This test to be performed at the conclusion of the holding period.

Custodians:
Army - EL
Navy - EC
Air Force - 80

Review activities:
Air Force - 11, 17
DSA - ES

User activities:
Army - WC
Navy - AS, OS, MC, CG, SH

Preparing activity: Navy - EC

Agent: DSA - ES

(Project 5960-2601)

Source: https://assist.dla.mil -- Downloaded: 202610-15T14:58Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:58Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:58Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 84 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

S/N-0102-014-1801 C-88384

Source: https://assist.dla.mil -- Downloaded: 202610-15T14:58Z
Check the source to verify that this is the current version before use.