MILITARY SPECIFICATION

CABLES, RADIO FREQUENCY, FLEXIBLE AND SEMIRIGID,
GENERAL SPECIFICATION FOR

This supplement forms a part of Military Specification
MIL-C-17G, dated 9 March 1990

SPECIFICATION SHEETS

MIL-C-17/2 - Cable, Radio Frequency, Flexible, Coaxial, 75 Ohms, M17/2-RG6.
MIL-C-17/6 - Cables, Radio Frequency, Flexible, Coaxial, 75 Ohms, M17/6-RG11, Unarmored, M17/6-RG12, Armored.
MIL-C-17/15 - Cables, Radio Frequency, Flexible, Twin, 95 Ohms, Unarmored M17/015-RG022, and Armored M17/015-RG111.
MIL-C-17/16 - Cables, Radio Frequency, Flexible, Coaxial, Dual, 125 Ohms, M17/16-RG23 (Unarmored), M17/16-RG24 (Armored).
MIL-C-17/19 - Cables, Radio Frequency, Flexible, Triaxial, Pulse, 48 Ohms, M17/19-RG25.
MIL-C-17/21 - Cables, Radio Frequency, Flexible, Coaxial, Pulse, 48 Ohms, M17/21-RG26.
MIL-C-17/22 - Cables, Radio Frequency, Flexible, Coaxial, Pulse, 48 Ohms, M17/22-RG27 (Armored), M17/22-00001 (Unarmored).
MIL-C-17/23 - Cables, Radio Frequency, Flexible, Triaxial, Pulse, 48 Ohms, M17/23-RG28.
MIL-C-17/24 - Cable, Radio Frequency, Flexible, Coaxial, 75 Ohms, M17/24-RG34.
MIL-C-17/28 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/028-RG058.
MIL-C-17/29 - Cables, Radio Frequency, Flexible, Coaxial, 75 Ohms, M17/29-RG59.
MIL-C-17/30 - Cables, Radio Frequency, Flexible, Coaxial, 93 Ohms, M17/030-RG062.
MIL-C-17/31 - Cables, Radio Frequency, Flexible, Coaxial, 125 Ohms, M17/31-RG63, Unarmored, M17/31-RG79, Armored.
MIL-C-17/33 - Cables, Radio Frequency, Flexible, Coaxial, Pulse, 48 Ohms, M17/33-RG64.
MIL-C-17/34 - Cables, Radio Frequency, Flexible, Coaxial, Time Delay, 950 Ohms, M17/34-RG65.
* MIL-C-17/40 - Cable, Radio Frequency, Coaxial, RG-85A/U.
* MIL-C-17/43 - Cable, Radio Frequency, Coaxial, RG-88/U.
MIL-C-17/45 - Cables, Radio Frequency, Flexible, Twin, 78 Ohms, M17/045-RG108.
MIL-C-17/47 - Cable, Radio Frequency, Flexible, Coaxial, 185 Ohms, M17/47-RG114.
MIL-C-17/52 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/52-RG119, Unarmored, M17/52-RG120, Armored.
MIL-C-17/54 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/54-RG122.
MIL-C-17/56 - Cables, Radio Frequency, Flexible, Twin, 95 Ohms, M17/56-RG130 (Unarmored), M17/56-RG131 (Armored).
MIL-C-17/60 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/60-RG142.
MIL-C-17/62 - Cables, Radio Frequency, Flexible, Coaxial, 75 Ohms, M17/62-RG144.

* Inactive for new design.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:57Z
Check the source to verify that this is the current version before use.

MIL-C-17/64 - Cables, Radio Frequency, Flexible, Coaxial, 75 Ohms, M17/64-RG164, Unarmored, M17/64-RG035, Armored.
MIL-C-17/65 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms Unarmored M17/65-RG165, and Armored, M17/65-RG166.
MIL-C-17/67 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/67-RG177.
MIL-C-17/72 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/72-RG211.
MIL-C-17/73 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/73-RG212.
MIL-C-17/74 - Cables, Radio Frequency, Flexible, Coaxial 50 Ohms, Unarmored M17/74-RG213, and Armored M17/74-RG215.
MIL-C-17/75 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/75-RG214 and M17/75-RG365.
MIL-C-17/77 - Cable, Radio Frequency, Flexible, Coaxial, 75 Ohms M17/77-RG216.
MIL-C-17/78 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/78-RG217.
MIL-C-17/79 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms Unarmored M17/79-RG218, and Armored, M17/79-RG219.
* MIL-C-17/81 - Cable, Radio Frequency, Flexible, Coaxial, 50 ohms, M17/81-00001 and M17/81-00002 Armored.
MIL-C-17/84 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/84-RG223.
MIL-C-17/86 - Cable, Radio Frequency, Coaxial, RG-225/U.
MIL-C-17/87 - Cable, Radio Frequency, Coaxial, RG-226/U.
MIL-C-17/90 - Cables, Radio Frequency, Coaxial, 93 Ohms, M17/90-RG71.
MIL-C-17/92 - Cable, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/92-RG115.
MIL-C-17/93 - Cable, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/93-RG178 and M17/93-00001.
MIL-C-17/94 - Cables, Radio Frequency, Flexible, Coaxial, 75 Ohms, M17/094-RG179.
MIL-C-17/95 - Cables, Radio Frequency, Flexible, Coaxial, 95 Ohms, M17/095-RG180.
MIL-C-17/97 - Cables, Radio Frequency, Flexible, Coaxial, 93 Ohms, M17/97-RG210.
MIL-C-17/100 - Cable, Radio Frequency, Flexible, Coaxial, 95 Ohms, M17/100-RG133.
MIL-C-17/110 - Cable, Radio Frequency, Flexible, Coaxial, 75 Ohms, M17/110-RG302.
MIL-C-17/111 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/111-RG303.
MIL-C-17/112 - Cable, Radio Frequency, Flexible, Coaxial, M17/112-RG304.
MIL-C-17/113 - Cable, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/113-RG316.
MIL-C-17/116 - Cables, Radio Frequency, Flexible, Triaxial, 75 Ohms, M17/116-RG307.
MIL-C-17/119 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/119-RG174.
MIL-C-17/124 - Cables, Radio Frequency, Flexible, Triaxial, Pulse, 25 Ohms, M17/124-RG328.
MIL-C-17/126 - Cables, Radio Frequency, Coaxial, Low Noise, 72 Ohms, M17/126-RG391 (Unarmored), M17/126-RG392 (Armored).
MIL-C-17/127 - Cable, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/127-RG393.
MIL-C-17/128 - Cable, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/128-RG400.
MIL-C-17/129 - Cables, Radio Frequency, Coaxial, 0.250 Diameter, Semirigid, 50 Ohms, M17/129-RG401 and M17/129-00001.
MIL-C-17/130 - Cables, Radio Frequency, Coaxial, 0.141 Diameter, Semirigid, 50 Ohms, M17/130-RG402 and M17/130-00001 through M17/130-00003.
MIL-C-17/131 - Cables, Radio Frequency, Flexible, Triaxial, 50 Ohms, M17/131-RG403.
MIL-C-17/132 - Cables, Radio Frequency, Coaxial, Low Noise, 50 Ohms, M17/132-RG404.
MIL-C-17/133 - Cables, Radio Frequency, Coaxial, 0.086 Diameter, Semirigid, 50 Ohms, M17/133-RG405, M17/133-00001 through -00005.
MIL-C-17/134 - Cable, Radio Frequency, Triaxial, 0.245 Inch, 50 Ohm Waterblocked, Non-Water Blocked.
MIL-C-17/135 - Cable, Radio Frequency, Triaxial, Diameter 0.500 Inch, 50 Ohm, Waterblocked and Non-Waterblocked.
MIL-C-17/136 - Cable, Radio Frequency, Flexible, Coaxial, 75 Ohms, M17/136-00001.
MIL-C-17/137 - Cable, Radio Frequency, Flexible, Coaxial, 95 Ohms, M17/137-00001.
MIL-C-17/138 - Cable, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/138-00001.
MIL-C-17/139 - Cable, Radio Frequency, Flexible, Coaxial, 95 Ohms, M17/139-00001.
MIL-C-17/151 - Cables, Radio Frequency, Coaxial, 0.047 Inch Diameter, Semirigid, 50 Ohms, M17/151-00001 and M17/151-00002.

* Inactive for new design.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:57Z
Check the source to verify that this is the current version before use.

MIL-C-17/152 - Cable, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/152-00001.
MIL-C-17/154 - Cables, Radio Frequency, Coaxial, 0.034 Inch Diameter, Semirigid, 50 Ohms, M17/154-00001 and M17/154-00002.
MIL-C-17/155 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/155-00001.
MIL-C-17/156 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/156-00001.
MIL-C-17/157 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/157-00001.
MIL-C-17/158 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/158-00001.
MIL-C-17/159 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/159-00001.
MIL-C-17/160 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/160-00001.
MIL-C-17/161 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/161-00001.
MIL-C-17/162 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/162-00001.
MIL-C-17/163 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/163-00001.
MIL-C-17/164 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/164-00001.
MIL-C-17/165 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/165-00001.
MIL-C-17/166 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/166-00001.
MIL-C-17/167 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/167-00001.
MIL-C-17/168 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/168-00001.
MIL-C-17/169 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/169-00001.
MIL-C-17/170 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/170-00001.
MIL-C-17/171 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/171-00001.
MIL-C-17/172 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/172-00001.
MIL-C-17/173 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/173-00001.
MIL-C-17/174 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/174-00001.
MIL-C-17/175 - Cables, Radio Frequency, Flexible, Coaxial, 50 Ohms, M17/175-00001.
MIL-C-17/176 - Cables, Radio Frequency, Flexible, Twin, MIL-C-17/176-00002.
MIL-C-17/177 - Cables, Radio Frequency, Flexible, Triaxial, 95 ohms, M17/177-00001.
MIL-C-17/178 - Cables, Radio Frequency, Flexible, Triaxial, 95 ohms, M17/178-00001.
MIL-C-17/179 - Cables, Radio Frequency, Flexible, Triaxial, 75 ohms, M17/179-00001.
MIL-C-17/180(EC) - Cable, Radio Frequency, Flexible Coaxial, 75 ohms, M17/180-00001.
MIL-C-17/181(EC) - Cables, Radio Frequency, Flexible Coaxial, 75 ohms, M17/181-00001 Unarmored, M17/181-00002 Armored.
MIL-C-17/182(EC) - Cables, Radio Frequency, Flexible, Twin, 95 ohms, M17/182-00001 Unarmored, M17/182-00002 Armored.
MIL-C-17/183(EC) - Cables, Radio Frequency, Flexible, Coaxial, 50 ohms, M17/183-00001.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:57Z
Check the source to verify that this is the current version before use.

MIL-C-17/184(EC) - Cables, Radio Frequency, Flexible, Coaxial, 75 ohms, M17/184-00001.
MIL-C-17/185(EC) - Cables, Radio Frequency, Flexible, Coaxial, 93 ohms, M17/185-00001.
MIL-C-17/186(EC) - Cables, Radio Frequency, Flexible, Twin, 78 ohms, M17/186-00001.
MIL-C-17/187(EC) - Cables, Radio Frequency, Flexible, Coaxial, 50 ohms, M17/187-00001.
MIL-C-17/188(EC) - Cables, Radio Frequency, Flexible, Coaxial, 50 ohms, M17/188-00001.
MIL-C-17/189(EC) - Cables, Radio Frequency, Flexible, Coaxial, 50 ohms, M17/189-00001 Unarmored, M17/189-00002 Armored.
MIL-C-17/190(EC) - Cables, Radio Frequency, Flexible, Coaxial, 50 ohms, M17/190-00001.
MIL-C-17/191(EC) - Cable, Radio Frequency, Flexible, Coaxial, 75 ohms, M17/191-00001.
MIL-C-17/192(EC) - Cables, Radio Frequency, Flexible, Coaxial, 50 ohms, M17/192-00001.
MIL-C-17/193(EC) - Cables, Radio Frequency, Flexible, Coaxial, 50 ohms, M17/193-00001 Unarmored, M17/193-00002 Armored.
MIL-C-17/194(EC) - Cables, Radio Frequency, Flexible, Coaxial, 50 ohms, M17/194-00001.
MIL-C-17/195(EC) - Cables, Radio Frequency, Coaxial, 93 ohms, M17/195-00001.
MIL-C-17/196(EC) - Cables, Radio Frequency, Flexible, Coaxial, 50 ohms, M17/196-00001.
MIL-C-17/197(EC) - Cables, Radio Frequency, Flexible, Coaxial, 50 ohms, M17/197-00001.
MIL-C-17/198(EC) - Cables, Radio Frequency, Coaxial, 50 ohms, M17/198-00001.
MIL-C-17/199(EC) - Cables, Radio Frequency, Flexible, Coaxial, 50 ohms, M17/199-00001.
MIL-C-17/200(EC) - Cables, Radio Frequency, Flexible, Coaxial, 50 ohms, M17/200-00001.

RF Cable Selection Guide.

50 ohms, flexible, coaxial.

Part number	Overall diameter (OD)	Temp (°C)	Jacket	Frequency (GHz)	Notes
M17/93-RG178	.071 ±.004	-55 to +200	FEP	3	1/
M17/169-00001	.071 ±.004	-55 to +200	FEP		1/ 2/
M17/132-RG404	.071 ±.004	-55 to +200	FEP	3	Low noise 1/
M17/113-RG316	.098 ±.004	-55 to +200	FEP	3	1/
M17/172-00001	.098 ±.004	-55 to +200	FEP		1/ 2/
M17/138-00001	.098 ±.004	-55 to +200	PFA	3	1/
M17/119-RG174	.110 ±.004	-40 to +85	PVC	1	1/
M17/173-00001	.110 ±.004	-40 to +85	PVC		1/ 2/
M17/196-00001	.110 ±.005	-40 to +85	3/	1	1/
M17/152-00001	.114 ±.004	-55 to +200	FEP	12.4	1/
M17/54-RG122	.160 ±.005	-40 to +85	PVC	1	1/
M17/157-00001	.160 ±.005	-40 to +85	PVC		1/ 2/
M17/187-00001	.160 ±.005	-40 to +85	3/	1	1/
M17/198-00001	.160 ±.005	-40 to +85	3/		1/ 2/
M17/111-RG303	.170 ±.005	-55 to +200	FEP	3	4/
M17/170-00001	.170 ±.005	-55 to +200	FEP		2/ 4/
M17/028-RG058	.195 ±.004	-40 to +85	PVC	1	1/
M17/155-00001	.195 ±.004	-40 to +85	PVC		1/ 2/
M17/60-RG142	.195 ±.004	-55 to +200	FEP	12.4	4/

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:57Z
Check the source to verify that this is the current version before use.

50 ohms, flexible, coaxial - Continued.

Part number	Overall diameter (OD)	Temp (°C)	Jacket	Frequency (GHz)	Notes
M17/158-00001	.195 ±.004	-55 to +200	FEP		2/ 4/
M17/128-RG400	.195 ±.004	-55 to +200	FEP	12.4	1/
M17/175-00001	.195 ±.004	-55 to +200	FEP		1/ 2/
M17/183-00001	.195 ±.004	-40 to +85	3/	1	1/
M17/197-00001	.195 ±.004	-40 to +85	3/		1/ 2/
M17/84-RG223	.212 ±.004	-40 to +85	PVC	12.4	4/
M17/167-00001	.212 ±.004	-40 to +85	PVC		2/ 4/
M17/194-00001	.212 ±.004	-40 to +85	3/	12.4	4/
M17/200-00001	.212 ±.004	-40 to +85	3/		2/ 4/
M17/112-RG304	.280 ±.005	-55 to +200	FEP	12.4	4/
M17/171-00001	.280 ±.005	-55 to +200	FEP		2/ 4/
M17/73-RG212	.332 ±.004	-40 to +85	PVC	11	4/
M17/162-00001	.332 ±.004	-40 to +85	PVC		2/ 4/
M17/188-00001	.332 ±.004	-40 to +85	3/	11	4/
M17/199-00001	.332 ±.004	-40 to +85	3/		2/ 4/
M17/127-RG393	.390 ±.010	-55 to +200	FEP	10	1/
M17/174-00001	.390 ±.010	-55 to +200	FEP		1/ 2/
M17/86-00001	.430 ±.010	-55 to +200	Fiberglass	10	1/ 5/
M17/87-00001	.500 ±.010	-55 to +200	Fiberglass	10	.198 OD 1/ 5/ 6/ 7/
M17/74-RG213	.405 ±.007	-40 to +85	PVC	1	1/
M17/163-00001	.405 ±.007	-40 to +85	PVC		1/ 2/
M17/74-RG215	.405 ±.007	-40 to +85	PVC	1	.475 OD 3/ 5/
M17/189-00001	.405 ±.007	-40 to +85	3/	1	1/
M17/65-RG165	.410 ±.010	-55 to +250	Fiberglass	3	1/
M17/159-00001	.410 ±.010	-55 to +250	Fiberglass		1/ 2/
M17/65-RG166	.410 ±.010	-55 to +250	Fiberglass	3	.470 OD 1/ 7/
M17/92-RG115	.415 ±.015	-55 to +250	Fiberglass	12.4	1/
M17/168-00001	.415 ±.015	-55 to +250	Fiberglass		1/ 2/
M17/75-RG214	.425 ±.007	-40 to +85	PVC	11	1/
M17/164-00001	.425 ±.007	-40 to +85	PVC		1/ 2/
M17/190-00001	.425 ±.007	-40 to +85	3/	11	1/
M17/52-RG119	.465 ±.010	-55 to +200	Fiberglass	3	4/
M17/156-00001	.465 ±.010	-55 to +200	Fiberglass		4/ 2/
M17/52-RG120	.465 ±.010	-55 to +200	Fiberglass	3	.525 OD 4/ 7/
M17/78-RG217	.545 ±.010	-40 to +85	PVC	3	4/
M17/165-00001	.545 ±.010	-40 to +85	PVC		2/ 4/
M17/78-RG224	.545 ±.010	-40 to +85	PVC	3	.615 OD 4/ 5/ 6/ 7/
M17/192-00001	.545 ±.010	-40 to +85	3/	3	4/
M17/72-RG211	.730 ±.015	-55 to +200	Fiberglass	1	4/ 5/
M17/161-00001	.730 ±.015	-55 to +200	Fiberglass		2/ 4/
M17/89-RG228	.730 ±.015	-55 to +200	Fiberglass	1	.795 OD 4/ 5/ 6/ 7/
M17/79-RG218	.870 ±.010	-40 to +85	PVC	1	4/
M17/166-00001	.870 ±.010	-40 to +85	PVC		2/ 4/
M17/79-RG219	.870 ±.010	-40 to +85	PVC	1	.945 OD 4/ 7/
M17/193-00001	.870 ±.010	-40 to +85	3/	1	4/
M17/67-RG177	.895 ±.015	-40 to +85	PVC	5.6	4/
M17/160-00001	.895 ±.015	-40 to +85	PVC		2/ 4/
M17/81-RG220	1.120 ±.015	-40 to +85	PVC	1	1/ 2/ 4/

1/ Stranded inner conductor.
2/ Non-swept cable.
3/ Cross-linked polyolefin.
4/ Solid inner conductor.
5/ To be revised.
6/ Inactive for new design.
7/ Armor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:57Z
Check the source to verify that this is the current version before use.

Cross-reference, swept cable to non-swept counterpart.

Swept	Non-swept
MIL-C-17/28	MIL-C-17/155
MIL-C-17/52	MIL-C-17/156
MIL-C-17/54	MIL-C-17/157
MIL-C-17/60	MIL-C-17/158
MIL-C-17/65	MIL-C-17/159
MIL-C-17/67	MIL-C-17/160
MIL-C-17/72	MIL-C-17/161
MIL-C-17/73	MIL-C-17/162
MIL-C-17/74	MIL-C-17/163
MIL-C-17/75	MIL-C-17/164
MIL-C-17/78	MIL-C-17/165
MIL-C-17/79	MIL-C-17/166
MIL-C-17/84	MIL-C-17/167
MIL-C-17/92	MIL-C-17/168
MIL-C-17/93	MIL-C-17/169
MIL-C-17/111	MIL-C-17/170
MIL-C-17/112	MIL-C-17/171
MIL-C-17/113	MIL-C-17/172
MIL-C-17/119	MIL-C-17/173
MIL-C-17/127	MIL-C-17/174
MIL-C-17/128	MIL-C-17/175
MIL-C-17/183	MIL-C-17/197
MIL-C-17/187	MIL-C-17/198
MIL-C-17/188	MIL-C-17/199
MIL-C-17/194	MIL-C-17/200

50 ohms, semirigid, coaxial.

Part number	Overall diameter (OD)	Temp (°C)	Jacket	Frequency (GHz)	Notes
M17/154-00001	.034 ±.001	-40 to +100	Copper	20	1/
M17/154-00002	.034 +.002, -.001	-40 to +100	Copper	20	1/ 2/
M17/151-00001	.047 ±.001	-40 to +100	Copper	20	1/
M17/151-00002	.047 +.002, -.001	-40 to +100	Copper	20	1/ 2/
M17/133-RG405	.086 ±.001	-40 to +100	Copper	20	17
M17/133-00001	.086 +.002, -.001	-40 to +100	Copper	20	1/ 2/
M17/133-00002	.086 ±.001	-40 to +100	Copper	20	3/
M17/133-00003	.086 +.002, -.001	-40 to +100	Copper	20	2/ 3/
M17/133-00004	.086 ±.001	-40 to +100	Copper	20	47
M17/133-00005	.086 +.002, -.001	-40 to +100	Copper	20	2/ 4/
M17/130-RG402	.141 ±.001	-40 to +100	Copper	20	17
M17/130-00001	.141 +.002, -.001	-40 to +100	Copper	20	1/ 2/
M17/130-00002	.141 ±.001	-40 to +100	Copper	20	47
M17/130-00003	.141 +.002, -.001	-40 to +100	Copper	20	2/ 4/
M17/129-RG401	.250 ±.001	-40 to +125	Copper	18	17
M17/129-00001	.250 +.002, -.001	-40 to +125	Copper	18	1/ 2/

1/ Silver copperweld center conductor.
2/ Tinned OD.
3/ Silver copper center conductor.
4/ Nickel-coated, copper-clad steel center conductor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:57Z
Check the source to verify that this is the current version before use.

75 ohms, coaxial.

Part number	Overall diameter (OD)	Temp (°C)	Jacket	Notes
M17/94-RG179	.100 ±.005	-55 to +200	FEP	1/ 2/
M17/110-RG302	.202 ±.005	-55 to +200	FEP	2/
M17/179-00001	.240 maximum	-55 to +150	Polyester braid	1/
M17/29-RG59	.242 ±.004	-40 to +85	PVC	2/
M17/184-00001	.242 ±.004	-40 to +85	4/	
M17/2-RG6	.332 ±.004	-40 to +85	PVC	2/ 3/
M17/180-00001	.332 ±.004	-40 to +85	4/	3/
M17/6-RG11	.405 ±.007	-40 to +85	PVC	1/
M17/181-00001	.405 ±.007	-40 to +85	4/	
M17/62-RG144	.410 ±.010	-55 to +200	Fiberglass	1/ 2/
M17/77-RG216	.425 ±.007	-40 to +85	PVC	1/
M17/191-00001	.425 ±.007	-40 to +85	4/	3/
M17/6-RG12	.475 maximum	-40 to +85	PVC (aluminum)	Armored M17/6-RG11 1/
M17/24-RG34	.630 ±.010	-40 to +85	PVC	1/
M17/64-RG164	.870 ±.010	-40 to +85	PVC	
M17/64-RG35	.945 maximum	-40 to +85	PVC (aluminum)	Armored M17/64-RG164
M17/40-RG85	.565 maximum	-40 to +85	PVC	

1/ Stranded center conductor.
2/ Copperweld.
3/ Double shield.
4/ Cross-linked polyolefin.

Various impedances, flexible, coaxial.

Part number	Ohms	Overall diameter (OD)	Jacket	Temp (°C)	Notes
M17/126-RG391	72 ±3	.405 ±.010	PVC	-40 to +85	1/ Low noise
M17/126-RG392	72 ±3	.475 maximum	PVC (aluminum)	-40 to +85	1/ 2/ Low noise
M17/095-RG180	95 ±5	.141 ±.004	FEP	-55 to +200	1/
M17/177-00001	95 ±5	.184 ±.004	FEP	-55 to +200	1/
M17/97-RG210	93 ±5	.242 ±.008	Fiberglass	-55 to +200	3/
M17/030-RG062	93 ±5	.242 ±.007	PVC	-40 to +85	3/
M17/185-00001	93 ±5	.242 ±.007	5/	-40 to +85	
M17/90-RG71	93 ±5	.245 ±.005	Polyethylene	-55 to +80	3/
M17/195-00001	93 ±5	.245 ±.005	5/	-40 to +85	
M17/178-00001	95 ±5	.305 maximum	Polyester braid	-55 to +150	1/
M17/100-RG133	95 ±5	.405 ±.010	PVC	-40 to +85	
M17/31-RG63	125 ±6	.405 ±.010	PVC	-40 to +85	3/
M17/31-RG79	125 ±6	.475 maximum	PVC (aluminum)	-40 to +85	3/ 4/
M17/47-RG114	185 ±10	.405 ±.010	PVC	-40 to +85	3/

1/ Stranded center conductor.
2/ Armored.
3/ Copperweld.
4/ Inactive for new design.
5/ Cross-linked polyolefin.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:57Z
Check the source to verify that this is the current version before use.

Special application.

Part number	Application	Ohms	Overall diameter (OD)	Jacket	Temp (°C)	Notes
M17/45-RG108	Twin axial	78 ±7	.235 ±.010	PVC	-40 to +80	2/
M17/186-00001	Twin axial	78 ±7	.235 ±.010	1/	-40 to +80	2/
M17/182-00001	Twin axial	95 ±5	.420 ±.010	1/	-40 to +80	2/ Double shield
M17/56-RG130	Twin axial	95 ±5	.625 ±.015	PVC	-40 to +80	2/ 3/
M17/56-RG131	Twin axial	95 ±5	.710 maximum	PVC (aluminum)	-40 to +80	2/ 3/ 4/
M17/015-RG022	Twin axial	95 ±5	.420 ±.010	PVC	-40 to +80	3/ Double shield
M17/015-RG111	Twin axial	95 ±5	.490 maximum	PVC (aluminum)	-40 to +80	2/ 4/ Double shield
M17/16-RG23	Twin axial	125 ±5	.650 ±.020	PVC	-40 to +80	2/ Double shield each core shielded
M17/16-RG24	Twin axial	125 ±5	.735 maximum	PVC (aluminum)	-40 to +80	2/ 4/ Double shielded each core shielded
M17/34-RG65	Time delay	950 ±50	.405 ±.010	PVC	-40 to +80	5/
M17/176-00002	Twin axial	77 ±7	0.145	PFA	-55 to +200	2/ 6/

1/ Cross-linked polyolefin.
2/ Stranded center conductor.
3/ To be revised.
4/ Armored.
5/ Core center conductor.
6/ Data buss applications for MIL-STD-1760.

Pulse.

Part number	Ohms	O.D.	Jacket	Temp (°C)	Notes
M17/131-RG403	50 ±2	.116 ±.012	FEP	-55 to +200	4/ 2/ Triaxial
M17/116-RG307	75 ±4	.265 ±.005	Polyethylene	-55 to +80	4/ 2/ Triaxial
M17/21-RG26	48 ±4	.425 ±.015	Rubber	-40 to +80	1/ 3/
		.575 maximum	Aluminum	-40 to +80	
M17/33-RG64	48 ±4	.460 ±.015	Rubber	-40 to +80	4/ Double braid
M17/19-RG25	48 ±4	.505 ±.015	Rubber	-40 to +80	4/ Triaxial
M17/22-00001	48 ±4	.595 ±.015	Rubber	-40 to +80	4/
M17/22-RG27	48 ±4	.670 maximum	Aluminum	-40 to +80	4/ 3/
M17/125-RG329	50 ±4	.700 ±.020	Rubber	-40 to +80	4/ Triaxial
M17/23-RG28	48 ±4	.735 ±.020	Rubber	-40 to +80	4/ Triaxial
M17/124-RG328	25 ±2.5	1.460 ±.020	Polyethylene	-55 to +80	4/ 5/ Triaxial

1/ Stranded center conductor.
2/ Copperweld.
3/ Armored.
4/ Inactive for new design.
5/ Cord center conductor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:57Z
Check the source to verify that this is the current version before use.

Cross reference, PVC to polyolefin.

Cross-linked polyolefin	PVC jacket
MIL-C-17/180	MIL-C-17/2
MIL-C-17/181	MIL-C-17/6
MIL-C-17/182	MIL-C-17/15
MIL-C-17/183	MIL-C-17/28
MIL-C-17/184	MIL-C-17/29
MIL-C-17/185	MIL-C-17/30
MIL-C-17/186	MIL-C-17/45
MIL-C-17/187	MIL-C-17/54
MIL-C-17/188	MIL-C-17/73
MIL-C-17/189	MIL-C-17/74
MIL-C-17/190	MIL-C-17/75
MIL-C-17/191	MIL-C-17/77
MIL-C-17/192	MIL-C-17/78
MIL-C-17/193	MIL-C-17/79
MIL-C-17/194	MIL-C-17/84
MIL-C-17/195	MIL-C-17/90
MIL-C-17/196	MIL-C-17/119
MIL-C-17/197	MIL-C-17/155
MIL-C-17/198	MIL-C-17/157
MIL-C-17/199	MIL-C-17/162
MIL-C-17/200	MIL-C-17/167

RG cross reference.

RG number	Initial specification sheet number	Current specification sheet number or status	Connector accommodation series
5B	MIL-C-17/1	MIL-C-17/162	
6A	MIL-C-17/2		N, SC
8A	MIL-C-17/3	MIL-C-17/163	
9B	MIL-C-17/4	MIL-C-17/164	
10	MIL-C-17/5	MIL-C-17/74	
11	MIL-C-17/6		N, C, SC
12	MIL-C-17/7	MIL-C-17/6	
13	MIL-C-17/8	MIL-C-17/77	
14	MIL-C-17/9	MIL-C-17/165	
17	MIL-C-17/10	MIL-C-17/166	
18	MIL-C-17/11	MIL-C-17/166	
19	MIL-C-17/12	MIL-C-17/81	
20	MIL-C-17/13	MIL-C-17/81	
21	MIL-C-17/14	MIL-C-17/162	
22	MIL-C-17/15		MIL-C-3655
23	MIL-C-17/16		MIL-C-3655
24	MIL-C-17/17	MIL-C-17/16	
25	MIL-C-17/18	MIL-C-17/19	MIL-C-3607
26	MIL-C-17/20	MIL-C-17/21	MIL-C-3607
27	MIL-C-17/22		MIL-C-3607
28	MIL-C-17/23	Canceled	
29		replaced by RG58	
34	MIL-C-17/24		
35	MIL-C-17/25	MIL-C-17/64	
55	MIL-C-17/26	MIL-C-17/167	

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:57Z
Check the source to verify that this is the current version before use.

RG cross reference - Continued.

RG number	Initial specification sheet number	Current specification sheet number or status	Connector accommodation series
57	MIL-C-17/27	MIL-C-17/56	
58	MIL-C-17/28	MIL-C-17/155	TNC, BNC, SMA
59	MIL-C-17/29		TNC, BNC, SMA
62A	MIL-C-17/30		TNC, BNC
62B	MIL-C-17/91 (USAF)	MIL-C-17/97	
63	MIL-C-17/31		N, C, SC
64	MIL-C-17/32	MIL-C-17/33	MIL-C-3607
65	MIL-C-17/34		TNC, BNC
71	MIL-C-17/90		
74A	MIL-C-17/35	MIL-C-17/165	
79	MIL-C-17/36	MIL-C-17/31	
81	MIL-C-17/37	Canceled	
82	MIL-C-17/38	Canceled	
84	MIL-C-17/39	Canceled	
85	MIL-C-17/40		
86	MIL-C-17/41	Canceled	
87A	MIL-C-17/42	MIL-C-17/86	
88	MIL-C-17/43	Inactive	
94	MIL-C-17/44	MIL-C-17/87	
108	MIL-C-17/45		MIL-C-3655
111	MIL-C-17/46	MIL-C-17/15	
114	MIL-C-17/47		N, C, SC
115	MIL-C-17/48	MIL-C-17/168	
116	MIL-C-17/49	MIL-C-17/86	
117	MIL-C-17/50	MIL-C-17/72	
118	MIL-C-17/51	MIL-C-17/161	
119	MIL-C-17/52	MIL-C-17/156	MIL-C-3643
120	MIL-C-17/53	MIL-C-17/52	
122	MIL-C-17/54	MIL-C-17/157	TNC, BNC, SMA
126	MIL-C-17/55	Canceled	
130	MIL-C-17/56		MIL-C-3655
131	MIL-C-17/57	MIL-C-17/56	
133	MIL-C-17/100		
140	MIL-C-17/58	MIL-C-17/110	
141	MIL-C-17/59	MIL-C-17/170	
142	MIL-C-17/60	MIL-C-17/158	TNC, BNC, SMA
143	MIL-C-17/61	MIL-C-17/112	
144	MIL-C-17/62		N, SC
146	MIL-C-17/63	Canceled	
149	MIL-C-17/117	MIL-C-17/126	
150	MIL-C-17/117	MIL-C-17/126	
151	MIL-L-3890/1		
152	MIL-L-3890/1		
153	MIL-L-3890/1		
154	MIL-L-3890/1		
155	MIL-L-3890/1		
156	MIL-C-17/101	Canceled	
157	MIL-C-17/102	Canceled	
158	MIL-C-17/103	Canceled	
161	MIL-C-17/118	Canceled	
164	MIL-C-17/64		
165	MIL-C-17/65	MIL-C-17/159	N, C, SC, HN
166	MIL-C-17/66	MIL-C-17/65	
174	MIL-C-17/119	MIL-C-17/173	SMA, SMB
176	MIL-C-17/120	Canceled	
177	MIL-C-17/67	MIL-C-17/160	N, HN
178	MIL-C-17/93	MIL-C-17/169	SMA, SMB, SMC

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:57Z
Check the source to verify that this is the current version before use.

RG cross reference - Continued.

RG number	Initial specification sheet number	Current specification sheet number or status	Connector accommodation series
179	MIL-C-17/94		SMA, SMB, SMC
180	MIL-C-17/95		TNC, BNC
181	MIL-C-17/104	Canceled	
187	MIL-C-17/68	MIL-C-17/94	
188	MIL-C-17/69	MIL-C-17/113	
190	MIL-C-17/105	Canceled	
191	MIL-C-17/106	Canceled	
195	MIL-C-17/70	MIL-C-17/95	
196	MIL-C-17/71	MIL-C-17/169	
209	MIL-C-17/96	Canceled	
210	MIL-C-17/97		TNC, BNC
211	MIL-C-17/72	MIL-C-17/161	C, SC, LT
212	MIL-C-17/73	MIL-C-17/162	N, C, SC
213	MIL-C-17/74	MIL-C-17/163	N, C, SC
214	MIL-C-17/75	MIL-C-17/164	N, C, SC
215	MIL-C-17/76	MIL-C-17/163	N
216	MIL-C-17/77		N
217	MIL-C-17/78	MIL-C-17/165	N, SC
218	MIL-C-17/79	MIL-C-17/166	N, C, SC, LC, LT
219	MIL-C-17/80	MIL-C-17/166	
220	MIL-C-17/81	Inactive	QL
221	MIL-C-17/82	MIL-C-17/81	
222	MIL-C-17/83	MIL-C-17/162	
223	MIL-C-17/84		TNC, BNC, SMA
224	MIL-C-17/85	MIL-C-17/165	
225	MIL-C-17/86		
226	MIL-C-17/87		
227	MIL-C-17/88	MIL-C-17/86	
228	MIL-C-17/89	MIL-C-17/161	
230	MIL-C-17/98 (USAF)	Canceled	
231	MIL-C-23806/1		
232	MIL-C-22931/11		
233	MIL-C-22931/13		
234	MIL-C-22931/15		
235	MIL-C-17/99	MIL-C-17/92	
236	MIL-C-22931/9		
237	MIL-C-22931/9		
240	MIL-C-22931/13		
242	MIL-C-22931/15		
244	MIL-C-22931/10		
245	MIL-C-22931/10		
246	MIL-C-22931/12		
247	MIL-C-22931/12		
248	MIL-C-22931/14		
249	MIL-C-22931/14		
250	MIL-C-22931/16		
251	MIL-C-22931/16		
252	MIL-C-22931/9		
253	MIL-C-22931/9		
254	MIL-C-22931/11		
255	MIL-C-22931/11		
257	MIL-C-22931/13		
258	MIL-C-22931/13		
264	MIL-C-23020/4		
265	MIL-C-22931/7		
266	MIL-C-17/122	Canceled	

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:57Z
Check the source to verify that this is the current version before use.

RG cross reference - Continued.

RG number	Initial specification sheet number	Current specification sheet number or status	Connector accommodation series
267	MIL-C-22931/6	MIL-C-22931/11	
268	MIL-C-22931/5	Canceled	
269	MIL-C-22931/11		
270	MIL-C-22931/13		
279	MIL-C-17/123	Canceled	
280	MIL-C-17/107	Canceled	
281	MIL-C-17/108	Canceled	
293	MIL-C-23020/1		
294	MIL-C-23020/2		
295	MIL-C-23020/3		
296	MIL-C-17/114	Canceled	
297	Drawing RE49C781		
298	MIL-C-22667		
299	Waveguide		
300	Waveguide		
301	MIL-C-17/109	Canceled	
302	MIL-C-17/110		TNC, BNC
303	MIL-C-17/111	MIL-C-17/170	TNC, BNC
304	MIL-C-17/112	MIL-C-17/171	TNC, BNC
305	Drawing RE496783 1/		
306	MIL-C-17/115	MIL-C-23806/2	
307	MIL-C-17/116		MIL-C-3607
308 - 315	MIL-R-9671		
316	MIL-C-17/113	MIL-C-17/172	SMA, SMB, SMC
317	MIL-C-23020/5		
318	MIL-C-22931/11		
319	MIL-C-22931/13		
320	MIL-W-85		
321	MIL-C-22931/15		
322	MIL-C-22931/15		
325		Canceled	
326	Drawing SC-DL-598921		
327		Canceled	
328	MIL-C-17/124		MIL-C-3607
329	MIL-C-17/125	Canceled	
330		Canceled	
331 - 336	MIL-C-23806/1 and 2		
337 - 359	MIL-W-85		
360	MIL-C-23806/3		
361	Drawing RE49D826		
363		Canceled	
364		Canceled	
365	SCL 6624/4		
366	Drawing RE49C828		
367	Drawing RE49C829		
369	MIL-C-22931		
370	MIL-C-22931		
375	Waveguide drawing RE49C833		
376 2/			
377	MIL-C-22931		
378	MIL-C-22931/13		
382	MIL-I-3890/3		

1/ Same as RG 290 except FEP.
2/ Same as RG 323 except corrugated aluminum outer conductor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:57Z
Check the source to verify that this is the current version before use.

RG cross reference - Continued.

RG number	Initial specification sheet number	Current specification sheet number or status	Connector accommodation series
385	MIL-C-22931/17		
388	MIL-C-23020		
389	DL-SC-B-459378		
391	MIL-C-17/126		N, SC
392	MIL-C-17/126		
393	MIL-C-17/127	MIL-C-17/174	N
396		Canceled	
399	MIL-C-22931/18		N, HN
400	MIL-C-17/128	MIL-C-17/175	TNC, BNC, SMA
401	MIL-C-17/129		TNC, N
402	MIL-C-17/130		SMA, TNC
403	MIL-C-17/131		
404	MIL-C-17/132		
405	MIL-C-17/133		SMA

Nato preferred cables.

NATO	Military pin	NATO	Military pin
NWR-1	M17/74-RG213	NWR-32	M17/113-RG316
NWR-2	M17/028-RG058	NWR-33	M17/094-RG179
NWR-3	M17/16-RG11	NWR-34	M17/93-RG178
NWR-4	M17/31-RG63	NWR-35	M17/75-RG214
NWR-5	M17/79-RG218	NWR-36	M17/86-00001
NWR-6	M17/64-RG164	NWR-45	M17/119-RG174
NWR-7	M17/100-RG133	NWR-46	M17/133-RG405
NWR-8	M17/33-RG65	NWR-47	M17/054-RG122
NWR-10	M17/65-RG165	NWR-48	M17/84-RG223
NWR-11	M17/29-RG59	NWR-49	M17/130-RG402
NWR-12	M17/030-RG062	NWR-50	M17/73-RG212
NWR-13	M17/72-RG211	NWR-51	M17/129-RG401
NWR-16	M17/62-RG144	NWR-52	M17/78-RG217
NWR-17	M17/74-RG215	NWR-53	M17/77-RG216
NWR-18	M17/6-RG12	NWR-54	M17/97-RG210
NWR-19	M17/79-RG219	NWR-55	M17/90-RG71
NWR-20	M17/64-RG35		
NWR-25	M17/60-RG142		
NWR-29	M17/124-RG328		
NWR-30	M17/111-RG303		
NWR-31	M17/110-RG302		

CONCLUDING MATERIAL

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 6145-1118)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:57Z
Check the source to verify that this is the current version before use.