MILITARY SPECIFICATION SHEET

CABLE, RADIO FREQUENCY, FLEXIBLE COAXIAL,
75 OHMS, M17/2-RG6

This amendment forms a part of Military Specification Sheet MIL-C-17/2A, dated 24 April 1978, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* REQUIREMENTS, Environmental and mechanical, Adhesion of conductors, Inner conductor to core: Delete "4 pounds, minimum; 12 pounds, maximum" and substitute "7 pounds, minimum; 25 pounds, maximum."

* REQUIREMENTS, Electrical, Corona extinction voltage: Delete "2,700 Vrms, minimum" and substitute "3,000 Vrms, minimum."

REQUIREMENTS, Electrical, Capacitance: Delete "20.5 pF per foot, maximum" and substitute "22 pF per foot, maximum."

NOTE: The margin of this amendment is marked with asterisks to indicate where changes (additions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - SH
Air Force - 11, 17, 99
DLA - ES, IS

User activities:
Army - AR, AT, ME
Navy - AS, MC, OS
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project 6145-0793-1)

Source: https://assist.dla.mil - Downloaded: 2026-10-15T15:58Z
Check the source to verify that this is the current version before use.