MILITARY SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, FLEXIBLE COAXIAL, 75 OHMS, M17/6-RG11, UNARMORED, M17/6-RG12, ARMORED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the cables described herein shall consist of this document and the latest issue of Specification MIL-C-17.




FIGURE 1. Configuration.

TABLE I. Description.

Components	Construction details
Inner conductor	Seven strands of tinned, copper wire, .0159 inch each. Overall diameter: .0477 inch ±.0020.
Dielectric core	Type A-1: Solid polyethylene. Diameter: .285 inch ±.007.
Outer conductor	Single braid of AWG #33, bare copper wire. Diameter: .340 inch maximum. Coverage: 95.3% nominal Carriers: 24 Ends: 8 Picks/inch: 6.5% ±10
Jacket	Type IIa. Diameter: .405 inch ±.007.
Armor (M17/6-RG12 only)	Single braid of aluminum-alloy wire. Diameter: .475 inch maximum.

FSC 6145

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:58Z
Check the source to verify that this is the current version before use.

ENGINEERING INFORMATION:

Continuous working voltage: 3,700 Vrms, maximum.
Operating frequency: 1 GHz, maximum.
Velocity of propagation: 65.9 percent, nominal.
Power ratings: See figure 2.
Operating temperature range: -40° to +85°C maximum.
Weight: 9.8 pounds per 100 feet maximum(M17/6-RG11); 14.4 pounds per 100 feet, maximum (M17/6-RG12).

Inner conductor properties:
DC resistance (maximum at 20°C): 1.48 ohms per 100 feet.
Elongation: 20 percent, minimum.
Engineering notes: This cable useful in low temperature applications. (See connector series "N", "C", and "SC" per MIL-C-39012, NATO preferred type NWR3, M17/6-RG11, NATO preferred type NWR18, M17/6-RG12.)

REQUIREMENTS:

Dimensions, configuration, and descriptions: See figure 1 and table I.

Environmental and mechanical:
Visual and mechanical examination: Applicable.
Eccentricity: 10 percent, maximum.
Adhesion of conductors:
Inner conductor to core: 4 pounds, minimum; 15 pounds, maximum.
Aging stability: +98° ±2°C.
Cold bend: -40° ±2C.
Dimensional stability: +85° ±2°C.
Inner conductor from core: 0.062 inch, maximum.
Inner conductor from jacket: 0.125 inch, maximum.
Contamination: Applicable.

Electrical:
Spark test: 5,000 Vrms, minimum.
Voltage withstanding: 10,000 Vrms, minimum.
Corona extinction voltage: 5,000 Vrms, minimum.
Characteristic impedance: 75 ohms ±3.
Attenuation: 5.2 dB per 100 feet, maximum at .4 GHz; 9.4 dB per 100 feet, maximum at 1 GHz.
Structural return loss: Not applicable.
Capacitance 20.5 pF per foot, maximum.

Part number: See table II.

Supersession data: See table II.

TABLE II. Cross reference of part number.

Part number	Superseded part number or type designation
M17/6-RG11	RG-11A/U
M17/6-RG12	RG-12A/U

NOTE: Revision letters are not used to denote changes due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:58Z
Check the source to verify that this is the current version before use.




FIGURE 2. Power rating @ 25°C sea level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-C-17/6B CABLES, RADIO FREQUENCY, FLEXIBLE COAXIAL, 75 OHMS, M17/6-RG11, UNARMORED, M17/6-RG12, ARMORED

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:58Z
Check the source to verify that this is the current version before use.