MIL-C-46372A(MU)
27 FEBRUARY 1964
SUPERSEDING
MIL-C-46372(MU)

MILITARY SPECIFICATION

COLLIMATOR, INFINITY AIMING REFERENCE: M1

1. SCOPE

1.1 This specification covers the Infinity Aiming Reference Collimator, M1 which consists of a collimator with integral tripod and cover. This equipment is referenced throughout this specification as "Collimator".

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-O-13830—Optical Components of Fire Control Instruments: General Specification Governing the Manufacture, Assembly and Inspection of.
MIL-F-13926—Fire Control Materiel: General Specification Governing the Manufacture and Inspection of.
MIL-P-14232—Parts, Equipment and Tools for Ordnance Materiel; Packaging of.
MIL-I-45208—Inspection System Requirements.

STANDARDS

MILITARY

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109—Quality Assurance Terms and Definitions.
MIL-STD-202—Test Methods for Electronic and Electrical Component Parts.

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

F8644275—Collimator, Infinity Aiming Reference: M1.
IEL-8644275—List of Inspection Equipment Numbers for Infinity Aiming Reference: M1.
LSQAP-8644275—List of Supplementary Quality Assurance Provisions List for Collimator, Infinity Aiming Reference: M1.

PACKAGING DATA SHEET

MIL-P-14232/P8644275—Packaging of Collimator, Infinity Aiming Reference: M1.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:45Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. The materials shall be in accordance with the drawings, material specifications and general specifications forming a part of this specification.

3.2 Fabrication. The collimator shall be manufactured in accordance with Drawing F8644275 "Collimator, Infinity Aiming, Reference: M1 and drawings pertaining thereto. The requirements of this specification are detailed only to the extent considered necessary to obtain the desired optical and mechanical characteristics, performance and permanence to insure inherent quality and performance capabilities.

3.3 General specifications. The contractor shall be responsible for adherence to, and compliance with, the following requirements of Specifications MIL–O–13830 and MIL–F–13926.

3.3.1 *MIL–O–13830.*

(a) Cleanliness.
(b) Illuminated reticle.

3.3.2 *MIL–F–13926.*

(a) Order of precedence.
(b) Dimensions and tolerances.
(c) Inorganic protective surface finishes.
(d) Part identification and marking.
(e) Workmanship.

3.4 Environmental.

3.4.1 *Storage temperatures.* The collimator shall show no evidence of physical failure and shall meet all requirements of this specification at standard ambient temperature, +60° F. to +90° F. after having been exposed and thermally stabilized at ambient temperatures of —80° F. and +160° F.

3.4.2 *Operating temperatures.* The collimator shall meet the applicable requirements of 3.9 to 3.9.4 inclusive while exposed to and thermally stabilized at ambient temperatures of +150° F. and —40° F. Upon return to standard ambient temperature the collimator shall be subjected to the requirements of 3.4.3.

3.4.3 *Vibration.* The collimator unit enclosed in its cover with the tripod legs secured in place, shall be vibrated while in a horizontal position at a constant frequency of 30 cycles per second with an amplitude of $\frac{1}{16}$ inch ($\frac{1}{8}$ inch maximum excursion) for a period of 5 minutes plus or minus 15 seconds. Subsequent to vibration the collimator shall meet the requirements of 3.5 to 3.11.4 inclusive.

3.5 Cleanliness. Subsequent to vibration the optical system shall meet the cleanliness requirements of Specification MIL–O–13830 and there shall be no more than 3 particles of dirt visible on the reticle and the area of such particle shall not be in excess of the area equivalent to a size 10 dig. There shall be no dirt within the optical system which interferes with observation or adversely affects image quality.

3.6 Sealing.

3.6.1 *Collimator unit (telescope).* The collimator unit shall show no evidence of leakage when subjected to an internal pressure of dry nitrogen of 5 psi for a period of five minutes. The dew point of the nitrogen shall be at least as low as minus 25° F. The collimator shall not be immersed in water to determine area of leakage.

3.6.2 *Rain.* The collimator unit with the cover secured in place and the legs folded to the carrying position shall be exposed to the requirements of Procedure I of the rain test specified in Specification MIL–F–13926. Immediately following the rain test the interior of the cover or the collimator shall show no evidence of water penetration.

3.7 Accuracy.

3.7.1 *Reticle lean.* With the zero vertical reticle line parallel to the image of a plumb line the bubble of the level vial shall be within the central graduation marks on the vial.

3.7.2 *Reticle accuracy.* The angle subtended by the two 50 mil graduation lines on the horizontal axis of the reticle pattern shall be 100 mils plus or minus 0.25 mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:45Z
Check the source to verify that this is the current version before use.

3.7.3 *Parallax.* The parallax between the center cross of the reticle pattern and the image of an infinity target shall not exceed 0.1 mil.

3.8 **Mechanical.**

3.8.1 *Elevation travel.* The elevation travel of the line of sight shall cover the minimum excursion from minus 800 mils to plus 800 mils when the tripod legs are fully extended.

3.8.2 *Azimuth travel.* The instrument shall provide a full and unrestricted 6400 mils azimuth rotation.

3.8.3 *Open sight.* The line of sight of the open sight shall be parallel to the optical axis within one degree.

3.9 **Operability.** There shall be no looseness of assembly, shake, restriction or binding of any part of the equipment when the collimator is placed from the carrying position to operational position. The hinge of the tripod legs shall have sufficient torque to support the fully extended legs in a horizontal position.

3.9.1 *Knob travel.* Each knob shall provide full locking to free movement of the instrument component.

3.9.2 *Knob locks.* The locks shall be operable when exposed to the requirements of 3.4.2 and shall meet the requirements of Table I when exposed to temperatures of +60° F. to +90° F. The part shall not move when the test value is applied.

TABLE I. *Knob Locks*

Lock control	*Torque to secure (inch pounds)*	*Value to test*
Rotate collimator on tripod	25	50 inch pounds of torque
Cross level the collimator	25	50 inch pounds of torque
Elevate the collimator	25	10 foot pounds of torque
Telescope of tripod legs	25	40 pounds of force

3.9.3 *Scope alinement.* With the lock released the minimum torque required to rotate the scope to center the level vial shall not be less than 8 inch pounds and the maximum torque required shall not exceed 22 inch pounds when checked at standard ambient temperature. The maximum torque shall not exceed 35 inch pounds when checked at extreme temperature of 3.4.2.

3.9.3.1 *Azimuth fine adjustment.* The torque required to operate the azimuth fine adjustment knob shall not exceed 5 inch pounds when checked at standard ambient temperatures and not to exceed this value by more than one hundred percent when exposed to and checked at extreme temperatures of 3.4.2.

3.9.4 *Lamp housing.* When exposed to the extreme temperatures of 3.4.2 lamp housing and lamp shall be removable and replaceable on the collimator.

3.10 **Electrical.**

3.10.1 *Reticle illumination.* With the reticle light energized by a 12 volt power source, the reticle shall appear clearly defined when observed in a dark room through a four power telescope.

3.10.2 *Circuitry.* The circuitry of the collimator assembly shall be in accordance with the applicable electrical schematic drawings.

3.10.3 *Dielectric strength.* There shall be no puncture of insulation, no sparkover, no decrease in dielectric strength, when the insulated areas of the circuitry is subjected to an alternating current (ac) root mean square (rms) potential of 1000 volts plus twice the rated voltage at a frequency of 60 cycles per second (cps) for a period of not more than 30 seconds nor less than 5 seconds.

3.10.4 *Insulation resistance.* Unless otherwise specified on applicable drawings, all insulation between ungrounded circuits and ground, and between isolated circuits, shall have a minimum resistance of 100 megohms with 500 volts direct current (dc) applied.

3.11 **Cover assembly.**

3.11.1 *Fastening devices.* Catches and

Source: https://assist.dla.mil -- Downloaded: 20261O-22T05:45Z
Check the source to verify that this is the current version before use.

similar fastening devices used to secure the cover shall function without interference; and, when secured, shall securely fasten the cover to the base.

3.11.2 *Carrying handle.* The carrying handle shall be securely attached, and show no evidence of looseness of assembly.

3.11.3 *Strap security.* The strap shall be subjected to a direct pull of 25 pounds of ninety degrees to the securing surface, the strap shall remain secure, the rivets firm, and the cover shall subsequently meet the requirements of 3.6.2.

3.11.4 *Gasket and collar.* The rubber gasket at the base of the cover assembly shall be securely attached and show no gap where ends meet. The rubber collar on the cover shall be securely fastened to the cover assembly.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 *General provisions.* The quality assurance provisions of this specification and of other documents referenced herein form the basis for inspection to be performed by the supplier. Inspection shall be in accordance with the requirements of Specification MIL–I–45208 and the component inspection requirements of Specification MIL–F–13926. Definitions of inspection terms not otherwise defined herein shall be as listed in Standard MIL–STD–109.

4.2 Inspection provisions.

4.2.1 *Inspection lot.* Unless otherwise specified by the contracting officer, inspection lot size, formation, and presentation of lots shall be in accordance with "Submission of Product" as specified in Standard MIL–STD–105.

4.2.2 *Examination and tests.* Components and subassemblies shall be inspected in accordance with the inspection provisions contained in Specification MIL–F–13926 and List of Supplementary Quality Assurance Provisions, LSQAP–8644275. Examinations and tests related to Section 3 herein shall be performed on a defect (individual characteristic) basis in accordance with Standard MIL–STD–105, and the inspection level and sampling plans specified in Table II titled "Classification of Defects". Examinations and tests for Packaging, Packing and Marking shall be in accordance with Specification MIL–P–14232 and Section 5 herein. The tabulated classification of defects shall constitute the minimum inspection to be performed by the supplier prior to Government acceptance or rejection by lot. The Government reserves the right to inspect for any applicable requirement, and to reject individual nonconforming items.

TABLE II. *Classification of Defects*
Use Inspection Level II of Table I with Sampling Plan Table II–A of Standard MIL–STD–105

	Requirement	*Test procedure*
Critical: None.		
Major: AQL .65 Percent defective.		
101. Physical failure, post vibration	3.4.3	4.5.1.2
102. Leakage (collimator)	3.6.1	4.5.3.1
103. Cleanliness	3.5	4.5.2
104. Reticle lean	3.7.1	4.5.4.1

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:45Z
Check the source to verify that this is the current version before use.

TABLE II. *Classification of Defects*—Continued

	Requirement	Test procedure
105. Reticle accuracy	3.7.2	4.5.4.2
106. Parallax	3.7.3	4.5.4.3
Major: AQL 1.0 percent defective.		
107. Elevation travel	3.8.1	4.5.5.1
108. Azimuth travel	3.8.2	4.5.5.2
109. Open sight	3.8.3	4.5.5.3
110. Operability (60 to 90°F)	3.9	4.5.6.1
111. Knob travel	3.9.1	4.5.6.2
112. Knob locks	3.9.2	4.5.6.3
113. Torque, scope alinement	3.9.3	4.5.6.4
114. Torque, azimuth fine adjustment	3.9.3.1	4.5.6.5
115. Lamp housing	3.9.4	4.5.6.6
116. Improper reticle illumination	3.10.1	4.5.7.1
117. Circuitry error	3.10.2	4.5.7.2
118. Dielectric strength failure	3.10.3	4.5.7.3
119. Insulation resistance failure	3.10.4	4.5.7.4
120. Fastening devices non-conforming	3.11.1	4.5.8.1
121. Carrying handle insecure	3.11.2	4.5.8.2
122. Strap security failure	3.11.3	4.5.8.3
123. Adherence of Gasket and collar	3.11.4	4.5.8.4
Minor: 4.0 percent defective.		
201. Locking compound on screw heads	3.3.2(e)	Visual
202. Paint finishes	3.3.2(e)	Visual

4.2.3 *Disposition on non-conforming product.* Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in Standard MIL–STD–105.

4.3 Control tests. One collimator shall be selected at random from each 100 produced, or from each month's production, whichever occurs first. Control samples shall be subjected to the following examinations and tests:

Control test	*Requirement*	*Test procedure*
Materials	3.1	Per Dwgs and Specifications
Fabrication	3.2	Per Applicable Dwgs
General Specifications	3.3	MIL–STD–13926 and MIL–O–13930

4.3.2 *Environmental.* Three collimators shall be selected at random from each 50 produced, or from each months production whichever occurs first. Control samples shall have successfully met all acceptance tests herein prior to conducting the following examinations and tests:

Control test	*Requirement*	*Test procedure*
Temperature tests	3.4.1, 3.4.2, 3.9 to 3.9.4 incl.	4.5.1.1. and 4.5.6
Sealing test	3.6.1	4.5.3.1
Rain test	3.6.2	4.5.3.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:45Z
Check the source to verify that this is the current version before use.

4.3.3 *Control test failure.* Should the control test sample fail to meet the specified test requirements, acceptance of the product will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved.

4.4 Inspection equipment. Except as otherwise provided for by the contract, the contractor shall furnish and maintain all required measuring and testing equipment in accordance with the "Measuring and Test Equipment" requirement of Specification MIL–I–45208. The Government reserves the right to use the test equipment for its own independent inspections to the extent that such use will not unduly interfere with the contractor's delivery schedule.

4.4.1 *Government furnished inspection equipment.* Where the contract provides for Government furnished test equipment, care and maintenance of test equipment shall be in accordance with "Measuring and Test Equipment", and "Government Furnished Material" requirements of Specification MIL–I–45208.

4.4.2 *Contractor furnished inspection equipment.*

4.4.2.1 *Government design.* All inspection equipment required by drawings forming a part of the contract and not provided by the Government shall be supplied by the contractor in accordance with the List of Inspection Equipment Numbers, IEL–8644275. Alternate designs may be substituted only as provided by "Inspection Provisions" of Specification MIL–I–45208.

4.4.2.2 *Contractor design.* The contractor shall design and supply inspection equipment compatible with the "Test Methods and Procedures" specified in 4.5, and with the "Component Inspection" requirements of Specification MIL–F–13926. Concept, construction, materials, dimensions, and tolerances used in design of test equipment shall be so selected and controlled as to insure that the test equipment will permit positive rejection of a product which exceeds the prescribed tolerance limit, and will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit. Construction shall be such as to facilitate routine calibration of the equipment.

4.4.2.3 *Devices used for environmental testing.* All environmental testing devices used to determine conformance of the environmental requirements (listed below) shall conform to the "Test Facilities" requirements outlined in Specification MIL–F–13926.

(a) Vibration (3.4.3).
(b) Temperature (3.4.1) (3.4.2) (3.9).
(c) Sealing (3.6).

4.4.2.4 *Device to test reticle lean, reticle accuracy, parallax, elevation travel, and open sight.* This device shall be so constructed as to permit location of the collimator in its normal operating position and shall have sufficient mediums to test the requirements listed above. The mediums noted below shall be to the accuracies stated. Each medium used for measuring reticle lean, reticle accuracy, parallax, elevation travel, and open sight shall have sufficient acceptance and rejection limitation markings or pips marked thereon and shall be within ten (10) percent of the specified tolerance and plumb within twenty-five (25) seconds.

(a) Rigidity, stability, ease of maintenance, and adaptability of set-up and calibration equipment with complete provisions, are prime requirements.
(b) All special set-up and calibration equipment necessary for certification of device accuracy shall be furnished and will become a part of the device.

4.5 Test methods and procedures.

4.5.1 *Environmental tests.*

4.5.1.1 *Storage and operating temperatures.* This test shall be conducted in accord-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:45Z
Check the source to verify that this is the current version before use.

ance with Procedure I of Specification MIL–F–13926. While stabilized at each temperature extreme specified in 3.4.2 the collimator shall be subjected to the tests specified in 4.5.6 through 4.5.6.6 inclusive, and shall conform to the requirements specified therein. Upon completion of the specified exposures and return to standard ambient temperature (60 to 90 degrees Fahrenheit) the collimator shall be inspected and shall show no evidence of glass breakage or other physical failure in accordance with 3.4.1. The collimator shall then be subjected to all the tests in this specification and shall meet the requirements specified therein.

4.5.1.2 *Vibration.* This test shall be conducted in accordance with Procedure V of Specification MIL–F–13926 except that the collimator assembly shall be secured in a horizontal position and the time period shall be as specified in 3.4.3. Subsequent to vibration the collimator assembly shall be subjected to a visual and tactile examination and shall show no evidence of damage. The collimator assembly shall then be subjected to the remaining tests in this specification and shall meet the specified requirements.

4.5.2 *Cleanliness.* Immediately after vibration the optical system of the collimator unit shall be inspected for cleanliness in accordance with Specification MIL–O–13830 and 3.5 herein and shall meet the requirements specified. Dirt particles which interfere with the legibility or accuracy of the reticle pattern shall be cause for rejection. The mean diameter of a size 10 dig is equal to 0.10 millimeter.

4.5.3 *Sealing tests.*

4.5.3.1 *Collimator unit (telescope).* The sealing tests shall be accomplished by means of commercial equipment which shall include a sensitive pressure gage capable of testing to the requirements of 3.6.1. The equipment shall be attached to the collimator unit by means of the 10 x 24 threaded hole in Housing 8644277. The pressure of dry nitrogen gas indicated in 3.6.1 is applied and then cut off. Evidence of leakage can be determined by observing the gage for drop of pressure for time interval specified. Upon completion of the test, the collimator shall be bled to the pretest pressure and sealed.

4.5.3.2 *Leakage, cover (rain).* This test shall be conducted in accordance with Procedure I of the rain test in Specification MIL–F–13926. Upon completion of this test, the cover shall be removed and the collimator and equipment shall be examined for evidence of water penetration or damage in accordance with requirements of 3.6.2.

4.5.4 *Accuracy tests.*

4.5.4.1 *Reticle lean.* Reticle lean test shall be performed with aid of a collimating telescope, herein after referred to as auxiliary telescope; with a reticle plumbed and adjusted to infinity focus. Reticle accuracies shall meet the requirements of 4.4.2.4. Position the collimator in front of the auxiliary telescope so the optical axes are coincident. Align the zero vertical line image of the collimator parallel with the vertical reticle line of the auxiliary telescope. With the zero vertical line image of the collimator plumbed, the bubble of the level vial shall be within the central graduation marks of the vial in accordance with the requirements of 3.7.1.

4.5.4.2 *Reticle accuracy.* This test shall be accomplished with the aid of an auxiliary telescope and calibrated reticle with accuracies as specified in 4.4.2.4. The calibrated reticle shall have a horizontal line 100 mils in length with vertical marks at the center and each end. A mil block at either end of the horizontal line will enable the observer to detect error. With the auxiliary telescope focused on the collimator reticle image, both 50 mil marks of the reticle image shall coincide within the allowable tolerance in accordance with the requirements of 3.7.2.

4.5.4.3 *Parallax.* This test shall be performed with the auxiliary telescope positioned as specified in 4.5.4.1. Parallax shall be removed from the auxiliary telescope by means of auto collimation. The test shall be made by sighting through the auxiliary telescope to the collimator center cross image.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T05:45Z
Check the source to verify that this is the current version before use.

Parallax will be recognized as any apparent displacement of the collimator center cross image in relation to the auxiliary telescope reticle when the observer's head is moved from side to side, or up and down. Any movement of the observer's head shall not cause displacement of the collimator center cross image to exceed the requirement specified in 3.7.3.

4.5.5 *Mechanical tests.*

4.5.5.1 *Elevation travel.* The elevation travel test shall be made by means of a wall chart located a suitable distance from the collimator. The chart shall have a plumbed line with a mark for the line of sight of the collimator and marks located 800 mils above and below the collimator line of sight mark. With legs fully extended in a horizontal position and the elevation clamping mechanism released, the collimator shall be elevated and depressed through the entire excursion indicated. Sighting of the collimator shall be accomplished by means of the open sight located on the collimator and shall meet the minimum requirements specified in 3.8.1.

4.5.5.2 *Azimuth travel.* This test shall be made with the wall chart specified in 4.5.5.1. Sighting of the collimator shall be accomplished by means of the open sight located on the collimator. With open sight aligned with the plumbed line and the azimuth clamping mechanism released, the collimator shall be rotated 6400 mils and shall meet the requirements of 3.8.3.

4.5.5.3 *Open sight.* This test shall be accomplished with the aid of an auxiliary telescope and a calibrated target. The center of the calibrated target shall be coincident with the optical line of sight of the auxiliary telescope and shall contain a one degree radius circle the center of which shall represent the center of the open sight of the collimator. With the collimator positioned in front of the auxiliary telescope as specified in 4.5.4.1 and the calibrated target located to the rear of the auxiliary telescope, the open sight shall read within the limits of the circle in compliance with the requirements of 3.8.3.

4.5.6 *Operability tests.*

4.5.6.1 *Operability.* The collimator assembly shall be manually set up in the operational position from the carrying position. This shall be a visual and tactile examination of the collimator for conformance to the requirements specified in 3.9.

4.5.6.2 *Knob travel.* There shall be a tactile examination for movement of the knobs to provide full locking and free movement of each specific component as specified in 3.9.1.

4.5.6.3 *Knob locks.* With each knob of the collimator assembly locked by application of the measured torque value in Table I, there shall be no movement of the collimator when the specified test values are applied in conformance with the requirements of Table I. The measured torque values shall be applied with standard measuring equipment.

4.5.6.4 *Scope alignment.* The troque required to rotate the scope to center the level vial shall be measured with standard measuring equipment. The measured torques values shall not exceed the values specified in 3.9.3 for the temperatures indicated.

4.5.6.5 *Azimuth fine adjustment.* The torque required to operate the azimuth fine adjustment shall be measured with standard measuring equipment attached to the fine adjustment knob. The measured torque values shall not exceed 5 inch pounds at standard ambient temperature (+60° +90° F.) and shall not exceed this value by more than 100 percent when exposed to the extreme temperature, in accordance with the requirements of 3.9.3.1.

4.5.6.6 *Lamp housing.* The replacement of the lamp shall be accomplished by means of a tactile examination at the specified temperatures in accordance with the requirements of 3.9.4.

4.5.7 *Electrical tests.*

4.5.7.1 *Reticle illumination.* The reticle

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:45Z
Check the source to verify that this is the current version before use.

illumination test shall be accomplished by means of a visual examination in a darkened area with the reticle lamp energized by a 12 volt source. The intensity of the lamp shall be varied from maximum to minimum illumination. The reticle markings and light intensity shall be clearly defined when observed in accordance with the requirements of 3.10.1.

4.5.7.2 *Circuitry.* A continuity check of the collimator assembly shall be made utilizing standard testing equipment to determine conformance with the requirements specified in 3.10.2.

4.5.7.3 *Dielectric strength.* This test shall be performed in accordance with Dielectric Strength, Method 301 of Standard MIL–STD–202. Standard measuring equipment shall be used for all measurements. There shall be no evidence of failure or decrease in dielectric strength when subjected to the specified voltage for the time period indicated in 3.10.3.

4.5.7.4 *Insulation resistance.* Insulation resistance shall be measured using Method 302, test condition B, of Standard MIL–STD–202 by means of standard measuring equipment. Resistance shall be measured at areas specified and shall meet the minimum resistance specified in conformance with the requirements of 3.10.4

4.5.8 *Cover assembly tests.*

4.5.8.1 *Fastening devices.* The inspection of fastening devices shall be accomplished by means of a visual and tactile examination of catches or similar fastening devices used to secure the cover. to determine compliance with 3.11.1.

4.5.8.2 *Carrying handle.* The carrying handle shall be inspected by a visual and tactile examination initially to determine compliance with 3.11.2. The collimator shall then be subjected to being lifted 3 feet from the ground and returned, at least fifty full cycles by means of the carrying handle. Subsequent to the lifting test, the handle assembly shall again be examined to determine any detrimental effects or indication of poor workmanship.

4.5.8.3 *Strap security.* The test shall be accomplished with a commercial fish scale attached to the strap and subjected to a direct pull as indicated in 3.11.3. After completion of the test, the strap shall be visually examined for any slippage, or looseness of rivets, to determine compliance with the requirements of 3.11.3. The collimator shall then be subjected to the test specified in 4.5.3.2 to determine compliance with 3.11.3.

4.5.8.4 *Gasket and collar.* The gasket and collar shall have a visual and tactile examination to assure that there is proper adhesion to the cover as specified in 3.11.4.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking. Packaging, packing and marking shall be in accordance with Specification MIL–P–14232 and Packaging Data Sheet MIL–P–14232 P8614275. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use. The Collimator Infinity Aiming Reference: M1 is an optical instrument on a tripod, with protective cover, intended to be used for indirect laying of field artillery weapons by establishing an optical reference from which weapon deflection angles can be measured. It has a mil scale reticle which when illuminated functions as an optical projection system simulating a grid board type of infinity target reference.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Selection of applicable levels of preservation, packaging, and packing (see 5.1).
(c) Applicable stock number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:45Z
Check the source to verify that this is the current version before use.

Custodian:
Army—MU

Preparing activity:
Army—MU
Project No. 1240–A393Y

Source: https://assist.dla.mil -- Downloaded: 202640-22T05:45Z
Check the source to verify that this is the current version before use.