MILITARY SPECIFICATION

FUZE SETTER SET: M63

1. SCOPE

1.1 This specification covers performance requirements, quality assurance provisions, and packaging data for a fuze setter set consisting principally of a fuze setter body, an adapter, and removable socket or sockets. The set is hereinafter referred to as "fuze setter" (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-F-13926	Fire Control Materiel: General Specification Governing the Manufacture and inspection of
MIL-P-14232	Parts, Equipment and Tools for Ordnance Materiel, Packaging of
MIL-I-45607	inspection Equipment, Supply and Maintenance of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions

DRAWINGS

U.S. Army, Frankford Arsenal

F8614051	Fuze Setter Set: M63
IEL 8614051	List of Inspection Documents for Fuze Setter Set: M63

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

PACKAGING DATA SHEET

MIL-P-14232/P8614051 Packaging of Fuze Setter Set: M63

(Copies of specifications, standards, drawings, and packaging data sheets required by stipplers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Fabrication.- The fuze setter shall be manufactured in accordance with Drawing F8614051 and drawings pertaining thereto-

3.2 General specification.- The contractor shall be responsible for adherence to the following requirements of MIL-F-13926:

(a) Order of precedence
(b) Dimensions and tolerances
(c) Inorganic protective surface finishes
(d) Electrical assemblies
(e) Part identification and marking
(f) Workmanship
(g) Soldering electrical connections

3.3 Environmental service conditions.

3.3.1 Extreme operating temperatures.- Unless otherwise specified, the fuze setter shall meet the requirements of 3.4 while exposed to, and thermally stabilized at, ambient temperatures of -400 and +150° Fahrenheit (F).

3.3.2 Standard ambient temperature.- Unless otherwise specified, the fuze setter shall meet the following requirements at a standard ambient temperature between +60° and +90°F.

3.3.3 Vibrating.- The fuze setter shall withstand a vibration of 30 ± 5 cycles per second frequency with an amplitude of 1/16 inch (1/8 inch maximum excursion) for a period of 5 minutes ± 15 seconds. Subsequent to vibration there shall be no evidence of loosened or damaged parts, and the fuze setter shall meet the following requirements of this specification.

3.4 Operability.

3.4.1 Rotation.- The direction of rotation specified in 3.4.1.1 and 3.4.1.2 as viewed from above the fuze setter with the fuze setter in the operating position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

3.4.1.1 Counterclockwise.- The running torque required to rotate the body of the fuze setter counterclockwise about the adapter shall not exceed 4.0 pound-inches at the standard ambient temperature of 3.3.2, and 8.0 pound-inches at the extreme operating temperatures of 3.3.1.

3.4.1.2 Clockwise.- There shall be no slippage between the adapter and the body of the fuze setter when a 300 pound-inch torque is applied to the body in the clockwise direction.

3.4.2 Socket.- When inserted into the adapter the socket shall lock in place shall be free from shake or wobble. The force required to-remove the socket from or replace it into the adapter shall be not less than 2 pounds nor more than 20 pounds. These requirements shall be met with the fuze setter in the operating position.

3.4.3 Light switch.- With a three-volt dc power source applied as shown on Drawing F8614051, the fuze setter shall meet the requirements of 3.4.3.1 and 3.4.3.2.

3.4.3.1 Function.- The switch shall function to complete the circuit when a force of 4 ± 1 pounds is applied to depress the button. The switch shall return to the open position when the force is released.

3.4.3.2 Illumination stability.- With the switch button depressed, there shall be no flicker or illumination failure when the fuze setter is shaken manually.

3.5 Continuity.- The light assembly shall demonstrate continuity in accordance with the applicable electrical schematic drawings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General Provisions.- The component inspection requirements of MIL-F-13926 form a part of the Quality Assurance Provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 Inspection Provisions.

4.2.1 Submission of Product.- Unless otherwise specified herein, or by the contracting officer, inspection lot size, formation, and presentation of lots shall be in accordance with “Submission of Product” as specified in MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

4.2.2 Examination and tests .- (Components and subassemblies shall be inspected in accordance with the inspection provisions contained in MIL-F-13926 and the Supplementary Quality Assurance Provisions (SQAP) listed in the List of Inspection Documents, IEL 8614051. Examinations and tests related to Section 3 herein shall be performed on a defect (individual characteristic) basis in accordance with the "Classification of Defects" as specified in Table I below, and the inspection level and sampling plans specified in MIL-STD-105. Examinations and tests for packaging, packing and marking shall be in accordance with MIL-P-14232 and Section 5 herein. The tabulated classification of defects shall constitute the minimum inspection to be performed by the supplier prior to Government acceptance or rejection by lot. The Government reserves the right to inspect for any applicable requirement, and to reject individual non-conforming items.

TABLE I - (CLASSIFICATION OF DEFECTS

Use Inspection Level II of Table I with
Sampling Plan Table II-A of MIL-STD-105

CRITICAL: NONE	REQUIREMENTS	TEST PROCEDURES
MAJOR: AQL 1.0 percent defective		
101. Physical failure post vibration	3.3.3	4.5.3
102. Performance failure post vibration	3.3.3	4.5.3
103. Running torque exceeds required force	3.4.1.1	4.5.4.1
104. Adapter fails to lock in place or remain secure in lock position	3.4.1.2	4.5.4.1
105. Socket difficult to remove or insert or remain free f-rem shake or wobble	3.4.2	4.5.4.2
106. Instrument light switch requires excess force to function	3.4.3.1	4.5.4.3
107. Instrument light switch fails to function properly when the required force is applied and then released	3.4.3.1	4.5.4.3
108. Instrument lamp flickers or fails to light when switch button is depressed	3.4.3.2	4.5.4.4
109. Lack of continuity	3.4.4	4.5.4.5
MINOR: NONE DEFINED		

4.2.3 Disposition of non-conforming product.- Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.3 Special sampling.

4.3.1 General.- One fuze setter shall be selected at random by a Government representative as a sample from each 100 produced, or from each months production whichever occurs first. The sample shall meet the requirements and tests in Table 11.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

TABLE 11

CHARACTERISTICS	REQUIREMENTS	TEST PROCEDURES
301. Fabrication	3.1	4.5.1
302. General specification	3.2	MIL-F-13926 visual

4.3.2 Environmental.- Three fuze setters shall be selected at random by a Government representative as samples from each 100 produced, or from each month's production, whichever occurs first. The samples shall have successfully met the requirements and tests specified in Table I and shall then meet the requirement and test of Table III.

TABLE 111

CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
303. Performance at extreme operating temperatures	3.3.1	4.5.2

4.3.3 Failure of sampling.- Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the represented lot will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved.

4.4 Inspection equipment.- Except as otherwise provided for by the contract, the contractor shall maintain all required measuring and testing equipment in accordance with the applicable requirements specified in MIL-I-45607. The Government reserves the right to use the test equipment for its own independent inspections to the extent that such use will not unduly interfere with the contractor's delivery schedule.

4.4.1 Government furnished inspection equipment.- Where the contract provides for Government furnished test equipment, care and maintenance of test equipment shall be in accordance with the applicable requirements specified in MIL-I-45607.

4.4.2 Contractor furnished inspection equipment.

4.4.2.1 Government design.- All inspection equipment required by drawings forming a part of the contract and not provided by the Government shall be supplied by the contractor in accordance with the requirements of 4.4 and the List of Inspection Documents, IEL 8614051.

4.4.2.2 Contractor design.- The contractor shall provide inspection equipment compatible with the "Test methods and proocedures" specified in 4.5 and with the "Component lnspection" and "Test Facilities" .requirements of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, ma-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

terials, dimensions, and tolerances used in the design of test. equipment shall be so-selected and controlled as to insure that the test equipment will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.

4.4.3 Test equipment.- In conjunction with 4.4.2.2 the following test equipment shall be utilized in the performance of the applicable tests as specified in 4.5:

ITEM NUMBER	EQUIPMENT	TEST REQUIREMENTS
1	Vibration Fixture	Test Facilities of MIL-F-13926
2	*Heat* Chamber	Test Facilities of MIL-F-13926
3	Cold Chamber	Test Facilities of MIL-F-13926
4	Torque Wrench	Reading within 1/4 Pound-inch
5	Power Source 3V DC	± 2 Percent

4.5 Test methods and procedures.

4.5.1 Fabrication. - To determine compliance with 3.1, the fuze setter shall be visually inspected for proper fabrication in accordance with the specified drawing and drawings pertaining thereto.

4.5.2 Extreme operating temperatures.- The operating temperature test cosists of exposing the fuze setter to the temperatures indicated in 3.3.1 by means of equipment complying with the requirements of 4.4.3. The test shall be conducted in accordance with Procedure I of MIL-F-13926, and the conditions of 3.3.1 shall apply. While thermally stabilized at these temperatures, the fuze setter shall be subjected to and meet the performance requirements specified in 3.3.1.

4.5.,3 Vibration.- The vibration test shall be performed on a device with mean-d for measuring and controlling the direction of vibration and providing adjustment to the amplitudes and frequencies within the specified limits of 3.3.3. The fuze setter shall be rigidly mounted on the vibrating device and vibrated in accordance with the requirements specified in 3.3.3. Subsequent to vibration the fuze setter shall be subjected to visual and tactile examinations for evidence of loose or damaged parts. When there is no evidence of loose or damaged internal or external parts, the fuze setter shall be inspected in accordance with the methods and procedures in 4.5.4.

4.5.4 Performance.

4.5.4.1 Rotation.- The fuze setter shall be mounted as indicated in 3.4.1. The apparatus for performing the test shall consist of a suitable holding device. The socket shall be inserted into the body of the fuze setter as in intended operation. The fuze setter shall then be set up for testing by mechanically securing the socket only. in the holding device. With provisions for applying the load specified in 3.4.1.2,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

and with the force applied. in a clockwise direction, the handles shall remain stationary. In the counterclockwise direction, the handles shall rotate in compliance with the requirements of 3.4.1.1.

4.5.4.2 Socket.- With provisions-for applying the load specified in 3.4.2, the sockry shall be capable of being removed from or replaced into the adapter. Subsequent to insertion into the adapter, pressure shall be applied by the hand along the periphery of the socket to determine compliance with the requirements of 3.4.2.

4.5.4.3 Light switch.- The fuze setter shall be mounted in a suitable position with the provisions for applying the load as specified in 3.4.3.1. With the three volt D.C. power supply applied, the fuze setter shall then be visually examined in a dark area to determine compliance with the requirements of 3.4.3.1. When the specified load is applied to depress the light switch button the instrument lamps shall light. Removing the load shall return the button to its normal OFF position, and the light shall be out.

4.5.4.4 Illumination stability.- Subsequent to the test in 4.5.4.3, the fuze setter shall be visually examined in a dark area for the requirements of 3.4.3.2. When manually depressing the switch button the instrument lamps shall light. Hold the depressed button for ten seconds. Illumination at this point shall remain steady, and slight manual shaking of the instrument. shall not cause flickering. Releasing the switch button. shall cause the light to go out and remain out without evidence of flickering. The switch shall be capable of ten consecutive contacts at ten-second intervals without flicker or illumination failure.

4.5.4.5 Continuity.- The continuity check of the instrument light circuit shall be made using standard measuring equipment to determine compliance with the requirements of 3.5.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packing. and marking." Packaging, packing, and marking shall be in accordance with MIL-P-14232 and Packaging Data Sheet MIL-P-14232/P8614051. The level of-protection shall be as specified in the procurement document."

6. NOTES

6.1 Intended use.- The fuze setter is intended for use in hand-setting Fuzes M562, M563, M564, and M565. The adapter assembled in the fuze setter body is designed to accept an interchangeable socket.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. - Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Selection of an applicable level of preservation, packaging, and packing.
(c) Applicable stock number.
(d) Applicable packaging data sheet number (see 5.1).

Custodian:

Army-Mu

Preparing activity:

Army-MU

Project No. 1290-A163Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

Commanding Officer
Frankford Arsenal
ATTN: SMUFA- N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.