MIL-M-46379A(MU)
3 June 1968
SUPERSEDING
MIL-M-46379(MU)
1 July 1963

MILITARY SPECIFICATION

MOUNT SIGHT, INFINITY REFLEX: 10511780 AND 10553489

1. SCOPE

1.1 This specification covers two type mounts used to support one of the following: Sight, Infinity Reflex: 8566264, 8566264-1, 8566351, and Sight, Reflex: Helicopter: XM60, XM60E1.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-F-13926	Fire Control Materiel: General Specification Governing the Manufacture and Inspection of
MIL-P-14232	Parts, Equipment and Tools for Army Materiel, Packaging and Packing of
MIL-I-45607	Inspection Equipment, SupplY and Maintenance of

STANDARDS

Military

MIL-STD-105	Sampling procedures and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions

DRAWINGS

U.S. Army, Frankford Arsenal

F10511780	Mount, Sight, Infinity Reflex: 10511780
F10553489	Mount, Sight, Infinity Reflex: 10553489

FSC 1270

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

PACKAGING DATA SHEET S

10511780	packaging of Mount, Sight Infinity, Reflex: 10511780
10553489	packaging of Mount, Sight, Infinity, Reflex: 10553489

(Copies of specifications, standards, drawings, and packaging data sheets required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.) "

3. REQUIREMENTS

3.1 Materials.- Materials shall be in accordance with the drawings, material specifications, and general specifications forming a part of this specification.

3.2 Fabrication.- The mount shall be manufactured in accordance with the applicable drawing specified in Section 2 and drawings pertaining thereto.

3.3 General specification.- The contractor shall be responsible for adherence to, and compliance with, the following requirements of Specification MIL-F-13926:

(a) Order of precedence
(b) Dimensions and tolerances
(c) Inorganic protective surface finishes
(d) part identification and marking
(e) Workmanship

3.4 Environmental.

3.4.1 Operating temperatures.- The mount shall be operable while exposed to and thermally stabilized at ambient temperatures of minus 40" Fahrenheit (F) and plus 150°F.

3.4.2 Vibration.- The mount shall meet the requirements of 3.5.1 and 3.5.2 after being vibrated for five minutes plus or minus 15 seconds at an amplitude of 1/16 inch (1/8 inch total excursion) at a frequency of 30 cycles per second.

3.5 Operability.

3.5.1 Mounting plate.- With the lever lock out of detent, the running torque required to rotate the sight mounting plate shall not be less than 5 inch pounds nor more that 20 inch pounds with a fully depressed lever when checked at an ambient temperature of plus 60° to 90°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

3.5.2 Lever lock.- With the lever lock in detent at either of the two positions, the lock shall securely lock the assembly. Angular displacement of the sight mounting plate shall not exceed 2 roils when a torque of 70 + 5 inch pounds is applied at plus 60° to 90°F.

4. QUALITY ASSURANCE PROVISiONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions.- The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) each of the type mount specified in the contract. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection.

4.3 Inspection provisions.

4.3.1 Submission of product.- Unless otherwise specified by the contracting officer, inspection lot size, lot formation and presentation of lots shall be in accordance with "Submission of product" provisions of MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

4.3.2 Examination and tests.- components and subassemblies shall be inspected in accordance with the inspection provisions contained in MIL-F-13926, and the Supplementary Quality Assurance Provisions (SQAP) listed in the List of Inspection Documents (IEL) when provided with the technical data package (TDP). Examinations and tests related to Section 3 herein shall be performed on a single defect (individual characteristic) basis in accordance with MIL-STD-105, and the sampling plans specified in Table I and 4.4.1. Examinations and tests for Packaging,. Packing and Marking shall be in accordance with MIL-P-14232 and Section 5 herein. The tabulated classification of defects in Table I shall constitute the minimum inspection to be performed by the supplier prior to Government acceptance or rejection by lot.

TABLE I - CLASSIFICATION OF DEFECTS

CRITICAL: NONE
MAJOR : AQL 1.0 percent defective

CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
101. Physical failure (post vibration)	3.4.2	4.6.2
102. Mounting plate torque not within limits	3.5.1	4.6.3
103 . Lever lock failure	3.5.2	4.6.4

MINOR: NONE

NOTE : Tests in Table I shall be conducted in accordance with all requirements in the "Test Facilities" requirement of MIL-F-13926 except the requirement for "Test Chambers".

4.3.3 Acceptance and rejection.- Rejected lots shall be screened for al 1 defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.4 Control tests.

4.4.1 Special sampling.- Three mounts shall be selected at random as samples from each 100 produced, or from each month's production whichever occurs first. The sample shall meet the requirements of Table I subsequent to meeting the requirements specified herein.

CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
301. Operating temperature"	3.4.1	4.6.1

4.4.1.1 Failure of sample.- Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the product will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved (see 4.3.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

4.4.2 First article samples.- Unless otherwise specified in the contract (see 4.2), all tests listed in Table I and 4.4.1 shall be conducted on initial production samples subsequent to meeting the certification requirements in 4.4.3.

4.4.3 Certification.- Certification shall include test data and results for all characteristics specified in Table II. Certification will be required prior to performing final acceptance inspection and shall suffice for the remainder of the production quantities, provided the manufacturing processes and techniques used to produce the items for which certification was issued have not been changed or revised. Any and all changes will require a new certification from the contractor.

TABLE II

CHARACTERISTIC	REQUIREMENT	TEST DATA TO COMPLY WITH
401. Materials	3.1	Applicable Drawings,
402. Fabrication	3.2	Standards, and
403. General specification	3.3	Specifications

4.5 Inspection equiPment.- Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-I-45607.

4.5.1 Government furnished inspection equipment.- Where the contract provides for Government-furnished test equipment, SUPPLY and maintenance of test equipment shall be in accordance with the applicable requirements specified in MIL-I-45607.

4.5.2 Contractor furnished inspection equipment.

4.5.2.1 Government design.- Unless otherwise specified in the contract, all inspection equipment specified by drawing number in specification or SQAP forming a part of the contract shall be supplied by the contractor in accordance with technical data listed in the List of Inspection Documents (IEL), when provided with the Technical Data Package (TDP).

4.5.2.2 contractor design.- The contractor shall provide inspection equipment compatible with the "Test Methods and Procedures" specified in 4.6 and with the "Component Inspection" and "Test Facilities" requirements of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test Equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions and tolerances used in the design of test equipment shall be so selected and controlled as to insure that the test equipment will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when non-conforming. construction shall be such as to facilitate routine calibration of test equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

4.6 Test methods and procedures.

4.6.1 Operating temperatures.- This test shall be conducted in accordance with the "Test Facilities" requirements of MIL-F-13926, except that in lieu of the "Standard ambient test conditions" the extreme temperatures in 3.4.1 shall apply. Utilizing test equipment conforming to 4.5, gradually change chamber temperature to prevent thermal shock until the external surface of the mount is thermally stabilized in turn at each extreme temperature in 3.4.1. Maintain each extreme temperature for the uninterrupted period of time required to determine that the mounting plate is rotatable and that the locking lever is operable.. Upon completion of this examination, the mount shall be returned to between plus 60° and 90°F, and examined for evidence of damage. Subsequent to this test, the mount shall meet 3.5.1 and 3.5.2 in accordance with 4.6.3 and 4.6.4, respectively.

4.6.2 Vibration.- This test shall be conducted by vibrating the mount in a vertical plane in accordance with the conditions of amplitude, frequency and time duration in 3.4.2. Subsequent to vibration, the mount shall be subjected to a visual and tactile examination to determine that no evidence of damage exists. The mount shall then be subjected to tests 4.6.3 and 4.6.4.

4.6.3 Mounting plate.- The mount shall be positioned on a device that suspends the body of the mount from a horizontal mounting surface. With the lever lock out of detent, apply the specified torque to the sight mounting plate by means of a calibrated pull scale. The torque required to move the mounting plate from one detent to the other shall be within the limits specified in 3.5.1.

4.6.4 Lever lock.- This test shall be performed utilizing the same set-up as in the previous test with the aid of an auxiliary telescope and a calibrated wall target. Secure the lever lock in either detent. Mount the auxiliary telescope on the sight mounting plate with the telescope reticle aligned with the center of the target and the reticle line plumb. Sight through the telescope and apply the torque specified in 3.5.2 at the outer edge of the sight mounting plate by means of a calibrated pull scale. Angular displacement shall not exceed the limit specified in 3.5.2. Repeat this procedure with the lever lock secured at the other detent and the telescope realigned with the target.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking.- Packaging, packing and marking shall be in accordance with the applicable Packaging Data Sheet specified in Section 2. The level of protection shall be as specified in the procurement document.

6. Noms

6.1 Intended use.- This mount is primarily intended as a mounting device for Sight, Infinity, Reflex: 8566264, 8566264-1, 8566351 and Sight, Reflex, Helicopter: XM60, XM60E1 when suspended from the overhead section of a helicopter. The sight is used by the pilot to hold the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

helicopter on a collision course with the target during the time the missile, launched from the helicopter, **is in flight to the target.**

6.2 Ordering data.- Procurement documents should specify the following:

a. Title, **number and date of this specification**
a **Selection of applicable levels of preservation, packaging and packing (5.1)**
c. Applicable packaging data sheet number (see 5.1)
d. Applicable stock number

custodian:

Army - MU

Preparing activity:

Army - MU

project No. 1270-A030

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*.

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
Department of the Army

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:46Z
Check the source to verify that this is the current version before use.