MILITARY SPECIFICATION

ROCKET ARMAMENT PANEL: 8933209

This amendment forms a part of Military Specification MIL-R-46388(MU), dated 17 September 1963.

Paragraph 3.1: Add the following subparagraph:

"3.1.1 Installation of hardware.- All installation of hardware shall be performed by swaging, unless other methods of installation are specifically called out on the drawing. The assembly shall not contain any of the following defects:

a. Cracks or deformation of the circuit board adjacent to installed hardware.
b. Cracks, ruptures, or delamination of the circuit board.
c. Bent terminals or mechanical stand-offs.
d. Loose or improperly installed hardware (swaged type).
e. Damage to the rollover flange of the swaged hardware such that two or more full length cracks are located within a 45 degree angle.

NOTE: Cracks which do not extend more than halfway through the rollover flange shall be disregarded."

Paragraph 4.5.1.2: Delete and substitute:

"4.5.1.2 Post vibration.- Subsequent to vibration the panel shall be thoroughly inspected for the physical defects outlined in 3.1.1. Any one defect shall be cause for rejection."

Custodian:

Army-MU

Preparing activity:

Army-MU

Project No. 1270-A042Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:48Z
Check the source to verify that this is the current version before use.