MILITARY SPECIFICATION

RANGE FINDER, FIRE CONTROL: M17B1C

1. SCOPE

1.1 This specification covers one type of coincidence image instrument known as Rangefinder: M17B1C for determining range measurements in meters in the 90MM Gun Tank: M48A3 Fire Control System.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-O-13830 —Optical Components for Fire Control Instruments; General Specification Governing the Manufacture, Assembly and Inspection of

MIL-F-13926 —Fire Control Materiel: General Specification Governing the Manufacture and Inspection of

MIL-P-14232 —Parts, Equipment and Tools for Ordnance Materiel, Packaging of

MIL-I-45208 —Inspection Requirements, General Specification for

STANDARDS

MILITARY

MIL-STD-105 —Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-109 —Quality Assurance Terms and Definitions

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

F8205604 —Rangefinder, Fire Control: M17B1C

IEL-8205604 —List of Inspection Equipment Numbers For Rangefinder: M17B1C

LSQAP-8205604 —List of Supplementary Quality Assurance Provisions For Rangefinder: M17B1C

PACKAGING DATA SHEET

MIL-P-14232/P5800850 —Packaging of Rangefinder, Fire Control: M17B1C

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with drawings, material specifications, and general specifications forming a part of this specification.

3.2 Fabrication. The rangefinder shall be manufactured in accordance with Drawing F8205604 and drawings pertaining thereto.

3.3 General specifications. The contractor shall be responsible for adherence to, and compliance with, the following requirements of Specifications MIL-O-13830 and MIL-F-13926.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:49Z
Check the source to verify that this is the current version before use.

3.3.1 *MIL–O–13830*
(a) Cleanliness
(b) Illuminated reticle

3.3.2 *MIL–F–13926*
(a) Order of precedence
(b) Dimensions and tolerances
(c) Inorganic protective surface finishes
(d) Electrical and electronic assemblies
(e) Part identification and marking
(f) Workmanship

3.4 Pre-vibration.

3.4.1 *Orientation.* The rangefinder prior to vibration shall be set up in a horizontal position as shown on the Drawing F8205604 and all instructions thereon, and the following conditions shall be established prior to testing.

(a) The line through the centers of the two mounting bearings horizontal.
(b) Identified production end housings in place.
(c) Level bubble centered within width of a vial graduation.
(d) Calibrating reticle illuminated. (See 6.8.)
(e) Occluder set at midindex.
(f) Filters out of the optical system.
(g) A target provided at 1,200 meters ±100 meters, and the range scale set to agree with the range chosen.
(h) Set the vertical calibration knob at midpoint of total travel within 10° and slip the scale to aline indices. Establish vertical coincidence of the target image.
(i) Set the horizontal calibration knob at midpoint of total travel within one division on the scale. Slip the scale to zero index. Make a series of five horizontal coincidence readings on the target image. Rotate the knob to the median reading.
(j) Set the deflection (azimuth) and elevation boresight knobs and the auxiliary deflection and elevation boresight knobs at midpoint of travel between stops within 0.1 mil graduation. Slip the deflection scales to the three (3) position and slip the elevation scales to the two (2) position.
(k) The left boresight reticle shall be set to bring the line of sight 1 mil below the horizontal, and 1 mil to the right of the perpendicular, to a centerline through the center of the mounting bearing within .05 mil (reticle line width). The knobs shall then be locked.
(l) The right boresight reticle shall be set so that its line of sight coincides with the aiming point of the left reticle within .05 mil (reticle line width). The knobs shall then be locked.

3.4.2 *Knob travel (calibrated).*

3.4.2.1 *Horizontal knob.* The horizontal calibration knob shall read within 7 units of error (UOE) of its midpoint of travel when horizontal coincidence is established at 1,200 meters ± 100 meters.

3.4.2.2 *Vertical knob.* The vertical knob shall be within 30° of its previously established midpoint.

3.4.2.3 *Deflection and elevation boresight knob scales.* The scale readings on all boresight knobs shall be within 0.7 mil (knob graduation) of their midpoints.

3.4.3 *Calibration reticle setting accuracy.* The calibrating reticle (lower) that is fixed with respect to the external field shall lie in its entirety between 5 and 12 mils to the left and above the center of the boresight cross, and the vertical line of the calibrating reticle shall be within 3 mils left and 1 mil right of the vertical centerline of the sighting reticle. The halving knob shall then be adjusted to position the movable (upper bar) of the calibrating reticle so that movement of the correction system (ICS) knob will cause the upper bar to pass within one reticle line thickness of the lower reticle, yet maintain a recognizable separation between the two reticle bars during movement. The halving

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:49Z
Check the source to verify that this is the current version before use.

knob shall then be within one-half turn of its midpoint of total travel. All coincident readings of the target shall be made in the center five mils of the true field unless otherwise required. Five reticle coincidence settings shall be made with the ICS adjustment. The median of the base five readings shall read within 7 UOE of the (25) position.

3.5 Vibration. After meeting all the above requirements, the range finder shall be vibrated at an amplitude of not less than 1/16 inch (⅛ inch total excursion) at a frequency of 30 cycles per second for a duration of 5 minutes ± 15 seconds.

3.6 Post-vibration.

3.6.1 *Post-vibration optical recheck.* With the rangefinder restored to the conditions of 3.4.1 (a) through (g), the rangefinder shall meet the requirements of 3.6.1.1 to 3.6.1.4 inclusive. Subsequent to meeting the above requirements the rangefinder shall meet all requirements of 3.6.2 to 3.6.16 inclusive. (See 6.4.)

3.6.1.1 *Image.* The target image shall not have changed coincidence by more than 0.5 mil in vertical calibration or more than 25 UOE in horizontal calibration as measured against a calibrated external target using the median of five coincident settings made with the horizontal calibration knob. (See 3.8.)

3.6.1.2 *Horizontal calibration.* Set the horizontal calibration knob at the new median setting (see 3.6.1.1). Then using the ICS knob obtain a new median from five ICS settings of the calibrating reticle. This median shall not differ by more than 5 UOE from the median reading established in 3.4.3 prior to vibration.

3.6.1.3 *Calibrating reticle setting.* The space between the calibrating reticles shall not decrease past a distinguishable spacing and shall not increase in excess of 0.2 mil.

3.6.1.4 *Alinement of sighting reticles.* The line of sight of the left telescope through the boresight mark shall not have changed by more than 0.25 mil in deflection (azimuth) and 0.5 mil in elevation from the setting introduced in 3.4.2.3. The line of the sight through the aiming point of the right telescope shall coincide with the aiming point of the left telescope within a maximum angular separation of 0.1 mil.

3.6.2 *Inspection for dirt and bright spots.*

3.6.2.1 *Inspection for dirt.* The maximum real diameter of any one defect shall not exceed 0.2 mil in the outer 22½°, and 0.05 mil in the central 17½° of the apparent field as viewed at the eyepiece. The sum of the maximum real diameter of dirt and pinholes in the rangefinder shall not exceed 1 mil. The range finder shall meet the cleanliness requirements of Specification MIL-O-13830. Visible dirt on the optical surfaces shall not exceed in size and number the limitations for size and number of digs permitted for each surface as specified on applicable drawings.

3.6.2.2 *Bright spots.* Bright spots (pinholes) in reticle shall not exceed in size and number the limitations for size and number of digs permitted for that surface as specified on the applicable drawings.

3.6.3 *Parallax.*

3.6.3.1 *Parallax of sighting reticles.* Utilizing a target at 1,200 meters ± 100 meters and with the range scale set to agree with the range chosen, parallax in the right and left systems at the optical axis (boresight cross) shall not exceed 0.1 mil, nor shall there be more than 0.1 mil parallax between reticles.

3.6.3.2 *Parallax of the calibrating reticles.* The median of five ICS readings taken with the eye centered at 0.030 inch to the left, and the median of five readings taken with the eye centered at 0.030 inch to the right of the center of the common exit pupil shall not differ by more than 6 UOE as measured on the ICS knobs.

3.6.3.3 *Parallax of the target images.* Utilizing a target at 1,200 meters ± 100 meters, the median of five coincidence readings taken with the eye centered 0.030 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:49Z
Check the source to verify that this is the current version before use.

to the left of the center of the exit pupil shall not differ from the median of five coincidence readings taken with the eye centered 0.030 inch to the right of the center of the exit pupil by more than 6 UOE as read on the horizontal calibration knob.

3.6.4 *Exit pupil.* The minimum diameter of either exit pupil when viewed through the common eyepiece in the direction of the optical axis shall be 0.110 inch (2.79 millimeters).

3.6.4.1 *Exit pupil concentricity.* The exit pupils shall be concentric to one another within 0.3 mm.

3.6.4.2 *Magnification.* The magnification of the left and right systems shall be equal within one percent.

3.6.5 *Eyepiece focus.* The eyepiece focus shall be adjustable over the range of ± 3 diopters as read on the diopter scale. The zero of the diopter scale shall indicate zero diopters within 0.25 diopter as measured against the left target image.

3.6.6 *Resolution.* The resolution on the optical axis of each optical system shall be 6 seconds of arc or less.

3.6.7 *Light transmission.* The difference in light transmission between the two optical systems shall not exceed 30 percent of the higher transmission value.

3.6.8 *Sighting reticles.*

3.6.8.1 *Accuracy of sighting reticles.* The angular value of the total horizontal lines and spaces of the reticles, in either field of view, shall be 40 mils ± 1.0 mil.

3.6.8.2 *Plumb travel.* The left boresight mark when projected into the eyepiece shall not deviate from a plumbline by more than 0.2 mil when the rangefinder is elevated from 8° depression to 19° elevation, starting with the line of sight in coincidence with the plumbline.

3.6.8.2.1 *Elevation travel.* The rangefinder shall display unrestricted movement through an excursion of at least 22° in elevation above a horizontal line of sight and 15° in depression below a horizontal line of sight.

3.6.8.3 *Parallelism of sighting reticle and image.* When either sighting reticle is projected into the eyepiece, the forty mil horizontal reticle line shall be parallel to the image of a horizontal target line within 43 minutes of arc. (43 minutes of arc is equivalent to an angle subtended by a 0.5 mil block at one end of the forty mil reticle line when the other end of the reticle line is in coincidence with the target line.)

3.6.8.4 *Tilt variation between reticles.* When the right reticle is superimposed on the left reticle, the variation between the reticles as measured at the 40 mil horizontal reticle lines shall not exceed the width of a reticle line at one extremity of the 40 mil reticle lines when the other extremity of both 40 mil reticle lines are coincident.

3.6.9 *Coincidence reticles.*

3.6.9.1 *Parallelism of calibrating reticles.* Each calibrating reticle shall be parallel to the image of a plumbline within 1' of arc.

3.6.9.2 *Reversing reticles.* Utilizing the halving knob, the upper and lower reticle bars shall be reversed by putting the upper bar below. The median of five reticle coincidence readings on the ICS knob shall not differ by more than 5 UOE from the median established in 3.6.1.2.

3.6.9.3 *Vertical movement accuracy.* The rangefinder shall be reset to the requirements of 3.6.1.2. When the vertical calibration knob is rotated to its maximum counterclockwise (CCW) position and the reticle returned to its original position by means of the halving knob, the median of 5 deflection readings (UOE) of the calibrating reticle using the ICS knob shall not differ by more than 10 UOE from the median of 5 deflection readings obtained when the vertical calibration knob is rotated to maximum clockwise (CW) position and the reticle returned to its original position by means of the halving knob.

3.6.9.4 *Horizontal movement accuracy.*

Source: https://assist.dla.mil -- Downloaded: 202610-22T05:49Z
Check the source to verify that this is the current version before use.

From the setting of 3.6.1.2 the horizontal calibration knob shall be rotated from the median setting (coincidence position of left and right images) to + and —40. The range for each extreme shall be equivalent to the corresponding change in the number of UOE on the knob scale within 10 percent. In addition, five UOE are allowed to cover the error in the positioning of the horizontal calibrating wedge relative to the ranging plane and its angular tolerance.

3.6.9.5 *ICS calibration.* From the settings of 3.6.1.2, offset the ICS knob 20 UOE CCW and re-establish reticle coincidence by rotation of the horizontal calibration knob. Then rotate the ICS knob 40 UOE CW and re-establish reticle coincidence by rotation of the horizontal calibration knob. The excursion of the horizontal calibration knob shall be 40 UOE ± 10 UOE as measured on the knob scale.

3.6.10 *Filters.* The introduction of filters into the optical system shall not cause more than 1 UOE change in horizontal calibration nor more than 0.1 mil in vertical calibration in coincidence.

3.6.11 *Compensator elevation error.* When the rangefinder is actuated to cover the range span from 500 to 4,400 meters, the elevation of the two target images shall not change with respect to each other by more than 0.1 mil.

3.6.12 *Range output accuracy.* With the rangefinder set as in 3.6.1.2, the output shaft shall be set to the values computed from the formula: $P = 23.454 \text{ Log } 10\ R - 58.577$, where P is the shaft position in turns and R is the target range in meters. At 1,200 meters on the range scale $P = 13.64$.

3.6.12.1 *Output shaft excursion.* The range of rotation of the output shaft shall be from $P = 3.76 \pm 0.05$ to $P = 27.25 \pm 0.20$ turns.

3.6.12.2 *Output shaft tolerance.* When ranging on targets at the ranges specified in table I the position of the output shaft for each range shall not differ from the P value computed from the formula given in 3.6.12 in excess of the tolerances given in table I.

TABLE I. *Tolerance on Position of Rangefinder Output Shaft*

Exact range in meters within spread	Tolerance in turns
500 to 540	±0.16 to ±0.17
650 to 750	±0.09 to ±0.11
1,100 to 1,300	0*
1,600 to 2,000	±0.09 to ±0.12
2,200 to 2,800	±0.13 to ±0.16
3,800 to 4,400	±0.22 to ±0.26

3.6.12.3 *Range scale tolerance.* The readings of the range scale shall agree with the positions taken by the output shaft when checked to the requirements of table II.

TABLE II. *Tolerance on Reading of Range Scale*

Position of output shaft	Reading of range scale	Tolerance on range scale reading (plus or minus)
$P = 5.12$	520 meters	5 meters
$P = 9.51$	800 meters	5 meters
$P = 13.64$	1,200 meters	0 meters
$P = 18.84$	2,000 meters	10 meters
$P = 20.16$	4,100 meters	20 meters

3.6.13 *Cross field errors.* From the median setting established in 3.6.1.2 and using a 1,200 meter (± 100 meters) target, establish coincidence of the target with the horizontal calibration knob at a point 20 mils (± 2 mils) above, below, right, and left of the center of the field (boresight cross). The median of 5 coincidence readings at each point shall not differ from the median UOE reading obtained at the center of the field by more than 6 UOE.

3.6.14 *Base length.* The base length of the rangefinder measured optically, when identified production end housing assemblies are installed, shall be 79 inches ± 0.15 inch.

3.6.15 *Boresight knobs.*

3.6.15.1 *Elevation.* Rotation of the elevation boresight knobs shall cause the line of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:49Z
Check the source to verify that this is the current version before use.

sight to move at least 5 mils in depression and 2 mils in elevation from the nominal position established in 3.4.1 (k) and (l).

3.6.15.2 *Deflection.* Rotation of the deflection boresight knobs shall cause the line of sight to move at least 4.5 mils each side of the nominal position established in 3.4.1 (k) and (l).

3.6.15.3 *Backlash.* Backlash in the boresight knobs shall not exceed 0.05 mils in the line of sight as read on the knob scales.

3.6.15.4 *Locks.* Actuation of the locks of the deflection and elevation boresight knobs shall not cause more than 0.05 mil shift in the line of sight and not more than 0.05 mil rotation of the boresight knob.

3.6.15.5 *Lock retention.* When the locks of the boresight knobs are in the locked positions, the knob shall not move when a torque of 12 pound inches is applied to the knob.

3.6.16 *Calibration knobs.*

3.6.16.1 *Backlash.* Backlash in the ICS knob shall not exceed ½ UOE and backlash in the horizontal calibration knob shall not exceed 1 UOE.

3.6.16.2 *Locks.* Locking of the horizontal and vertical calibration knobs by setting the knobs in the serration detent shall not introduce deflection error in excess of ¼ UOE or elevation error in excess of the width of the index line, as read on the knob scales.

3.7 **Operability.** When the rangefinder is exposed to the ambient temperatures indicated in table III the maximum torque required for operation of the controls shall not exceed the values specified in the table.

3.8 **Horizontal calibration, post environmental.** Each rangefinder, after meeting the vibration requirements of 3.6, and again after meeting the environmental requirements of 3.10, shall be recollimated if the following mandatory requirements are not met (see note).

(a) The horizontal calibration knob shall read within 25 units of error (UOE) of its midpoint of total travel when horizontal coincidence is established at 1,200 meters ± 100 meters.

(b) Five reticle coincidence settings shall be made within the ICS knob. The median of the five readings shall read within 12 UOE of the (25) position.

Note. Instruments which are recollimated must meet the requirements of 3.4.2.1, 3.4.3, 3.6.2.1, 3.6.3, 3.9 and 3.9.1.

3.9 **Sealing.** The rangefinder body and end housings shall show no evidence of leakage in excess of the following when subjected to an internal pressure of 6 inches of mercury at standard ambient temperature (60° to 90° F.) for a period of 12 hours. Correction shall be made for any pressure variation resulting from temperature and barometric changes.

Rangefinder body .....0.3 inch mercury
End Housing .....0.1 inch mercury

3.9.1 *Flushing.* Upon satisfactory completion of the sealing requirements of 3.9, the rangefinder and the end housings shall be flushed with dry nitrogen. The flushing shall continue until the gaseous mixture bled from the rangefinder and the end housings have a dewpoint of at least —25° F. The instruments shall then be sealed with an internal pressure of dry nitrogen of between 0.2 and 0.5 inches of mercury.

3.10 **Environmental requirements.**

3.10.1 *Storage temperatures.* The rangefinder, with the identified end housings attached, shall be exposed to ambient temperatures of —80° and +160° F. until thermal equilibrium is reached. After thermal equilibrium has been re-established at standard ambient temperature, the rangefinder and end housings shall show no evidence of physical failure such as cement separation, bonding failure, glass breakage, coating failure, etc., and shall meet the requirements of 3.11.

3.10.2 *Operational temperatures.* The rangefinder, with the identified end housings attached, shall be exposed to an ambient tem-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:49Z
Check the source to verify that this is the current version before use.

TABLE III. *Operation at Room and Environmental Temperatures*

Control	Room +60° to 90° F. (standard ambient temperature)	Environmental —25° and 150° F.	
Range Knob	70 oz. inches	16 lb. inches	70 oz. inches
Deflection (azimuth) and elevation boresight knobs.	60 oz. inches	10 lb. inches	60 oz. inches
Horizontal and vertical calibration knobs (pull out force).	48 oz.	10 lb.	48 oz.
Horizontal and vertical calibration knob (rotation).	60 oz. inches	10 lb. inches	60 oz. inches
Halving knob	60 oz. inches	10 lb. inches	60 oz. inches
ICS knob	60 oz. inches	10 lb. inches	60 oz. inches
Diopter adjustment	30 oz. inches	10 lb. inches	30 oz. inches
Rheostat knob—reticle	30 oz. inches	8 lb. inches	30 oz. inches
Rheostat knob—range scale	20 oz. inches	5 lb. inches	20 oz. inches
Light switches	*m.o.	m.o.	m.o.
Computer switch	m.o.	m.o.	m.o.
Boresight and calibration locks	m.o.	m.o.	m.o.
Filter lever	m.o.	m.o.	m.o.
Occluder knob	m.o.	m.o.	m.o.

* m. o.—mechanically operable

perature of —40° until thermal equilibrium is reached and inspected at that temperature to insure that all knobs, locks, and operational adjustments are mechanically operable. The rangefinder, with end housings attached, shall then be exposed to an ambient temperature of —25° F. until thermal equilibrium is reached and then shall be inspected at this temperature for conformance with the requirements of 3.7 and table III. The rangefinder with end housings attached shall be exposed to an ambient temperature of +150° F. until thermal equilibrium is reached and inspected at this temperature for conformance to the requirements of 3.7.

3.11 *Post environmental check.*

3.11.1 *Optical check.* Any rangefinder which has been subjected to the environmental requirements of 3.10 shall be restored to the conditions of 3.4.1 (a) through (g) and comply with the following requirements after thermal equilibrium has been re-established at standard ambient temperature.

(a) The line of sight of the left telescope through the boresight mark shall not have changed by more than 0.5 mil in deflection (azimuth) and 0.5 mil in elevation from the values in 3.6.1.4. The line of sight of the right telescope shall coincide with the aiming point of the left telescope within a maximum angular separation of 0.3 mil. Lack of horizontal coincidence of target image shall not exceed 40 UOE. Coincidence of the target images shall be re-established by using the horizontal calibration knob only. Set the horizontal calibration knob to the new median reading of five horizontal coincidence readings of the target; then using the ICS knob, obtain a median from five ICS settings of the calibrating reticle. This median shall not differ by more than 5 UOE from median reading established in 3.6.1.2 prior to environmental exposure.

(b) The rangefinder shall meet the vertical calibration requirements of 3.6.1.3.

Source: https://assist.dla.mil -- Downloaded: 202640-22T05:49Z
Check the source to verify that this is the current version before use.

(c) The field error shall not have increased from the values established in 3.6.13 by more than 2 UOE.

3.11.2 *Horizontal calibration.* Each rangefinder which has met the requirements of 3.10 to 3.11.1 inclusive, shall be recollimated to meet the requirements of 3.8.

3.12 *Electrical check.* Electrical checks may be conducted at any time prior to final acceptance of the rangefinder.

3.12.1 *Insulation resistance.* Insulation resistance between ungrounded circuits and the body or frame and between isolated circuits shall not be less than 2 megohms with 500 volts dc applied.

3.12.2 *Continuity.* The electrical circuits shall be checked for continuity and shall conform to the wiring diagram.

4. QUALITY ASSURANCE PROVISIONS

4.1 **Responsibility for inspection.** The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 *General provisions.* The quality assurance provisions of this specification and of other documents referenced herein form the basis for inspection to be performed by the supplier. Inspection shall be in accordance with the requirements of Specification MIL–I–45208 and the component inspection requirements of Specification MIL–F–13926. Definitions of inspection terms not otherwise defined herein shall be as listed in Standard MIL–STD–109.

4.2 **Inspection provisions.**

4.2.1 *Inspection lot.* Unless otherwise specified by the contracting officer, inspection lot size, formation, and presentation of lots shall be in accordance with "Presentation of Lots and Drawing of Samples" specified in Standard MIL–STD–105.

4.2.2 *Examination and tests.* Components and subassemblies shall be inspected in accordance with the inspection provisions contained in Specification MIL–F–13926 and List of Supplementary Quality Assurance Provisions LSQAP 8205604. Examination and tests related to section 3 herein shall be performed on a defect (individual characteristic) basis in accordance with Standard MIL–STD–105, and the inspection level and sampling plans specified in tables IV and V titled "Classification of Defects". Examinations and tests for Packaging, Packing and Marking shall be in accordance with Specification MIL–P–14232 and section 5 herein. The tabulated classification of defects shall constitute the minimum inspection to be performed by the supplier prior to Government acceptance or rejection by lot. The Government reserves the right to inspect for any applicable requirements, and to reject individual nonconforming items.

TABLE IV. *Classification of Defects*

Use Inspection Level L7 and Sampling Plan Table IV–A of Standard MIL–STD–105

	Critical: None Major: AQL 6.5 percent	Requirement	Test procedure
101.	Controls, operability (minus 40° F.)	3.10.2	4.10.2
102.	Controls, torque (minus 25° F., plus 150° F.)	3.7	4.10.3
103.	Physical failure rangefinder (storage)	3.10.1	4.10.1
104.	Alinement of sighting reticles	3.11.1 (a)	4.11.1
105.	Image coincidence	3.11.1 (a)	4.11.2

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:49Z
Check the source to verify that this is the current version before use.

106.	Horizontal calibration	3.11.1 (a)	4.12
107.	Vertical calibration of images	3.11.3 (b)	4.11.3
108.	Calibration reticles	3.11.1 (b)	4.11.4
109.	Field error	3.11.1 (c)	4.11.5
110.	Sealing, main housing and end housing	3.9	4.9

Minor: None

Note. The tests for characteristics 101 and 102 shall be conducted at the temperatures indicated. The tests for characteristics 103 through 110 inclusive shall be conducted at standard ambient temperature (plus 60° to plus 90° F.) subsequent to the temperature cycling test. All tests shall be conducted in accordance with the quality assurance paragraph listed.

TABLE V. *Classification of Defects*

Use Inspection Level II, and Sampling Plan Table IV-A of Standard MIL-STD-105

Critical: None

Major: AQL 0.65 percent	*Requirement*	*Test procedure*
102. Horizontal calibration knob travel, pre-vibration	3.4.2.1	4.5.2.1
102. Vertical calibration knob travel, pre-vibration	3.4.2.2	4.5.2.2
103. Azimuth and elevation boresight knobs, pre-vibration	3.4.2.3	4.5.2.3
104. Calibration reticle setting accuracy, pre-vibration	3.4.3	4.5.3
105. Physical failure, post-vibration	3.6.1	4.6.1
106. Cleanliness post-vibration	3.6.2.1	4.6.6
107. Alinement of sighting reticles	3.6.1.4	4.6.5
108. Coincidence of target images	3.6.1.1	4.6.2
109. Calibration reticle setting	3.6.1.3	4.6.4
110. Horizontal calibration	3.6.1.2	4.6.3
111. Bright spots	3.6.2.2	4.6.7
112. Parallax of sighting reticles	3.6.3.1	4.6.8
113. Parallax of calibration reticles	3.6.3.2	4.6.9
114. Parallax of target images	3.6.3.3	4.6.10
115. Exit pupil and concentricity	3.6.4 & 3.6.4.1	4.6.11 & 4.6.11.1
116. Magnification	3.6.4.2	4.6.11.2
118. Definition (Resolution)	3.6.5	4.6.12
119. Light transmission	3.6.7	4.6.13
120. Accuracy of sighting reticles	3.6.8.1	4.6.14.1
121. Plumb travel and elevation travel	3.6.8.2 & 3.6.8.2.1	4.6.14.2 & 4.6.14.3
122. Parallelism of sighting reticle and image	3.6.8.3	4.6.14.4
123. Tilt variation between reticles	3.6.8.4	4.6.15.5
124. Parallelism of calibrating reticle	3.6.9.1	4.6.15.1
125. Reversing reticles	3.6.9.2	4.6.15.2
126. Vertical movement accuracy	3.6.9.3	4.6.15.3
127. Horizontal calibration	3.6.9.4	4.6.15.4
128. ICS calibration	3.6.9.5	4.6.15.5
129. Filter error	3.6.10	4.6.16
130. Compensator elevation error output	3.6.11	4.6.17
131. Range accuracy	3.6.12	4.6.18
132. Output shaft excursion and tolerance	3.6.12.1 & 3.6.12.2	4.6.18.1 & 4.6.18.2
133. Cross field error	3.6.13	4.6.19
134. Base length	3.6.14	4.6.20
135. Knob travel	3.6.15	4.6.21
136. Elevation boresight knob movement	3.6.15.1	4.6.21.1
137. Deflection (azimuth) boresight knob movement	3.6.15.2	4.6.21.2
138. Backlash, boresight knobs	3.6.15.3	4.6.21.3
139. Boresight lock error	3.6.15.4	4.6.21.4
140. Boresight knob lock retention	3.6.15.5	4.6.21.5
141. Backlash, ICS and horizontal calibration knob	3.6.16.1	4.6.22.1
142. Calibration lock error	3.6.16.2	4.6.22.2

Source: https://assist.dla.mil -- Downloaded: 202640-22T05:49Z
Check the source to verify that this is the current version before use.

Major: AQL 0.65 percent

		Requirement	Test procedure
143.	Operability, controls	3.7	4.7
144.	Horizontal, calibration, post environmental	3.8 & 3.11.2	4.8
145.	Sealing, main housing and end housing	3.9	4.9
146.	Insulation resistance	3.12.1	4.13
147.	Continuity	3.12 ?	4.14

Minor: None

Note. The above tests shall be conducted at standard ambient temperature (plus 60° to plus 90° F.) in accordance with the quality assurance paragraph listed.

4.2.3 *Disposition of nonconforming product.* Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Disposition of Nonconforming Product" specified in Standard MIL–STD–105.

4.3 Control tests. One rangefinder shall be selected at random from each 20 produced, or from each month's production, whichever occurs first. Control samples shall have successfully met all acceptance tests specified herein prior to conducting the following examinations and tests:

Control Test	Requirement	Test procedure
Materials	3.1	Drawings & Appropriate Specifications
Fabrication	3.2	Visual—As Per Drawing MIL–F–13926
General Specifications	3.3	Visual--MIL–F–13926 & MIL–O–13830

4.3.1 *Control test failure.* Should the control test sample fail to meet the specified test requirements, acceptance of the product will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved.

4.4 Inspection equipment. Except as otherwise provided for by the contract, the contractor shall furnish and maintain all required measuring and testing equipment in accordance with the "Inspection Equipment" requirement of Specification MIL–I–45208. The Government reserves the right to use the test equipment for its own independent inspections to the extent that such use will not unduly interfere with the contractor's delivery schedule.

4.4.1 *Government furnished inspection equipment.* Where the contract provides for Government furnished test equipment, care and maintenance of test equipment shall be in accordance with "Inspection Equipment", and "Government Furnished Material" requirements of Specification MIL–I–45208.

4.4.2 *Contractor furnished inspection equipment.*

4.4.2.1 *Government design.* All inspection equipment required by drawings forming a part of the contract and not provided by the Government shall be supplied by the contractor in accordance with the List of Inspection Equipment Numbers, IEL–820564. Alternate designs may be substituted only as provided by "Inspection Provisions" of Specification MIL–I–45208.

4.4.2.2 *Contractor design.* The contractor shall design and supply inspection equipment compatible with the "Test Methods and Procedures" specified in 4.5, and with the "Component Inspection" requirements of Specification MIL–F–13926. Concept, construction, materials, dimensions, and tolerances used in design of test equipment shall be so selected and controlled as to insure that the test equipment will permit positive rejection of a product which exceeds the prescribed tolerance limit, and will reliably indicate acceptability of a product which does not exceed 90 percent of the prescribed tolerance limit. Construction shall be such as to

Source: https://assist.dla.mil -- Downloaded: 202640-22T05:49Z
Check the source to verify that this is the currentversion before use.

facilitate routine calibration of the equipment.

4.5 Test methods and procedures.

4.5.1 *Orientation of rangefinder for tests, previbration.* The requirements for orientation shall be met with the rangefinder mounted on special test equipment with a line through the centers of the 2 mounting bearings horizontal. The geometric centers of the 2 mounting bearings and the bore on Adapter Assembly 8201530 shall be in a plane perpendicular to the horizontal line within the tolerance specified on Drawing F8205604. A line of sight through the rangefinder shall be directed to a calibrated target, positioned at the specified distance, appropriate for measuring the accuracy requirements of the rangefinder. The horizontal target line shall be coincident to the line through the centers of the 2 mounting bearings. The vertical target line shall be perpendicular to that line through the centers of the mounting bearings. The rangefinder shall be checked in sequence as specified in 3.4.1.

4.5.2 *Knob travel-previbration.*

4.5.2.1 *Horizontal calibration knob.* When the horizontal calibration knob has been set to the median coincidence reading (coincidence of left and right target image) established in 3.4.2.1, the knob shall be at the midpoint of rotation within the tolerance specified. Rotation in UOE displaced from initial established midpoint shall be read from knob scale. Slip scale to aline zero index upon successful completion of test.

4.5.2.2 *Vertical calibration knob.* When vertical coincidence of the left and right target image has been established as specified in 3.4.2.2, the vertical calibration knob shall be at the midpoint of rotation within the tolerance specified. Rotation from initial established midpoint shall be the measured distance between the fixed and movable index lines. Slip scale to aline index lines upon successful completion of test. Mark position of knob for subsequent test.

4.5.2.3 *Deflection and elevation boresight knobs.* The deflection and elevation boresight knobs shall be set to their midpoint of travel as specified in 3.4.1 (10), and the scales slipped to aline the deflection three (3) and elevation two (2) graduation line to the fixed index. When the line of sight through the boresight mark (center of boresight cross) of the left and right sighting reticle is alined to the positions specified in 3.4.1 (11) and 3.4.1 (12), the deflection and elevation boresight knobs shall be at their midpoint of rotation within the tolerance specified, as measured on the boresight scales. Slip scale to aline the deflection three (3) and elevation two (2) graduation line to the fixed indices upon successful completion of test as required by 3.4.2.3.

4.5.3 *Calibration reticle setting accuracy, previbration.* With the rangefinder oriented as in 3.4.1 and the calibration knobs set to midpoint within the tolerance specified in 3.4.3, the lower calibration reticle shall meet the requirements specified as measured on a target appropriate for measuring displacement of the calibration reticle with respect to the sighting reticle.

4.5.3.1 The upper calibration reticle shall be adjusted in elevation by means of the halving knob to meet the requirements specified. Mark position of halving knob for subsequent test.

4.5.3.2 The ICS knob shall move the upper calibration reticle in azimuth to vertically aline the calibration reticles. A group of five horizontal coincidence settings of the calibration reticles shall be accomplished by means of the ICS knob. The median of this group of settings shall not exceed the tolerance specified as read on the ICS knob scale.

4.6 Vibration. The rangefinder shall be mounted upon special test equipment and vibrated in accordance wtih the requirements specified in 3.5.

4.6.1 *Physical failure, post vibration.* As a result of vibration, the rangefinder shall show no signs of physical failure of mechanical or optical parts and shall meet the requirements specified in 3.6.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:49Z
Check the source to verify that this is the current version before use.

4.6.2 *Coincidence of target image.* When the vertical calibration knob is rotated to the position established in 4.5.2.2 vertical coincidence of the target images shall not have changed by more than the tolerance specified in 3.6.1.1, as read on a target appropriate for measuring displacement of target images. The median of five readings to bring the target images into horizontal coincidence, by means of the horizontal calibration knob, shall not differ from the zero setting established in 4.6.2.1 by more than the tolerance specified. Any change in UOE shall be read on the horizontal calibration knob scale. Slip scale to the new zero upon successful completion of test.

4.6.3 *Horizontal calibration.* The horizontal calibration knob shall be set to the median reading obtained in 4.5.2.1. A group of five horizontal coincidence settings of the calibration reticles shall be accomplished by means of the ICS knob. The difference between the median of this group and the value established in 4.5.3.2 shall not exceed the tolerance specified in 3.6.1.2.

4.6.4 *Calibration reticle setting.* Subsequent to vibration, the space between the two calibration reticles shall meet the requirements specified in 3.6.1.3 when the vertical calibration knob is rotated to the position established in 4.5.2.2 and the halving knob is rotated to the position established in 4.5.3.1.

4.6.5 *Alinement of sighting reticles.* The line of sight through the boresight mark of the left and right sighting reticles shall again be alined to the positions specified in 3.5.1 (11) and 3.5.1 (12). Any change in the alinement of the sighting reticles from the values established in 4.5.2.3 shall not exceed the tolerance specified, as read on the knob scale, required by 3.6.1.4.

4.6.6 *Cleanliness, dirt, post-vibration.* The rangefinder shall be inspected for cleanliness in accordance with Specification MIL-O-13830, and shall meet the requirements specified in 3.6.2.1.

4.6.7 *Bright spots.* The reticles, illuminated by the lamps in the rangefinder, shall be visually inspected for conformance with the requirements specified in 3.6.2.2.

4.6.8 *Parallax of sighting reticles.* The test shall be conducted with each sighting reticle projected into the optical system, in turn. Parallax at the reticle boresight mark for each optical system shall not exceed the tolerance specified. When the image of the left and right sighting reticles are superimposed, the parallax between the reticles shall not exceed the tolerance specified in 3.6.3.1. Parallax is any apparent movement of the reticles in relation to each other or to the target in the field of view caused by movement of the observer's head.

4.6.9 *Parallax of the calibration reticles.* The test shall be conducted with the aid of an auxiliary testing device containing a center aperture that will permit controlled scanning of the exit pupil. This device shall be positioned over the rangefinder eyepiece. A group of five horizontal coincidence settings of the calibration reticles shall be accomplished by means of the ICS knob when the eye is positioned the specified distance to the left of exit pupil center. A group of five readings shall be taken with the eye positioned to the right of exit pupil center. The difference between the median of the left group and the median of the right group shall not exceed the tolerance specified, as read on the ICS knob scale required by 3.6.3.2.

4.6.10 *Parallax of the target images.* The auxiliary testing device described in the test for parallax of calibration reticles shall be used for this test. The images of a target at 1,200 meters plus or minus 100 meters shall be brought into coincidence by means of the range knob. Coincidence shall then be disturbed by rotation of the horizontal calibration knob. A group of five horizontal coincidence settings of the target image shall be accomplished by means of the horizontal calibration knob when the eye is positioned the specified distance to the left of exit pupil center. A group of five readings shall be taken with the eye positioned to the right of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:49Z
Check the source to verify that this is the current version before use.

exit pupil center. The difference between the median of the left group and the median of the right group shall not exceed the tolerance specified in 3.6.3.3 as read on the horizontal calibration knob scale.

4.6.11 *Exit pupil.* This test shall be conducted in accordance with Specification MIL-O-13830 and shall meet the tolerance requirements specified in 3.6.4. The exit pupils shall be measured at the smallest diameter when they are irregular or oval.

4.6.11.1 *Exit pupil concentricity.* The concentricity of the exit pupils shall be inspected with the aid of a dynameter (standard measuring equipment) positioned at the eyepiece and a light source at the end housing windows. Both exit pupils shall be in sharp focus and each shall be compared for location by first placing the occluder into either the right or left optical system and note position of the exit pupil. Rotate occluder into the other system and compare positions on the scale of the dynameter. The exit pupils shall be concentric to each other within the 0.3 millimeter tolerance specified in 3.6.4.1.

4.6.11.2 *Magnification.* The magnification of the rangefinder shall be inspected by using an improvised diaphragm placed in the end housing assembly window. The diaphragm shall have a 20 millimeter diameter hole or aperture. Place a light source at the diaphragm. Using the dynameter specified in 4.6.11.1 positioned at the eyepiece, adjust for a sharp focus of the 20 millimeter aperture. When the aperture is sharply focused the diameter of the aperture is read directly on the dynameter scale, for both right and left optical systems. The diameters shall read 23 millimeters plus or minus one percent. The magnification of the right and left optical systems shall be within one percent tolerance as specified in 3.6.4.2.

4.6.12 *Eyepiece focus.* The diopter movement of the eyepiece shall be tested manually and visually for the requirements specified. Focus of the rangefinder eyepiece shall be tested with the aid of a calibrated dioptometer, having a magnification of at least three-power (3X), adjusted for infinity focus for the observer's eye, and the diopter scale set to zero. The zero setting of the range finder eyepiece diopter scale shall be within the tolerance specified in 3.6.5 when sharp focus of the left target image is obtained, while viewing through the dioptometer and eyepiece simultaneously.

4.6.12.1 *Resolution.* This test shall be conducted in accordance with Specification MIL-O-13830. The resolving power of each system shall meet the requirements specified in 3.6.6. The auxiliary telescope used in this test shall be at least a three-power (3X) instrument.

4.6.13 *Light transmission.* Filters shall be transferred out of the optical systems for this test. Light rays from a concentrated source entering the rangefinder, through each end housing window, shall be measured at the eyepiece by means of a photometer, consisting of a light source, photocell and micrometer. The difference in light transmission between the two optical systems shall meet the requirements specified in 3.6.7.

4.6.14 *Sighting reticles.*

4.6.14.1 *Accuracy of sighting reticles.* This test shall be conducted in accordance with Specification MIL-O-13830. The angle subtended by the total horizontal lines and spaces of the left and right sighting reticles shall meet the requirements specified in 3.6.8.1.

4.6.14.2 *Plumb travel.* A line of sight through the boresight mark of the left sighting reticle coincident to a plumbline shall not deviate from that plumbline by more than the tolerance specified when the rangefinder is manually elevated from 8° depression to 19° elevation as required by 3.6.8.2.

4.6.14.3 *Rangefinder elevation movement.* Rangefinder shall be elevated and depressed to meet the requirements specified in 3.6.8.2.1.

4.6.14.4 *Parallelism of sighting reticle and image.* Using an auxiliary telescope the parallelism of the 40 mil horizontal reticle line to the image of a horizontal target line

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:49Z
Check the source to verify that this is the current version before use.

shall be measured on the boresight knob on a target appropriate for measuring any cant of the reticle line. Parallelism of the left and right sighting reticle shall meet the requirements specified in 3.6.8.3.

4.6.14.5 *Tilt variation between reticles.* When the right sighting reticle is superimposed on the left sighting reticle, using an auxiliary telescope, the tilt variation between reticles, as measured at one extremity of the 40 mil reticle line, shall not exceed the tolerance specified when the other extremity of both 40 mil reticle lines are coincident. Tilt between reticles shall be measured on the boresight knob on a target appropriate for measuring tilt variation between reticles within the tolerance specified in 3.6.8.4.

4.6.15 *Coincident reticles.*

4.6.15.1 *Parallelism of calibrating reticles.* Each calibrating reticle, in turn, shall be tested for parallelism to the image of a plumbline and shall be parallel within the tolerance specified. When one extremity of a vertical side of the calibration reticle is alined coincident to the image of a plumbline, the other extremity shall be parallel to that plumbline within the width of the calibration reticle at that extremity and shall meet the requirements of 3.6.9.1.

4.6.15.2 *Reversing reticles.* With the calibration reticles in reversed position (upper bar immediately under the lower bar), a group of five horizontal coincidence settings of the calibration reticles shall be accomplished by rotating the ICS knob. The difference between the median of this group and the value established in 4.6.3 shall not exceed the tolerance specified in 3.6.9.2 as read on the ICS knob scale. Upon successful completion of the vertical movement accuracy test, restore the calibration reticles to their proper position.

4.6.15.3 *Vertical movement accuracy.* Set the horizontal calibration knob and the ICS knob to the median values obtained in 4.6.3. The vertical calibration knob shall be rotated to the maximum CCW position and the upper calibration reticle, controlled by the halving knob, shall be positioned immediately above the lower reticle (separated by a minimum distinguishable spacing). A group of five horizontal coincidence settings of the calibration reticle shall be accomplished by means of the ICS knob. The vertical calibration knob shall then be rotated to the maximum CW position and the upper calibration reticle again positioned as above. A group of five horizontal coincidence settings of these reticles shall be accomplished by means of the ICS knob. The difference between the median of the first group and the median of the second group shall not exceed the tolerance specified in 3.6.9.3 as read on the ICS knob scale. Upon successful completion of this test, return calibration reticles to normal position.

4.6.15.4 *Horizontal movement accuracy.* The line of sight of the rangefinder shall be directed to a target of known distance within 1,100 and 1,300 meters and range scale set to agree with the range chosen. The target shall be in coincidence and the horizontal calibration and ICS knobs set to established median positions. The horizontal calibration knob shall be rotated plus 40 UOE, then coincidence of the target images re-established by means of the ranging knob. The corresponding change in range, as read on the range scale, shall be equivalent to the change in the number of UOE within the tolerance specified. This test shall be repeated with the horizontal calibration knob rotated to minus 40 UOE as required by 3.6.9.4.

For computing the change in range that corresponds to the change in UOE use the following approximation:

$$\text{The change in range for 1 UOE} = 2.90 \frac{R^2}{(1000)}$$

Where R=Range scale reading

This approximation is good for a maximum of 10 UOE.

4.6.15.5 *ICS calibration.* The horizontal calibration knob and the ICS knob shall be set to the values established in 4.6.3. The

Source: https://assist.dla.mil -- Downloaded: 20261O-22T05:49Z
Check the source to verify that this is the current version before use.

ICS and horizontal calibration knobs shall be rotated to the positions specified, as measured on the knob scales. The position of the horizontal calibration knob, as a result of this excursion, shall not exceed the tolerance specified in 3.6.9.5 and as read on the horizontal calibration knob scale.

4.6.16 *Filters.* Introduction of the filters shall not cause the target images to shift horizontally with respect to each other by more than the tolerance specified in 3.6.10.

4.6.17 *Compensator elevation error.* The rangefinder range scale shall be set to 500 meters with the target images in vertical coincidence. Any vertical shift of the target images shall not exceed the tolerance specified when the range scale is actuated from 500 meters to 4,400 meters. Image shift shall be measured on a target appropriate for measuring image shift within the specified tolerance in 3.6.11.

4.6.18 *Range output accuracy.* The horizontal calibration knob shall be set at zero index. Then attach a revolution type counter disk to the output shaft of the rangefinder. Position an improvised index, for reading the revolution counter. Set the range scale of rangefinder to 1,000 meters, then adjust the counter disk zero, to the index and secure in position. When any range between 500 meters and 4,400 meters is chosen, observe the revolutions of the counter disc, the range scale, and the rotation of the output shaft. The readings shall meet the tolerances specified in table I and table II and shall also meet the requirements of 3.6.12.

4.6.18.1 *Output shaft excursion.* The output shaft excursion shall be tested for full revolutions from one extreme to the other extreme and must have sufficient revolutions to meet the high and low requirements within the specified tolerances in 3.6.12.1.

4.6.18.2 *Output shaft tolerance.* The rangefinder line of sight shall be directed to a target or targets positioned at known distances between 500–540 meters, 650–750 meters, 1,100–1,300 meters, 2,200–2,800 meters and 3,800–4,400 meters. The *P* value for the known range shall be computed from the formula specified and shall be computed for each target. The median of each group of five range readings (rotational position of output shaft) shall meet the requirements within the UOE tolerance specified in table I. Unit of error tolerances shall be converted to output rotations using the formula *I UOE* equals $0.000029R$ and then compared with the difference between the indicated output shaft value of the median range reading and the computed *P* value for a specific range as illustrated in tables I and II and required by 3.6.12.2.

4.6.18.3 *Range scale tolerance.* When the rangefinder output shaft is rotated to the nominal positions (*P*-value) specified for the ranges in column I, table II, the range scale shall indicate these ranges respectively within the tolerance specified in 3.6.12.3. The nominal positions of the output shaft shall be computed from the formula $P=23.454 \text{ Log } 10_R-58.577$.

4.6.19 *Cross field error.* This test shall require five targets positioned at 1,200 meters plus or minus 100 meters. One target shall be positioned at the center of the field (a line of sight through the reticle boresight mark) with the remaining four targets positioned at the specified number of mils from the center of the field. Set the rangefinder range scale to the range chosen and sight on target in the center of the field. The target at the center of the field shall be in coincidence when the horizontal calibration and ICS knobs are set to their established median positions. A group of five horizontal coincidence settings shall be taken on each target, in turn, by means of the horizontal calibration knob. The difference between the median of the center target and the medians of each group of five settings shall not exceed the tolerance specified in 3.6.13 measured on the horizontal calibration knob scale.

4.6.20 *Base length.* All control knobs of the rangefinder shall be set to their individual established median positions and the range scale set to 4,400 meters of range. A plumbline shall be positioned approximately

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:49Z
Check the source to verify that this is the current version before use.

3 to 4 inches in front of each end housing window. The measured distance between plumblines shall be 79.000 inches plus or minus 0.15 inches (2.0059 meters plus or minus 3.81 millimeters). The test for base length shall be performed with the aid of an auxiliary testing device, positioned at the eyepiece of the rangefinder. This device shall be capable of focusing on the etched dots on Objectives 8200012, 8200005, and the plumblines. The scale or reticle of the device shall be capable of measuring the actual separation between dot images and plumbline images formed at the rangefinder eyepiece. Focus the device on the etched dots, then turn occluder of rangefinder so that left dot image is observed. Record scale reading of position of left dot. Turn occluder so that right dot image is observed. Record scale reading of position of right dot. The difference between the two recorded readings shall be used as the *A* factor in the formula for computing base length error. Repeat the operations listed above to measure the difference between plumblines. The difference between the two recorded readings shall be used as the *B* factor in the following formula for computing base length error where 10 equals the power of the rangefinder.

$$10\ (A-B) = \text{Base length error}$$

The base length error shall not exceed the tolerance specified in 3.6.14.

4.6.21 *Boresight knob.*

4.6.21.1 *Elevation.* The lines of sight, through the boresight mark of the left and right sighting reticle, shall be oriented to the position established in 4.6.14.3. Each mil of rotation of the elevation boresight knobs, clockwise and counterclockwise from the established nominal position, shall cause a comparable change in the line of sight and shall meet the excursion requirements specified in 3.6.15.1 and measured on the boresight knob from a target appropriate for measuring elevation movement of the reticle.

4.6.21.2 *Deflection.* The line of sight, through the boresight mark of the left and right sighting reticle, shall be oriented to the position established in 4.6.2.3. Each mil of rotation of the deflection boresight knobs, clockwise and counterclockwise from the established nominal position, shall cause a comparable change in the line of sight and shall meet the excursion requirements specified in 3.6.15.2 measured on the boresight knob from a target appropriate for measuring deflection movement of the reticle.

4.6.21.3 *Backlash boresight knobs.* Rotate the deflection boresight knob in a continuous clockwise direction to move the vertical reticle line of the boresight reticle into coincidence with a vertical target line. Record the setting of the knob scale. Rotate the knob through one full resolution clockwise to move the vertical reticle line past the vertical target line, then by a continuous counterclockwise rotation of the azimuth knob bring the vertical reticle line into coincidence with the vertical target line and read the knob scale. The difference between the recorded reading and the second reading is the amount of backlash. Repeat this operation for the elevation boresight knob using the horizontal reticle line and a horizontal target line. Backlash for each elevation and each deflection knob shall not exceed the limit specified in 3.6.15.3. Rotation of the knobs must be uniform in each direction. The reticle line shall not override the target line during these operations. If override occurs, this test is nullified and the operations specified will again be performed.

4.6.21.4 *Boresight locks.* Actuation of the deflection and elevation boresight knob locks shall not cause the boresight knobs to rotate or cause the line of sight to change by more than the specified tolerance in 3.6.15.4 measured on the knob scale.

4.6.21.5 *Boresight knob lock retention.* This test shall be performed with a special testing adapter affixed to the boresight knob, and a torque wrench (Standard Measuring Equipment) to test torques. The boresight knob lock retention shall meet the requirements specified in 3.6.15.5 when the indicated torque is applied to the knob.

4.6.22 *Calibration knobs.*

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T05:49Z
Check the source to verify that this is the currentversion before use.

4.6.22.1 *Backlash in ICS knob and horizontal calibration knob.* These tests shall be conducted similar to 4.6.21.3. The upper calibration reticle shall be alined to vertical target line by means of the ICS knob. The clockwise rotation of the knob shall be to the clockwise stop before beginning the counterclockwise rotation. The lower calibration reticle shall be alined to the vertical target line by means of the horizontal calibration knob. The results of this test shall meet the requirements specified in 3.6.16.1.

4.6.22.2 *Calibration locks.* This test may be conducted concurrent with the backlash test for calibration knobs. Any error caused by the engagement of the horizontal and vertical calibration knobs with the serration detents shall not exceed the tolerance specified in 3.6.16.2.

4.7 Operability. The maximum torques required to rotate the controls of the range finder shall not exceed those values specified in column I, table III, while at an ambient temperature of plus 60° to 90° F. These tests shall be conducted with special testing adapters (STE) and torque wrenches to measure the torques required by 3.7.

4.8 Horizontal calibration, post-environmental. Each rangefinder that has been adjusted to and has met the requirements of 3.8 shall be subjected to the following test prior to final acceptance and shipment:

(1) The range finder shall be set up as specified in 4.5.1 and tested in accordance with 4.5.2.1. The horizontal calibration of the target images shall meet the requirements specified.

(2) A group of five coincidence settings of the calibration reticles shall be made by means of the ICS knob. The median of the five settings shall not exceed the tolerance specified as read on the ICS scale.

4.9 Sealing and flushing of rangefinder main body and end housing assembly.

4.9.1 The rangefinder body and end housing assembly shall be flushed with dry nitrogen. The rangefinder body and end housing assembly shall then be sealed with an internal pressure of 6 inches of mercury. After a period of 12 hours, the body and end housing shall show no evidence of leakage of dry nitrogen in excess of the tolerance specified. The sealing test shall be conducted with standard test equipment that shall be capable of measuring any drop in internal pressure of rangefinder body and end housing assembly within the tolerance specified in 3.9 and 3.9.1. The dewpoint shall meet the specified requirement and then sealed with the required quantity for shipping and storage.

4.10 Storage temperatures. Environmental test shall be performed using the contractor's Government approved refrigeration and heating equipment. The operability and torque test on the rangefinder may be conducted concurrent with the storage test. Caution must be exercised so as not to expose the rangefinder to thermal shock during environmental test. Temperature changes shall be gradual and in accordance with 3.10.1.

4.10.1 *Physical failures, post-environmental.* Subsequent to the exposure to the storage temperatures, the rangefinder shall be returned to room temperature and examined for evidence of physical failure of optical and mechanical parts. Failure of rangefinder to meet this test in 3.11.1 shall be cause for rejection of the rangefinder.

4.10.2 *Operational temperatures.* When thermal equilibrium is reached at minus 40° F., the controls listed in table III shall be mechanically operable and in accordance with 3.10.2.

4.10.3 *Controls, torque.* When thermal equilibrium is reached at minus 25° and plus 150° F., all controls shall meet the applicable torque requirements contained in table III.

4.11 Post-environmental check. Subsequent to the test specified in 4.10.1 the rangefinder shall be set up as specified in 4.5.1. The boresight knobs and calibration knobs shall be set to their established values.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:49Z
Check the source to verify that this is the current version before use.

4.11.1 *Alinement of sighting reticles.* The line of sight through the boresight mark of the left sighting reticle shall meet the requirements specified. The line of sight through the boresight mark of right sighting reticle shall coincide with the aiming point of the left telescope within the tolerance specified in 3.11.1.

4.11.2 *Image coincidence.* Obtain a new median of five coincidence settings of the target images by means of the horizontal calibration knob. The difference between the new median reading and the median obtained in 4.5.2.1 shall not exceed the UOE tolerance specified in 3.11.1.

4.11.3 *Vertical calibration of images.* This test shall be conducted as indicated in 4.6.2. Verticle calibration of the images shall meet the requirements specified in 3.11.1.

4.11.4 *Calibration reticles setting.* This test shall be conducted as indicated in 4.6.4. The calibrating reticles setting shall meet the requirements specified in 3.11.1.

4.11.5 *Field error.* This test shall be conducted as indicated in 4.8. Field error shall meet the requirements specified in 3.11.1.

4.12 **Horizontal calibration.** Set horizontal calibration known to median setting obtained in 4.5.2.1. Obtain a new median of five ICS settings of the calibrating reticle using the ICS knob. The difference between the new median setting and the median obtained in 4.5.3 shall not exceed the UOE tolerance specified in 3.11.2.

4.13 **Insulation resistance.** This test shall be conducted in accordance with Specification MIL-F-13926 by use of standard measuring equipment and shall meet the requirements of 3.13.1. Remove all lamp bulbs and remove ground connection, identified as wire number 17 on Drawing C8620852 before conducting this test.

4.14 **Continuity.** The electrical circuits shall be checked for continuity by use of standard measuring equipment and shall conform to the wiring diagram and 3.12.2.

4.15 **Packaging, packing and marking.** Quality Assurance Provisions for packaging, packing and marking shall be in accordance with Specification MIL-P-14232.

5. PREPARATION FOR DELIVERY

5.1 **Packaging, packing, and marking.** Packaging, packing, and marking shall be in accordance with Specification MIL-P-14232 and Packaging Data Sheet MIL-P-14232/P5800850. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 **Intended use.** The Rangefinder: M17B1C is a full field superimposed coincidence type instrument, intended for installation in the 90MM Gun Tank: M48A3. This rangefinder is commander operated. It employs a 10 power optical system, with a 4° field of view and has a base length, including end housings, of 79 inches and furnishes range data to a trajectory computing system.

6.2 **Ordering data.** Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Selection of an applicable level of preservation, packaging, and packing.
(c) Applicable stock number.
(d) Applicable packaging data sheet number (see 5.1).

6.3 **Position of adapter link assembly.** No rangefinder shall be accepted for testing which has not been previously inspected, prior to assembly of the main hanger bearings, for precise positioning of the Adapter Link Assembly 8201530 as required by Drawing P8620777-4. Two production end housings shall be identified as components of each rangefinder by stenciling the rangefinder serial number and end housing position (left and right) on the exterior of each end housing. Under no circumstances will temporary substitution of other end housings be permitted for completion of requirements herein or for shipment of the rangefinder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:49Z
Check the source to verify that this is the current version before use.

6.4 Post-vibration. Should the rangefinder fail to meet all requirements of 3.6.1, the contractor may request that the identified end housing assemblies be removed and replaced, using only the same identified end housings, in order to insure that the installation of the end housings was not at fault. Should the results of the second installation be at variance with the first, one or more additional installations may be made until two consecutive installations repeat within required limits, after which the instrument shall be considered acceptable to this stage (3.6.1).

6.5 Definitions. The term "median" as used herein, is defined as that range or setting which divides the series into an upper and lower half. Example—in a set of five range readings 2,000, 2,050, 2,080, 2,060, 2,025 the median would be 2,050. Two ranges are higher and two are lower.

6.6 Environmental exposure. Pre-Ordnance environmental exposure by the contractor for the purpose of stabilizing a complete instrument or any part thereof, prior to Ordnance inspection, will be permitted and encouraged provided such treatment is part of the established process for all instruments. This process shall not be limited to those instruments selected for environmental testing.

6.7 Output shaft. For the computation of UOE with respect to the amount of turns of the output shaft use the relationship that $0.000029R$ (R is range in meters) corresponds to 1 UOE change in ranging. (This formula should not be used for application for values in excess of 5 UOE.)

6.8 Illuminating the calibrating reticle. The calibrating reticle lamp shall not be left on for more than 2 minutes at any one time. If it is necessary to turn on the reticle lamp again, allow at least 1 minute between checks. Establish alinement of the coincidence reticle using the cover protected ICS and halving knobs.

Custodian:
Army—MU

Preparing activity:
Army—MU
Project No. 1240–A263Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:49Z
Check the source to verify that this is the current version before use.