AMENDMENT 1
14 FEBRUARY 1964

MILITARY SPECIFICATION

SIGHT, INFINITY: 8635466

This amendment forms a part of Military Specification MIL–S–46371(MU), 12 April 1963.

Paragraph 3.5: Delete paragraph and substitute:

"**3.5 Alignment.** With the mounting surface in a vertical plane and the locating key horizontal within 1.0 minute, the center of the reticle pattern shall be projected 26° ± 1.0 minute below a horizontal plane."

Paragraph 4.6.2.3: Delete paragraph and substitute:

"**4.6.2.3** *Device used to test accuracy requirement.* The device shall position the sight on a keyed locating surface with the mounting surface in a vertical plane and the key horizontal within 1.0 minute. The surface used for measuring the projected reticle image shall be graduated in 1.0 ± 0.2 mil increments, horizontally and vertically, in a manner suitable for measuring the subtended angle of the projected reticle pattern and the boresight adjustment requirements. The surface shall be positioned 26° ± 1.0 minute from a horizontal plane.

Custodian:

Army—MU

Preparing activity:

Army—MU

Projecet No. 1240–A388Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:45Z
Check the source to verify that this is the current version before use.