MILITARY SPECIFICATION

SIGHT, INFINITY: 8635466

This amendment forms a part of Military Specification MIL-S-46371(MU), dated 12 April 1963.

Paragraph 3.5: Delete paragraph and substitute:

"3.5 Alignment. With the mounting surface in a vertical plane and the locating key horizontal within 1.0 minute, the center of the reticle pattern shall be projected 26° ± 1.0 minute below a horizontal plane."

Add new paragraph 3.6 as follows:

"3.6 Environmental"

Paragraphs 4.3 and 4.3.1 Delete and substitute as follows:

"4.3 First Article (Initial Production) Approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of 3 infinity sights manufactured in the same manner using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing shall be obtained from the same source of supply as used in regular production.

4.3.1 Government Testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials."

Add new paragraph 4.3.2 as follows:

"4.3.2 Contractor Testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

Paragraph 4.6.2.3: Delete paragraph and substitute:

"4.6.2.3 Device used to test accuracy requirement.- The device shall position the sight on a keyed locating surface with the mounting surface

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:45
Check the source to verify that this is the current version before use.

in a vertical plane and the key horizontal within 1.0 minute. The surface used for measuring the projected reticle image shall be graduated in 1.0 ± 0.2 mil increments, horizontally and vertically, in a manner suitable for measuring the subtended angle of the projected reticle pattern and the boresight adjustment requirements. The surface shall be positioned 26° ± 1.0 minute from a horizontal plane.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A125

Source: https://assist.dla.mil - Downloaded: 2026-10-22T05:45Z
Check the source to verify that this is the current version before use.