MIL-T-46385A(MU)
9 September 1968
SUPERSEDING
MIL-T-46385(MU)
1 August 1963

MILITARY SPECIFICATION

TELESCOPE, ELBOW: M114

1. SCOPE

1.1 This specification covers one type of elbow telescope known as Telescope, Elbow: Ml14. This telescope is primarily inteded to lay the 105MM Howitzer M102 in direct fire.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-O-13830	Optical Components of Fire Control Instruments: General Specification Governing the Manufacture, Assembly and Inspection of
MIL-F-13926	Fire Control Materiel: General Specification Governing the Manufacture and Inspection of
MIL-P-14232	Parts, Equipment and Tools for Army Materiel; Packaging and Packing of
MIL-I-45607	Inspection Equipment, Supply and Maintenance of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions

DRAWINGS

U.S. Army Frankford Arsenal

F8626440	Telescope, Elbow: M114

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T05:48Z
Check the source to verify that this is the current version before use.

PACKAGING DATA SHEET

8626440 Packaging of Telescope, Elbow: M114

(Copies of specifications, standards, drawings and packaging sheets required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS:

3.1 Materials. - Materials shall be in accordance with drawings, material specifications, and general specifications forming a part of this specification.

3.2 Fabrication. - The telescope shall be fabricated in accordance with Drawing F8626440 "Telescope, Elbow M114," and drawings pertaining thereto.

3.3 General specifications. - The contractor shall be responsible for adherence to and compliance with the following requirements of Specifications MIL-O-13830 and MIL-F-13926.

3.3.1 MIL-O-13830.

(a) Cleanliness
(b) Illuminated reticle

3.3.2 MIL-F-13926.

(a) Order of precedence
(b) Dimensions and tolerances
(c) Inorganic protective surface finishes
(d) Part identification and marking
(e) Workmanship

3.4 Environmental.

3.4.1 Storage temperatures. - The telescope shall be exposed and thermally stabilized at ambient temperatures of -80° and +160°F. Upon return to a standard ambient temperature of 60° to 90°F, the telescope shall show no evidence of physical failure and shall meet the following requirements of this specification.

3.4.2 Operating temperatures. - The telescope shall be exposed and thermally stabilized at ambient temperatures of -40° and +150°F. During thermal stabilization at each of the above temperatures, the telescope shall meet the applicable requirements of 3.9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:48Z
Check the source to verify that this is the current version before use.

I

3.5 Vibration. - The telescope shall be vibrated at a constant frequency of 30 cycles per second with an amplitude of 1/16 inch (1/8 inch total excursion) for a period of 5 minutes ±15 seconds. Subsequent ot vibration, the telescope shall show no evidence of damage or physical failure and shall meet the requirements of 3.6 to 3.10 inclusive.

3.6 Cleanliness. - The telescope shall meet the cleanliness requirements of Specification MIL-O-13830, and there shall be no more than two particles of dirt visible on the surfaces of the sliding reticle, and no more than two particles of dirt visible on the surfaces of the reticle lens (a total quantity of four particles on both optical elements). Each particle shall not be in excess of an area equivalent to a size ten dig. There shall be no dirt on other surfaces which interferes with observation or adversely effects image quality.

3.7 Sealing. - The telescope shall show no evidence of leakage when subjected to an internal pressure of dry nitrogen at 5 psig for five minutes. The interior atmosphere of the accepted telescope shall contain nitrogen (dewpoint of nitrogen shall be at least as low as -25°F) at a pressure of between 0.1 and 0.25 psig.

3.8 Accuracy.

3.8.1 Orientation. - With the telescope mounted on the front mounting surface and the rear angular locating surface of the ojective tube housing, the plane of the objective tube and the locating key shall be horizontal.

3.8.2 Collimation.

3.8.2.1 Reticle lens. - The extreme left and- right zero graduations shall coincide with a horizontal target line 20 mils above the geometric axis of the objective tube with ± 0.5 mil. The vertical line of the HEXM482 ballistic data on the reticle lens shall be 36.5 mils ± 3 mils in azimuth from the boresight cross of the sliding reticle at the zero elevation position.

3.8.2.2 Sliding reticle. - With the telescope positioned as in 3.8.1 and the horizontal line of the boresight cross in coincidence with the zero graduation on the extreme right, the horizontal line shall be in coincidence with the zero graduation on the extreme left with 0.2 mil; the line of sight through the boresight cross shall be parallel in azimuth to the geometric axis of the objective tube within 0.5 mil.

3.8.3 Eyepiece focus. - The eyepiece focus shall be adjustable over the range of plus and minus four diopters as read on the diopter scale. The zero of the diopter scale shall indicate zero diopters within 0.25 diopter.

3.8.4 Reticle accuracy. - The angular values, between the zero and maximum scale graduations for each of the three scales on the reticle lens shall be as indicated on the applicable drawings within 3.0 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:48Z
Check the source to verify that this is the current version before use.

3.8.5 Image tilt. - With the telescope positioned as in 3.8.1, the image of a plumb line over the full field of view shall be vertical within one degree.

3.8.6 Reticle shift. - Changing the direction of rotation of the reticle knob shall not cause the horizontal line of the boresight cross to exceed the tolerance specified in 3.8.2.2; nor shall cause the boresight cross to shift in azimuth in excess of 0.05 roil.

3.8.7 Resolution. - The resolution on the optical axis shall be five seconds of arc or less.

3.8.8 Reticle plumb travel. - With the telescope positioned as in 3.8.1, the line of sight through the boresight cross of the sliding reticle shall track a plumb line within plus or minus 0.5 mil, (total lateral spread not to exceed 0.5 roil) when the reticle is depressed by rotation over an excursion of 60 mils as read on the mil scale of the reticle lens.

3.8.9 Parallelsim of reticle and image. - With the telescope positioned as in 3.8.1, the vertical line of the mil scale shall be parallel to the image of the plumb line within 30 minutes.

3.8.10 Parallax. - With the boresight cross positioned with 2.0 mils of the optical axis, parallax at the boresight cross shall not exceed 0.25 mil between 125 yards and infinity.

3.9 Operability. - The running torque required to rotate the diopter adjustment and the reticle knob shall not exceed the values specified in Table I at temperatures indicated when subjected to the requirements of 3.4.2.

TABLE I- OPERABILITY

Control	Plus 60° to 90°F	Minus 40°F	Plus 150°F
Diopter adjustment	5 inch lbs	9 inch lbs	5 inch lbs
Reticle Slide adjustment	4 inch lbs	8 inch lbs	4 inch lbs

3.10 Illumination. - When illuminated, the markings on the reticle and reticle lens shall appear clearly defined when observed in a darkened area.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract of purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any other facilities

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T05:48Z
Check the source to verify that this is the current version before use.

suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions. - The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 First article (initial Production) approval. - The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) telescopes plus three (3) each of all items covered by SQAP. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.2.1 Government testing. - When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including cerificates of conformance for materials.

4.2.2 Contractor testing. - When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor’s inspection.

4.3 Inspection provisions.

4.3.1 Submission of product. - Unless otherwise specified by the contracting officer, inspection lot size, lot formation and presentation of lots shall be in accordance with "Submission of Product" provisions of MIL-STD-105.

4.3.2 Examination and tests.

4.3.2.1 Components and subassemblies. - All components and subassemblies shall be inspected in accordance with the inspection provisions contained in Supplementary Quality Assurance Provisions (SQAP) listed in the List of Inspection Documents (IEL), when provided with the technical data package (TPD). In the absence of SQAP’s the applicable Quality Assurance Provisions of MIL-F-13926 shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:48Z
Check the source to verify that this is the current version before use.

4.3.2.2 Final acceptance inspection. - Subsequent to first article approval, examination and tests related to Section 3 herein shall be performed on a single defect (individual characteristic) basis in accordance with MIL-STD-105 and the sampling plans specified in Table II herein. Examination and tests for Packaging, Packing and Marking shall be in accordance with MIL-P-14232 and Section 5 herein. The tabulated classification of defects in Table II shall constitute the minimum inspection to be performed by the supplier after first article approval and prior to Government acceptance or rejection by item or lot.

TABLE II - CLASSIFICATION OF DEFECTS

CLASS	CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
CRITICAL 100% INSPECTION			
1.	Sealing	3.7	4.6.1.2
2.	Pressure	3.7	4.6.1.2
MAJOR AQL 1.0% DEFECTIVE			
101.	Pre-vibration collimation	3.8.2.1 & 3.8.2.2	4.6.2.2
102.	Vibration	3.5	4.6.2.3
103.	Cleanliness	3.6	4.6.2.4
104.	Post-vibration	3.5	4.6.2.5
105.	Eyepiece focus	3.8.3	4.6.2.6
106.	Reticle plumb travel	3.8.8	4.6.2.7
107.	Reticle shift	3.8.6	4.6.2.8
108.	Parallax	3.8.10	4.6.2.9
109.	Resolution	3.8.7	4.6.2.10
110.	Image tilt	3.8.5	4.6.2.11
111.	Reticle accuracy	3.8.4	4.6.2.13
112.	Operability	3.9	4.6.2.14
113.	Illumination	3.10	4.6.2.15
114.	Parallelism image & reticle	3.8.9	4.6.2.12
MINOR: None defined			

4.3.3 Acceptance and rejection. - Rejected lots shall be screened for all defective characteristics. Removal or correctionof defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.4 Special sampling.

4.4.1 General. - Three telescopes shall be selected at random as a special sampling from each 100 produced. The sample shall meet the requirements and tests in Table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:48Z
Check the source to verify that this is the current version before use.

TABLE III

CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
301. Fabrication	3.1	Certification
302. General specification	3.2	Certification
303. Temperature storage	3.4.1	4.6.1.1
304. Temperature operating	3.4.2	4.6.1.1
305. Operability (Torque at oper temp)	3.9	4.6.2.14

4.4.2 Failure of sample. - Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the represented inspection lot will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved (see 4.3.3).

4.5 Inspection equipment. - Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-I-45607.

4.5.1 Government furnished inspection equipment. - Where the contract provides for Government furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements specified in MIL-I-45607.

4.5.2 Contractor furnished inspection equipment.

4.5.2.1 Government design. - Unless otherwise specified in the contract, all inspection equipment specified by drawing number in specifications or SQAP forming a part of the contract shall be supplied by the contractor in accordance with technical data listed in the List of Inspection Documents when provided with the Technical Data Package (TDP).

4.5.2.2 Contractor design. - The contractor shall design and supply inspection equipment compatible with the "Test Methods and Procedures" specified in 4.6 of this specification and with the component inspection procedures specified in "Examination" and "Test Facilities" requirements of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions and tolerance used in the design of test equipment shall be so selected and controlled as to insure that the test equipment will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.

4.5.3 Test equipment. - In conjunction with 4.5.2.2, the following standard test equipment shall be utilized in the performance of the applicable tests as specified in 4.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:48Z
Check the source to verify that this is the current version before use.

NOMENCLATURE	DESCRIPTION
1. Hot & cold chamber	Standard type conforming to the accuracies outlined in test facilities specified under test facilities of MIL-F-13926
2. Power supply	Standard shop type to provide a 3 V.D.C output, within 10% accuracy
3. Torque wrench	Standard shop type accurate to within 10% of drawing tolerance

4.6 Test methods and procedures.

4.6.1 Environmental.

4.6.1.1 Temperature test. - The telescope shall be subjected to test Procedure I of MIL-F-13926; however, the temperatures specified in 3.4.1 and 3.4.2 shall apply. When the item under test has been stabilized at the temperature specified, the result of the specified test shall conform to the limits outlined in 3.4.1 and 3.4.2 using test procedures outlined here in.

4.6.1.2 Sealing. - This test shall be performed on a 100% inspection basis using testing equipment the accuracy of which shall conform to the accuracy depicted on Drawing F8565556. When using pressure test fixture, the fixture shall be set-up as outlined in set-up instructions shown on Drawing F8565556, The gas used shall be dry nitrogen having a dew point or -25°F. After connecting the test equipment to the unit under test, adjust the pressure to the pressure specified in 3.7 and maintain the pressure for the time specified in 3.7. pressure to remain constant to assure compliance wiht 3.7.At the completion of the test, connect a dew point tester to the exit port and purge the unit under test until -25°F is recorded and seal the unit after adjusting the internal pressure in the unit to the value specified in 3.7. Record this internal pressure.

4.6.1.2.1 Internal pressure. - This test to be performed using standard shop type pressure gage and standard shop type inspection techniques. This test to be performed on a 100% inspection basis just prior to packaging. Any unit found not containing the internal pressure recorded in 4.6.1.2 shall be rejected and repressurized and retested in accordance with 4.6.1.2. All retested units shall be set aside for a minimum of 12 hours and then retested for internal pressure in accordance with 3.7. Should the unit fail the second test, the unit is to be considered rejected.

4.6.2 Performance.

4.6.2.1 Orientation. - Position Fixture F7573980 in accordance with set-up instructions outlined on the drawing and position and secure Adapter F8566269 and the unit under test to the fixture as outlined in the adapter set-up instructions. Upon completion of all set-up instructions, the unit shall be orientated as outlined in 3.8.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:48Z
Check the source to verify that this is the current version before use.

4.6.2.2 Collimation (pre-vibration). - With the unit positioned as outlined in 4.6.2.1, position the intersecting point of the boresight cross of the sliding reticle in coincidence with the horizontal reticle line of the projected reticle. Observe where this point falls with respect to the vertical limit lines of the projected reticle target. This intersecting point must fall within the limits of the pip lines to assure conformance with 3.8.2.2. Record this position. When this coincidence has been established, sight through the telescope and observe where the left and right zero range lines fall with respect to the projected target line. Both extreme zero range lines must coincide to this target line within the limit of the tolerance lines located above and below this projected target line to assure conformance with 3.8.2.1. Record this position. Also observe where the vertical line of the HEX M482 scale falls with respect to the corresponding target line. This vertical reticle line must coincide with the limits of projected reticle tolerance lines to assure conformance with 3.8.2.1. Record tis position. By means of the range knob, raise the horizontal line of the boresight cross to coincide with extreme right zero range line and observe where the opposite end of this horizontal line falls with respect to the extreme left zero range line. They must coincide within the limits of 3.8.2.2. Use one half the space of the tolerance lines used when determining the location of the extreme zero range line. Record this position.

4.6.2.3 Vibration. - This test shall be performed using devices the accuracy of which shall be equal or exceed the accuracy depicted on Drawings F7560085 and F8295974. The test is to be performed as outlined in Procedure V of MIL-F-13926, the frequency and duration shall be as outlined in 3.5. At the conclusion of the test, the unit under test shall be subject to a visual and tactile examination and shall be subjected to the following test to determine conformance with 3.5.

4.6.2.4 Cleanliness. - The unit under test shall be subjected to the test procedures outlined in MIL-O-13830 for conformance to the requirements outlined in 3.6.

4.6.2.5 Post-vibration. - Reassemble the unit to the final test fixture and repeat the test procedure outlined in 4.6.2.2. The unit under test shall not have moved from the previously recorded settings for those requirements outlined in 3.8.2.1 and 3.8.2.2.

4.6.2.6 Eyepiece focus. - This test is to be accomplished by placing a white background in front of the telescope's window. Eyepiece focus is to be measured using a 3 power dioptometer conforming to the accuracies depicted on Drawing 7680632. Adjust the dioptometer eyepiece assembly to the dioptometer's optical axis. Next direct the dioptometer's line of sight toward a 500 feet distant target such as a smoke stack, edge of a building, or some other well defined target image. Adjust the objective assembly until parallax is removed. Parallax is defined as any apparent movement between the reticle and target image when the head is moved from side to side or up and down. Set zero diopters on the eyepiece of the unit under test and align the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:48Z
Check the source to verify that this is the current version before use.

dioptometer's optical axis to the optical axis of the unit under test and obtain a clear sharp image of the telescope reticle on the optical axis. Make all measurements on the dioptometer by adjusting the objective assembly. Any and all adjustments to be within the limits of 3.8.3. Rotate the telescope's eyepiece assembly and observe the amount of rotation from the zero diopter reading for conformance to the requirement outlined in 3.8.3.

4.6.2.7 Reticle plumb travel. - With the telescope positioned as outlined in 4.6.2.2, observe where the intersecting point of the boresight cross of the sliding reticle falls with respect to the intersecting point of the projected reticle centerlines. By means of the range knob, activate the boresight cross from reticle's geometric axis (20 nil graduation) to each extreme of the mil scale and observe parallelism between this intersecting point and the projected reticle centerline. Parallelism to be maintained with the limits of 3.8.8.

4.6.2.8 Reticle shift. - With the telescope positioned as outlined in 4.6.2.2, sight through the telescope and observe coincidence between the intersecting point boresight cross and the projected center reticle lines while rotating the range knob first in the clockwise and then counterclockwise direction. Rotation of the knob shall not shift the horizontal line of the boresight cross in excess of the limits of 3.8.6. During this rotation of the range knob also observe that the horizontal line of the boresight cross does not shift from the zero range lines when coincidence has been established as outlined in 4.6,2.2.

4.6.2.9 Parallax. - This test may be performed with the telescope positioned as outlined in 4.6.2.2. Adjust the collimator projector to either parallax kistance specified in 3.8.10. Sight through the telescope and by means of the range knob position the horizontal line of the boresight on the geometric axis of the telescope under test (use 20 mil graduation for location of teometric axis). Observe any apparent movement between the intersecting point of the boresight cross and the intersecting point of the projector collimators center horizontal and vertical reticle lines. Any apparent movement between these two points when the inspectors head is moved up and down or from side to side is considered parallax. The amount of movement shall not exceed the limits specified in 3.8.10. Repeat this procedure wiht the projector collimator set to infinity.

4.6.2.10 Resolution. - To perform this test, a wall target containing the appropriate resolution target shall be employed. Construction of the resolution target and the method of inspection shall be as outlined in MIL-O-13830. The telescope must resolve the test pattern within the limits outlined in 3.8.7. Durin this test, the telescope may be supported in a "V" block. The use of packing or shims may be used to position the telescope. When making this test, use a dioptometer having a minimum of 3 power.

4.6.2.11 Image tilt. - This test may be performed with the telescope positioned as outlined in 4.6.2.2. The test is performed by sighting through the auxillary telescope and observe parallelism between the center vertical reticle line of the projector collimator and the center vertical reticle line of the auxillary telescope. They must be parallel within the limits of the angular lines of the projector collimator reticle to assure compliance with 3.8.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:48Z
Check the source to verify that this is the current version before use.

4.6.2.12 Parallelism of image and reticle. - With the telescope and fixture positioned as outlined in 4.6.2.1, sight through the telescope and observe parallelism between the mil scale vertical line and the corresponding projected reticle line. The extent of non-parallelism is to be estimated and shall not exceed the width of a tick line of the mil scale to assure conformance with paragraph 3.8.9.

4.6.2.13 Reticle accuracy. - This test may be performed with the telescope positioned as outlined in 4.6.2.2. To facilitate this inspection, the telescope may be unlocked in the adapter and the zero range graduations of the reticle placed in coincidence with zero range lines of the projected target. To obtain this coincidence, shim the unit in the mount. When this coincidence has been established, observe coincidence between the maximum range line of the scales. They must be within the limit lines of the projected reticle for each scale to assure compliance with 3.8.4.

4.6.2.14 Operability. - This test will be performed at the temperature specified in 3.9 using a torque wrench and appropriate adapters. Running torque readings shall conform to the limits specified in 3.9.

4.6.2.15 Illumination. - Connect a three volt lamp assembly to the telescope to illuminate the reticle assembly and observe the reticle's lines and figures. They shall appear clear and well defined when viewed in a darkened area to conform to the requirement of 3.10.

5. PREPARATION FOR DELIVERY

5.1b Packaging, packing and marking. - Packaging, packing and marking shall be in accordance with packaging data sheet 8626440. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use. - The Elbow Telescope: M114 is primarily intended to be used as the direct fire telescope on the Howitzer: M102. The telescope employs a reticle inscribed for ranges in meters for 105MM ammunition, HEXM482 and HEP-T-M327 and a Mil scale for elevation angles between 0 and 60 mils.

6.2 Ordering data. - Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Selection of applicable levels of preservation, packaging and packing.
(c) Applicable packaging data sheet number (see 5.1).
(d) Applicable stock number.

Custodian:
Army - MU

Preparing activity:
Army - MU
Project No. 1240-A108

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:48Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

YES NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T05:48Z
Check the source to verify that this is the current version before use.