MILITARY SPECIFICATION

TELESCOPE, ELBOW: M114

This amendment forms a part of Military Specification MIL-T-46385A(MU) dated 9 September 1968.

Paragraph 3.7: Delete and substitute:

"3.7 Sealing and Purging.

3.7.1 Sealing. - The telescope shall be capable of sustaining an internal pressure of 5.0 ± 0.1 PSI for a period of 2 hours without loss of pressure in excess of 0.2 PS1.

3.7.2 Purging. - The telescope shall be purged with dry nitrogen supplied at a pressure of 5 ± 1/4 PS1 until the dew point of emergent gas is not higher than -25°F. Purging aperture shall be quickly and positively closed to minimize intermingling of external atmosphere upon disconnection of purging equipment."

Table I: Delete and substitute:

"CONTROL	AT + 60° to + 90°F	AT -40°F and + 150°F
DIOPTER ADJ.	3 to 5 in. lbs.	9 in. lbs. max.
RETICAL SLIDE ADJ	2 to 4 in. lbs.	8 in. lbs. max."

Table II:

Characteristic 1: Change requirement para from "3.7" to "3.7.1",
Characteristic 2: Change "Pressure" to "purging" and requirement para from "3.7" to"3.7.2".

Paragraph 4.6.1.2: Lines 7, 8 and 9: Change "3.7" to "3.7.l". Line 8: Delete "to remain constant" and add "shall remain within 0.2 psi"

Patagraph 4.6.1.2.1: Delete

Paragraph 4.6.2.1: Change "7573980" to "11738255".

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A501

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:47Z
Check the source to verify that this is the current version before use.