INCH-POUND

MIL-F-71127 (AR)
AMENDMENT 3
05 December 1995
SUPERSEDING
AMENDMENT 2
09 November 1994

MILITARY SPECIFICATION

FUZE, POINT DETONATING, PRACTICE, M775 WITH PYROTECHNIC SIGNATURE CARTRIDGE

This amendment forms a part of MIL-F-71127 (AR), dated 26 May 1992, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.10, Delete:

"3.10 Ogive weld and mechanical joint test. The ogive shall withstand an axial pulling force of 50 + 5 pounds on the ogive at both the forward and rear section joint and at the rear section joint after it is properly assembled to an M775 fuze body."

and substitute:

"3.10 Ogive weld and mechanical joint test. The ogive shall withstand an axial pulling force of 50 + 5 pounds on the ogive when applied to the forward joint and the rear section joint after it is properly assembled to an M775 fuze body."

PAGE 6

4.1.3.2, Delete: "c. Rivet, dwg MS9403".

and substitute: "c. Rivet, dwg 12929047".

AMSC N/A FSC 1390
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.

PAGE 7

4.3.1, under Part Description:

Delete: "Packing preformed AMS 3303 O-Ring ... 2929048 ... 10".

Delete: "Fuze Body Assembly ... 9387100 ... 20".

* Delete: "Body, Fuze ... 12944162 ... 10".

and substitute: "Body, Fuze ... 9343991 ... 10".

* Delete: "Metal Parts Assembly Fuze M775 ... 12944172 ... 20"

and substitute: "Metal Parts Assembly Fuze M779/M775 ... 12953583 ... 20".

PAGE 8

* Table I, under Examination or test: Delete: "Body, Fuze ... (Dwg. 12944172)"

and substitute: "Body, Fuze ... (Dwg. 9343991)".

PAGE 12

Section pertaining to the Packing Preformed AMSD 3303 O-Ring: Delete in its entirety.

* Table I, under Examination or test: Delete: "Metal Parts Assembly Fuze M775 ... 12944172"

and substitute: "Metal Parts Assembly Fuze M779/M775 ... 12953583".

PAGE 13

Table I, Under Loading Assy, Fuze M775, delete:

"Fuze chamber operation test",

and substitute:

"Fuze sleeve and chamber operation test".

Under Conformance Criteria, delete:

"25", and substitute: "50".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.

PAGE 13 (cont)

Delete in its entirety:

"Fuze body assembly (Dwg. 9387100)

Examination for defects ... 10 ea ... 3.2 ... 4.4.2.23

Combined welded and mechanical joint test ... 10 ea ... 3.2 ... Test/4.5.13.2".

Under Fuze, PD, Practice, M775, delete:

"Fuze sleeve and chamber operation test ... 50 ea ... 3.9 ... Test/4.5.16".

Under last line, add:

"Combined welded and mechanical joint test ... 10 ea ... 3.2 ... Test/4.5.13.2".

PAGE 14

* Add the following:

"TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS MIL-F-71127 (AR)

PARAGRAPH	TITLE Fuze, Point Detonating, Practice M775	SHEET 7 OF 7		DRAWING NUMBER See below
				NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Spring Ball			
	(Dwg. 9344006)			
	Examination for defects	10 units	3.2	4.4.2.11
	Spring embrittlement test	10(a) units	3.8	4.5.3
	Pin, Packing Clip			
	(Dwg. 9344001)			
	Examination for defects	10 units	3.2	4.4.2.12
	Clip, Packing			
	(Dwg. 9344004)			
	Examination for defects	10 units	3.2	4.4.2.13
	Packing Clip Assembly			
	(Dwg. 9344005)			
	Examination for defects	10 units	3.2	4.4.2.14
	Packing clip pull test	10(a) units	3.2	4.5.9

NOTES: (a) Only 10 units are required if non destructive examination is followed by destructive tests.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used."

Source: https://assist.dla.mil -- Downloaded: 20261O-23T04:21Z
Check the source to verify that this is the current version before use.

PAGE 18

* 4.4.2.1, Sheet 1 of 3, Drawing Number: Delete existing drawing number and substitute "9343991".

Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

* Major 111: Delete "True position of minor striker hole to rear cavity" and substitute: "Location of minor striker hole".

PAGE 19

* 4.4.2.1, Sheet 2 of 3, Drawing Number: Delete existing drawing number and substitute "9343991".

Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 20

* 4.4.2.1, Sheet 3 of 3, Drawing Number: Delete existing drawing number and substitute "9343991".

Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 21

4.4.2.2, Minor 203 and Minor 204: Delete in their entirety.

PAGE 27

* 4.4.2.8, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 28

* 4.4.2.9, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 29

* 4.4.2.10, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 30

* 4.4.2.11, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.

PAGE 33

* 4.4.2.14, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 35

* 4.4.2.16, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 36

* 4.4.2.17, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 37

4.4.2.18: Add the following:

"Major 111 Distance between forward face and forward face of rear flange ... III ... 3.2 ... Gage".

PAGE 38

4.4.2.18, Minor 203: Delete in its entirety.

PAGE 39

* 4.4.2.19, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 40

* 4.4.2.20, Sheet 1 of 1, Under Next Higher Assembly: Delete existing drawing number and substitute "12953583".

PAGE 41

* 4.4.2.21: Delete in its entirety.

PAGE 42

* 4.4.2.22, Sheet 1 of 2, Under Title: Delete current entry and substitute: "Metal Parts Assembly Fuze M779/M775".

Under Drawing Number: Delete existing drawing number and substitute "12953583".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.

PAGE 43

4.4.2.22, Major 102: Delete in its entirety.

* 4.4.2.22, Sheet 2 of 2, Under Title: Delete current entry and substitute: "Metal Parts Assembly".

Under Drawing Number: Delete existing drawing number and substitute "12953583".

PAGE 51

4.5.11, line 5: Change the word "clot" to "clip".

4.5.12, line 3: Change the word "clot" to "clip".

The margins of this amendment are marked with an asterisk, or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-0839)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:21Z
Check the source to verify that this is the current version before use.