MILITARY SPECIFICATION

POWER SUPPLY PP-1104( )/G

This amendment forms a part of Military Specification MIL-P-55151B(EL), dated 15 May 1973.

PAGE 1

2.1 SPECIFICATIONS, FEDERAL: Delete:

PPP-T-76	Tape, Pressure-Sensitive Adhesive Paper, Water Resistant, (For Carton Sealing)

SPECIFICATION, MILITARY: add:

MIL-P-19644	Plastic Molding Material (Polystyrene Foam, Expanded Bead)
MIL-P-26514	Polyurethane Foam, Rigid Or Plastic, For Packaging

STANDARDS, FEDERAL: add:

FED-STD-356	Commercial Packaging of Supplies and Equipment

PAGE 2

3.2, add "(see 4.16)" to end of paragraph.

3.3, add "(see 4.4)" to end of paragraph.

PAGE 4

3.7, first line, after "shall be cleaned" add: "as per MIL-P-11268."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:29Z
Check the source to verify that this is the current version before use.

PAGE 6

3.13, Workmanship, replace entire paragraph with the following:

"3.13 Workmanship. The equipment shall be manufactured and assembled in accordance with requirement 9 of MIL-STD-454 and the applicable portions of the following paragraphs:

(a) In MIL-P-11268:

General requirements for plastic Cleaning

Wiring and cabling, including:	General requirements for securing of parts.
Slack	Process for welding.
Protection	Cleaning after welding.
Clearance	Controls
Splicing	Self-tapping screws
Connections, general.	
Grounding, general	
Shielding on wire and cable	Cleaning prior to welding
Soldering and brazing	

PAGE 7

TABLE II, Inspection 5, Environmental

Under "Unit 3", remove Vibration, sequence "1" and under "Unit 1", add Vibration, sequence "4".

Under "Unit 3", change Fungus, sequence "2" to sequence "1".

PAGE 9

TABLE III, under "Reqt. Para", add "3.2" for Visual and mechanical

PAGE 10

4.5.3.1 Sampling for Group C inspection, replace entire paragraph with the following:

"4.5.3.1 Sampling for Group C inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:29Z
Check the source to verify that this is the current version before use.

4.5.3.1.1 Three (3) samples of the complete equipment shall be selected at random, one (1) sample for each subgroup 1 through subgroup 3 in Table V. The samples shall be selected at the start of the contract from the first quality conformance inspection lot. These samples shall constitute the Group C requirement for first 200 units produced.

4.5.3.1.2 Thereafter, two (2) samples of the complete equipment shall be selected at random, one (1) sample for each subgroup 1 and subgroup 2 in Table V from every 200 units and fraction thereof produced."

PAGE 11

TABLE V, transfer the Vibration test from Subgroup 3 to Subgroup 1, after the Altitude test.

4.6, add the following to the end of the paragraph: "During operating cycle, the Power Supply PP-1104( )/G shall be adjusted to deliver 50 amperes at 28 ± 1 volt DC output. At the end of the final "ON" period, the power supply shall be tested to determine compliance with the requirements of 3.4.2 Output."

PAGE 15

SECTION 5. PREPARATION FOR DELIVERY, replace entire section with the following:

"5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A, B or Commercial as specified (see 6. 2).

5.1.1 Level A, maximum military protection.

5.1.1.1 Cleaning. Power Supply PP-1104( )/G shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Power Supply PP-1104( )/G shall be dried in accordance with the applicable procedure of MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:29Z
Check the source to verify that this is the current version before use.

5.1.1.3 Preservation application. None required.

5.1.1.4 Unit packaging. Unit packaging shall be in accordance with the methods prescribed in MIL-P-116 as prescribed herein.

5.1.1.4.1 Technical literature. Each technical literature shall be packaged method IC-1.

5.1.1.4.2 Power Supply PP-1104( )/G. Each power supply PP-1104( )/G shall be packaged method III as follows: cushion each power supply on all surfaces with cells or pads or both fabricated of fiberboard conforming to PPP-F-320, type CF, class weather resistant, veriety SW, grade W5c, designed to protect all projections and absorb the shock of impact in handling and transit. As an alternate, cushioning material may be fabricated of plastic molding material conforming to MIL-P-19644 or polyurethane foam conforming to MIL-P-26514. Place the cushioned unit within a close-fitting fiberboard box conforming to PPP-B-636, W5c. Close the box in accordance with the appendix of the box specification.

5.1.2 Level B, minimum military protection.

5.1.2.1 Cleaning, drying, preservation and unit packaging. Each power supply shall be cleaned, dried, preserved and unit packaged as specified in 5.1.1.

5.1.3 Commercial packaging. Commercial packaging shall be in accordance with Fed. Std. No. 356.

5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2). Shipping containers for level A and B shall be capable of stacking and supporting superimposed loads during shipment and storage without damaging the container(s) or its contents.

5.2.1 Level A, maximum military protection. Power Supply PP-1104( )/G, packaged as specified in 5.1, shall be individually packed within a close-fitting box conforming to PPP-B-601, overseas type; PPP-B-621, style 4, class 2; or PPP-B-585, style 2 or 3, class 3. Skids, 3 x 4 inch, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Place the technical literature, packaged as specified in 5.1.1.4.1, on top of the contents, directly under the lid of the container. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto except that metal strapping shall conform to QQ-S-781, type 1, finish A.

Source: https://assist.dla.mil -- Downloaded: 202610-22T22:29Z
Check the source to verify that this is the currentversion before use.

5.2.2 Level B, minimum military protection. Power Supply PP-1104( )/G, packaged as specified in 5.1, shall be individually packed within a close-fitting box conforming to PPP-B-601, domestic type; PPP-B-621, style 4, class 1; or PPP-B-585, style 2 or 3, class 3. Skids, 3 x 4 inch, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Place the technical literature, packaged as specified in 5.1.1.4.1, on top of the contents, directly under the lid of the container. Closure and strapping shall be in accordance with the applicable container specification or appendix.

5.2.3 Commercial packing. Commercial packing shall be in accordance with Fed. Std. No. 356.

5.3 Marking.

5.3.1 Military marking. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

5.3.2 Commercial marking. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with Fed. STD. No. 356."

Custodian:
ARMY - EL

Preparing activity
ARMY - EL
Project 6130-A166

Source: https://assist.dla.mil -- Downloaded: 202610-22T22:29Z
Check the source to verify that this is the currentversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:29Z
Check the source to verify that this is the current version before use.