MIL-P-83037A(USAF)
11 April 1968
Superseding
MIL-P-83037 (USAF)
2 June 1967

MILITARY SPECIFICATION

PLATFORM, CARGO, AERIAL DELIVERY A/E29H-1

1. SCOPE

1.1 This specification covers aerial delivery cargo platforms designated A/E29H-1. The modular components can be assembled or disassembled in the field to form an aerial delivery platform. Platforms of 8, 12, 16, 20, or 24 feet in length can be formed by utilizing the appropriate components (see 6.3).

*

2. APPLICABLE DOCUMENTS

*2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

QQ-P-416	Plating, Cadmium (Electrodeposited)
PPP-B-636	Box, Fiberboard

Military

MIL-P-3982	Hardware (Fasteners and Related Items); Packaging and Packing for Shipment and Storage of

STANDARDS

Military

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification of US Military Property

DRAWINGS

Air Force

65B3717	Rail Set, Platform, Cargo HCK-( )/E29H-1
65C3721	Nose, Skid - Aerial Delivery Platform

FSC 1670

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:34Z
Check the source to verify that this is the current version before use.

65B3722	Pallet Set, Cargo, Aircraft, HCK-( )/E29H-1
65E3727	Skid - Aerial Delivery Platform
65B3728	Skid Set, Platform HCK-( )/E29H-1
65D3729	Nose - Aerial Delivery Platform
65B3730	Bumper, Metal HCK-49/E29H-1, Set
65D3731	Rail, Side - Aerial Delivery Platform
65E3735	Platform, Cargo, Aerial Delivery A/E29H-1, Assembly of
65D3779	Panel - Aerial Delivery Platform, Assembly of
66C1884	Plate, Bridle Attachment - Cargo Extraction
67B1902	Bridle Plate Set HCK-( )/E29H-1

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preproduction. This specification makes provisions for preproduction testing.

*3.2 Components. The platforms shall consist of the following major components, as required (see 6.3):

Item No.	Description
1	Pallet set
2	Rail set
3	Bumper set
4	Skid set
5	Bridle plate set

3.3 Materials. Materials and hardware shall conform to the subsidiary specifications referenced on the applicable detail drawings.

3.4 Construction. The platform and components shall be constructed in accordance with the requirements of Drawing 65E3735 and the applicable detail drawings thereto.

3.5 Performance

3.5.1 Panel assembly

3.5.1.1 Tiedown ring. The completed panel assembly tiedown rings shall show no evidence of failure when pulled to a proof load of 5,000 pounds in any direction.

3.5.1.2 Puncture. Any 1-inch-square area of the panel shall withstand 750 pounds applied load without sustaining permanent deformation in excess of 1/16 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:34Z
Check the source to verify that this is the current version before use.

3.5.1.3 Lower skin strength. Any panel shall withstand 5,000 pounds applied to a 2-inch-diameter area at the plan view centroid without permanent deformation of the lower skin.

*3.5.1.4 Load rating per panel. For airdrop use, the platform shall be capable of supporting a load of 3,000 pounds per panel or 1,500 pounds per linear foot for any assembled length.

3.6 Finish

3.6.1 Protective coatings. No protective surface coating, neither chemical nor electrolytic, shall be used on aluminum components. All steel components shall be cadmium plated in accordance with QQ-P-416.

3.7 Identification of product. Equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130.

3.8 Workmanship. The platform and components shall be constructed and finished in a thoroughly workmanlike manner. Particular attention shall be given to accuracy of dimensions.

4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the supplier may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of tests. The inspection and testing of the platform shall be classified as follows:

a. Preproduction tests

b. Acceptance tests.

4.3 Preproduction testing

4.3.1 Preproduction test sample. One platform of each size on the contract or order shall be subjected to the preproduction tests specified in 4.3.2.

4.3.2 Preproduction tests. The preproduction tests shall consist of all the tests described under 4.5. Assembly of the platform as specified in 4.5.1 shall be performed in the presence of the contracting officer or his authorized representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:34Z
Check the source to verify that this is the current version before use.

*4.4 Acceptance tests. The acceptance tests shall consist of:

a. Individual tests

b. Sampling tests.

*4.4.1 Individual tests. The individual tests shall consist of:

a. Visual examination of components (see 4.5.2)

b. Dimensional inspection (see 4.5.3)

*4.4.2 Sampling tests. One platform from each lot of 25 complete platforms, or fraction thereof, produced shall be subjected to the assembly inspection specified in 4.5.1.

*4.4.2.1 Lot. A lot shall consist of platforms and components manufactured under essentially the same conditions and submitted for acceptance at substantially the same time.

*4.4.2.2 Rejection and retest. When one or more items from a lot fail to meet the specification, acceptance of all items in the lot shall be withheld until the extent and cause of failure have been determined. The contractor shall explain fully to the Government representative the cause of failure and the action taken to preclude recurrence. After correction, all of the sampling tests shall be repeated.

*4.4.3 Defects in items already accepted. The investigation of a test failure could indicate that defects may exist in items already accepted. If so, the contractor shall fully advise the procuring activity of all the defects likely to be found and the method of correcting them.

4.5 Test methods

4.5.1 Assembly inspection. The platform shall be assembled from completely fabricated items and inspected as specified in 4.5.1.1 and 4.5.1.2 (see 6.4).

4.5.1.1 Assembled platform dimensional inspection. A dimensional check shall be performed on the assembled platform to determine compliance with assembled dimensions as specified on Drawing 65E3735.

4.5.1.2 Assembled platform flatness. A visual check shall be made of the lower surface to determine that the side rail lower surface does not protrude below the adjacent panel lower surface. A visual check shall be made to determine that interconnecting panel edges form a flat plane at the lower joint surface.

Source: https://assist.dla.mil -- Downloaded: 202640-23T07:34Z
Check the source to verify that this is the currentversion before use.

*4.5.2 Visual examination of components. Each platform component shall be visually examined for compliance with the workmanship requirement specified herein and compliance with the requirements of the applicable detail drawings for finished parts.

*4.5.3 Dimensional inspection. Each component shall be inspected for compliance with the dimensional requirements on the applicable detail drawings.

4.5.4 Panel assembly tests

4.5.4.1 Tiedown ring. The tiedown rings of the completed panel assembly shall be subjected to a proof load of 5,000 pounds in all directions. There shall be no evidence of failure of the tiedown rings as a result of this test.

4.5.4.2 Puncture. A load of 750 pounds shall be applied to 1-inch-square areas of the panel. This load shall be applied to a sufficient number of areas on the panel to determine that no permanent deformation in excess of 1/16 inch occurs.

4.5.4.3 Lower skin strength. A load of 5,000 pounds shall be applied to a 2-inch-diameter area of the panel at the plan view centroid. There shall be no permanent deformation of the lower skin.

*4.6 Inspection of preparation for delivery requirements. Sample items or packs and the inspection of the packaging, packing, and marking for shipment and storage shall be in accordance with section 5 or the documents specified therein.

*5. PREPARATION FOR DELIVERY

5.1 Packaging

5.1.1 Level A

5.1.1.1 Hardware. Hardware items in the quantities specified on Drawing 65B3717, 65B3722, 65B3728, 65B3730, and 67B1902 shall be packaged in five boxes in accordance with level A of MIL-P-3982. Contact preservatives shall not be required.

5.2 Packing

5.2.1 Level A

5.2.1.1 Panels (Drawing 65D3779). Two panels, separated by two each 1/4-inch-thick plywood separators, shall be stacked and securely held together by two flat steel straps over two grooved wood buffer blocks (each end) located approximately 2 feet from the end of the panels.

5.2.1.2 Side rails (Drawing 65D3731). Two side rails of the same length shall be nested after inserting 5/8-inch-thick wood separators at 4-foot maximum intervals.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:34Z
Check the source to verify that this is the current version before use.

The side rails so nested shall be placed in a snug-fitting wood container along with the quantity of packed 3/8-inch bolts specified on Drawing 65B3717. The container shall be reinforced with flat steel or nylon straps placed girthwise at approximately 3-foot intervals.

5.2.1.3 Skids (Drawing 65E3727). Four skids of the same length shall be nested and securely strapped together with flat steel or nylon strapping positioned girthwise and located 1 foot from each end and spaced no more than 3 feet apart. The packed 3/8-inch screws and 3/8-inch nuts specified on Drawing 65B3728 shall be nested in the trough of the uppermost skid and securely held in place by one of the girthwise straps.

5.2.1.4 Skid nose (Drawing 65C3721). Four skid noses separated by fiberboard pads and packed 1/4-inch screws and 1/4-inch nuts specified on Drawing 65B3728 shall be packed in a snug-fitting fiberboard shipping container conforming to style FTC, V3c or V3s of PPP-B-636, except that weight and dimensional limitations shall be waived. Each shipping container shall be reinforced with four flat steel or nylon straps (two each side).

5.2.1.5 Nose (Drawing 65D3729). One nose and eight bolts and eight nuts as specified on Drawing 65B3730 shall be packed as specified in 5.2.1.4.

5.2.1.6 Bridle attachment plate (Drawing 66C1884). Four bridle attachment plates of equal length and eight bolts and eight nuts as specified on Drawing 67B1902 shall be packed as specified in 5.2.1.4.

5.2.2 Level B. Level B packing shall be the same as level A packing specified under 5.2.1.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The A/E29H-1 aerial delivery cargo platforms covered by this specification are intended for use as bases for supporting aerial delivery loads during transportation, extraction from aircraft, and ground impact. The components covered herein will be used to make up aerial delivery platforms which can be assembled in the field to provide various lengths as needed.

*6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:34Z
Check the source to verify that this is the current version before use.

b. Quantity of each component required

c. Selection of applicable levels of packing (see 5.2).

*6.3 Additional identifying information. Drawing 65B3735 lists the following five subassemblies for each length:

a. Pallet Set - Drawing 65B3722

b. Rail Set - Drawing 65B3717

c. Bumper Set - Drawing 65B3730

d. Skid Set - Drawing 65B3728

e. Bridle Plate Set - Drawing 67B1902.

These subassemblies may be ordered as needed to assemble platforms in various configurations; i.e., sets a and b are the components of the basic platform required for conventional aerial delivery while the addition of sets c, d, and e adapts the platform for use via low altitude parachute extraction system (LAPES) techniques. Each set is designated by a part number to identify the part size or number of parts required for each length (see table I). For example, to assemble a basic platform 16 feet in length Pallet Set 65B3722-3 and Rail Set 65B3717-3 are required. To adapt this platform for delivery by LAPES, Skid Set 65B3728-3, Bumper Set 65B3730-1, and Bridle Set 67B1902-1 should be added.

6.4 Tools to be used for assembly. The following tools should be used to assemble components to form complete platforms:

a. 2 each sawhorses, 4 feet high, 6 feet long (minimum of 2), or similar movable stands

b. 2 each 9/16-inch wrenches (sockets with speed handle and ratchet, or box-end and impact wrench preferred)

c. 1 each 3/8-inch wrench, box-end

d. 1 each screwdriver, No. 3 Phillips head

e. 1 each screwdriver, No. 2 Phillips head.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:34Z
Check the source to verify that this is the current version before use.

* TABLE I. Sets Required for Platform Lengths

ASSEMBLY PART NO.					SET NOMENCLATURE & PART NUMBER OF SET
65E3735-5	65E3735-4	65E3735-3	65E3735-2	65E3735-1	
-1	-1	-1	-1	-1	BRIDLE PLATE SET 67B1902
-5	-4	-3	-2	-1	SKID SET 65B3728
-5	-4	-3	-2	-1	RAIL SET 65B3717
-1	-1	-1	-1	-1	BUMPER SET 65B3730
-5	-4	-3	-2	-1	PALLET SET 65B3722
24 Ft	20 Ft	16 Ft	12 Ft	8 Ft	

6.5 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Air Force - 11

Preparing activity:
Air Force - 11

Review activity:
Air Force - 82

Project No. 1670-F291

Source: https://assist.dla.mil -- Downloaded: 202610-23T07:34Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

AFLC–WPAFB–OCT 67 2M

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:34Z
Check the source to verify that this is the current version before use.