MILITARY SPECIFICATION

SIMULATOR, TARGET KILL, PARTS FOR
AND LOADING, ASSEMBLING AND PACKING

This amendment forms a part of military specification MIL-S-70536(AR) dated 5 May 1986 and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and " is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1 Other Government documents, drawings and publications. Add the following drawing to "Product and Packaging Drawings":

"8837375 - ARRADCOM Environmental Testing Criteria for OCONUS Shipping Containers."

PAGE 3

3.3.1 Visual signature. Delete "(1-5 knots)" and substitute "(0-5 knots) relative wind indication."

3.3.2 Delete and substitute:

'3.3.2 Functioning. The target kill simulator shall fire when subjected to a power source of 12 volts, current limited to 1.2 amps.W

Add the following paragraphs:

"3.4.6 Five foot drop test. The simulator shall not detonate nor split but remain operable when tested as specified in 4.5.4.7."

"3.5 Packaging tests. The packaged simulators shall not function when tested as specified in 4.5.5."

3.5 First article Inspection. Change "3.5" to '3.6".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:39Z
Check the source to verify that this is the current version before use.

PAGE 4

3.6 Workmanship. Change "3.6" to "3.7".

Add the following paragraph 3.8

"3.8 Electric match no fire test. The electric match assembly shall not fire when subjected to the applicable current specified on Dwg. 9354515."

* 4.3.1 Submission:

Add to list: "Spring, Short Circuit, 12953395".

Delete from list: "Cap, Short Circuit, 9342157".

PAGE 5

* Table I Cap, Short Circuit: Delete in its entirety and substitute:

"Spring, Short Circuit
(Dwg. 12953395)
Examination for defects 32 3.2 4.4.2.3"

PAGE 6

Under Table I First article inspection, delete "Consequential" tests and "Sequential* tests in their entirety and substitute the following:

"Examination of Test	# of Samples	AQL	Req. Para	Para. Ref.
Sequential test				
Leakage test	1 box		3.4.4	4.5.4.4
Seven foot drop	1 box		3.5	4.5.5.1
Transportation vibration	1 box		3.5	4.5.5.2
Loose cargo	1 box		3.5	4.5.5.3
Five foot drop (Note 1)				
Hot	20		3.4.6	4.5.4.7
Cold	20		3.4.6	4.5.4.7
Ambient	20		3.4.6	4.5.4.7
Leak test (Note 2)	60		3.4.3	4.5.4.3
Jumble	30		3.4.5	4.5.4.6
Function	30		3.3	4.5.4.2,4.5.3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

Delete Note 1 in its entirety and substitute the following:

"1. Twenty items to be conditioned at each temperature prior to five foot drop test followed by functioning.

2. Leak tested items to be used for jumble test and ambient functioning."

PAGE 8

4.4.2.1 Minor 201. Change "3.6" to "3.7".

* Add Major "105 Pull test, spring to pins 30, 0-1, 3.2, Gage".

PAGE 9

4.4.2.2 Add the following:

"Major 102, Outside diameter base crimp, max., 0.40%, 3.2, Gage"

* "Major 103, Finish missing or improperly applied, 0.40%, 3.2, visual"

Minor 201. Change "3.6" to "3.7".

PAGE 10

* 4.4.2.3: Delete in Its entirety and substitute new 4.4.2.3 included.

PAGE 11

4.4.2.4 Minor 201. Change "3.6" to "3.7".

PAGE 12

4.4.2.5 Add Major 103.

"103 No-Fire Test 50, 0-1 3.8, 4.5.6".

Minor 201: Change "3.6[8] to "3.7".

PAGE 13

4.4.2.6 Delete Major 102 in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70536 (AR)
AMENDMENT 2

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Spring, Short Circuit	1 OF 1	12953395
			NEXT HIGHER ASSEMBLY: 12556037

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	ID of coils		0.40%	3.2	Gage
102	Centerline distance		0.40%	3.2	Gage
103	Height coils, max.		0.40%	3.2	Gage
104	Total height, max.		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.7	Visual

REMARKS

AMSMC ( ) 1570, 1 Feb 85 Replaces SMC-QA (D) Form 160, 1 Aug 83, which may not be us

Source: https://assist.dla.mil -- Downloaded: 20260-23T03:39Z
Check the source to verify that this is the current version before use.

PAGE 15

4.4.2.8 Delete Majors 105 to 111 in their entirety and substitute the following:

"Critical	# Units	AQL	Req. Para.	Para. Ref.
* 1 Jumble (Note 1)	32	0-1	3.4.5	4.5.4.6
* 2 Leakage of explosive or evidence of loose powder on exterior of assembly	-	100%	3.2	Visual
Major				
105 Leakage Test	1 box	0-1	3.4.4	4.5.4.4
106 Leak Test (Note 1)	182	0-1	3.4.3	4.5.4.3
* 107 (Deleted from previous amendment)				
108 Five Foot Drop (Note 2)				
Hot	50		3.4.6	4.5.4.7, 4.4.5.1
Cold	50		3.4.6	4.5.4.7, 4.4.5.2
Ambient	50		3.4.6	4.5.4.7, 4.4.5.1
109 Height of Assembly, max.		0.40%	3.2	Gage
* 110 Assembly damaged to the extent that powder may leak		0.40%	3.2	Visual"

Minor 201 Change "3.6" to "3.7".

NOTE 1. Delete in its entirety and substitute the following:

"1. Leak tested items used for Jumble test and Five foot drop test.

2. Items to be conditioned at appropriate temperatures prior to Five foot drop followed by functioning."

PAGE 16

4.4.2.9: Minor 203: Change "3.6" to "3.7".

PAGE 17

4.4,2.10: Minor 203: Change "3.6" to "3.7".

Source: https://assist.dla.mil -- Downloaded: 20261O-23T03:39Z
Check the source to verify that this is the current version before use.

PAGE 18

4.4.2.11: Minor 206: Change "3.6" to "3.7".

PAGE 18A

4.4,2,12: Add new page 18A included.

PAGE 18B

4.4.2.13: Add new page 18B included.

PAGE 18c

4.4.2.14: Add new page 18c included.

PAGE 18D

4.4.2.15: Add new page 18D Included.

PAGE 18E

4.4.2.16: Add new page 18E included.

PAGE 18F

* 4.4.2.17: Add new page 18F included.

PAGE 19

4.4.3.1 Moisture Content. under Table II, delete lines 2 and 3, "Composition, Black Smoke" and "Paper-and paper products" in its entirety.

PAGE 20

4.5.2.1 Co mposition, ignition. In line 3, delete "Method 101.2" and substitute "Method 101.2.1".

PAGE 21

4,5.2.2 Delete in its entirety.

4.5.3.2 Delete in Its entirety and substitute:

"4.5.3,2 "Functioning. The target kill simulator assembly shall function when subjected to the conditions specified in 3.3.2. observation shall be made for compliance with the applicable requirement."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-70536 (AR)
AMENDMENT 2

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Alternate Plug Assemby				12913036
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Resistance of assembly improper		0.40%	3.2	Gage
102	Crimp improper or pin damaged		0.40%	3.2	Visual
Minor					
201	Any component missing, damaged or improperly assembled		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.7	Visual

REMARKS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

MIL-S-70536 (AR)
AMENDMENT 2

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.13	Plug	1 OF 1	12913037
			NEXT HIGHER ASSEMBLY 12913036

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness of body, max.		0.40%	3.2	Gage
102	True position of pin/wire hole(s)		0.40%	3.2	Gage
103	Overall width improper				
Minor					
201	Presence of crimp hole(s)		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.7	VIsual

NOTES:

AMSMC(m 1570, 1 Feb 85 Replac(SMC-QA (D) Form 160, 1 Aug 83, which may not be u(

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-S-70536 (AR)
AMENDMENT 2

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Pin, Connector				12913038
					NEXT HIGHER ASSEMBLY 12913036
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Large outside diameter		0.40%	3.2	Gage
102	True position of inside diameter		0.40%	3.2	Gage
Minor					
201	Width of slit		.65%	3.2	Gage
202	Poor workmanship		1.00%	3.7	Visual

REMARKS

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	Alternate Plug, Closure	1 OF 1	12913029
			NEXT HIGHER ASSEMBLY: ---

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Large outside diameter improper (max)		0.40%	3.2	Gage
102	Smaller outside diameter improper		0.40%	3.2	Gage
103	Length of post improper		0.40%	3.2	Gage
Minor					
201	Length of plug		0.60%	3.2	Gage
202	Poor workmanship		1.00%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

MIL-S-70536 (AR)
AMENDMENT 2

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.16	Closure Assembly				12913792
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Tube assembled improperly to the extent that wire will not thread through hole		0.40%	3.2	Visual
Minor					
201	Adhesive improper		0.65%	3.2	Visual
202	Poor Workmanship		1.0%	3.7	Visual
COVER:					

Source: https://assist.dla.mil -- Downloaded: 20260-23T03:39Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Simulator, Target Kill Assembly (prior to sealing with tape)				9390392
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical 1	Short circuit spring missing or damaged		100%	3.2	Visual
Major	None defined.				
Minor	None defined.				

REMARKS

Source: https://assist.dla.mil -- Downloaded: 2026-01-23T03:39Z
Check the source to verify that this is the current version before use.

4.5.4.3 Leak test. Delete in its entirety and substitute the following:

‘4 ,5.4,3 Leak test. The simulators shall be tested for leakage by submersing them in water (at 70° ± 5°F) contained in a vacuum chamber. A vacuum diferential of at least 6 inches of mercury shall be drawn and held for 30 seconds while observing for air bubbles. A steady stream or recurring stream from any surface or seam shall constitute a failure. The cartridges shall be wiped dry prior to functioning, (NOn-Destructive Test)”,

Add the following paragraphs:

“4. 5.4.7 Five foot drop test. The simulators shall be tested in accordance with MIL-STD-331, Test 111.1, procedure 2, 1.5 Meter Drop test. The simulators shall be dropped at each of the five orientations as required in the procedure after temperature conditioning in accordance with 4.5.4.1 and 4.5.4,2, The simulators shall be functioned in accordance with 4.5.3 following the drop. Observations shall be made for compliance with applicable requirements. (Destructive Test).”

“4.5.5 Packaging tests. (First article only). A total of one(1) fully packed wood box containing 60 simulators shall be subjected to tests specified in 4.5.5.1, 4,5.5.2 and 4.5.5.3 at ambient temperature.”

“4.5.5.1 Seven foot drop test. The wood box shall be tested in accordance with ARDEC drawing 8837375 test number 13, with the exception that the box be dropped in only one (1) orientation, bottom down. Observations shall be made for compliance with applicable requirements..

“4.5.5.2 Transportation vibration, The wood box shall be subjected to secured cargo vibration as specified in MIL-STD-810, Method 514.3 Category 1 Figures 514.3-4 through 514.3-6. Observations shall be made for compliance with applicable requirements.”

"4.5.5.3 Loose cargo vibration. The wood box shall be tested in accordance with ARDEC drawing 8837375 test number 14. observations shall be made for compliance with applicable requirements.”

Source: https://assist.dla.mil -- Downloaded: 2026t0-23T03:39Z
Check the source to verify that this is the currentversion before use.

‘4.5.6 Electric match no fire test. The electric match assembly shall be tested for the no-fire condition by applying the current specified on Dwg. 9354515. observation shall be made for compliance with applicable requirements. (Non-destructive test)”.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made, This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations, Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian
Army-AR

Preparing activity
Army-AR

(Project 1370-A 345)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:39Z
Check the source to verify that this is the current version before use.