INCH-POUND

MIL-T-83027C
AMENDMENT 1
30 OCTOBER 1994

MILITARY SPECIFICATION

TRANSMITTER, RATE OF FLOW, (FUEL TRU-98/A)

This amendment forms a part of MIL-T-83027C, dated 5 February 1986, and is approved for use with the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Delete 2.1.1 and add: "Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2)."

Under SPECIFICATIONS, Federal, delete " PPP-B-636" entirely and add: "PPP-B-1672, Boxes, Shipping, Reusable With Cushioning."

In the "Beneficial comments" Block, line three, delete "MMEDO" and add "TICLA."

PAGE 2

Under SPECIFICATIONS, Military, add: "MIL-B-121, Barrier Material, Greaseproofed, Waterproofed, Flexible, Heat Sealable."

Under STANDARDS, add "FEDERAL." Under STANDARDS, Federal, add "FED-STD-101, Preservation, Packaging And Packing Materials: Test Procedures."

Under STANDARDS, Military, delete MIL-STD-143 entirely and add: "MIL-STD-970, Standards and Specifications, Order Of Preference For."

Under STANDARDS, Military, delete MIL-STD-794 entirely and add: "MIL-STD-2073-1, DOD Material procedures For Application And Development Of Packaging Requirements."

Under STANDARDS, Military, delete MIL-STD-831 entirely.

Delete paragraph that begins with, "(Copies of specifications, standards, handbooks, drawing and publications....." entirely and add: "(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Document Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)."

Add "2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:33Z
Check the source to verify that this is the current version before use.

PAGE 3

Delete 3.1 entirely and add: "3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.2) in accordance with 4.4."

3.2 Line three, delete "MIL-STD-143" and add: "MIL-STD-970."

Add "3.3.8 Cadmium. Cadmium shall not be used by the transmitter without written approval of the preparing activity. Cadmium shall not be used on the exterior of the transmitter. Cadmium shall not come into contact with the fluid being measured."

PAGE 14

Delete "TABLE IV" entirely and add new attached "TABLE IV Test tolerance in +PPH."

PAGE 21

4.1 Line three, after "requirements," add: "(examinations and tests)."

Add "4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material."

4.2 After "a. First article tests," add: "(see 4.4)." After "b. Quality conformance tests," add "(see 4.5)."

PAGE 22

Delete 4.4.2 entirely.

PAGE 23

Delete 4.4.3 entirely and add: "4.4.2 First article tests. The first article tests shall consist of all the tests specified under 4.6. Unless otherwise specified by the procuring activity, tests shall be conducted in the order listed."

PAGE 25

Add "4.6.4.1 Hysteresis. For TRU-98/A-7 transmitters, at each test point the reading taken (after vibration) going douwnscale shall be subtracted from the reading going upscale. The difference shall be within the hysteresis tolerance of TABLE IV."

4.6.33 Line two, delete "test level G."

Delete section 5 entirely and add:

"5. PACKAGING

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:33Z
Check the source to verify that this is the current version before use.

TABLE IV. Test tolerance in + PPH

	TRU-98/A-1 RANGE		TRU-98/A-2 RANGE		TRU-98/A-3 RANGE		TRU-98/A-4 RANGE		TRU-98/A-5 RANGE		TRU-98/A-6 RANGE		TRU-98/A-7 & A-8 RANGE	
TEST	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW
VOLTAGE VARIATION AND FREQUENCY	32	8	40	10	48	12	60	18	80	20	100	25	60	10
POSITION	50	15	50	55	16	60	18	18	70	20	90	28	60	15
FRICTION														
ROOM AND HIGH TEMP	30	10	50	10	55	12	100	18	70	20	90	28	90	10
LOW TEMPERATURE	50	15	50	15	55	16	100	18	70	25	90	30	90	15
VIBRATION														
SIGNAL OSCILLATION	140	40	140	40	160	45	160	50	180	55	200	60	170	40
SIGNAL VARIATION	140	40	140	40	160	45	160	50	180	55	200	60	170	40
HYSTERESIS (DOWNSCALE MINUS UPSCALE, ROOM TEMPERATURE)	----	---	----	---	----	---	----	---	----	---	-----	----	90	12

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:33Z
Check the source to verify that this is the current version before use.

5.1 Preservation. Preservation shall be level "A" or "C" as specified (see 6.2).

5.1.1 Preservation-packaging. Unless otherwise specified by the contracting activity, item shall be packaged in Quantity Unit Pack (QUP) of one each. Each item will be provided a preservation method IC-1 in accordance with MIL-P-116.

5.1.2 Cleaning. Item shall be cleaned in accordance with MIL-P-116 C-1 process.

5.1.3 Drying. Immediately after cleaning, the item shall be dried following any one or combination of the drying procedures listed in MIL-P-116. The drying procedures employed shall not be injurious to the item.

5.1.4 Level A. Item shall be preserved in accordance with MIL-P-116 and MIL-STD-2073-1 to provide a method IC-1.

5.1.5 Level C. Item shall be individually preserved in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from the supply source to the first receiving activity as specified in MIL-P-116 and MIL-STD-2073-1.

5.2 Packing. Packing shall be level "A," "B," or "C" as specified (see 6.2).

5.2.1 Container-cushioning. Unit container requirements shall conform to MIL-B-121, barrier material, unless otherwise specified by the contracting activity. Unit containers shall be large enough to allow for application of cushioning/wrap material, of sufficient density and thickness to protect the unit container from punctures. Intermediate/shipping containers shall be large enough to allow for the application of sufficient cushioning material, between the unit container and intermediate/shipping container. Cushioning material shall be of sufficient density and thickness to ensure shock transmission does not exceed peak values in G's established for the item.

5.2.2 Level A. Fiberboard containers do not meet Level "A" container criteria.

5.2.3 Level B. Item will be preserved as specified in 5.1 and shall be packed in exterior containers conforming to PPP-B-1672, weather-resistant unless otherwise specified by the contracting activity. Exterior container shall be uniform shape, size, and minimum tare and cube, consistent with the protection required. Closure shall be in accordance with appropriate PPP-B-1672 procedure and contracting activity.

5.2.4 Level C. Item will be packed in such a manner that will afford adequate protection against physical damage during direct domestic shipment from the supply source to the first receiving activity. These packs shall conform to MIL-STD-2073-1.

5.3 Marking. Unit, intermediate, and exterior containers shall be marked in accordance with special markings required by the contracting activity and MIL-STD-129.

5.4 Inspection and test. Test of methods of preservation shall be accomplished in accordance with section 4 of MIL-P-116 to ensure compliance with section 5 of this specification. Packaging tests shall be conducted in accordance with rough handling as specified in FED-STD-101."

Under "6. NOTES" add: "(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:33Z
Check the source to verify that this is the current version before use.

PAGE 33

Under 6.2, delete "6.2 Ordering data. Procurement documents should specify the following:" and add: "6.2 Acquisition requirements. Acquisition documents must specify the following:"

Under 6.2, add "(f) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1)."

PAGE 34

Delete 6.6 entirely and add: "6.6 First article. When the first article inspection is required, the contracting officer should provide specific quidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first production item, a sample selected from the first production items, or a standard production item from the contractor's current inventory (see 3.1) and the number of items to be tested as specified in 4.4."

Custodian:
AIR FORCE -99
NAVY -AS

Preparing activity:
AIR FORCE -71

Project number:
6620-F547

Source: https://assist.dla.mil -- Downloaded: 202640-23T07:33Z
Check the source to verify that this is the currentversion before use.