[INCH-POUND]
A-A-1753A
July 29, 1993
SUPERSEDING
A-A-1753
July 8, 1981

COMMERCIAL ITEM DESCRIPTION

POACHER, EGG

The General Services Administration has authorized the use of this commercial item description as a replacement for Federal Specification RR-K-260, type V, which has been canceled.

1. SCOPE

1.1 Scope. This commercial item description covers an aluminum 4-cup egg poacher.

2. APPLICABLE DOCUMENTS

2.1 The documents referenced in this commercial item description shall be the issues in effect on the date of the invitation for bids or request for proposals unless otherwise specified. These documents form a part of this commercial item description to the extent specified. In the event of a conflict between this commercial item description and a document referenced herein, this commercial item description shall take precedence.

Federal Standard:

FED-STD-376 = Preferred Metric Units For General Use By The Federal Government.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor Street, Fort Worth, TX 76102.

DISTRIBUTION STATEMENT A : Approved for public release. Distribution is unlimited.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

Copies of Federal standards are available from the General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

Copies of military standards may be obtained from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

ASTM Standard:

E 29 - Standard Practice For Using Significant Digits In Test Data To Determine Conformance With Specifications.

Application for copies of ASTM standards should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.

3. SALIENT CHARACTERISTICS

3.1 Design and construction.

3.1.1 Pan. The pan shall be formed seamless from a single piece of aluminum with an initial thickness of 0.032 inch (0.813 mm). The pan shall have a capacity of 1-1/2 to 2 quarts (1.4 liter to 1.9 liter). The pan shall have a handle formed from either 0.050 inch (1.270 mm) corrosion-resisting steel, tin-plated steel, or a suitable plastic. Metal handles shall be attached by spot welding or riveting. The plastic handle shall be attached by corrosion-resistant machine screws. The handle shall have a minimum length of 6 inches (152.4 mm).

3.1.2 Egg rack. The egg rack and cups shall be formed from aluminum with a minimum thickness of 0.025 inch (0.635 mm). The rack shall be removable from the pan and shall contain 4 egg cups. The egg cups shall be removable from the rack. The egg cups shall have a non-stick finish obtained by coating with polytetrafluoroethylene or a similar substance. The rack shall contain perforations to allow passage of steam.

3.1.3 Cover. The pan shall be provided with a cover. The cover shall be formed seamless from a piece of aluminum with a minimum thickness of 0.032 inch (0.813 mm). The cover shall be provided with either an aluminum or plastic handle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

3.2 Marking. The poachers shall be marked with the manufacturer's name, trade name, or trademark of such known character that the source may be readily determined.

3.3 Workmanship. The egg poachers shall be clean and free from any cracks, fractures, malforming, scale, pits and flux deposits. The egg poachers shall have no sharp edges, slivers, burrs, deep scratches, tool marks, or other defects which might affect serviceability, durability, or appearance.

3.4 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

3.5 Measurement system. The values stated in inch-pound units are to be regarded as the standard. The values stated in parentheses are for informational purposes only.

3.6 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within tolerances specified using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the specification preparing activity for changes to this document.

3.7 Commercial item. The use of the term "commercial item description" in this document does not imply that any item or items offered are not required to conform with all requirements specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor certification. The contractor shall certify that the item meets the salient characteristics and the requirements of this commercial item description, and, except for any government unique requirements specified, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace, or is the same product that has been successfully been delivered to the government on a previous contract or purchase order. The government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.2 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

Except as otherwise specified in the contract or order, the use of the contractor's own or any other facilities suitable for the performance of the inspection requirements specified herein shall be permitted, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.3 Sampling. The levels of inspection and acceptable quality levels (AQL's) shall be in accordance with MIL-STD-105.

4.4 Lot formation. All egg poachers from the same manufacturer offered for delivery at one time shall be considered a lot for purposes of inspection.

4.5 Sampling for visual and dimensional examination. A random sample of egg poachers shall be selected from each lot in accordance with inspection level S-4, AQL 4.0 expressed in terms of defects per hundred units. The sample unit shall be one egg poacher with cover. The sample egg poachers (and covers) shall be visually and dimensionally examined to verify compliance with table I and the remainder of this commercial item description. All dimensions are absolute as defined in ASTM E 29.

TABLE I. Classification of defects

Examine	Defect
Finish	Area of corrosion
	Stained or discolored
Construction and Workmanship	Scratch or tool mark on interior surface, clearly noticeable 1/
	Scratched, pitted, or tool mark on exterior surfaces
	Any sharp edge, sliver or burr
	Any part missing, or not specified size
	Any component fractured, split, bent, buckled, punctured or otherwise impaired
Marking	Missing or illegible
Handles	Not securely attached

1/ - An unacceptable scratch is one that will catch a fingernail when run across it.

4.6 Examination for preparation for delivery. A random sample of shipping containers shall be selected from each lot for examination of the unit, intermediate and shipping containers (as applicable) for conformance with the preservation, packaging, packing, labeling, and marking required in the contract or order. Samples shall be selected in accordance with inspection level S-2, acceptable quality level (AQL) 6.5, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

description.

A sample unit shall be one shipping container.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking. The packaging, packing, and marking shall be as specified in the contract or order.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number and date of this commercial item description.
b. The packaging, packing, and marking desired.

6.2 National Stock Number (NSN): The following NSN corresponds to this CID - 7330-00-272-3117.

MILITARY INTERESTS:

Military Coordinating Activity:

Army - GL

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review Activities:

Army - MD, QM
Air Force - 84, 50

User Activity:

Navy - MC

Civil Agency Coordinating Activity:

VA - OSS

Preparing Activity:

GSA - FSS

(DoD Project 7330-0662)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.