[INCH-POUND]
A-A-265A
June 21, 1993
SUPERCEDES
A-A-265
April 21, 1980

COMMERCIAL ITEM DESCRIPTION

MOPPING OUTFIT, FLOOR

The General Services Administration has authorized the use of this commercial item description.

1. SCOPE

1.1 Scope. This commercial item description covers a galvanized steel mopping bucket with an integral foot activated wringer.

2. APPLICABLE DOCUMENTS

2.1 The documents referenced in this commercial item description shall be the issues in effect on the date of issuance of the invitation for bids or request for proposals unless otherwise specified. These documents form a part of this commercial item description to the extent specified. In the event of a conflict between this commercial item description and a document referenced herein, this commercial item description shall take precedence.

Federal Standard:

FED-STD-376 - Preferred Metric Units for General Use by The Federal Government.

Copies of Federal standards are available from the General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Seattle, WA, and the GSA Specifications Unit (3FBP-W), 7th and D Streets S.W., Washington, DC 20407.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any information which might improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor Street, Fort Worth, TX 76102.

DISTRIBUTION STATEMENT A: Approved for public release; distribution unlimited.

FSC 7920

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

Copies of military standards may be obtained from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

ASTM:

A 525 - Standard Specification for General Requirements for Sheet Steel, Zinc-Coated (Galvanized) by the Hot-Dip Process

E 29 - Standard Practice For Using Digits in Test Data to Determine Conformance With Specifications.

Applications for copies of ASTM standards should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.

3. SALIENT CHARACTERISTICS

3.1 Outfit. The outfit shall consist of a mop bucket with an integral pull-through type roller wringer assembly.

3.1.1 Bucket. The bucket shall be round or oval, straight sided or tapered. The bucket shall have a minimum capacity of 16 quarts (15.14 L). This capacity is to be measured void of any components, such as the wringer assembly. The bucket shall have a galvanized bail with a finished diameter no less than 0.24 inch (6.10 mm). The bucket shall have a foot tab on the bottom edge placed to prevent tipping of the bucket when the wringer is used. The sides and bottom of the bucket, and the foot tab, shall be composed of galvanized steel a minimum of 0.023 inch (0.58 mm) thick.

3.1.1.1 Coating. The bucket shall be zinc coated as specified by designation G-90 of ASTM A525 as a minimum. The finished product shall have all seams sealed and shall not show evidence of pitting, flash, thin spots, uneven coating, missing coating, slivers, points, or rust.

3.1.1.2 Leakage. The bucket shall not leak when tested as specified in 4.4.2. There shall be no leakage around the seams, or around any fasteners extending through the bucket.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.

3.1.2 Wringer. The wringer shall be a pull-through type that is closed against the mop by pressure on a foot lever. The wringer assembly shall consist of two or more rollers, one or more stationary and one movable. The movable roller shall be forced against the stationary roller(s) by downward pressure on an external foot actuated lever with enough force to wring water out of a mop being drawn between the rollers without deformation of the wringer assembly or the bucket. The wringer assembly shall have a spring of sufficient force to move the moveable roller completely to it's at-rest position when released. The rollers shall be a minimum of 8-1/8 inches (20.64 cm) long and a minimum of 1-3/8 inch (3.49 cm) in diameter. The rollers shall be uniform in diameter, smooth or textured, and shall be natural rubber, synthetic rubber, wood, or a combination, and shall turn smoothly and easily. The wringer shall operate in a manner that can in no way be injurious to the operator. The operation of the wringer shall not cause any portion of the wringer assembly to extend any further beyond the top edge of the bucket than exists when the wringer is in the released position.

3.3 Marking for identification. The manufacturer's name, trade name or trademark of such known character easily identifiable with the manufacturer shall be applied to the bucket in a permanent manner. The marking shall not be removable.

3.4 Workmanship. The finished outfit shall be clean and smooth and shall not contain any burrs, points, thin spots, tool marks, missing galvanization, or other defects that might impair serviceability, durability or appearance.

3.5 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

3.6 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch/pound units, provided they fall within the tolerances specified using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this commercial item description are met.

3.7 Measurement systems. The values stated in inch-pound units are to be regarded as the standard. The metric values stated in parentheses are for information purposes only.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.

4.2 Sampling. The levels of inspection and acceptable quality levels (AQL's) shall be in accordance with MIL-STD-105. A lot shall be all outfits offered for inspection at one time. A sample unit shall be one complete outfit. Tolerances specified shall be absolute limits as defined in ASTM E29.

4.3 Visual and dimensional inspection. The samples shall be inspected for visual and dimensional defects in accordance with Table I. The inspection level shall be S-3 and the AQL shall be 4.0 defects per hundred units.

Table I. Visual and dimensional examination.

Examine:	Defects:
Bucket	Dimensions not as specified.
	Not round or oval shape.
	Capacity not as specified.
	Coating not as specified.
	Bail absent, deformed, or not coated.
Wringer	Rollers not specified dimensions.
	One roller not fixed or one not movable.
	Rollers not material specified.
	Rollers not smooth, uniform, and even.
	Rollers do not turn easily and smoothly.
	Wringer action not foot operated.
	Movable roller does not move freely.
	When released, moveable roller does not return immediately to full open position.
Assembly	Wringer not permanently attached to bucket.

4.4 Testing. The inspection level for the following tests shall be S-2. The failure of any sample of any test shall fail the lot.

4.4.1 Capacity. Select a single bucket from the samples. With the bucket on a flat hard surface, 16 quarts (15.14 L) of water shall be poured into the bucket. If necessary, a bucket without the wringer may tested to demonstrate capacity (see 4.4.1.1). If bucket cannot hold a minimum of 16 quarts (15.14 L), the sample shall fail.

4.4.1.1 Alternate capacity. If it is necessary to remove the wringer assembly to allow the full 16 quarts of water to be introduced, the contractor may use an alternate bucket of the exact same dimensions but without the wringer to demonstrate capacity. This is in order to prevent the destruction of a production bucket/wringer assembly by removal of the permanently attached wringer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.

4.4.2 Leakage. On a flat, clean, dry surface the sample buckets shall be filled to the rim with water. The bucket shall be allowed to stand for a minimum of 15 minutes. At the end of this time the bucket and the surface it has been sitting on shall be examined. Any evidence of leakage shall fail the sample.

4.4.3 Use. On a flat hard floor, 10 quarts (9.46 L) of water shall be placed into each sample bucket. A cotton string floor mop of dry head weight 14 +/- 2 ounces (435 +/- 62 g) shall be thoroughly wetted in the bucket, introducing the mop through the wringer assembly. With one foot on the stabilizing tab, the other foot shall depress the foot lever causing the rollers to contact and squeeze the mophead. As the mop is pulled through the wringer, water shall be squeezed from the mophead and fall back into the bucket. If the wringer assembly visibly distorts or separates in any way or if any water leaks out of the bucket, the sample shall fail. If any portion of the wringer extends from the top of the bucket further than the at-rest position, or if any portion of the wringer impacts the leg of the user, the sample shall fail.

4.5 Examination for preparation for delivery. A random sample of shipping containers shall be selected from each lot for examination of the unit, intermediate, and shipping containers (as applicable) for conformance with the packaging, packing, and marking required in the contract or order. Samples shall be selected in accordance with inspection level S-2, AQL 6.5 defects per hundred units. A sample unit shall be one shipping container.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking. The packaging, packing, and marking shall be as specified in the contract or order.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number, and date of this commercial item description.
b. The packaging, packing, and marking required.

6.2 National Stock Number. NSN 7920-00-579-8484 is the only NSN known to reference this document.

MILITARY INTEREST:
NONE: DoD has determined that no military activity has an official interest in this commercial item description.

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.