INCH-POUND

MIL-R-23417/26A
25 April 1991

SUPERSEDING
MIL-R-23417/26
19 September 1967

MILITARY SPECIFICATION SHEET

RESOLVER, ELECTRICAL, AC
TYPE 15R11W4A

This specification is approved for use by all Departments and Agencies of the Department of Defense. The requirements for acquiring the Electrical Resolvers described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) cited in the solicitation: MIL-R-23417.

TABLE I. Requirements.

Requirements	Value	Unit	Tolerance
Excitation winding	Stator		
Rated frequency	400	Hz	±1%
Input voltage:			
Maximum	26	volts (rms)	±1%
Test	15	volts (rms)	±1%
Minimum	5	volts (rms)	±1%
Primary current	14	milliamps	nominal
Primary power	0.044	watts	nominal
D.C. resistance:			
Rotor	130	ohms	±15%
Stator	165	ohms	±15%
Compensator	215	ohms	±15%
Impedance:			
Zro	200+j1200	ohms	R±15%+jx±10%
Zso	225+j1050	ohms	R±15%+jx±10%
Zco	275+j1100	ohms	R±15%+jx±10%
Zrs	285+j125	ohms	nominal
Transformation ratio:			
Output/input	0.980	-----	±1%
Rotor/compensator	0.980	-----	±0.1%

AMSC - N/A FSC 5990

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:44Z
Check the source to verify that this is the current version before use.

TABLE I. Requirements - Continued.

Requirements	Value	Unit	Tolerance
T. R. variation (R/C) due to voltage	0.05	percent	maximum
Equality of transformation ratios:			
Output/input	0.1	percent spread	maximum
Rotor/compensator	0.1	percent spread	maximum
Phase shift:			
Output/input	8.5	degrees	±0.5
Rotor/compensator	8.5	degrees	±0.5
Phase shift variation (R/C) due to voltage	±0.5	degrees	maximum
Interaxis error	±5.0	minutes	maximum
Functional error	±0.1	percent	maximum
Null voltage:			
Fundamental	8.0	mV(rms) output	maximum
Total	15	mV(rms) output	maximum
Shift of resolver zero			
With voltage	±1.0	minutes	maximum
With frequency	±0.05	minutes	maximum
Harmonic distortion	0.1	percent	maximum
Temperature rise	15	degrees C	maximum
Mechanical breakaway torque:	0.15	oz-in	maximum
@ -55°C	0.30	oz-in	maximum
Radial play	0.0005	inches	maximum
End play	0.0010	inches	±0.0005
Resonant frequency	----	kHz	minimum
Low corner frequency	63.5	Hz	maximum

NOTE:

1. A voltage value of 5 to 26 volts shall be entered in the "volts" designation space on the identification plate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:44Z
Check the source to verify that this is the current version before use.

TABLE II. Part identifying number variant characteristics.

Part Identifying No. 1/	A ±.010	B ±.010	G Maximum	Shaft Style	Terminal End	U ±.0000 -.0005
M23417/26-01A	.555	.500	2.100	Spline	Terminal Board	.1872
M23417/26-02A	.305	.250	1.850	Plain	Wire Leads	.1200
M23417/26-03A	.492	.437	1.850	Plain	Wire Leads	.1200
M23417/26-04A	.555	.500	1.850	Plain	Wire Leads	.1200
M23417/26-05A	.305	.250	2.100	Plain	Terminal Board	.1200
M23417/26-06A	.492	.437	2.100	Plain	Terminal Board	.1200
M23417/26-07A	.555	.500	2.100	Plain	Terminal Board	.1200

1/ Part identifying number M23417/26-01A shall be the NATO standard.

1/ The suffix letter following the numerical dash number corresponds to the latest modification letter in the type designation.

TABLE III. Part identifying number cross-reference. 1/

SUPERSEDED PART NUMBERS		NEW PART IDENTIFYING NUMBERS
MIL-R-23417/26	MIL-R-23417/6	
M23417/26-01	MK 4 MOD 0	M23417/26-01A
M23417/26-02		M23417/26-02A
M23417/26-03		M23417/26-03A
M23417/26-04		M23417/26-04A
M23417/26-05		M23417/26-05A
M23417/26-06		M23417/26-06A
M23417/26-07		M23417/26-07A

1/ All line items shown in Table III refer to equivalent and interchangeable electrical resolvers of the same type designation modification. Part number changes do not affect form, fit or function of the electrical resolvers listed therein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:44Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AR
Navy - AS
Air Force - 85

Review activities:
Navy - OS, EC
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - MI, AV, ME, AT
Navy - CG, MC
Air Force - 14, 19

Preparing activity:
Army - AR

(Project 5990-0392)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:44Z
Check the source to verify that this is the current version before use.