MIL-R-23417/35A
28 APRIL 1970
SUPERSEDING
MIL-R-23417/35
16 October 1967


MILITARY SPECIFICATION SHEET

RESOLVER, ELECTRICAL

TYPE 08R3N4B

The complete requirements for procuring the resolver described herein shall consist of this document and the latest issue of MIL-R-23417.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.



FSC 5990

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T16:45Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in inches.
2. Unless otherwise specified, tolerances on decimals are ±.005 and angles ±2°.
3. Perpendicularity and concentricity shall be measured with the unit in a vertical position supported by the shaft, then the housing rotated.
4. Terminal sequence shall be as shown and identified by molded lettering on the end cap or permanently affixed thereto. Terminal lead wires shall depart through the back surface of the terminal end of the resolver in any acceptable manner.
5. Minor variations of unit configuration are permitted for undimensioned design detail.
6. Solder pin terminal stress shall be tested in accordance with MIL-STD-202, Method 211, as a qualification test. The terminals shall be capable of withstanding, without damage or loosening, a steady pull of the force specified in any direction by a wire fastened in the normal manner. Internal connections to terminals shall be welded or soldered with high temperature solder SN-5 per QQ-S-571.
7. Mark on housing is to match shaft mark within 10° when rotor is set at approx. resolver zero, and will bear no relation to the center lines shown on the drawing.
8. Pending issuance of a qualified products list (QPL) a sample of the resolvers to be furnished under this specification shall be subjected to the preproduction tests as specified in MIL-R-23417.
9. For information only see synchro mounting clamp MS17183 or equal.
10. Leads shall be type E-28.
11. A voltage value of .5 to 26V shall be entered in the 'Volts' designation space on the identification plate.
12. The weight shall be attached to the end of each wire, pulling straight away from the resolver. The lead shall then be bent 90° at the point of exit from the housing and while in this attitude the resolver rotated 360° counterclockwise. Any indication of the lead pulling loose, wire strands breaking, or permanent deformation of the insulation shall be cause for rejection under qualification tests.
13. The front retainer shall be threaded or a snap ring.

Source: https://assist.dla.mil -- Downloaded: 20260-19T16:45Z
Check the source to verify that this is the current version before use.

RESOLVER, ELECTRICAL: TYPE 08R3N4B

PERFORMANCE REQUIREMENTS AND CHARACTERISTICS

	Value	Unit	Tolerance
1. Excitation winding	Stator	---	---
2. Rated frequency	400	Hz	±1%
3. Input voltage:	11.8	Volts rms	±1%
Test	11.8	Volts rms	±1%
4. Primary current	42	Milliamps	Nominal
5. Primary power	.112	Watts	Nominal
6. DC resistance:			
Stator	50	Ohms	Reference
Rotor	63.3	Ohms	Reference
7. Impedance:			
Zso	66 +j279	Ohms	R±15%, +jx±10%
Zrs	113 + j37.3	Ohms	Reference
Zro	83 +j327	Ohms	R±15%, +jx±10%
8. Transformation ratio			
Output/input	1.000	---	±2%
9. Equality of transformation ratio	.15	Percent	Maximum
10. Phase shift	9.75	Degrees	±2
11. Null voltage:			
Fundamental	15	Mv rms	Maximum
Total	20	Mv rms	Maximum
12. Electrical error:			
@ 23° C	±3	Minutes	Maximum
@ -55° C and +125° C	±6	Minutes	Maximum
13. Friction torque:			
@ 23° C	.04	Oz-In	Maximum
@ -55° C and +125° C	.1	Oz-In	Maximum
14. Temperature rise	20	° C	Maximum
15. Radial play	.0004 (For reversal of 1/2 lb load)	Inches	Maximum
16. End play	.0001-.0015 (For reversal of 1/2 lb load)	Inches	Min-Max
17. Wire lead stress (see note 12)	2	Pound	Minimum
18. Terminal stress (see note 6)	3	Pound	Minimum

Part number: The part number consists of the basic number of this specification sheet and a dash number taken from table I.

Example:

M23417/ 35 -01

Basic document number

Spec sheet number

Dash number from table I

Source: https://assist.dla.mil -- Downloaded: 202610-19T16:45Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and characteristics.

Dash No.	Shaft diameter	Shaft style	Termination	Shaft length	
				L (ref)	L' - dim to first mounting flange surface (±.010)
-01	.090	Plain	Wire leads	.325	.365
-02	.090	Plain	Wire leads	.406	.446
-03	.090	Plain	Wire leads	.500	.540
-04	.090	Plain	Solder pins	.325	.365
-05	.090	Plain	Solder pins	.406	.446
-06	.090	Plain	Solder pins	.500	.540

Custodians:
Army - MU
Navy - AS
Air Force - 80

Review activities:
Army - MU, EL
Navy - AS, SH, EC
Air Force - 11, 17, 80
DSA - ES

User activities:
Army - MI, ME, AV
Navy - CG, SH
Air Force - 19

Preparing activity:
Air Force - 80

Agent:
DSA - ES

(Project 5990-0251)

Source: https://assist.dla.mil -- Downloaded: 20261O-19T16:45Z
Check the source to verify that this is the current version before use.