INCH-POUND

MIL-C-46577D (AR)
AMENDMENT 2
31 October 1996
SUPERSEDING
AMENDMENT 1
20 May 1981

MILITARY SPECIFICATION

CARTRIDGE, 20MM, ARMOR PIERCING INCENDIARY, M53

This amendment forms a part of Military Specification MIL-C-46577D (AR), dated 7 December 1973, and is approved for use by all the Departments and Agencies of the Department of Defense.

PAGE 2

* 2.1, Make the following changes:

Under Drawings, add “10534010 - Waterproofness Testing Apparatus”.

Under Publications, add “SCATP-7.62 - Ammunition Ballistic Acceptance Test Methods, Test Procedures for 7.62MM Cartridges”.

PAGE 3

* 3.9, Delete in its entirety and substitute the following:

“3.9 Waterproofness. The cartridge shall not release more than one bubble of air from the mouth of the case when subjected to a pressure differential of 7.5 psi for 30 seconds.”.

PAGE 8

* 4.4.4, Table I, Waterproofness, Under Sample Size Production Lot, delete “20” and substitute “23”.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:21Z
Check the source to verify that this is the current version before use.

4.4.4, Table I, Make the following changes:

* Note 8/, Delete in its entirety and substitute the following:

"8/ Waterproofness. Failure of two or more of the sample cartridges to comply with the specified waterproofness requirement shall cause rejection of the lot. If one cartridge of the sample fails to comply, a second sample of 23 cartridges shall be tested. The lot shall be rejected if two or more of the combines samples fail to comply with the waterproofness requirement.".

Note 9/, Delete in its entirety and substitute the following:

"9/ Accuracy. If the average mean radius of the sample cartridges exceeds the applicable requirement, a retest sample of 100 cartridges shall be tested for the accuracy parameter only. The lot shall be rejected if the average mean radius of the 10 accuracy targets exceeds the requirement.".

Note 11/, Delete "If one or two cartridges fail to comply with the requirement, a second sample of 20 cartridges shall be tested." and substitute "If one or two cartridges fail to comply with the requirement, a second sample of 20 cartridges shall be tested for the incendiary performance parameter only.".

PAGE 11

* 4.4.4.1, Table II, Note 2/, Line 1, Delete ", excepting those from the waterproofness test (Table I),".

PAGE 12

* 4.4.4.1, Table II, Note 2/, Delete "Misfire(s) occurring in the waterproofness test shall be handled in accordance with AMCR 715-505, Volume 8.".

PAGE 14

* 4.5.5, Delete "and Waterproofness" from title.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:21Z
Check the source to verify that this is the current version before use.

4.5.6, Add “The 200 yard range may be reduced by 11.5 yards to accommodate combining test phases. Any variation from 200 yard range requires direct proportional adjustment of the average mean radius.”.

* Add the following paragraph:

“4.5.13 Waterproofness. The method of test shall be as specified in SCATP-7.62. The equipment required to conduct this test is specified on drawing 10534010. The container shall be evacuated to a pressure of 7.5 psi below atmosphere, and held at that pressure for 30 seconds.”.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

Review activities:
Air Force-70

(Project 1305-0159)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:21Z
Check the source to verify that this is the current version before use.