MIL-I-46559A(MU)
30 July 1969
SUPERSEDING
MIL-I-46559 (ORD)
20 July 1961

MILITARY SPECIFICATION
INITIATOR, CARTRIDGE ACTUATED: M3A2 AND M3A1C METAL PARTS ASSEMBLY

1. SCOPE

1.1 This specification covers Initiator, Cartridge Actuated: M3A2 and M3A1C, Metal Parts Assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military
- MIL-A-2550 - Ammunition and Special Weapons, General Specifications for

STANDARDS

Military
- MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
- MIL-STD-109 - Quality Assurance Terms and Definitions
- MIL-STD-413 - Visual Inspection Guide for Rubber O-Rings
- MIL-STD-1167 - Ammunition Data Cards

DRAWINGS

Munitions Command
- D8595822 - Initiator, Cartridge Actuated, Metal Parts Assembly
- F8796541 - Container, Fiber, Ammunition M376 for Initiator Cartridge Actuated: M3A2, in Fiber Container, M376

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

2.1 DRAWINGS (Cont'd)

Munitions Command

F8796542 - Box, Packing, Ammunition for Initiator, Cartridge Actuated, M3A2, in Fiber Container, M376

IEL-8595822 - Inspection Equipment List for Initiator, Cartridge Actuated, Metal Parts Assembly

(Copies of specification, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other Publications - The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bid or request for proposal shall apply.

ASA B46.1 - Surface Texture

(Application for copies should be addressed to the American Standards Association, 10 East 40th Street, New York, N.Y. 10016.)

3. REQUIREMENTS

3.1 General - Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings and referenced specification.

3.2 Mechanical Properties - Mechanical properties required by the drawing or specification shall be uniform throughout the part within specified tolerance. Requirements for all alloy steel parts shall be achieved by quenching and tempering.

3.3 Hydrostatic Pressure - The subassembly consisting of a cap, chamber and plug simulating the firing pin housing, without firing pin hole and with an "O" ring, shall withstand a constant internal pressure of 5500 to 6500 pounds per square inch (psi) for 15 seconds, minimum (min.) without application of any external load other than that applied by the liquid pressure and shall show no evidence of leakage or mechanical failure (see 6.2).

3.4 Firing Pin Release - The firing pin of the assembled initiator, less safety pin, cartridge, cartridge retainer and chamber, shall release from the cocked position when the application of an axial load of 20 to 35 pounds has withdrawn the initiator pin 3/4 inch, maximum (max.).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

3.5 Initiator pin security.- The initiator pin of the assembled initiator, less cartridge, cartridge retainer and chamber, shall not withdraw beyond the safety pin when subjected to an axial load of 200 to 220 pounds. Application of load shall cause no permanent deformation of the safety pin.

3.6 Protective finish.- Protective finish shall be in accordance with the applicable specifications and drawings and shall apply to all surfaces of the component, regardless of contour.

3.7 Residual magnetism.- The metal parts assembly shall not deflect the indicator of the compass more than 3 degrees in either direction when passed in front of the compass at a distance of 6 inches.

3.8 Workmanship.- The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.8.1 Metal defects.- The component shall be free from cracks, splits, cold shuts, inclusion, porosity or other metal defects.

3.8.2 Burr.- The part shall not have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.8.3 Foreign matter.- The part or assembly shall not contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.2 First article sample.

4.2.1 Initial production sample.- At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 50 units (unplated) of each heat treated component for hardness tests, 23 units of each component treated with protective finish, 5 completed assemblies and 10 sets of unassembled components for visual and dimensional examination and shall be tested as indicated in Table I.

TABLE I

Paragraphs Requirements	Tests	Kind of Test	Sample Size	Type of Test Destr.	Non-Destr.
3.2	4.3.3.1	Hardness	50	X	-
3.3	4.3.3.2	Hydrostatic Pressure	Each	-	X
3.4	4.3.3.3	Firing Pin Release	Each	-	X
3.5	4.3.3.4	Initiator Pin Security	Each	-	X
3.6	4.3.3.5	Protective Finish	23 of each Comp.	X	-
3.7	4.3.3.6	Residual Magnetism	Each	-	X

The sample shall be manufactured using the same materials, equipment, processes and procedures as used in regular production. All parts and materials including packaging and packing shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and tests.- After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government approved laboratory or such other facility as specified in the contract.

4.2.1.2 Initial production sample failure.- Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submittal of product.- The contractor shall submit the product in accordance with MIL-STD-105.

4.3.1.2 Size of lot.- A lot of metal parts assemblies shall consist of 1200 initiators, max. (exclusive of test samples) provided the homogeneity requirements of inspection lots have been retained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.3.2 Examination.- One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plan and associated criteria in Tables II and III. For an individual defect (single characteristic) the criteria in Table II shall be used. For total defects within a major or minor group, the criteria in Table III shall be used. All nonconforming material shall be rejected. Inspection for "O" rings shall be in accordance with MIL-STD-413. The roughness comparison specimens prescribed in ASA B46.1 shall be used as a basis of comparison for surface roughness determination. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

TABLE II

Lot Size	Sample Size	Acceptance Numbers Major	Minor
1 - 300	100% Examination	-	-
301 - 1300	100	1	2
1301 - 3200	150	2	3
3201 - 8000	225	3	4
8001 - 22000	300	4	5

TABLE III

Total Allowable Defects Per Sample Size

Sample Size for Major Defects Number of Defects in Class	100	150	225	300
2 - 3	1	2	3	4
4 - 7	2	3	4	5
8 - 19	3	4	5	7
20 - 43	4	5	8	10
Over 43	5	8	11	14
Sample Size for Minor Defects Number of Defects in Class	**110**	**150**	**225**	**300**
2 - 3	2	3	4	5
4 - 7	3	4	5	7
8 - 16	4	5	8	10
17 - 48	6	8	11	14
Over 48	8	11	17	20

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.3.2.1 Retainer, Cartridge, Drawing D8593013, covering a detail of Drawing D8595822.

	Defect	Method of Inspection
CRITICAL		
1.	Metering slots in base missing	Visual
MAJOR		
101.	Pitch diameter of thread, max.	Gage
102.	Minor diameter of thread, max.	Gage
103.	Concentricity of cavity with pitch diameter of thread	Gage
104.	Perpendicularity of pitch diameter of thread with base	Gage
105.	Symmetry of metering slots in base with body	Gage
106.	Diameter of cavity, max.	Gage
107.	Depth of cavity	Gage
108.	Depth to bottom of counterbore	Gage
109.	Depth of metering slots in base	Gage
110.	Total length	Gage
111.	Length of effective thread, min.	Gage
112.	Width of metering slots in base	Gage
113.	Internal radius at mouth of cavity missing or incorrect	Gage
114.	Drill point in base, max.	Gage
115.	Number of elongated slots incorrect	Visual
116.	Thread damaged or not full	Visual
117.	Metal defective	Visual
118.	Protective finish inadequate or defective	Visual
119.	Burr	Visual
120.	Foreign matter	Visual
MINOR		
201.	Pitch diameter of thread, min.	Gage
202.	Diameter of body	Gage
203.	Diameter of cavity, min.	Gage
204.	Diameter of head	Gage
205.	Length of elongated slots	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

Defect	Method of Inspection
MINOR (Cont'd)	
206. Length of head	Gage
207. Width of elongated slots	Gage
208. Location of elongated slots	Gage
209. Angle between head and body	Gage
210. Location of metering slots	Visual
211. Profile of elongated slots	Visual
212. Marking missing, incorrect or illegible	Visual
213. Radius missing or incorrect, except as otherwise classified	Visual
214. Surface finish improper except as otherwise classified	Visual

4.3.2.2 Chamber, Drawing D8593014 covering a detail of Drawing D8595822.

CRITICAL	
None defined	
MAJOR	
101. Pitch diameter of large thread, min.	Gage
102. Major diameter of large thread, min.	Gage
103. Pitch diameter of small thread, min.	Gage
104. Major diameter of small thread, min.	Gage
105. Concentricity of counterbore with pitch diameter of large thread	Gage
106. Concentricity of datum diameter with small thread	Gage
107. Diameter of counterbore	Gage
108. Depth of cavity	Gage
109. Thickness of wall, min.	Gage
110. Location of datum diameter	Gage
111. Profile of gas port	Gage
112. Thread damaged or not full	Visual
113. Chamfer at base of cavity missing or incorrect	Visual
114. Metal defective	Visual
115. Protective finish inadequate or defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.3.2.2 (Cont'd)

Defect	Method of Inspection
MAJOR (Cont'd)	
116. Surface finish at end of gas port improper	Visual
117. Burr	Visual
118. Foreign matter	Visual
MINOR	
201. Pitch diameter of large thread, max.	Gage
202. Pitch diameter of small thread, max.	Gage
203. Diameter of cavity	Gage
204. Diameter of hole	Gage
205. Diameter of small thread pilot	Gage
206. Diameter of large thread pilot	Gage
207. Depth of counterbore	Gage
208. Total length	Gage
209. Length of large thread pilot	Gage
210. Length to end of large thread	Gage
211. Length of gas port	Gage
212. Thickness of wall, max.	Gage
213. Location of small thread	Gage
214. Marking missing, incorrect or illegible	Visual
215. Radius or chamfer missing or incorrect	Visual
216. Surface finish improper, except as otherwise classified	Visual

4.3.2.3 Pin, Initiator, Drawing C8595403, covering a detail of Drawing D8595822.

CRITICAL	
None defined	
MAJOR	
101. Concentricity of groove in head with body	Gage
102. Symmetry of head with body	Gage
103. Diameter of body	Gage
104. Diameter of groove in body, min.	Gage
105. Diameter of groove in head, min.	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.3.2.3 (Cont'd)

Defect	Method of Inspection
MAJOR (Cont'd)	
106. Length to shoulder at head, min.	Gage
107. Location of groove in head	Gage
108. Location of groove in body	Gage
109. Profile of groove in body	Gage
110. Profile of groove in head	Gage
111. Metal defective	Visual
112. Protective finish inadequate or defective	Visual
113. Surface finish on body and body groove improper	Visual
114. Burr	Visual
115. Foreign matter	Visual
MINOR	
201. Diameter of groove in head, max.	Gage
202. Diameter of pull hole	Gage
203. Diameter of undercut, min.	Gage
204. Length to shoulder at head, max.	Gage
205. Width of head	Gage
206. Width of shoulder at body groove	Gage
207. Width of groove in head	Gage
208. Width of undercut, max. if applicable	Gage
209. Total length	Gage
210. Thickness of head	Gage
211. Location of pull hole	Gage
212. Angle at base of body	Gage
213. Profile of head	Gage
214. Marking missing, incorrect or illegible	Visual
215. Radius or chamfer missing or incorrect	Visual
216. Surface finish improper, except as otherwise classified	Visual

4.3.2.4 Cap, Drawing D8595404, covering a detail of Drawing D8595822.

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.3.2.4 (Cont'd)

Defect		Method of Inspection
MAJOR		
101.	Pitch diameter of large thread, max.	Gage
102.	Minor diameter of large thread, max.	Gage
103.	Pitch diameter of small thread, max.	Gage
104.	Minor diameter of small thread, max.	Gage
105.	Concentricity of pitch diameter of large thread with pitch diameter of small thread including perpendicularity with base of large thread cavity	Gage
106.	Concentricity of hole counterbore with hole	Gage
107.	Concentricity of hole with pitch diameter of small thread including perpendicularity with base of large thread cavity	Gage
108.	Symmetry of flats with pitch diameter, large thread	Gage
109.	Diameter of hole	Gage
110.	Diameter of hole counterbore	Gage
111.	Diameter of pin holes	Gage
112.	Depth of large thread cavity	Gage
113.	Depth of small thread cavity	Gage
114.	Length of effective large thread, min.	Gage
115.	Length of effective small thread, min.	Gage
116.	Thickness of wall	Gage
117.	Height, max.	Gage
118.	Internal radius at base of large thread cavity missing or incorrect	Visual
119.	Thread damaged or not full	Visual
120.	Metal defective	Visual
121.	Protective finish inadequate or defective	Visual
122.	Surface finish of hole improper	Visual
123.	Burr	Visual
124.	Foreign matter	Visual
MINOR		
201.	Pitch diameter of large thread, min.	Gage
202.	Pitch diameter of small thread, min.	Gage
203.	Pitch diameter of set screw thread	Gage
204.	Minor diameter of set screw thread, max.	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.3.2.4 (Cont'd)

Defect	Method of Inspection
MINOR (Cont'd)	
205. Diameter of boss	Gage
206. Diameter of flange holes	Gage
207. Diameter of groove	Gage
208. Depth of hole counterbore	Gage
209. Total length	Gage
210. Length between flange holes	Gage
211. Length of flange	Gage
212. Width across body flats	Gage
213. Width of groove	Gage
214. Width of flange	Gage
215. Thickness of flange	Gage
216. Location of pin holes	Gage
217. Location of groove	Gage
218. Location of flange hole	Gage
219. Location of set screw holes	Gage
220. Location of initiator pin hole	Gage
221. Marking missing, incorrect or illegible	Visual
222. Radius or chamfer missing or incorrect except as otherwise classified	Visual
223. Surface finish improper, except as otherwise classified	Visual

4.3.2.5 Pin, Safety, Drawing B8595405, covering a detail of Drawing D8595822.

CRITICAL

None defined

MAJOR

101. Diameter of wire	Gage
102. Profile incorrect	Visual
103. Metal defective	Visual
104. Protective finish inadequate or defective	Visual
105. Burr or sharp edge	Visual
106. Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.3.2.5 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Diameter of head	Gage
202. Total length	Gage
203. Radius missing or incorrect	Visual

4.3.2.6 Spring, Initiator, Drawing B8595406, covering a detail of Drawing D8595822.

CRITICAL	
None defined	
MAJOR	
101. Load at specified heights	Gage
102. Height solid, max.	Gage
103. Ends incorrect	Visual
104. Protective finish inadequate or defective	Visual
105. Burr or sharp edges	Visual
106. Foreign matter	Visual
MINOR	
201. Diameter outside, closed, max.	Gage
202. Diameter inside, min.	Gage

4.3.2.7 Pin, Firing, Drawing C8596168 covering a detail of Drawing D8595822.

CRITICAL	
None defined	
MAJOR	
101. Concentricity of body with cavity	Gage
102. Concentricity of body with striker	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.3.2.7 (Cont'd)

Defect	Method of Inspection
MAJOR (Cont'd)	
103. Diameter of body	Gage
104. Diameter of cavity	Gage
105. Diameter of striker	Gage
106. Diameter of ball hole, max.	Gage
107. Depth of ball hole counterbore, max.	Gage
108. Location of datum diameter	Gage
109. Radial profile of striker	Gage
110. Radial location of ball holes	Visual
111. Metal defective	Visual
112. Protective finish inadequate or defective	Visual
113. Surface finish improper	Visual
114. Burr or sharp edge	Visual
115. Foreign matter	Visual
MINOR	
201. Diameter of cavity counterbore	Gage
202. Diameter of ball hole, min.	Gage
203. Diameter of ball hole counterbore	Gage
204. Diameter at midsection	Gage
205. Depth of cavity counterbore	Gage
206. Depth of cavity	Gage
207. Depth of ball hole counterbore, min.	Gage
208. Total length	Gage
209. Length from body to striker	Gage
210. Length to ball hole	Gage
211. Drill point cavity, max.	Visual
212. Radius or chamfer missing or incorrect	Visual

4.3.2.8 Housing, Firing Pin, Drawing D8596169, covering a detail of Drawing D8595822.

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.3.2.8 (Cont'd)

Defect		Method of Inspection
MAJOR		
101.	Pitch diameter of small thread, min.	Gage
102.	Major diameter of small thread, min.	Gage
103.	Pitch diameter of large thread, min.	Gage
104.	Major diameter of large thread, min.	Gage
105.	Concentricity of counterbore with cavity	Gage
106.	Concentricity of flange with pitch diameter of small thread	Gage
107.	Concentricity of groove with flange	Gage
108.	Concentricity of striker hole with cavity	Gage
109.	Concentricity of pitch diameter of large thread with cavity	Gage
110.	Concentricity of cavity with pitch diameter of small thread, including perpendicularity with face of flange	Gage
111.	Perpendicularity of boss face with pitch diameter of large thread	Gage
112.	Diameter of cavity, max.	Gage
113.	Diameter at external datum location	Gage
114.	Diameter of groove	Gage
115.	Diameter of flange, min.	Gage
116.	Diameter of small thread undercut, min.	Gage
117.	Length from rear flange to cavity	Gage
118.	Length to internal datum diameter	Gage
119.	Width of rear flange	Gage
120.	Angle of external datum diameter	Gage
121.	Angle at internal datum diameter	Gage
122.	Height of boss	Gage
123.	Profile of groove	Gage
124.	Radius at root of boss	Gage
125.	Thread damaged or not full	Visual
126.	Metal defective	Visual
127.	Protective finish inadequate or defective	Visual
128.	Surface finish in cavity improper	Visual
129.	Burr or sharp corner	Visual
130.	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.3.2.8 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Pitch diameter of small thread, max.	Gage
202. Pitch diameter of large thread, max.	Gage
203. Diameter of cavity, min.	Gage
204. Diameter of flange, max.	Gage
205. Diameter of body	Gage
206. Diameter of counterbore	Gage
207. Diameter of undercut in cavity, if applicable	Gage
208. Diameter of striker hole	Gage
209. Diameter of small thread pilot	Gage
210. Depth to bottom of cavity	Gage
211. Total length	Gage
212. Length from small thread pilot to flange	Gage
213. Length across flanges	Gage
214. Length of body	Gage
215. Width of undercut in cavity if applicable	Gage
216. Width of undercut, small thread	Gage
217. Width of groove	Gage
218. Location of flange	Gage
219. Radius or chamfer missing or incorrect, except as otherwise classified	Visual
220. Surface finish improper, except as otherwise classified	Visual

4.3.2.9 Seal, Drawing B10524102 covering a detail of Drawing D8595822.

CRITICAL	
None defined	
MAJOR	
101. Diameter outside, min.	Gage
102. Width, min.	Gage
103. Thickness, min.	Gage
104. Cut, cracked or split	Visual
105. Flash	Visual
106. Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.3.2.9 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Diameter outside, max.	Gage
202. Width, max.	Gage
203. Thickness, max.	Gage

4.3.2.10 Assembly, Drawing D8595822, less C8595403, C8595405, D8593013 and D8593014.

CRITICAL	
1. Protrusion of firing pin	Gage
2. Steel ball missing	Gage
MAJOR	
None defined	
MINOR	
None defined	

4.3.2.11 Assembly, Drawing D8595822.

CRITICAL	
1. Any part missing, except as otherwise classified	Visual
2. Improper assembly	Visual
MAJOR	
101. Initiator pin not free to rotate	Manual
102. Safety pin loose or deformed	Manual and Visual
103. Marking missing, incorrect or illegible	Visual
MINOR	
201. Shipping cap missing	Visual
202. Protective finish inadequate or defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.3.2.12 Packing in Fiber Container, Drawing F8796541.

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
None defined	
MINOR	
201. Gap between body and cover, max.	Manual
202. Contents loose	Manual
203. Metal ends loose or distorted	Manual
204. Cut or damaged through all impregnated layers	Visual

4.3.2.13 Packing in Wood Box, Drawing F8796542.

CRITICAL	
None defined	
MAJOR	
None defined	
MINOR	
201. Contents loose	Manual
202. Hardware missing, loose, broken or improperly engaged	Manual and Visual
203. Strapping missing, loose, broken or improperly assembled	Manual and Visual
204. Contents of box exposed	Visual
205. Box damaged	Visual
206. Marking missing, incorrect or illegible	Visual
207. Number of units incorrect	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.3.3 Inspection testing.- The following tests shall be performed in accordance with the provisions of 4.4.

4.3.3.1 Hardness.- Fifty units from each heat treated lot of components shall be tested for compliance with the values on the applicable drawing. Failure of any unit to comply with drawing requirements shall be cause for rejection of the lot of components.

4.3.3.2 Hydrostatic pressure.- Each subassembly shall be subjected to the internal hydrostatic pressure. Failure of any subassembly to comply with the requirements of 3.3 shall be cause for rejection of the subassembly.

4.3.3.3 Firing pin release.- The initiator pin of each subassembly shall be subjected to the firing pin release test. Failure of any subassembly to comply with the requirements of 3.4 shall be cause for rejection of the subassembly.

4.3.3.4 Initiator pin security.- The initiator pin of each subassembly shall be subjected to the initiator pin security test. Failure of any subassembly to comply with the requirements of 3.5 shall be cause for rejection of the subassembly.

4.3.3.5 Protective finish.- The number of units for protective finish tests shall be in accordance with the applicable specifications. Failure of any sample to comply with the requirements of the applicable specification shall be cause for rejection of the lot.

4.3.3.6 Residual magnetism.- Each initiator shall be tested for excessive residual magnetism. Failure of any initiator to comply with the requirements of 3.7 shall be cause for rejection of the initiator.

4.3.4 Inspection equipment.- The examination and tests shall be made using equipment listed on IEL-8595822.

4.4 Test methods and procedures.

4.4.1 Hardness.- Prior to the application of protective finish, a hardness testing machine shall be used to determine the hardness values specified on the applicable drawing.

4.4.2 Hydrostatic pressure.- Prior to the application of protective finish, the subassembly shall be mounted in a device, using the fixture for properly sealing all openings and subjected to the hydrostatic pressure to determine compliance with the requirements of 3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

4.4.3 Firing pin release.- The subassembly shall be secured in the fixture. A pull shall be applied to the initiator pin in the longitudinal direction in conjunction with the fixture which registers the amount of pull.

4.4.4 Initiator pin security.- The subassembly shall be secured in the fixture with the safety pin in place. A pull shall be applied to the initiator pin in the longitudinal direction in conjunction with the fixture which registers the amount of pull. The test shall be performed with the safety pin in each position.

4.4.5 Protective finish.- Test procedures and inspection for protective finish shall be in accordance with the specifications referenced on the component drawing.

4.4.6 Residual magnetism.- The initiator shall be tested for excessive residual magnetism in an area free of local magnetic effects by placing the initiator 6 inches from and at the same height as the compass, in a north-south horizontal position (cap end at south) with the compass set in an east-west heading. The initiator shall be moved slowly past the compass in a longitudinal direction for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the initiator.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking.- Packaging, packing and marking shall be in accordance with drawings F8796541 and F8796542.

5.2 Data card.- Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 Ordering data.- Procurement documents should specify the title, number and date of this specification.

6.2 A "mechanical failure" is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A214

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

YES NO (If "yes", in what way?)

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity - Optional)

DATE

DD FORM 1426

REPLACES EDITION OF 1 OCT 54 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:17Z
Check the source to verify that this is the current version before use.