MILITARY SPECIFICATION

FUZE, DEMOLITION KIT, TRAINING, M1147 PARTS, ASSEMBLING, AND PACKING

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the parts, assembling, and packing of one type of fuze designated as Fuze, Demolition Kit, Training, M1147.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.

FSC 1375

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:18Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent herein.

DRAWINGS

U. S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

PRODUCT AND PACKAGING DRAWINGS

8799682 - Carton, Packing, Ammunition, for Fuze, Demolition Kit, M1134, or M1147
8799683 - Container, Fiberboard, Ammunition, for Fuze, Demolition Kit, M1134, or M1147
8845376 - Fuze, Demolition Kit, Training, M1147

INSPECTION EQUIPMENT DRAWINGS

EL-8845376 - Fuze, Demolition Kit, Training, M1147

(Copies of specifications, standards, drawings, and publications required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

3.2 Training fuze assemblies. The training fuze assemblies shall comply with all requirements specified on Drawing (dwg.) 8845376 and with all requirements specified in applicable specifications.

3.3 Drop test. The armed fuze shall not return to the unarmed position when dropped from a height of 40 feet onto 12 inches of hard packed dry earth. During the fall, the longitudinal axis of the fuze shall be in the horizontal position with the spring plunger pin pointing upright. The test shall be conducted as specified in 4.5.1.

3.4 Fuze functioning. The training fuze, with the cotter pin removed, shall arm when a withdrawal force of 35 pounds maximum is applied to the arming assembly as specified in 4.5.2. The fuze shall be considered as armed when the spring plunger clears the spring stop of the arming assembly and remains in that position. It shall not return to the unarmed position when the spring is fully compressed and released from that position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:18Z
Check the source to verify that this is the current version before use.

3.5 First article. This specification makes provisions for first article inspection. Requirements for submission of first article samples by the contractor shall be as specified in the contract.

3.6 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, cracks, chips, sharp edges, unblended radii, surface defects, dirt, grease, hot rolling defects, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Surface coatings shall be continuous except for a few light scratches. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. The following types of inspection shall be conducted on this item:

a. First article inspection

b. Quality conformance inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated:

Part Description	Drawing	Quantity
Pin Arming	8845378	5
Housing	8845381	5
Stop, Spring	8845379	5
Fuze, Demolition Kit Training M1147	8845376	5

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:18Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46561D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Pin Arming (Dwg. 8845378) Examination for defects	5		3.1	4.4.2.1
	Housing (Dwg. 8845381) Examination for defects	5		3.1	4.4.2.2
	Stop, Spring (Dwg. 8845379) Examination for defects	5		3.1	4.4.2.3
	Fuze, Demoliltion Kit Training M1147 (Dwg. 8845376) Examination for defects	5		3.1	4.4.2.5
	Drop Test	5		3.3	4.5.1
	Fuze Functioning	5		3.4	4.5.2

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:18Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. An inspection lot shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:18Z
Check the source to verify that this is the current version before use.

TABLE II. Quality conformance inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46561D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8845378
4.4.2.1	Pin, Arming				NEXT HIGHER ASSEMBLY 8858429
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of large thread		.40%	3.1	Gage
102	Major diameter of large thread, max.		.40%	3.1	Gage
103	Diameter of shaft, max.		.40%	3.1	Gage
104	Total length, max.		.40%	3.1	Gage
Minor					
201	Operation missing		.65%	3.1	Visual
202	Protective coating missing or inadequate		.65%	3.1	Visual
203	Evidence of poor workmanship		1.0%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:18Z
Check the source to verify that this is the current version before use.

TABLE II. Quality conformance inspection - Continued

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46561D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Housing				8845381
					NEXT HIGHER ASSEMBLY 8845376
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of threads to center hole (2 places)		.40%	3.1	Gage
102	Diameter of center hole, min.		.40%	3.1	Gage
103	Symmetry of slots with center hole		.40%	3.1	Gage
104	Concentricity of neck outside diameter with center hole		.40%	3.1	Gage
105	Pitch diameter of larger thread		.40%	3.1	Gage
106	Pitch diameter of smaller thread		.40%	3.1	Gage
107	Minor diameter of larger thread, min.		.40%	3.1	Gage
108	Minor diameter of smaller thread, min.		.40%	3.1	Gage
109	Depth of larger hole, min.		.40%	3.1	Gage
110	Depth of smaller hole, min.		.40%	3.1	Gage
111	Diameter of neck		.40%	3.1	Gage
112	Width of slot, min.		.40%	3.1	Gage
113	Distance from end of neck to shoulder		.40%	3.1	Gage
114	Diameter of larger hole, min.		.40%	3.1	Gage
115	Depth of slot, min.		.40%	3.1	Gage
Minor					
201	Protective coating missing or inadequate		.65%	3.1	Visual
202	Evidence of poor workmanship		1.0%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:18Z
Check the source to verify that this is the current version before use.

TABLE II. Quality conformance inspection - Continued

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46561D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Stop, Spring				8845379
					NEXT HIGHER ASSEMBLY 8845380
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diamater of thread		.40%	3.1	Gage
102	Major diameter of thread, max.		.40%	3.1	Gage
103	Diameter of longitudinal hole, min.		.40%	3.1	Gage
104	Concentricity of longitudinal hole with pitch diameter		.40%	3.1	Gage
105	True position of cotter pin hole		.40%	3.1	Gage
Minor					
201	Protective finish missing, or inadequate		.65%	3.1	Visual
202	Evidence of poor workmanship		1.0%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:18Z
Check the source to verify that this is the current version before use.

TABLE II. Quality conformance inspection - Continued

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46561D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Pin assembly				8858429
					NEXT HIGHER ASSEMBLY 8845380
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Protrusion of plunger		.40%	3.1	Gage
Minor					
201	Coating missing from threads		.65%	3.1	Visual/Manual
202	Evidence of poor workmanship		1.0%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:18Z
Check the source to verify that this is the current version before use.

TABLE II. Quality conformance inspection - Continued

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46561D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Fuze, Demolition Kit, Training M1147				8845376
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Warning stencil missing		100%	3.1	Visual
Major					
101	Any component missing		.40%	3.1	Visual
102	Arming assembly not properly staked		.40%	3.1	Visual
103	Drop Test	5-0-1		3.3	4.5.1
104	Fuze Functioning		100%	3.4	4.5.2
Minor					
201	Protective coating damaged		.65%	3.1	Visual
202	Marking missing, misleading or unidentifiable		.65%	3.1	Visual
203	Evidence of poor workmanship		1.0%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:18Z
Check the source to verify that this is the current version before use.

TABLE II. Quality conformance inspection - Continued

CLASSIFICATION OF DEFECTS & TESTS MIL-F-46561D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Inner Carton, sealed				8799682
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Contents loose		.40%	3.1	Manual
102	Corners not blunted		.40%	3.1	Visual
Minor					
201	Lable missing		.65%	3.1	Visual
202	Lable data improper, incomplete or illegible		.65%	3.1	Visual
203	Evidence of poor workmanship		1.0%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:18Z
Check the source to verify that this is the current version before use.

TABLE II. Quality conformance inspection - Continued

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46561D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Barrier bag, sealed				8799682
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Area for subsequent seals missing		.40%	3.1	Visual
102	Air not exhausted		.40%	3.1	Visual
103	Seal inadequate		.40%	3.1	Manual
Minor					
201	Marking missing, misleading, illegible or improperly located		.65%	3.1	Visual
202	Evidence of poor workmanship		1.0%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:18Z
Check the source to verify that this is the current version before use.

TABLE II. Quality conformance inspection - Continued

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46561D(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Outer carton, sealed		8799682
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Carton damaged		.40%	3.1	Visual
102	Contents loose		.40%	3.1	Manual
103	Closing flap insecure		.40%	3.1	Visual
Minor					
201	Marking missing, misleading, illegible, or unidentifiable		.65%	3.1	Visual
202	Evidence of poor workmanship		1.0%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:18Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1 and on EL-8845376. The contractor shall submit, for approval, inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and 6.3 herein.

4.5 Method of inspection.

4.5.1 Drop test. The armed fuze shall be assembled into the applicable inspection equipment with the fuze in the required position and dropped onto the hard packed earth. Observation shall be made for return of the fuze to the unarmed position. Any fuze which returns to the unarmed position shall be classified defective.

4.5.2 Fuze functioning. The cotter pin or ring assembly shall be removed. The fuze shall be placed in the applicable test equipment, the required withdrawal force applied and observation made for fuze arming. The spring of the arming assembly shall then be fully compressed and released from that position. If a fuze does not arm as required or should it return to the unarmed position it shall be classified defective. After completion of the test, the fuze shall be manually returned to the unarmed position, the cotter pin or ring assembly reassembled into the arming assembly and the pin properly split.

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level A. Training fuzes shall be preserved, packaged, and marked in accordance with the requirements of drawing 8799682.

5.2 Packing.

5.2.1 Level C. The packaged fuzed shall be packed and marked in accordance with drawing 8799683.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use on the Fuze, Demolition Kit, Training M1147.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-I, Dover, New Jersey 07801.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:18Z
Check the source to verify that this is the current version before use.

6.4 Army designs. Army designed inspection equipment (See EL-8845376) is not mandatory for use. The contractor may design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A239)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:18Z
Check the source to verify that this is the current version before use.