MILITARY SPECIFICATION

PRIMERS, PERCUSSION, M28A2 AND M28B2
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-P-46565C (MU) dated 8 May 1973 and is approved for use within the US Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* Add new paragraph 2.3 as follows:

"2.3 Order of precedence. In the event of a conflict between the text of this specification and the reference cited herein, the text of this specification shall take precedence."

PAGE 3

* 3.5.2 Delete in in its entirety and substitute the following:

"3.5.2 Pressure resistance. The M28A2 Primer assembly shall withstand a pressure of 40,000 plus or minus 4,000 pounds per square inch (psi) and the M28B2 primer assembly shall withstand a pressure of 54,500 to 57,000 psi without evidence of rupture, or any part of the primer becoming detached, when tested as specified in 4.3.2."

PAGE 5

4.2.1,b: Delete "one lot" and substitute "two lots". Add after manufacture "A lot of black powder shall be used to completion."

PAGE 11

4.2.3.5 Delete in its entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:19Z
Check the source to verify that this is the current version before use.

* 4.3.2 Delete in its entirety and substitute the following:

"4.3.2 Proving ground."

4.3.2.1 Primer assembly functioning and presssure resistance. The sample primers shall be sent to a Government Proving Ground for testing.

4.3.2.1.1 M28A2 Primer percussion. The M28A2 primer percussion shall be assembled into complete rounds for which they are standard and fired at the required pressure.

4.3.2.1.2 M28B2 Primer percussion. The M28B2 primer percussion shall be assembled to the M14B4 cartridge case, M760 projectile and fired from an M119 howitzer using the PXR200-1 propelling charge to obtain the required pressure. The rounds shall be fired in an acceptable gun, based upon current gun tube condemnation criteria. The test rounds (charges and projectiles) shall be uniformly temperature conditioned at 70°F ± 2.5° for a minimum of 24 hours prior to testing. The M760 projectile metal parts assembly shall be inert loaded and dummy fuzed to an as fired weight of 33.0 ± 0.2 pounds.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1390-A494)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:19Z
Check the source to verify that this is the current version before use.