MIL-T-46555B (MU)
24 September 1965
SUPERSEDING
MIL-T-46555A (ORD)
12 December 1961

MILITARY SPECIFICATION

TRACER, XM10, PARTS FOR, AND LOADING, ASSEMBLING, AND PACKING

1. SCOPE

1.1 This specification covers the parts for, and loading, assembling, and packing for one type of tracer designated as Tracer, XM10.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116	- Preservation, Methods of
MIL-B-153	- Barium Peroxide
MIL-G-155	- Graphite, Dry (For use in Ammunition)
JAN-M-382	- Magnesium Powder (For use in Ammunition)
JAN-M-454	- Magnesium-Aluminum Alloy, Powdered
MIL-A-2550	- Ammunition and Special Weapons; General Specification for
MIL-P-20307	- Polyvinyl Chloride (For use in Pyrotechnics)
MIL-S-20322	- Strontium Nitrate Non-Hygroscopic
MIL-C-20470	- Calcium Resinate
MIL-I-45607	- Inspection Equipment, Supply and Maintenance of

FEDERAL

RR-S-366 - Sieves; Standard for Testing Purposes

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105).

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-286 - Propellants, Solid. Sampling, Examination, and Testing
MIL-STD-414 - Sampling Procedures and Tables for Inspection by Variables for Percent Defective.
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

ARMY

8849014 - Tracer, XM10, Loading Assembly.
8858379 - Carton, Packing, Ammunition, For Tracer XM10
8858380 - Box, Packing, Ammunition, For Tracer XM10

PUBLICATIONS

ARMY

IEL 8849014 - Index of Inspection Equipment Lists

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material

3.1.1 Igniter Composition - The materials used in the igniter composition shall be in accordance with applicable specifications and, in addition, shall be of the type and class as follows:

3.1.1.1 Barium peroxide - The barium peroxide used shall comply with the requirements of Specification MIL-B-153, Class C.

3.1.1.2 Magnesium powder - The magnesium powder used shall comply with the requirements of Specification JAN-M-382, Type III, Granulation 15.

3.1.1.3 Calcium resinate - The calcium resinate used shall comply with the requirements of Specification MIL-C-20470, either Type I or Type II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

3.1.1.4 Graphite - The graphite used shall comply with the requirements of Specification MIL-G-155.

3.1.2 Tracer Composition - The materials used in the tracer composition shall be in accordance with the applicable specifications and, in addition, shall be of the type and class as follows:

3.1.2.1 Strontium nitrate - The strontium nitrate used shall be anhydrous and shall comply with the requirements of Specification MIL-S-20322, Grade B.

3.1.2.2 Magnesium - aluminum alloy - The powdered magnesium-aluminum alloy shall comply with the requirements of Specification JAN-M-454, Type B, except that it shall comply with the following granulation requirements using U.S. Standard sieves complying with the requirements of Specification RR-S-366:

Thru No. 100 sieve - 85.0 percent, minimum (min.)
Thru No. 200 sieve - 15.0 percent, maximum (max.)

3.1.2.3 Polyvinyl chloride - The polyvinyl chloride shall comply with the requirements of Specification MIL-P-20307.

3.1.3 Parts - All parts shall be in accordance with applicable drawings and specifications.

3.2 Compositions - No ingredients other than those specified shall be utilized and no ingredients shall be omitted.

3.2.1 Igniter composition, K-29- The igniter composition, K-29, shall comply with Table I.

Table I
Igniter Composition

Constituent	Percent by Weight
Barium peroxide	80.5 ± 2.0
Magnesium (free metallic) powder	16.5 ± 2.0
Calcium resinate	2.0 ± 0.5
Graphite	1.0 ± 0.5

3.2.2 Tracer composition, R-45 - The tracer composition, R-45, shall comply with Table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

TABLE II

TRACER COMPOSITION

Constituent	Percent by Weight
Strontium nitrate	56.0 ± 2.0
Magnesium-aluminum alloy	37.0 ± 2.0
Polyvinyl chloride	7.0 ± 1.0

3.3 Moisture and total volatile content (see 6.4).

3.3.1 Igniter composition - The moisture and total volatile content of the igniter composition shall not exceed 0.14 percent at the time of manufacture of the pellets when tested as specified in 4.3.1.

3.3.2 Tracer composition - The moisture and total volatile content of the tracer composition shall not exceed 0.14 percent at the time of manufacture of the pellets when tested as specified in 4.3.1.

3.4 Tracers - The tracers shall comply with all requirements specified on Drawing (dwg.) 8849014 and with all requirements specified in applicable specifications.

3.5 Proving ground - The tracers shall ignite and shall produce visible evidence of burning of the tracer composition for 3.7 seconds min., when tested as specified in 4.3.2.

3.6 Workmanship - All parts shall be free from dirt, grease, chips, cracks, and other foreign matter. The cleaning method used shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents used.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.

b. Number of units of product inspected.

c. Results obtained, by defect code, for all inspection performed.

d. Drawing, specification number and date, together with an identification and date of changes.

e. Certificates of compliance on all material purchased by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.2 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Inspection provisions.

4.2.1 Lot formation - A lot shall consist of loaded tracers produced by one manufacturer in one unchanged process, in accordance

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:16Z
Check the source to verify that this is the current version before use.

with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification, and process changes not affecting safety, performance, or fit, as determined by the Government, shall not necessitate changing the lot interfix number. Product shall be submitted in accordance with Standard MIL-STD-105 (or MIL-STD-1235, when applicable). Each lot shall contain:

a. tracer parts in accordance with the same drawing and drawing revision, same specification and specification revision.

b. tracer and igniter compositions in accordance with the same specification and specification revision from one manufacturer.

c. tracer and igniter composition constituent materials, each from one manufacturer only.

4.2.2 Examination.-Inspection for Critical defects shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with Standard MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Washer, closing (see dwg. 8849013, covering a detail of dwg. 8849014).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Outside diameter, min.	Gage	01001
Minor:	AQL 1.5 percent		
201.	Inside diameter, max.	Gage	01002
202.	Thickness, min.	Gage	01003
203.	Protective finish incomplete or inadequate	Visual	01004
204.	Evidence of poor workmanship (see 3.6)	Visual	01005

4.2.2.2 Sealing washer and closing disc (see dwg. 8849011 and 8849012, covering details of dwg. 8849014).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 0.40 percent		
101.	Washer torn or distorted	Visual	02001
102.	Disc with ragged edges or perforations	Visual	02002
Minor:	AQL 1.0 percent		
201.	Foreign matter	Visual	02003
202.	Evidence of poor workmanship (see 3.6)	Visual	02004

4.2.2.3 Body (see dwg. 8849015, covering a detail of dwg. 8849014).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 1.0 percent		
101.	Pitch diameter of thread, min.	Gage	03001
102.	Major diameter of thread, min.	Gage	03002
103.	Concentricity of charge cavity diameter with pitch diameter of thread	Gage	03003
104.	Diameter of charge cavity, max.	Gage	03004
105.	Depth of charge cavity, max.	Gage	03005
106.	Distance to end of thread, min.	Gage	03006
107.	Protective finish incomplete or inadequate.	Visual	03007
Minor:	AQL 4.0 percent		
201.	Pitch diameter of thread, max.	Gage	03008
202.	Major diameter of thread, max.	Gage	03009
203.	Total length	Gage	03010
204.	Outside diameter, max.	Gage	03011
205.	Distance between wrench flats	Gage	03012
206.	Distance from forward end to shoulder, min.	Gage	03013
207.	Inside diameter of washer cavity	Gage	03014
208.	Diameter of surface to rear of flange, min.	Gage	03015
209.	Depth of washer cavity	Gage	03016
210.	Distance to flange	Gage	03017
211.	Diameter of thread pilot	Gage	03018
212.	Evidence of poor workmanship (see 3.6)	Visual	03019

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

4.2.2.4 Tracer assembly, prior to assembling closing disc and closing washer (see dwg. 8849014).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Charge missing or less than min. required depth from shoulder	Visual	04001
102.	Sealing washer missing	Visual	04002
Minor:	AQL 1.0 percent		
201.	Charge chipped or broken on any one step in excess of 1/3 the total area of the step, or total aggregate of chipped or broken area of all steps in excess of 1/3 the total area of the largest step	Visual	04003
202.	Evidence of poor workmanship (see 3.6)	Visual	04004

4.2.2.5 Tracer assembly (see dwg. 8849014).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Closing washer loose or missing	Visual-Manual	05001
102.	Closing disc punctured or loose	Visual-Manual	05002
103.	Crimp not full 360 degrees	Visual	05003
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	05004

4.2.2.6 Carton, prior to sealing (see dwg. 8858379).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.40 percent		
101.	Number of tracer assemblies incorrect	Visual	06001
102.	Any packing material missing or insufficient	Visual	06002

Minor: None defined

4.2.2.7 Carton, sealed (see dwg. 8858379).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Carton damaged exposing contents	Visual	07001
102.	Marking misleading or unidentifiable	Visual	07002
Minor:	AQL 1.0 percent		
201.	Carton insecurely sealed	Visual	07003
202.	Contents loose	Manual	07004

4.2.2.8 Bag, sealed (see dwg. 8858379).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		
Minor:	AQL 1.0 percent		
201.	Marking missing or unidentifiable	Visual	08001
202.	Seal insecure or mislocated	Visual	08002

4.2.2.9 Packing box, prior to sealing (see dwg. 8858380).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.65 percent		
101.	Number of bags incorrect	Visual	09001
102.	Bag torn or perforated	Visual	09002
103.	Packing material missing or insufficient	Visual	09003

Minor: None defined.

4.2.2.10 Sealed packing box (see dwg. 8858380).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.0 percent		
101.	Box damaged exposing contents	Visual	10001
102.	Board broken	Visual	10002
103.	ICC nomenclature misleading or unidentifiable	Visual	10003
104.	Strapping missing or loose	Visual-Manual	10004
105.	Packing material missing or insufficient	Visual	10005
Minor:	AQL 1.5 percent		
201.	Strapping improperly engaged	Visual-Manual	10006
202.	Marking misleading or unidentifiable	Visual	10007
203.	Seal insecure or mislocated	Visual	10008

4.2.3 Testing

4.2.3.1 Moisture and total volatile content of igniter composition (Major defect, Code No. 11001) and tracer composition (Major defect, Code No. 11002), see 3.3 - The contractor shall provide adequate controls to assure the compliance of each lot with the applicable requirement. The contractor shall test for verification at least one representative sample of each composition during each eight hours production of tracer assembles. Composite samples shall not be used in determining compliance. The igniter and tracer compositions shall be tested as specified in 4.3.1 and any failure to comply with the applicable requirement shall be cause for rejection of the eight hours production represented by the sample.

4.2.3.2 Proving ground (see 3.5) - The following test shall be performed as specified in 4.3.2.

4.2.3.2.1 Functioning - Major defect, Code No. 12001.

4.2.3.2.1.1 Beginning with the first lot produced and

Source: https://assist.dla.mil -- Downloaded: 20261O-22T06:16Z
Check the source to verify that this is the current version before use.

continuing until three consecutive lots have complied with the applicable requirements specified, the sampling plan and procedure for this test shall be in accordance with Standard MIL-STD-414, Section B, Part I, Code letter I, and AQL 1.5 percent. Calculations shall be in accordance with Example B2, page 38.

4.2.3.2.1.2 After three consecutive lots have met the criteria of 4.2.3.2.1.1, the sampling plan and procedure for this test shall be in accordance with Standard MIL-STD-414, Section B, Part I, Code letter F, and AQL 1.5 percent. Calculations shall be in accordance with Example B2, page 38. If any tracer fails to ignite or fails to produce visible evidence of burning, the lot shall be rejected.

4.2.3.2.1.3 Refiring - If for any reason the proof director considers that the test conditions have detrimentally affected the test results, he shall declare the results invalid and perform a new test on additional tracers as required.

4.2.3.3 Heat Seal Test of Barrier Bag, (Major Defect, Code No. C80C5), see dwg. 8858379 - Sampling, acceptance criteria, and test procedures for this test shall be as prescribed in Specification MIL-P-116 for the "Heat Seal Test".

4.2.4 Inspection Equipment.-Index of Inspection Equipment Number IEL 8849014 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the IEL may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed on the IEL shall be in accordance with Specification MIL-I-45607.

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:16Z
Check the source to verify that this is the current version before use.

4.2.4.3 Government use of contractor's inspection and test equipment.-The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government..

4.3 Test methods and procedures

4.3.1 Determination of moisture and total volatile content of igniter and tracer compositions - The moisture and total volatile content of these compositions shall be determined in accordance with Standard MIL-STD-286, Method 101.1.2.

4.3.2 Proving ground - The sample tracers shall be assembled into inert or HE loaded 90mm cartridges, M71A1. The assembled rounds shall be fired at ambient temperature from the appropriate weapon and observation made for burning of the tracer composition. Burning times shall be recorded to the nearest 0.1 second.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level C - The tracers shall be preserved and packaged in accordance with dwg. 8858379.

5.2 Packing

5.2.1 Level C - The cartons shall be packed in accordance with dwg. 8858380.

5.3 Marking - The carton shall be marked in accordance with dwg. 8858379. The wood box shall be marked in accordance with dwg. 8858380.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced Inspection Equipment Lists (IEL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.7.

6.3.1 Inspection equipment lists.-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (OO Form 1242-3) the numbers of drawings of existing equipment designs or codes as indicated in paragraph 6.3.2. Design action required of the contractor with respect to the different types of drawings that may be listed is described in paragraphs 6.3.3 and 6.3.4. Action required by the contractor with respect to commercial inspection equipment is described in 6.3.5. The contractor will be required to prepare detailed drawings in accordance with 6.3.6 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3, 6.3.4, 6.3.5 and 6.3.6 will be designated in the IEL by the following codes:

CDAF - Contractor's design responsibility on Army format in accordance with MIL-D-45608.
CDCF - Contractor's design responsibility on contractor format.
AD - Army design.
ADMU - Army design, mandatory for use.
CE - Commercial equipment.
SCD - Specification control drawing.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications, mandatory and non-mandatory. When an inspection

Source: https://assist.dla.mil -- Downloaded: 20261O-22T06:16Z
Check the source to verify that this is the current version before use.

equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 Specification control drawing.-Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagramatic or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

6.3.5 Commercial equipment.-Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and Government. Contractors are not required to furnish drawings of commercial inspection equipment, but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.6 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Contractor designs identified as CDCF may be developed on the format the contractor normally employs in his equipment

Source: https://assist.dla.mil -- Downloaded: 20261O-22T06:16Z
Check the source to verify that this is the currentversion before use.

design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDAF shall comply with the format and requirements of MIL-D-45608, and in addition, contain the detail and information specified above. Final approved contractor designs identified as CDCF shall be suitable for microfilming. They must be non-reproducible diazo or electrostatic prints of top quality full size with black lines on white background and shall provide a legible print produced via the 35mm microfilm process. Contractors shall submit one copy of the final design as a rolled set or flat set.

6.3.7 Submission of contractor designs.-Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. Design review will normally be accomplished within one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs.

6.4 Igniter and tracer compositions moisture exposure - The igniter and tracer compositions, and the pellets formed thereof, are hygroscopic and will deteriorate rapidly when exposed to moisture. Small amounts of moisture present in or absorbed by the compositions or pellets prior to, or after loading into tracer assemblies, will eventually result in unsatisfactory functioning. It is highly desirable that the ingredients, compositions, pellets, and loaded tracers be carefully safeguarded from exposure to moisture and humid atmospheres. For assurance of a satisfactory loaded tracer, it is recommended that the blending and pelletizing building be air conditioned in a manner which will hold the humidity of the atmosphere as low as practicable.

6.5 It is not intended to ship these compositions or pellets. It is intended that the compositions and pellets thereof be prepared at the plant where the loading of the tracers will be accomplished.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project No. 1315-A461

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:16Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:16Z
Check the source to verify that this is the current version before use.