JAN-C-691

23 NOVEMBER 1948

NATIONAL MILITARY ESTABLISHMENT SPECIFICATION

CARBINES, CALIBER .30, M2 AND M3

This specification was approved by the Departments of the Army, the Navy, and the Air Force for use of procurement services of the respective Departments.

A. APPLICABLE SPECIFICATIONS, OTHER PUBLICATIONS, AND DRAWINGS

A–1. *Specifications.*—

A–1a. The following specifications, of the issue in effect on date of invitation for bids, form a part of this specification:

U. S. ARMY SPECIFICATIONS

52–0–1—General Specification Governing the Manufacture and Inspection of Small Arms Weapons, Spare and Replacement Parts, and Accessories.
57–0–2—Finishes, Protective, for Iron and Steel Parts.
100–2 —Standard Specification for Marking Shipments by Contractors.

A–1b. All specifications listed on the applicable drawing shown in paragraph A–2, of the issue in effect on date of application for bids, form a part of this specification.

A–2. *Other publications.*—The following publication, of the issue in effect in date of invitation for bids, forms a part of this specification:

BUREAU OF SUPPLIES AND ACCOUNTS PUBLICATION

Navy Shipment Marking Handbook.

A–3. *Drawings.*—The following drawings, of the issue in effect on date of invitation for bids, form a part of this specification:

U. S. ARMY ORDNANCE DEPARTMENT DRAWINGS

42–56–1—Carbine, Cal. .30, M2
42–67–1—Carbine, Cal. .30, M3

B. TYPES

B–1. This specification covers the following types of carbines:

Carbine, caliber .30, M2
Carbine, caliber .30, M3

C. MATERIAL AND WORKMANSHIP

C–1. See specification No. 52–0–1.

D. GENERAL REQUIREMENTS

D–1. *Components and assemblies.*—

D–1a. *General.*—Components shall conform to the dimensions and be within the tolerances after they are given the final or protective finish specified on the drawings. All surfaces shall be free of burrs and other defects which would affect smoothness of operation and handling of gun.

D–1b. *Protective finish.*—Protective finish shall be as prescribed on the drawings and shall meet the requirements of U. S. Army Specification No. 57–0–2, Finishes, Protective, for Iron and

801550—48—(E-174)

Source: https://assist.dla.mil -- Downloaded: 2026-1
Check the source to verify that this is the current vers

Steel Parts. Sand or shot blasting, when used, shall not injure functioning surfaces; and such surfaces shall be thoroughly cleaned of all grit before applying the protective finish.

D–1c. *Barrel.*—The chamber and bore shall be smooth and free of scratches, pits, rings, and other defects. The lands shall be sharp and well defined. Burrs and sharp edges shall be removed from edge of chamber. After proof-firing, the chamber and bore dimensions shall be within the tolerances shown on the drawing.

D–1d. *Safety.*—The safety shall operate freely and shall positively block the trigger when in the "safe" or "on" positions.

D–1e. *Selector.*—The selector shall operate freely and maintain its setting during functioning of the carbine. The carbine shall not fire automatically on the semi-automatic setting, and shall fire automatically only when so set. Firing (finger off trigger) shall not occur when the selector position is changed.

D–1f. *Bolt assembly.*—The bolt assembly shall move freely through its full range of travel.

D–1g. *Firing pin.*—The firing pin point shall be smooth and well formed.

D–1h. *Gas cylinder.*—The hole in which the piston operates shall be straight, smooth, and free of burrs, ridges, and other processing defects.

D–1i. *Stock and handguard.*—The direction of the grain in wood stocks and handguards shall be in the longitudinal direction of the component. Slight deviation in grain direction, small knots, slight sap streaks, small checks, and cracks shall not be cause for rejection provided they do not appear in thin sections. Material with small checks, cracks, and knot holes may be used if filled with shellac, plastic wood, or other suitable material subject to the approval of the inspector. Wood stocks and handguards shall be treated with chinawood oil base finish or a finish satisfactory to the contracting officer and allowed to dry in a vertical position with the butt down.

D–1j. *Front band assembly.*—The front band assembly shall satisfactorily assemble with the bayonet knife, M4.

D–1k. *Component identifications.*—Components and assemblies, wherever practicable, shall bear identifying marks of the manufacturer located so as not to weaken the component or affect functioning. In cases of components and assemblies furnished by a subcontractor, an identifying mark of the subcontractor may also be used at the discretion of the prime contractor.

D–1*l.* *Magazine.*—The magazine shall be free of dents, cracks, sharp edges, and other defects which would affect functioning of either the magazine or the carbine. The magazine shall insert freely in the magazine opening and shall be held securely in place by the magazine catch.

D–1m. *Marking.*—Each accepted carbine and certain components either as of the unit assembly or as spare parts, unless otherwise prescribed in the contract or purchase order, shall, after

Source: https://assist.dla.mil -- Downlo
Check the source to verify that this is the

proof-firing and final inspection, be appropriately marked as prescribed in paragraph F–1d.

D–2. *Trigger pull.*—The trigger pull shall be smooth and shall be within the range of 5 to 7 pounds. The pressure shall be applied approximately ⅝ inch from the lower end of the trigger and exerted parallel with the axis of the bore. There shall be no alteration of any component beyond the prescribed tolerances in order to meet the requirements.

D–3. *Firing pin protrusion.*—The firing pin protrusion shall be gaged for compliance with the drawing.

D–4. *Firing pin indent.*—The striker indent, taken in pure copper cylinder as specified in paragraph F–4, shall be 0.011 to 0.016 inch; and it shall not be off-center more than one-half the diameter of the striker point.

D–5. *Interchangeability.*—All components and assemblies that are replaceable shall be interchangeable.

D–6. *Proof-firing.*—Each assembled weapon, spare barrel, and spare bolt assembly shall be proof-fired as described in paragraph F–6. Enlargement of breeching space due to proof-firing shall not exceed 0.001 inch, and there shall be no appreciable enlargement of the bore. Before proof-firing, the breeching space shall be within the limits shown on the drawing, 1.290 + 0.004 inches. After proof-firing, breeching space shall be within 1.290 + 0.005 inches.

D–7. *Functioning.*—The carbine shall function smoothly and properly under firing conditions; and the allowable malfunctions shall not exceed the numbers specified in table I.

TABLE I.—*Malfunctions allowable in 500-round function firing test.*

MALFUNCTIONS	Allowable
Failure of trigger to release (any cause)	0
Failure to close (due to any rifle component)	2
Failure to eject cartridge case from action	3
Failure to extract from chamber	0
Failure to feed (bolt closed on empty chamber)	0
Failure to feed (bolt held open by live round)	1
Loose barrel and receiver	0
Automatic firing (semi-automatic setting)	0
Semi-automatic firing (automatic setting)	0
Safety fails to function	0
Hangfire (noticeable)[1]	
Misfire[1]	
Pierced primers (due to carbine component)[1]	

[1] See paragraphs F–11a and F–11b.

D–8. *Targeting.*—The assembled carbine shall require no greater range of sight adjustment in targeting than authorized in paragraph F–8.

D–9. *Accuracy.*—The accuracy of each carbine shall be such that five out of seven consecutive shots fired at a range of 100 yards shall be within or cut the edge of a 5-inch circle.

D–10. *Endurance.*—Carbines shall have a dependable endurance life of 4,500 rounds without substitution of any components,

Source: https://assist.dla.mil -- Downloaded: 2026-1
Check the source to verify that this is the current vers

without breakage or excessive wear of any component, and without malfunctions, in excess of the limits shown in table II.

TABLE II.—*Allowable malfunctions and broken or unserviceable parts in 4,500-round endurance firing test.*

MALFUNCTIONS	At end of 2250, not more than	At end of 4500, not more than	Reference abbreviation
Failure of trigger to release (any cause)	0	0	TFR
Failure to close (due to any rifle component)	2	4	BFC
Failure to eject cartridge case from action	8	16	EJ
Failure to extract from chamber	1	2	EX
Failure to feed (bolt closed on empty chamber)	1	2	FFC
Failure to feed (bolt held open by live round)	2	4	FF
Hangfire or misfire [1]			M
Loose barrel and receiver	0	0	LB
Pierced primer (due to carbine component)	0	0	P
Firing caused by change in selector setting	0	0	SF
Automatic fire on semi-automatic setting	0	0	FAS
Semi-automatic fire on automatic setting	0	0	FSA
Total shall not exceed	14	28	
BROKEN OR UNSERVICEABLE PARTS			
Broken, bent or burred cartridge ejector	0	1	
Broken bolt	0	0	
Broken slide	0	0	
Broken firing pin	0	1	
Broken piston	0	0	
Broken hammer	0	0	
Broken piston nut	0	0	
Broken operating spring	0	0	
Broken receiver	0	0	
Broken or burred extractor	1	2	
Broken or bent disconnector	0	0	
Broken safety	0	0	
Broken magazine catch	0	0	
Broken selector	0	0	
Broken or split handguard	0	0	
Broken or split stock	0	0	
Broken sear	0	0	
Broken trigger	0	0	
Broken or weak extractor spring	1	2	
Total permissible shall not exceed	2	6	

[1] See paragraphs F–11a and F–11b.

E. DETAIL REQUIREMENTS

E–1. *Sights, carbine, M2.*—

E–1a. *Front sight.*—The top of the front sight shall be at right angles with the sides and shall be smooth and clearly defined.

E–1b. *Rear sight assembly.*—The adjustments shall operate readily by hand with no appreciable looseness. There shall be no change in the adjustments when the weapon is fired.

E–2. No component of the assembled weapon shall interfere with a clear sight picture.

F. METHODS OF INSPECTION AND TESTS

F–1. *Inspection and tests.*—

F–1a. *Place of inspection.*—Unless otherwise specified, inspection and testing shall be conducted at the place of manufacture.

Source: https://assist.dla.mil -- Downlo
Check the source to verify that this is the

The inspector may subject all or part of any lot or lots of components or assemblies to such inspection as he deems necessary to determine compliance with the requirements.

F–1b. *Lot.*—A lot of carbines for inspection purposes shall consist of not more than 500 carbines unless otherwise authorized.

F–1c. *Visual inspection and operating tests.*—Each carbine shall be visually inspected for completeness of manufacture, assembly, finish, and workmanship. Components, spare parts, chamber, and bore shall be examined for rust, pits, powder fouling, burrs, and other defects. Inspection shall be made to determine the general quality and conformity of the protective finish and the completeness and clearness of prescribed markings. Carbine components and spare parts of the inspection lot shall be gaged for the dimensions shown on the drawings with gages furnished by the Government. Each carbine shall be operated by hand sufficiently to check the operation of all moving parts under semi- and full-automatic settings. When set for automatic fire and with the trigger pulled back, the hammer must fall when the operating slide is slowly pushed forward.

F–1d. *Marking.*—

F–1d(1). ***Proof-marking.***—Immediately after proof-firing, the person doing the proof-firing shall place proof-marks in the location prescribed below, on each accepted barrel, bolt and receiver.

F–1d(2) *Location of proof-marks.*—Each barrel shall be marked with the letter "P" on the top of the barrel at a point approximately two inches in front of the band. A suitable prick-punch mark shall be placed on the top of the receiver at a point approximately ⅜ inch in front of the rear sight base. A suitable prick-mark shall be placed on the top center surface of the bolt at a point approximately ⅝ inch from the front face of the bolt.

F–1d(3). *Stocks.*—The final acceptance stamp shall be placed on the right rear side of the stock on the flat portion, approximately midway between the pistol grip and butt plate.

F–1d(4). *Barrel.*—Each barrel shall have the manufacturer's identification mark placed on the front end of the barrel near the muzzle in such a position as to be readily identified.

F–1d(5). *Receiver.*—Each receiver shall be marked with the words Carbine, Cal. .30, M2, or Carbine, Cal. .30, M3, as required, and the manufacturer's name and the serial number.

F–1d(6). *Size and type of marking.*—The letter "P" on the barrel shall be at least 1/16 inch high. The manufacturer's identification marks, where placed on the stock, shall be approximately 5/16 inch high. The final acceptance stamp shall be at least ½ inch high and in accordance with Ordnance Department Drawing No. 20–10–2.

F–2. *Trigger pull test.*—Each carbine in the interchangeability test shall be tested for amount of trigger pull prior to the interchanging of the parts. Failure of the carbines to meet trigger pull requirements shall be cause for rejection of the lot.

F–3. *Firing pin protrusion test.*—Each carbine shall be gaged to assure compliance with the drawing requirement for firing

Source: https://assist.dla.mil -- Downloaded: 2026-1
Check the source to verify that this is the current vers

pin protrusion. The bolt assembly shall be removed from the carbine for this gaging. Care shall be exercised to assure that there is no interference with protrusion while this check is being made.

F–4. *Firing pin indent test.*—The firing pin indent shall be taken on at least one percent of all carbines submitted by determining five readings on each gun. To be acceptable, the extremes of the five determinations shall be within the limits prescribed. Copper compression cylinders of 99.90 percent pure copper, soft annealed (Government Standard) shall be used, inserted in a standard holding fixture.

F–5. *Interchangeability test.*—

F–5a. At least ten carbines selected at random by the inspector from each lot shall be tested for interchangeability as follows:

F–5b. Components and assemblies as itemized below shall be disassembled from the gun for interchangeability. Further disassembly of the assemblies as listed shall not be made.

COMPONENTS

Catch, magazine.
Disconnector.
Hammer.
Housing, trigger.
Sear.
Selector.
Slide, operating.
Spring, selector.
Bolt.
Extractor.
Guide, operating Slide spring.
Pin, trigger.
Pin, firing.
Pin, hammer.
Plunger, extractor spring.
Plunger, hammer spring.
Safety.
Spring, extractor plunger.
Spring, hammer.
Spring, operating slide.
Spring, sear.
Spring, sear.
Spring, trigger.
Trigger.
Screw, adjusting (carbine, M3)

ASSEMBLIES

Lever, disconnector
Plunger, disconnector spring
Ejector
Guard, hand
Plunger, magazine catch
Plunger, magazine catch, retainer w/plunger safety
Stock

ASSEMBLIES NOT TO BE INTERCHANGED

Barrel
Band, front

NOTE.—The components of the barrel assembly, front band assembly, stock assembly and operating slide assembly shall not be interchanged.

F–5c. Components and assemblies of each kind as itemized above shall be placed together and mixed. The carbines shall then be reassembled by using components and assemblies selected at random. One selection only for each component or assembly shall be permitted. At least 80 percent of the carbines shall be assembled without fitting or alteration of any component. Minor hand fitting will be allowed on 20 percent of the carbines provided no part is rendered unsuitable for assembly in other weapons and provided no special tools are required for the hand fitting.

Source: https://assist.dla.mil -- Downlo
Check the source to verify that this is the

The assembled carbines shall operate and function properly. Failure of the carbines to meet this test shall be cause for rejection of the lot.

F–5d. At least two carbines from which all components of the spare parts list have been removed shall be reassembled by using components inspected for use as spare parts. There shall be no hand fitting and the guns shall operate and function properly. Failure of the carbines to meet this test shall be cause for rejection of the lot.

F–5e. Each carbine assembled from interchangeable parts shall be subjected to a firing test of 30 rounds. Should a malfunction as listed in table I occur when thus firing these weapons after the interchangeability tests, then an additional 30 rounds shall be fired. If no further malfunction occurs, then the weapon shall be considered acceptable.

F–5f. The bayonet knife, M4, or a simulated gage shall satisfactorily assemble on interchange test guns. Ten guns from each interchange test shall be selected for this test. Should this bayonet knife test show over an extended period of time that no difficulty is encountered, the inspector may, at his discretion, reduce the check to one gun from each interchange test.

F–6. *Proof-firing test.*—Each assembled carbine, spare barrel, and spare bolt assembly shall be subjected to firing of one Government standard cartridge, high pressure test carbine caliber .30, M18, under supervision of the inspector. Suitable fixtures for proof-firing these spare components shall be provided by the contractor subject to the approval of the contracting officer. When proof-firing spare barrels, provisions shall be made to restrict travel of the piston to prevent damage to piston or piston nut.

F–7. *Functioning firing test.*—

F–7a. Each carbine of the first lot manufactured shall be tested by firing at least 500 rounds of cartridge, ball, carbine, caliber .30 ammunition. Each carbine of each subsequent lot shall be function fired 30 rounds, approximately half in automatic bursts of from 3 to 7 rounds, and the remainder semi-automatically. The trigger shall be pulled and slowly released on at least 2 rounds of semi-automatic fire to check trigger functioning. Satisfactory operation of each carbine during function firing is required.

F–7b. One carbine from each lot shall be selected and function fired 500 rounds Two magazines shall be used and each charged approximately equal number of rounds. Automatic and semi-automatic fire shall be alternated.

F–7c. Malfunctions in excess of those allowed in table I or any breakage shall be cause for rejection of the lot. The magazine is a part of the weapon and shall function satisfactorily in all firing tests.

F–7d. Functioning, targeting, and accuracy firing tests may be performed concurrently.

F–8. *Targeting firing test.*—

F–8a. Each carbine, caliber .30, M2, shall be targeted, 0 windage, with the elevation set at 100 yards and a six o'clock hold on

Source: https://assist.dla.mil -- Downloaded: 2026-1
Check the source to verify that this is the current vers

a 12-inch black bull's eye. Using U. S. Government standard cartridge, ball, carbine, caliber .30, M1, ammunition, five out of seven consecutive shots fired semi-automatically shall be within or cutting the black. Two clicks right or left windage shall be permitted to bring the group within the black.

F–8b. Each carbine, caliber .30, M8, shall be targeted by using a scope approved by the inspector. Using U. S. Government standard cartridge, ball, carbine, caliber .30, M1, ammunition, five out of seven consecutive shots fired semi-automatically shall fall within or cut a circle 5 inches in diameter at 100 yards.

F–8c. At the option of the contractor, the carbines may be fired for targeting at a range of not less than 90 feet. All weapons must be adjusted to meet the 100-yard requirements which will be determined by spot checking not less than 5 percent of the carbines at 100 yards.

F–9. *Accuracy firing test.*—

F–9a. Each carbine shall be fired at least 5 rounds of U. S. Government standard carbine, ball, carbine, caliber .30, M1, ammunition at a range of 100 yards, using a fixed or muzzle and elbow rest. Five out of seven consecutive shots shall be within or cut the edge of a circle 5 inches in diameter.

F–9b. At the option of the contractor, the carbines may be accuracy fired at a range of not less than 90 feet. All weapons must be adjusted to meet the 100-yard requirements which will be determined by spot checking not less than 5 percent of the carbines at 100 yards.

F–9c. Functioning, targeting, and accuracy firing tests may be performed concurrently. Targeting and accuracy firing shall be done semiautomatically.

F–10. *Endurance firing test.*—

F–10a. One carbine taken at random from the first lot of 500 carbines manufactured and one taken from each successive 6 lots of 500, found satisfactory in all other tests, shall be considered as representative weapons and subjected to endurance tests of 4,500 rounds of U. S. Government standard cartridge, ball, carbine, caliber .30, M1. Fifteen magazines shall be selected in such a manner that at least one sample shall represent each lot, charged 300 rounds each, and used in the test of the carbine. The weapon may be superficially cleaned and oiled after each approximate series of 500 rounds. The chamber shall be cleaned at least every 500 rounds or more often should excessive fouling occur. The weapon shall be disassembled, examined, cleaned, and oiled after each approximate series of 1000 rounds.

NOTE.—Care shall be exercised to avoid excessive oiling of the weapon as this is conducive to accumulations of powder residue which may interfere with functioning of the weapon.

F–10b. Endurance test shall be fired in alternate series of semi- and full-automatic fire. A series shall consist of 150 rounds of U. S. Government standard cartridge, ball, carbine, caliber .30, M1, brass. The magazine forms a part of the carbine and the number selected must therefore successfully pass this test.

[JAN–C–691]

Source: https://assist.dla.mil -- Downlo
Check the source to verify that this is the

F–10c. During this test, the gun shall be air cooled after each approximate 150 round series.

F–10d. Carbines fired in endurance tests shall be scrapped by the contractor.

F–10e. A complete, concise record of each endurance test shall be kept by the inspector.

F–10f. Malfunctions, broken, or unserviceable parts in excess of those shown in table II shall be cause for rejection. Malfunctions directly caused by component breakage shall be recorded as breakage and not as malfunctions. Broken components permitted in table II shall be immediately replaced upon discovery. Springs which have set sufficiently to cause malfunction shall be considered as broken components.

F–10g. At the completion of each endurance test a bayonet knife, M4, shall be fitted to the endurance gun. The assembly shall be tested by a strong forward lunge, driving the bayonet blade into a fixed block or plank of wood so that there is a noticeable resistance to withdrawal. A strong twist shall be made clockwise and counter-clockwise. Should breakage of any part of the carbine (with particular reference to the front band) result, a retest shall be made by subjecting five more guns from the same lot to this test. Breakage of any component or assembly of the five guns shall be cause for rejection of the lot of guns represented by the endurance test.

F–11. *Retests.*—

F–11a. *Hangfires and misfires.*—If hangfires or misfires occur during any part of the test, the carbines represented shall be checked for firing pin indent and protrusion. In the event that the firing pin indent and protrusion are not within the specified limits, the carbines shall not be accepted until properly corrected.

F–11b. *Defective ammunition.*—Malfunctions in any test traceable to defective ammunition shall not be counted against the carbine being tested.

F–11c. *Individual rejections.*—When any lot of components, spare parts, or carbines subject to one hundred percent inspection reaches a point where two percent of the lot has been rejected, inspection shall be suspended. Those items passed up to that point shall be accepted. The two percent found unsatisfactory shall be returned to the manufacturer for reconditioning. The remainder of the lot shall be returned to the manufacturer for his reinspection and reconditioning or replacement, except that in any firing test if any malfunctions, broken parts, or nonacceptable conditions listed in table I as nonacceptable are encountered, the lot of carbines shall be rejected as if it had occurred in the endurance test and shall be returned to the manufacturer for reconditioning or replacement. Any component, spare part, or carbine rejected individually may be reconditioned and resubmitted for reinspection and retest.

F–11d. *Lot rejection.*—When any one of a representative sample of a lot of components, spare parts, or carbines fails in any test

Source: https://assist.dla.mil -- Downloaded: 2026-1
Check the source to verify that this is the current vers

to meet the prescribed requirements, the lot shall be returned to the manufacturer for conditioning or replacement. Any lot of components, spare parts, or carbines returned to the contractor uninspected by reason of excess rejections or by reason of an unsatisfactory representative sample may be reconditioned and resubmitted. A sample twice the size of the original shall be taken for the retest, except that for the endurance firing test, a retest may be made from the original lot using another gun if requested by the contractor The cost of the carbine fired in the endurance retest and the expense involved shall be borne by the contractor.

F–11e. *Identity of defective samples.*—The inspector shall mark, tag, or otherwise adequately maintain the identity of all rejected samples until destroyed or otherwise disposed of to the satisfaction of the Government.

F–11f. *Rejections.*—Rejections as the result of a retest are final.

F–12. *Final inspection and acceptance.*—Carbines which have passed all tests shall be stamped with the Ordnance Department final acceptance stamp and Army inspector's stamp as prescribed on the drawings. Carbines and spare parts shall be inspected to assure that they are thoroughly clean and free of any contamination such as perspiration from handling, residual soldering or brazing flux, cutting or cooling compounds, buffing or grinding compounds, metallic residues from machine operations, residual heat treatment salts, powder fouling, and general contamination from floors, boxes, or dust. They shall be checked to assure that they are properly treated with the prescribed rust-inhibiting material. A lot of the unit items cannot be finally accepted without being accompanied by the proportional quantity of acceptable spare parts when such spare parts are included in the carbine contract or purchase order.

G. PACKAGING, PACKING, AND MARKING FOR SHIPMENT

G–1. Carbines and spare parts shall be packaged and packed according to applicable Ordnance Packaging Instructions listed on the List of Drawings and Specifications Drawing.

G–2. *Shipping containers.*—In addition to any special marking required by the contract or order, shipments for the Army and the Air Force shall be marked in accordance with the requirements of U. S. Army Specification No. 100–2; for the Navy, in accordance with the requirements of the Navy Shipment Marking Handbook.

H. NOTES

H–1. *Use.*—The carbines are standard items of issue and are used by service forces when authorized by equipment tables.

H–2. This specification replaces Army Ordnance Department Tentative Specification AXS–1489, 15 December 1944, and SXS–186, 9 April 1946.

[JAN–C–691]

Source: https://assist.dla.mil -- Downlo
Check the source to verify that this is the

H–3. Requests, requisitions, schedules, contracts, and orders should specify the following:

(a) Number, date, and revision of all applicable drawings.
(b) Title, number, and date of all applicable specifications.
(c) Whether the subject items are to be packed for domestic or overseas shipment.

H–4. If defective ammunition of any type is encountered in any firing tests, the Commanding Officer, Frankford Arsenal, should be notified and samples submitted for examination and information.

H–5. Copies of this specification and Army Ordnance Department drawings and publications (required for Army purchases) may be obtained from the Chief of Ordnance, Department of the Army, Washington 25, D. C.

H–6. Copies of Joint Army-Navy and National Military Establishment specifications (required for Army purchases) and U. S. Army specifications may be obtained as indicated in the Index of United States Army, Joint Army-Navy and Federal Specifications, and Standards. Copies of this index may be obtained from the Superintendent of Documents, Government Printing Office, Washington 25, D. C. Agencies within the Departments of the Army and the Air Force will obtain copies of Joint Army-Navy, National Military Establishment, United States Army, and Federal specifications through established departmental channels. Both the title and identifying symbol number should be stipulated when requesting copies of specifications.

H–7. Copies of Joint Army-Navy and National Military Establishment specifications (required for Navy purchases), Navy Department specifications, and the Navy Shipment Marking Handbook may be obtained from the Bureau of Supplies and Accounts, Department of the Navy, Washington 25, D. C., except that Naval activities should make application to the Supply Officer in Command, Naval Supply Depot, Norfolk, Virginia. Both the title and identifying symbol number should be stipulated when requesting copies of specifications.

Notice.—When Government drawings, specifications or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

ARMY: O.
NAVY: OMCS.

Source: https://assist.dla.mil -- Downloaded: 2026-1
Check the source to verify that this is the current vers