MIL-K-687E
AMENDMENT 2
22 December 1987
SUPERSEDING
INT. AMENDMENT 1(ME)
29 June 1983

MILITARY SPECIFICATION

KETTLES, HEATING, BITUMEN, TRAILER-MOUNTED "

This interim amendment is approved for use within the US Army Belvoir Research, Development, and Engineering Center, Department of the Army, with MIL-K-687E, dated 6 October 1982.

* 2.1.1, under SPECIFICATIONS, 'FEDERAL, delete O-E-915 in its entirety and substitute:

"A-A-393 - Extinguisher, Fire, Dry Chemical (Hand Portable)."

Under SPECIFICATIONS, MILITARY, delete MIL-E-52929 in its entirety and substitute:

"MIL-P-14105 - Paint, Heat Resisting (for Steel Surfaces).

MIL-C-46l68 - Coating, Aliphatic Polyurethane, Chemical Agent Resistant."

Under STANDARDS, add:

"FEDERAL

FED-STD-595 - Colors."

Under STANDARDS, MILITARY, add:

"MIL-STD-1472 - Human Engineering Design Criteria for Military Systems, Equipment, and Facilities."

* 3.1.1, table I, delete: "Shipping weight (maximum) 2200 pounds".

* After table I, add:

AMSC N/A FSC 3895
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-16T11:15Z
Check the source to verify that this is the current version before use.

"3.1.2 Weight. If the kettle's gross vehicle weight (GVW) in its fullest operational capacity (with a full tank of bitumen material and maximum fuel and lubrication) exceeds 3,000 pounds, it shall be equipped with brakes acting on all wheels as required by Federal Motor Carrier Safety Regulation (FMCSR) No. 393.42 (see 3.6.15)."

PAGE 5

*3.4.2, line 2, delete "O-E-915" and substitute "A-A-393".

PAGE 7

3.6.6, line 2 thru 4, delete second and third sentence;

Line 9, delete: "for not less than 100 level quality and shall be";

Line 10, delete: "having a minimum size of 7.00 by 16 load range C (6 ply rating";

* Line 15, delete; "of the C-4" and add:

"The Tire and Rim Association recommended tire pressure shall be stencilled "TP (specify)" in 1 inch high letters above or near each tire in accordance with MIL -STD-1472."

PAGE 9

* 3.6.14, line 13, delete "drier-mixer" and substitute "kettle".

* 3.9.3, line 8, after "enclosure" add, "without draining on or over other components of the kettle."

PAGE 12

* After 3.6.14.1, add:

3.6.15 Brake system. If required (see 3.1.2), the kettle shall be equipped with an air or air activated brake system. The system shall conform to the DOT Federal Motor Carrier Safety Regulations and, the DOT Federal Motor Vehicle Safety Standards. All brake system components and plumbing shall be located, installed, and protected to prevent damage or malfunction from ground obstruction, debris, and water and to obtain maximum safety, efficiency, and ease of maintenance. The brake system shall include service and emergency gladhands, relay emergency valve, straight air cylinders or chambers, foundation brakes on each wheel, and all other components and plumbing required for a complete matched brake system. The gladhands shall conform to SAE J318. The gladhands shall be colored coded yellow for service and red for emergency. The gladhands shall have a built in filter screen and rubberized dust seal. The dust seal shall not cause interference when the gladhand is coupled to the towing vehicle gladhand. The gladhands shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:15Z
Check the source to verify that this is the current version before use.

installed on the front of the trailer with the service on the curb side and emergency on the road side. In addition, brake line identification tags shall be furnished, When tested as specified in 4.5.2.14, the braking system shall bring the kettle, to a controlled panic stop and shall decelerate from 40 mph at a rate of 10 feet per second.

PAGE 15

3.11.1, line 5, add new sentence: "Within the scope of MIL-STD-209, this end item shall be considered a type II."

3,11.2, line 5, add new sentence: "Within the scope of MIL-STD-209, this end item shall be considered a type II."

* 3.12, add at end paragraph: "The identification plate(s) shall show the model number, NSN, serial number, weight, date of manufacture and date of delivery."

PAGE 16 .

* 3.12.2, line 6, after "as necessary.", add "Information shall be presented in the form of diagrams wherever possible. Operating positions of shift handles shall be illustrated and control movement shall be shown in planes parallel to the movement of actual controls as specified in MIL-STD-1472."

*3.14, delete in its entirety and substitute:

"3.14 Treatment and painting. The portions of the kettle normally Painted shall be cleaned, treated, and painted in accordance with MIL-T-704, type F or G, as applicable, when it will not be affected by elevated operating temperature. Unless otherwise specified (see 6.2), top coat color shall be camouflage green 383 conforming to MIL-C-46168. Parts of the kettle subjected to a temperature of 400 "F or over shall be painted with heat resistant paint conforming to MIL-P-14105, the color shall be in accordance with FED-STD-595, lusterless dark green No. 34079 unless otherwise specified."

* 3.16, line 1, after "provided with a", add "waterproof". Add at end of paragraph: "The toolbox lid shall be provided with a hasp that will accommodate a padlock that has a 3/8-inch diameter shackle."

PAGE 19

* 3.19.6.1, line 1, after "shall be a" delete "2- or".

* 3.19.6.3, line 6, delete "When a two cycle engine is used, the tank shall be marked indicating the gasoline and oil mixture."

PAGE 21

* 4.5.1, add:

"125. Brake system (if provided) not as specified."

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:15Z
Check the source to verify that this is the current version before use.

* After 4.5.2.13, add:

"4.5.2.14 Brake system. Test the kettle's brake (if provided) as specified herein:

a. Tow the trailer mounted kettle over the test course and when the prime mover reaches a speed of not less than 20 mph, make a panic brake stop using both primer mover and trailer brakes. Perform the test four times, allowing not more than 3 minutes between tests.
b. Tow the trailer mounted kettle at not less than 40 mph and apply service brakes to produce a deceleration rate of 10 feet per second, until the prime mover has slowed to 30 mph. Then immediately accelerate at wide-open-throttle again up to not less than 40 mph. Repeat the snubbing cycle for a total of 5 cycles and make a panic stop on the 6th cycle.

"4.5.2.14.1 Failure criteria. Failure to complete this test, inability to function and operate as specified shall constitute failure of this test."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

* 6.3, delete in its entirety and substitute:

"6.3 Lubricants. MIL-STD-838 Lubrication of Military Equipment prescribes the policy for using specification-type products wherever possible and provides specific requirements for potential use of non-standard proprietary products. MIL-STD-838 is implemented by MIL-HDBK-113 Guide for the Selection of Lubricants, Fluids, Perservatives and Speciality Products for Use in Ground Equipment Systems. The contracting officer should note that unless otherwise authorized by the US Army Belvoir Research, Development and Engineering Center (ATTN: STRBE-VF), Fort Belvoir, VA 22060-5606, lubricants, fluids, and greases for gound equipment systems must be restricted to those listed under MIL-HDBK-113, chapter 2.

Custodians:
Army - ME
Air Force - 99

Review activities:
Army - AT
Air Force - 84

Preparing activity:
Army - ME

Project 3895-0284

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:15Z
Check the source to verify that this is the current version before use.