NOT MEASUREMENT SENSITIVE

MIL-P-710F
21 November 1990
MIL-P-710E
30 June 1980

MILITARY SPECIFICATION

PUMPS, DEEP-WELL, PACKAGING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the minimum requirements for methods, materials, and procedure for the preservation, packing, and marking of deep-well pumps, their components, and accessories.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

TT-P-664	- Primer Coating, Alkyd, Corrosion-Inhibiting, Lead and Chromate Free, VOC-Compliant.
UU-T-81	- Tags, Shipping and Stock.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-P-40	- Packaging and Packing of Hand Tools.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC PACK
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:19Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-C-104	- Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-116	- Preservation, Methods of.
MIL-B-121	- Barrier Material, Greaseproof, Waterproofed, Flexible.
MIL-E-10062	- Engines: Preparation for Shipment and Storage of.
MIL-E-16298	- Electric Machines Having Rotating Parts and Associated Repair Parts, Packaging of.
MIL-T-22085	- Tape, Pressure-Sensitive Adhesive, Preservation and Sealing.
MIL-B-22191	- Barrier Material, Transparent, Flexible, Heat Sealable.
MIL-A-46153	- Antifreeze, Ethylene Glycol, Inhibited, Heavy Duty, Single Package.

STANDARDS

FEDERAL

FED-STD-101	- Preservation, Packaging, and Packing Materials: Test Procedures.

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Test Methods.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3953	- Strapping, Flat Steel and Seals.
D 4675	- Selection and Use of Flat Strapping Materials.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia PA 19103.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:19Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, (except for related associated detail specifications, specification sheets or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be as specified herein and in applicable specifications and standards. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification. Materials shall be free of defects (see 4.4).

3.2 Caution. Only type P-14 preservative shall be used on interior surfaces of pumps or pump components if they are to be used for potable water.

3.3 First article pack. Unless otherwise specified (see 6.2), a sample shall be subjected to first article pack inspection (see 6.3) in accordance with 4.3.

3.4 Preservation. Preservation shall be level A or C as specified (see 6.2).

3.4.1 Level A.

3.4.1.1 Disassembly. Disassembly of the pumps shall be only to the extent necessary to safeguard parts vulnerable to damage and loss. The extent of further disassembly shall be confined to the removal of protruding parts that would increase cubage; however, disassembly shall be limited to those parts that can be removed and reinstalled without special tools or skilled personnel. Removed bolts, nuts, pins, screws, and washers requiring a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative and then reinstalled in mating parts to prevent their loss. Keys removed shall be secured in the keyway of the shaft.

3.4.1.2 Matchmarking. Removed parts and parts remaining on the pumps shall be matchmarked when necessary to facilitate reassembly. Matchmarking information shall be on shipping tags conforming to UU-T-81, type A, grade optional and the tags shall be attached to mating parts. Waterproof ink shall be used for marking the information on the tags.

3.4.1.3 Preservatives. Preservatives specified herein shall conform to the applicable specifications listed in and shall be applied in accordance with MIL-P-116.

3.4.1.4 Unprotected surfaces. Unpainted exterior metal surfaces requiring the application of a contact preservative in accordance with MIL-P-116 and not specifically specified herein or in the end item specification shall be coated as follows.

3.4.1.4.1 Unfinished surfaces. Unfinished exterior metal surfaces shall be coated with type P-1 preservative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:19Z
Check the source to verify that this is the current version before use.

3.4.1.4.2 Machined surfaces. Exposed machine surfaces shall be coated with type P-6 or P-11 preservative and wrapped or covered, as applicable, with barrier material conforming to MIL-B-121, type I or II, grade A, class 2 or MIL-B-22191, type II, and the material secured in place with tape conforming to MIL-T-22085, type II.

3.4.1.5 Electric motors. Electric motors shall be preserved in accordance with MIL-E-16298, level A, using the alternate method specified for assembled machines, except the tape used for sealing openings shall conform to MIL-T-22085, type II.

3.4.1.6 Engines. Engines, engine components, and engine accessories shall be preserved in accordance with MIL-E-10062, level A, type II, method I.

3.4.1.6.1 Cooling systems. Engines with liquid cooling systems shall be preserved by the water and antifreeze procedure specified in MIL-E-10062, except the antifreeze shall conform to MIL-A-46153.

3.4.1.7 Flexible couplings. Unpainted metal surfaces of flexible couplings shall be coated with type P-1 preservative.

3.4.1.8 Drive belts and pulleys. Drive belts shall be removed or released from tension. Removed belts shall be preserved in accordance with MIL-P-116, method IC-1 or IC-3 and placed in the tool box or placed with the consolidated items. Unpainted pulley grooves shall be coated with primer conforming to TT-P-664.

3.4.1.9 Drive head assemblies with drip feed lubricators. The drive head oil reservoir shall be drained and the interior surfaces shall be coated with type P-10, type I, grade 10 oil. All other interior metal parts and surfaces requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with the oil specified herein. Openings into the drive head shall be covered and sealed with tape conforming to MIL-T-22085, type II. A shipping tag conforming to UU-T-81, type A shall be attached to the drive assembly indicating: "The drive head reservoir is drained. Refill to the operating level with approved lubricant. Remove tape from openings." Waterproof ink shall be used for marking the information on the tag.

3.4.1.10 Drive head assemblies with gear drive. The gear drive housing shall be drained. The oil well shall be filled to the operating level with type P-10 type I, grade 10 oil. All other metal surfaces within the housing and the shaft assembly shall be coated with the oil specified herein, applied by spraying. A shipping tag conforming to UU-T-81, type A shall be attached to the drive head assembly indicating: "The gear housing is filled to the operating level with grade 10 preservative oil. Unless the assembly is designed to operate on SAE 10 oil, drain and refill to the operating level with the recommended operational lubricants. If the assembly is designed to operate of SAE 10 oil, the preservative may be used until the first required lubricant change." Waterproof ink shall be used for marking the information on the tag.

3.4.1.11 Discharge head. Interior surfaces of the discharge head, except when rubber lined or otherwise treated to resist corrosion, shall be coated with type P-10, type I, grade 10 oil. Excess preservative shall be drained. The discharge

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:19Z
Check the source to verify that this is the current version before use.

outlet opening shall be covered with barrier-material conforming to MIL-B-121, type I, grade A, class 1 and the cover shall be secured in place with tape conforming to MIL-T-22085, type II.

3.4.1.12 Bowl assemblies and strainers. The pump bowls and the impeller assemblies, except porcelain lined bowls and impellers, or when otherwise treated to resist corrosion, shall be coated with type P-3 or type P-9 preservative. Each assembly shall be wrapped with barrier-material conforming to MIL-B-121, type I, grade A, class 2 and the wrap shall be secured in place with tape conforming to MIL-T-22085, type II.

3.4.1.13 Column pipes. The threaded ends and unpainted or untreated exterior surfaces of column pipes requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with type P-1 preservative.

3.4.1.14 Line shafts. Surfaces of line shaft sections requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-6 or P-11 preservative. Coated surfaces of each shaft section shall be spirally wrapped with barrier material conforming to MIL-B-121, type I, grade A, class 2. The wraps shall be secured with tape conforming to MIL-T-22085, type II.

3.4.1.15 Oil-enclosing tubes. Surfaces of oil-enclosing tubes requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated inside and outside with type P-10, type I, grade 10 oil. Each tube shall be wrapped with barrier material conforming to MIL-B-121, type I, grade A, class 2. The wraps shall be secured with tape conforming to MIL-P-22085, type II.

3.4.1.16 Column couplings. Threaded and other unpainted surfaces of column couplings requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative. Threads shall be protected with metal, fiber or plastic, threaded protectors. Metal thread protectors if not painted or otherwise treated to resist corrosion shall be coated with type P-1 preservative.

3.4.1.16.1 Line shaft couplings and oil-enclosing tube couplings. Line shaft couplings and oil-enclosing tube couplings, except rubber lined tube couplings, requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-10, type I, grade 10 oil. Each coupling, including rubber lined couplings shall be wrapped with barrier material conforming to MIL-B-121, type I, grade A, class 2, and the wraps secured in place with tape conforming to MIL-T-22085, type II.

3.4.1.17 Fittings, stabilizers, and valves. Interior surfaces of fittings, stabilizers, and valves requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with type P-10, type I, grade 10 oil. Fittings, stabilizers, and valves removed from the pump shall be individually wrapped with barrier material conforming to MIL-B-121, type I, grade A, class 2. The wraps shall be secured with tape conforming to MIL-T-22085, type II.

3.4.1.18 Gages. Gages, if removed from the pumps, shall be individually placed in boxes conforming to PPP-B-636, W5c or W6c. Cushioning shall be provided to prevent damage to the gages. Box closure and sealing shall be in accordance with method V, of the appendix to the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:19Z
Check the source to verify that this is the current version before use.

3.4.1.19 Magnetic starters. Magnetic starters shall be individually preserved in accordance with MIL-P-116, method IC-2, using the contractors commercial carton or a close fitting box conforming to PPP-B-636, class Domestic, variety and grade as applicable.

3.4.1.20 Submersible cables. Each submersible cable shall be coiled to a minimum safe diameter and the coil shall be secured with four evenly spaced ties of twine or tape.

3.4.1.21 Well seals. Well seals shall be preserved in accordance with MIL-P-116, method IC-2, using the contractors commercial carton or a close fitting box conforming to PPP-B-636, class Domestic, variety and grade as applicable.

3.4.1.22 Fire extinguishers. Unpainted exterior metal surfaces of the fire extinguishers requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with type P-1 preservative. The extinguishers shall be placed in the mounting brackets and secured.

3.4.1.23 Maintenance tools. Maintenance tools shall be preserved in accordance with level A preservation and packing requirements of PPP-P-40.

3.4.1.24 Repair parts. The preservative application criteria and applicable method(s) of preservation contained in MIL-P-116 shall be used to preserve the repair parts, unless detailed requirements are specified by the procuring activity.

3.4.1.25 Technical publications. Technical publications for each pump shall be preserved together in accordance with MIL-P-116, method IC-1 or IC-3.

3.4.1.26 Other components. Components of each pump, such as drive belts, gages, meters, valves, couplings, mechanisms, repair parts, tools, publications, and other components not specifically identified herein, including those removed by disassembly and requiring the protection of an interior container prior to packing shall be consolidated. Tool boxes, when furnished, shall be utilized. Components that will not fit in the toolbox shall be consolidated as follows:

For complete pumps that are to be packed in wood boxes, the components shall be consolidated in boxes conforming to PPP-B-636, W5c, W6c, or V3c, as applicable to the weight of contents. Box closure and sealing shall be in accordance with method V of the appendix to the box specification. For complete pumps that are to be packed in crates, the components shall be consolidated in boxes conforming to PPP-B-601, domestic type, style optional or PPP-B-621, class 1, style optional. Strapping of the boxes shall not be required. The drive heads, discharge heads, drivers, bowl assemblies, column bases, column pipes, oil-enclosing tubes, and line shafts shall not require consolidation.

3.4.2 Level C. Each pump and any components shall be preserved in accordance with the contractor's standard practice in a manner to prevent deterioration and damage during shipment from the contractor to the initial destination. The pumps shall be lubricated for operation service as required in the operator's manual.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:19Z
Check the source to verify that this is the current version before use.

3.5 Packing. Packing shall be level A or C as specified (see 6.2).

3.5.1 Level A.

3.5.1.1 Pump units not exceeding 1000 pounds. Unless otherwise specified herein, complete pump units, components, and accessories, including consolidated items, not exceeding 1000 pounds gross weight, preserved as specified in 3.4, shall be packed together in a box conforming to PPP-B-601, overseas type, style optional or PPP-B-621, class 2, style optional. The contents shall be blocked, braced, anchored or cushioned, as applicable, in accordance with MIL-STD-1186. Strapping shall conform to ASTM D 3953, type 1 or 2, zinc-coated, size as applicable and ASTM D 4675. When specified (see 6.2), bowl assemblies, column pipes, oil-enclosing tubes, and line shafts for each pump shall be packed separately as specified in 3.5.1.3 and 3.5.1.4.

3.5.1.2 Pump units exceeding 1000 pounds. Unless otherwise specified herein, complete pump units, components, accessories, including consolidated items, exceeding 1000 pounds, preserved as specified in 3.4, shall be packed together in a crate conforming to MIL-C-104, type I, class 2, style A. Blocking, bracing, anchoring, and cushioning shall be in accordance with MIL-STD-1186, and in accordance with the appendix to MIL-C-104. Strapping shall conform to ASTM D 3953, type 1 or 2, zinc-coated, size as applicable and ASTM D 4675. When specified (see 6.2), bowl assemblies, column pipes, oil-enclosing tubes, and line shafts for each pump shall be packed separately as specified in 3.5.1.3 and 3.5.1.4.

3.5.1.3 Bowl assemblies, column pipes, oil-enclosing tubes, and line shafts not exceeding 1000 pounds. Bowl assemblies, column pipes, oil-enclosing tubes, and line shafts required for each pump, not exceeding 1000 pounds, preserved as specified in 3.4, shall be packed together in a box conforming to PPP-B-601, overseas type, style optional or PPP-B-621, class 2, style optional. The contents shall be blocked, braced, anchored or cushioned, as applicable, in accordance with MIL-STD-1186. Strapping shall conform to ASTM D 3953, type 1 or 2, zinc-coated, size as applicable and ASTM D 4675. The packed items shall be shipped at the same time as the pump for which intended.

3.5.1.4 Bowl assemblies, column pipes, oil-enclosing tubes, and line shafts exceeding 1000 pounds. Bowl assemblies, column pipes, oil-enclosing tubes, and line shafts required for each pump, exceeding 1000 pounds, preserved as specified in 3.4, shall be packed together in a crate conforming to MIL-C-104, type I, class 2, style A. Blocking, bracing, anchoring, and cushioning shall be in accordance with MIL-STD-1186 and in accordance with the appendix to MIL-C-104. Strapping shall conform to ASTM D 3953, type 1 or 2, zinc-coated, size as applicable and ASTM D 4675. The packed items shall be shipped at the same time as the pump for which intended.

3.5.2 Level C. Each complete pump, components, accessories, and consolidated items, preserved as specified in 3.4, shall be packed for shipment in a manner which will ensure arrival at destination in a satisfactory condition. Preparation for delivery shall comply with applicable carrier rules and regulations.

3.6 Marking. In addition to any special marking specified in the contract or purchase order (see 6.2), marking shall be in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:19Z
Check the source to verify that this is the current version before use.

3.7 Workmanship. Workmanship shall be such as to provide maximum protection to the pumps by application of the requirements specified herein, to prevent corrosion, deterioration, and mechanical or physical damage during handling, shipment, and storage.

3.8 Depreservation guide. A depreservation guide shall be prepared for all levels of packaging and placed in a sealed waterproof envelope marked "Depreservation Guide", and the envelope secured to the pump unit in a conspicuous location. Unless otherwise specified (see 6.2), DA Form 2258, "Depreservation Guide for Vehicles and Equipment" shall be used (see 6.4).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of section 3. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Material inspection. The contractor is responsible for insuring that materials are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article pack inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article pack inspection.

4.3.1 Examination. The first article pack shall be examined as specified in 4.4.4. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article pack of boxed and crated equipment for level A or C shall be tested in accordance with 4.3.2.1 and 4.3.2.2, as applicable. Failure of the applicable test shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:19Z
Check the source to verify that this is the current version before use.

4.3.2.1 Boxed equipment. Boxed equipment not exceeding 200 pounds shall be subjected to the free-fall drop test in accordance with FED-STD-101, test method 5007, procedure E. Boxed equipment exceeding 200 pounds shall be subjected to the pendulum impact test in accordance with FED-STD-101, test method 5012, except the vertical height of drop shall be 18 inches.

4.3.2.2 Crated equipment. Crated equipment shall be subjected to the guided-impact test (railroad car) specified in MIL-STD-1186, appendix A. The test car shall strike a string of five empty cars, with draft gear extended and the brakes set. The speed shall be not less than 8 miles per hour and not more than 9 miles per hour. Packs not exceeding 9.5 feet in length shall have one impact applied to each end and each side of the pack. Packs exceeding 9.5 feet in length shall have one impact applied to each end of the pack.

4.3.2.3 Basis for failure. Shifting of contents, visible damage to the contents, or loosening or breaking of anchoring, blocking, or bracing within the pack shall constitute failure of the applicable test. In addition, the pump shall be subjected to the operational test(s) specified in the end item specification; any malfunction attributable to the first article pack test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Inspection stages. Inspection shall be in two stages as follows:

a. The first stage shall include inspection of materials, methods, containers, and markings prior to placing the items of equipment in shipping containers.
b. The second stage shall include inspection of materials and markings of the completed pack as prepared for shipment.

4.4.2 Unit of product. For the purpose of inspection, a unit of product for the first stage of inspection shall be a complete preserved pump with all accessories and consolidated containers, prior to placing in the shipping container. For the second stage of inspection, a unit of product shall be a completed pack prepared for shipment.

4.4.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105. Samples shall be selected in accordance with MIL-STD-105, tables I and IIa.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the defects marked "X" for the applicable level in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:19Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects.

No.	Defect	Level	
		A	C
101.	Materials, methods, and containers not as specified (see 3.1, 3.2, 3.4, and 3.5). Each incorrect material, method, or container shall constitute one defect.	X	-
102.	Disassembly not as specified (see 3.4.1.1).	X	-
103.	Removed bolts, nuts, pins, washers, and screws not coated with preservative as specified (see 3.4.1.1).	X	-
104.	Removed bolts, nuts, pins, screws, and washers not reinstalled as specified (see 3.4.1.1).	X	-
105.	Matchmarking not as specified (see 3.4.1.2).	X	-
106.	Printing on tags used for matchmarking not in waterproof ink as specified (see 3.4.1.2).	X	-
107.	Unprotected metal surfaces not coated with preservatives as specified (see 3.4.1.4.1 and 3.4.1.4.2).	X	-
108.	Preserved machined surfaces not wrapped or covered with barrier material and the wraps or covers not secured as specified (see 3.4.1.4.2).	X	-
109.	Electric motors not preserved in accordance with referenced documents as specified (see 3.4.1.5).	X	-
110.	Engine and engine accessories not preserved in accordance with the referenced document or as specified (see 3.4.1.6 and 3.4.1.6.1).	X	-
111.	Flexible couplings not preserved as specified (see 3.4.1.7).	X	-
112.	Drive belts not removed and preserved or not released from tension as specified (see 3.4.1.8).	X	-
113.	Unpainted pulley grooves not coated with primer as specified (see 3.4.1.8).	X	-
114.	Drive head assemblies with drip feed lubricators not preserved and not tagged as specified (see 3.4.1.9).	X	-
115.	Excess preservative not drained for drip feed lubricators and the openings not covered with tape as specified (see 3.4.1.9).	X	-
116.	Drive head assemblies with gear drives not preserved and tagged as specified (see 3.4.1.10).	X	-
117.	Discharge heads not preserved as specified and the outlet opening not covered as specified (see 3.4.1.11).	X	-
118.	Bowl assemblies and strainers not preserved as specified and not wrapped as specified (see 3.4.1.12).	X	-
119.	Column pipes not coated with type P-1 preservative as specified and the threads not protected as specified (see 3.4.1.13).	X	-
120.	Line shafts not coated with preservative as specified and not wrapped as specified (see 3.4.1.14).	X	-
121.	Oil-enclosure tubes not coated with preservative lubricating oil as specified and not wrapped as specified (see 3.4.1.15).	X	-
122.	Couplings not coated with the applicable type preservative as specified and the threads not protected as specified (see 3.4.1.16 and 3.4.1.16.1).	X	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:19Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects. (continued)

No.	Defect	Level	
		A	C
123.	Fittings, stabilizers, and valves not coated with preservative lubricating oil when required as specified and not wrapped when coated as specified (see 3.4.1.17).	X	-
124.	Gages, if removed, not preserved as specified (see 3.4.1.18).	X	-
125.	Magnetic starters not preserved as specified (see 3.4.1.19).	X	-
126.	Submersible cables not coiled and secured as specified (see 3.4.1.20).	X	-
127.	Well seals not preserved as specified (see 3.4.1.21).	X	-
128.	Fire extinguishers not preserved and secured in the mounting brackets as specified (see 3.4.1.22).	X	-
129.	Maintenance tools not preserved in accordance with the referenced document as specified (see 3.4.1.23).	X	-
130.	Repair parts not preserved as specified (see 3.4.1.24).	X	-
131.	Technical publications not preserved as specified (see 3.4.1.25).	X	-
132.	Consolidation not as specified (see 3.4.1.26).	X	-
133.	Pumps not preserved and lubricated as specified for level C (see 3.4.2).	-	X
134.	Packing not as specified (see 3.5.1 and 3.5.2).	X	X
135.	Marking illegible, incomplete, incorrect or missing (see 3.6).	X	X
136.	Depreservation guide not prepared as specified and not attached to pump as specified (see 3.8).	X	X
137.	Workmanship not as specified (see 3.7).	X	X

5. PACKAGING

(This section not applicable to this specification.)

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. This specification is intended to be used for reference in section 5 of equipment specifications, for direct reference in contracts or purchase orders, and as a guide in the preparation of packaging data sheets.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of the specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).
c. Time frame required for submission of first article pack (see 3.3).
d. Level of preservation and packing required (see 3.4 and 3.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:19Z
Check the source to verify that this is the current version before use.

e. When separate packing of bowl assemblies, column pipes, oil-enclosing tubes, and line shafts is required (see 3.5.1.1 and 3.5.1.2).
f. Any special marking (see 3.6).
g. When other than DA Form 2258 is to be used (see 3.8).

6.3 First article pack. The first article pack may be accomplished utilizing either the first article model or a production model. If the first article model is utilized, any preservation and packing shall be removed by the contractor at no expense to the Government, when requested by the Government, to facilitate comparison between the first article model and the production model. Any changes or deviations of production packs from the approved first article pack will be subject to the approval of the contracting officer. Approval of the first article pack will not relieve the contractor of his obligation to preserve, pack, and mark the pumps and accessories in accordance with this specification.

6.4 DA Form 2258. The contracting officer should arrange to furnish the necessary copies of DA Form 2258 when requested by the contractor.

6.5 Subject term (key word) listing.

Marking
Packing
Preservation

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - ME
Navy - YD

Review activity:
Army - SM

Preparing activity:
Army - ME

Project 4320-0313

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-P-710F	901121

3. DOCUMENT TITLE

Pumps, Deep-Well, Packaging Of

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)
	e. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
	(703) 664-5717	354-5717
c. ADDRESS (Include Zip Code) US Army Belvoir RDE Center ATTN: STRBE-TSE Ft. Belvoir, VA 22060-5606	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:19Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:19Z
Check the source to verify that this is the current version before use.