
INCH-POUND
MS27736F
14 February 2024
SUPERSEDING
MS27736E
w/AMENDMENT 1
23 January 2014

DETAIL SPECIFICATION SHEET

SWITCH, TOGGLE, FOUR POLE, ENVIRONMENTALLY SEALED, SOLDER TERMINAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the switch described herein shall consist of this specification and the latest issue of MIL-DTL-3950.



NOTES:
1. Dimensions are inches.
2. Unless otherwise specified, tolerance is ± .020 for two place decimals and ± .005 three place decimals.
3. For hardware and terminal screw detail specifications, see appendix of MIL-DTL-3950.
4. In event of a conflict between the text of this standard and the reference cited herein, the text of this standard shall take precedence.

FIGURE1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:49Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

All switches on this standard are designed so that the movement of the switch mechanism is opposite to that of the toggle lever.

Maximum weight is 0.20 pound.

Electrical rating: See table I.

TABLE I Detail Requirements.

	Circuit with Toggle Lever In			Current capacity (amperes) 28 volts DC			Current capacity(amperes) 115 volts, 60 and 400 Hertz AC		
MS part No.	Keying side	Center	Opposite keying side	Lamp-Load circuit	Resistive circuit	Inductive circuit	Lamp-Load circuit	Resistive circuit	Inductive circuit
MS27736-1	1-2 4-5 7-8 On 10-11	2-3 4-5 7-8 On11-12	2-3 5-6 8-9 On 11-12	5	20	12	4	15	15
MS27736-2	1-2 Mom. 4-5 7-8 On 10-11	2-3 4-5 7-8 On11-12	2-3 5-6 8-9 On 11-12	4	18	10	2	11	8
MS27736-3	1-2 Mom. 4-5 7-8 On 10-11	2-3 4-5 7-8 On11-12	2-3 Mom.5-6 8-9 On 11-12						
MS27736-21	1-2 4-5 7-8 On 10-11	Off	2-3 8-9 5-6 On 11-12	5	20	12	4	15	15
MS27736-22	Off	None	2-3 8-9 5-6 On 11-12						
MS27736-23	1-2 7-8 4-5 On 10-11	None	2-3 8-9 5-6 On 11-12						
MS27736-24	None	Off	2-3 8-9 5-6 On 11-12						
MS27736-25	None	Mom. Off	2-3 8-9 5-6 On 11-12	4	18	10	2	11	8
MS27736-26	1-2 Mom. 7-8 4-5 On 10-11	None	2-3 8-9 5-6 On 11-12						
MS27736-27	1-2 Mom. 7-8 4-5 On 10-11	Off	2-3 Mom. 8-9 5-6 On 11-12						
MS27736-28	1-2 Mom. 7-8 4-5 On 10-11	Off	None						
MS27736-29	Mom. Off	None	2-3 8-9 5-6 On 11-12						
MS27736-30	1-2 Mom. 7-8 4-5 On 10-11	None	Off						
MS27736-31	1-2 Mom. 7-8 4-5 On 10-11	Off	2-3 8-9 5-6 On 11-12						
MS27736-32	None	1-2 7-8 4-5 On10-11	2-3 Mom. 8-9 5-6 On 11-12						
MS27736-33	None	1-2 7-8 4-5 On10-11	2-3 8-9 5-6 On 11-12	5	20	12	4	15	15

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:49Z
Check the source to verify that this is the current version before use.

Referenced documents:
MIL-DTL-3950

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Army – CR
Navy – AS
Air Force – 85
DLA – CC

Preparing activity
DLA – CC

(Project 5930-2024-005)

Review activities
Army – AR, AV, MI
Navy – EC, MC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:49Z
Check the source to verify that this is the current version before use.