8 May 1975
SUPERSEDING
MIL-B-1309D
2 February 1974
(See Section 6)

MILITARY SPECIFICATION

BAYONET-KNIVES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 Scope. This specification covers the M4, M5A1, M6, M7 and the M1917 bayonet-knives designed for use as a hand weapon, for general purpose use in the field, or as a bayonet when attached to the muzzle end of a weapon (see 6.1).

* 2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-W-13855	-	Weapons, Small Arms and Aircraft Armament, Subsystems, General Specification For.
MIL-P-14232	-	Parts, Equipment and Tools For Army Materiel, Packaging and Packing of.
MIL-I-45607	-	Inspection Equipment, Acquisition, Maintenance and Disposition of.

STANDARDS

Military

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109	-	Quality Assurance Terms and Definitions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:08Z
Check the source to verify that this is the current version before use.

DRAWINGS

Rock Island Arsenal		
D7160944	-	Knife, Bayonet, M4.
D7267810	-	Knife, Bayonet, M5A1.
D7267616	-	Knife, Bayonet, M6.
D11010077	-	Knife, Bayonet, M7.
D11686400	-	Knife, Bayonet, M1917.
IEL7314828	-	Index of Inspection Equipment List for the Bayonet-Knife, M4.
IEL7314358	-	Index of Inspection Equipment List for the Bayonet-Knife, M5A1.
IEL7274611	-	Index of Inspection Equipment List for the Bayonet-Knife, M6.
IEL7274697	-	Index of Inspection Equipment List for the Bayonet-Knife, M7.
IEL11686400	-	Index of Inspection Equipment List for the Bayonet-Knife, M1917.

(Acceptance inspection drawings referenced in this specification form a part of above IEL.s.)

PUBLICATIONS

Rock Island Arsenal		
P7160944	-	Packaging Data Sheet for Bayonet-Knife M4.
P7267810	-	Packaging Data Sheet for Bayonet-Knife, M5A1.
P7267616	-	Packaging Data Sheet for Bayonet-Knife, M6.
P11010077	-	Packaging Data Sheet for Bayonet-Knife, M7.
P11686400	-	Packaging Data Sheet for Bayonet-Knife, M1917.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

* 3.1 First article. Requirements for submission of first article shall be specified in the contract (see 6.2). Unless otherwise specified (see 6.2), the first article shall include the pilot pack (see 5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:08Z
Check the source to verify that this is the current version before use.

* 3.2 Materials, construction and design. Bayonet-knives shall conform to the materials, construction and design specified herein, on Drawing D7160944, D7267810, D7267616, D11010077 and D11686400 as applicable, and in MIL-W-13855.

* 3.2.1 Handgrips. The handgrips shall be securely attached to the blade handle by screws so that there is no relative movement between the blade handle and the handgrips.

3.2.2 Latching mechanism.

* 3.2.2.1 Bayonet-knife, M5A1 and M6. The latching mechanism shall function without binding throughout its full range of travel. When fully depressed, the latching hooks shall not protrude above the track surfaces. When fully released, the latching mechanism shall return to its fully extended position.

* 3.2.2.2 Bayonet-knife, M1917. The catch and catch spring housing shall be capable of sliding through its full range of travel without binding. When fully released the catch and catch spring housing shall return under spring action to its fully extended position. The spring pin shall not protrude above the outside of the housing. When fully depressed the catch spring housing shall not protrude above the surface of the pommel.

* 3.2.2.3 Bayonet-knife, M4 and M7. Right and left hand bayonet releases shall rotate about their respective pins throughout the full range of travel without binding. When fully depressed, the catch hooks shall not protrude above the plate "T" slot surfaces. When fully released, the catches shall return to their fully extended position under spring action.

* 3.3 Performance.

* 3.3.1 Assembleability. Bayonet-knives shall be capable of being assembled to the applicable weapon without manually depressing the latching lever; shall be securely retained after assembly, and shall be readily detached when the latching lever is manually depressed. Testing shall be as specified in 4.5.3.2.

* 3.3.2 Resiliency. Bayonet-knives shall be capable of withstanding the following without fracture of the blade or permanent deformation of the blade of more than 3/16 inch. One and one-half inches of the pointed end of the blade shall be rigidly held. The grip end of the bayonet shall be slowly deflected through an arc of 1 1/4 inches to the right and 1 1/4 inches to the left of the vertical center of the blade. On each bend, the bayonet shall be held at the extreme deflection for approximately one second and then slowly released. Testing shall be as specified in 4.5.3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:08Z
Check the source to verify that this is the current version before use.

* 3.3.3 Impact. Bayonet-knives shall be capable of withstanding the following without fracture, permanent deformation, or loosening of any parts. The bayonet-knives shall be held with the blade point in an upward position. A weight, with a block of soft untreated maple wood attached, shall be dropped on the bayonet-knife point from a height of 12 to 18 inches. The surface of the wood block shall be directed to strike the bayonet point squarely, and the wood block shall be positioned so that the blade penetrates across the wood grain. The weight and height shall be such that 28 foot-pounds of energy is applied on impact to the M4, M7, and M1917 Bayonet-knives, and 48 foot-pounds to the M5A1 and M6 Bayonet-knives. Testing shall be as specified in 4.5.3.4.

* 3.3.4 Twist. Bayonet-knives shall be capable of withstanding the following without fracture, permanent deformation, or loosening of any parts. The bayonet-knives shall be clamped in a contractor designed Government approved fixture simulating the applicable weapon. The blade shall be twisted at a point 1.500 $\pm$ 0.1250 inches from the guard. Bending of the blade along the longitudinal axis shall be minimized. The M4, M7 and M1917 Bayonet-knives shall be given a twist of 25 foot-pounds torque, and the M5A1 and M6 Bayonet-knives shall be given a twist of 38 foot-pounds torque. The torque shall be applied in both clockwise and counter clockwise directions. Testing shall be as specified in 4.5.3.4.

* 3.3.5 Withdrawal. Bayonet-knives shall be capable of withstanding a gradually applied longitudinal tensile load of 250 pounds without fracture, permanent deformation, loosening of any parts, or detaching from a contractor designed, Government approved, fixture simulating the applicable weapon. Testing shall be as specified in 4.5.3.4.

* 3.3.6 Sharpness. Bayonet-knives shall be capable of severing a nylon twine in accordance with drawing A7274020 in not more than five strokes using a sharpness tester in accordance with Drawing A7274016. Testing shall be as specified in 4.5.3.4.

* 3.4 Interchangeability. Unless otherwise specified on the drawings, all parts shall be interchangeable between similar items. (In normal assembly operations there shall be no objections to preferential assembly of parts provided that all parts are dimensionally acceptable.) Testing shall be as specified in 4.5.3.5.

* 3.5 Marking. Bayonet-knives shall be clearly marked in accordance with MIL-W-13855.

* 3.6 Workmanship. Workmanship shall be in accordance with MIL-W-13855.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:08Z
Check the source to verify that this is the current version before use.

otherwise specified, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Quality assurance terms and definitions. Quality assurance terms and definitions used herein are in accordance with MIL-STD-109.

* 4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

* 4.4 First article inspection. The first article (initial production unit(s)) shall be submitted for inspection in accordance with the contract (see 6.2). The first article shall be representative of the production processes to be used during quantity production. The first article shall be subjected to the quality conformance inspection specified herein and such other inspections as necessary to determine that all requirements of the contract have been met.

4.5 Quality conformance inspection.

* 4.5.1 Inspection lot. The formation, size, and presentation of inspection lots of bayonet-knives, and parts, shall be in accordance with MIL-STD-105 and MIL-W-13855. Bayonet-knives shall be assembled from lots of component parts that have met all inspection requirements specified herein.

4.5.2 Examination.

* 4.5.2.1 Component parts and concurrent repair parts. Examination of parts shall be performed as specified in the contract (see 6.2). The contractor's examination of parts shall be accomplished prior to their assembly into the end item.

4.5.2.2 Bayonet-knives. Samples of bayonet-knives shall be taken from each inspection lot in accordance with MIL-STD-105 using inspection level I, and examined as specified in Table I. Bayonet-knives failing to meet the requirements shall be cause for rejection of the represented lot:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:08Z
Check the source to verify that this is the current version before use.

TABLE I

Characteristic	Requirement	AQL	Inspection Method
Handgrips	3.2.1	2.5	Visual, Manual
Latching mechanism	3.2.2	2.5	Visual, Manual
Marking	3.5	4.0	Visual
Workmanship	3.6	4.0	Visual

4.5.3 Testing.

* 4.5.3.1 Failure data. Unless otherwise specified herein, all tests shall be conducted on a complete bayonet-knife. If test requirements cited herein are not met, acceptance of the bayonet-knife shall be deferred and the contractor shall accomplish as applicable, the following actions:

a. Conduct a failure analysis study performing a dimensional physical and visual examination of the components which are suspected to be the cause of failure or malfunction.
b. Evaluate and correct the applicable production processes and procedures to prevent recurrence of the same defect(s) in future production.
c. Examine bayonet-knives, partially assembled bayonet-knives and components (including components and subassemblies at in-process or final assembly) to insure that material containing the same defect is purged from the inventory and not presented to the Government for acceptance.
d. Submit the results of the failure analysis and the corrective actions taken to the Government for review and approval prior to submitting a reconditioned lot or reconditioned bayonet-knife for retest.

* 4.5.3.2 Assembleability testing. Samples of bayonet-knives shall be taken from each inspection lot in accordance with MIL-STD-105 and tested for assembleability (see 3.3.2) using the test method specified in 4.6.1. Acceptance shall be based on an AQL of 0.65 percent defective.

* 4.5.3.3 Resiliency testing. Five bayonet-knives assembled with blades from each day's heat treat production shall be tested for resiliency (see 3.3.2) using the test method specified in 4.6.2. If batch type furnaces are used, samples of blades shall be taken so that all heat treat batches are represented. Any bayonet-knife failing to meet the requirements shall cause rejection of the represented blade production. At the discretion of the Government representative the test samples may be decreased to two assembled bayonet-knife blades from each day's heat treat production when a record of consistently satisfactory results has been established. Failure of any bayonet-knife blade on this reduced sampling shall be cause for rejection of the represented blade production and shall be cause for return to the sample of five bayonet-knives from each day's heat treat production of blades until it is again proven that production is satisfactory.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:08Z
Check the source to verify that this is the current version before use.

* 4.5.3.4 Impact, twist, withdrawal, and sharpness testing. Ten bayonet-knives from each day's production shall be tested for impact (see 3.3.3), twist (see 3.3.4), withdrawal (see 3.3.5), and sharpness (see 3.3.6), using the test methods specified in 4.6.3, 4.6.4, 4.6.5 and 4.6.6 respectively. Failure of any bayonet to meet the requirements shall be cause for rejection of the represented lot.

* 4.5.3.5 Interchangeability testing.

* 4.5.3.5.1 Bayonet-knives. Ten bayonet-knives from each inspection lot shall be tested for interchangeability (see 3.4) using the test method specified in 4.6.7. All bayonet-knives assembled from interchanged parts shall be tested for assembleability requirements using the test method specified in 4.6.1. Hand refinement of parts will be allowed on not more than two bayonet-knives during interchange of parts provided that no part is altered beyond drawing requirements. Failure of bayonet-knives to meet the requirements of the interchangeability test or failure of any bayonet-knife to meet the requirements of the assembleability test shall be cause for retest or rejection of the represented lot. At the discretion of the Government representative, an interchangeability retest may be allowed without reconditioning the lot of bayonet-knives. Failure in the retest shall cause rejection of the represented lot subject to reconditioning and further test as a reconditioned lot. A sample of 20 bayonet-knives from each retest or reconditioned lot shall be tested using the same procedure described above, except that hand refinement of parts will be allowed on not more than four bayonet-knives.

* 4.5.3.5.2 Concurrent repair parts interchangeability testing. At least two parts from each inspection lot of concurrent repair parts shall be tested for interchangeability using the test method specified in 4.6.7. Failure shall be cause for rejection of the represented lot.

* 4.5.3.6 Component parts and concurrent repair parts testing. Raw material testing, part testing, and certification of concurrent repair parts shall be performed in accordance with the criteria specified in the contract, (see 6.2). This will include chemical analysis and physical tests of materials, and tests of protective finish, heat treatment, bonding, and functioning of parts as applicable. Unless otherwise specified, the contractor shall be responsible for testing necessary to accomplish certification. For each inspection lot of bayonets, the contractor shall provide the Government representative with certified statement of compliance with applicable drawings and specifications of the phosphate coating. The contractor shall accomplish these tests prior to assembly of parts into the end item.

* 4.5.4 Inspection equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:08Z
Check the source to verify that this is the current version before use.

* 4.5.4.1 Acquisition, calibration, maintenance and disposition. Unless otherwise specified (see 6.2), responsibility for acquisition, calibration, maintenance and disposition of inspection and test equipment prescribed on the applicable List of Inspection Equipment (IEL) and for all other inspection equipment required by applicable specifications, shall be in accordance with MIL-I-45607.

* 4.5.4.2 Accuracy of standard measuring equipment. When commercial and modified commercial inspection and test equipment is used, it must be capable of repetitive measurements to an accuracy of 10 percent of the total tolerance of the characteristic being inspected.

* 4.5.5 Packaging examination and testing. Unless otherwise specified (see 6.2), the packaging and marking examination and testing shall be in accordance with MIL-P-14232.

4.6 Test methods.

* 4.6.1 Assembleability test. Bayonet-knives (see 4.5.3.2) shall be tested using the applicable functional fixture (see 4.5.4). Assemble the bayonet to the fixture without manually operating the locking device or releases and check for locking action. Depress the locking device or releases and disassemble the bayonet from the fixture.

* 4.6.2 Resiliency test. Bayonet-knives (see 4.5.3.3) shall be tested using a contractor designed, Government approved fixture. The blade shall be clamped and deflected as specified in 3.3.2. Blades having a set of 3/16 inch or less shall be straightened before being returned to the represented lot.

* 4.6.3 Impact test. Bayonet-knives (see 4.5.3.4) shall be tested using a contractor designed, Government approved fixture. The blade shall be positioned and struck with a wood block as specified in 3.3.3.

* 4.6.4 Twist test. Bayonet-knives (see 4.5.3.4) shall be tested using a contractor designed Government approved fixture. The blade shall be clamped and twisting applied as specified in 3.3.4.

* 4.6.5 Withdrawal test. Bayonet-knives (see 4.5.3.4) shall be tested using a contractor designed, Government approved testing device and fixture. The bayonet shall be clamped and tensile load tested as specified in 3.3.5.

* 4.6.6 Sharpness test. Bayonet-knives (see 4.5.3.4) shall be tested using twine and tester specified in 3.3.6 set-up and operated in accordance with Drawing A7274019. The number of strokes required to severe the twine shall be recorded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:08Z
Check the source to verify that this is the current version before use.

* 4.6.7 Interchangeability test. Bayonet-knives (see 4.5.3.5) shall be tested by disassembling and then reassembling parts using the parts and prearranged system in accordance with the criteria specified in the contract (see 6.2).

5. PREPARATION FOR DELIVERY

* 5.1 Pilot pack. The pilot pack shall consist of a complete bayonet-knife packaged in accordance with the applicable Packaging Data Sheet (see 6.2) for the level of protection specified in the contract (see 6.2), packed level C and forwarded in accordance with 3.1.

* 5.2 Preservation, packaging, packing and marking. Bayonet-knives shall be preserved, packaged, packed and marked in accordance with the applicable Packaging Data Sheets (see 6.2) for the level of protection specified in the contract.

* 5.3 Repair parts. Repair parts shall be preserved, packaged, packed and marked in accordance with the applicable Packaging Data Sheet, or other requirements and for the level of protection specified in the contract (see 6.2).

6. NOTES

* 6.1 Intended use. This specification is intended to cover, but not be limited to, procurement of the following bayonet-knives:

Bayonet-knife	Application
M4	- Carbine, Cal. .30, M1, M1A1, and M2
M5A1	- Rifle, Cal. .30, M1, M1C, and M1D
M6	- Rifle, 7.62MM, M14
M7	- Rifle, 5.56MM, M16 and M16A1
M1917	- Shotgun, 12 Ga., Riot Type

* 6.2 Ordering data. Procurement documents should specify:

a. Title, number, and date of this specification.
b. Lists of drawings and specifications pertinent to the bayonet-knife on order, showing the applicable revision dates (see 3.2 and 6.1).
c. Requirements for submission of first article and pilot pack (see 3.1, 4.4, and 5.1).
d. Examination and testing criteria for component parts and concurrent repair parts (see 4.5.2.1 and 4.5.3.6).
e. List of acceptance inspection equipment to be furnished the contractor and responsibilities for acquisition, calibration, maintenance, and disposition of acceptance inspection equipment, if different (see 4.5.4.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:08Z
Check the source to verify that this is the current version before use.

f. Packaging, examination and testing, if different (see 4.5.5).
g. Interchangeability test system (see 4.6.7).
h. Applicable Packaging Data Sheet and applicable levels of packaging and packing (see 5.1 and 5.2).
i. Packaging instructions for repair parts (see 5.3).

* 6.3 Contract data requirements. When warranted, requirements for reports of the results of examination and testing (e.g. assembleability, resiliency, impact, twist, withdrawal, sharpness, component parts, packaging, etc.) shall be specified on a DD Form 1423 included in the contract.

* 6.4 Unless otherwise specified (see 6.2) the contract should specify the application of MIL-I-45607 on the Management Control System Summary List, DD Form 1660.

* 6.5 When warranted, the contract should specify the application of MIL-I-45208 on the Management Control System Summary List, DD Form 1660.

* 6.6 Supersession data. This specification supersedes, and includes the requirements of:

MIL-B-1309D, Bayonet-Knives M5A1, M6, and M7 dated 2 February 1970
SAPD-303, Bayonet-Knife, M1917 dated 14 January 1966
SAPD-310, Bayonet-Knife, M4 dated 8 March 1966

* 6.7 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This is done as a convenience only and the Government assumes no liability whatsoever for inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue (see 6.6).

Custodian:
Army - WC

User Activity:
Navy - MC

Preparing Activity:
Army - WC

Project number:
1005-0532

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:08Z
Check the source to verify that this is the current version before use.