MIL-C-1314B(MU)
27 July 1973
SUPERSEDING
MIL-C-1314A
30 April 1964

MILITARY SPECIFICATION

CARTRIDGE, CALIBER .45, TRACER, M26

1. SCOPE

1.1 This specification covers Cartridge, Caliber .45, Tracer, M26, intended for use in Caliber .45 Weapons.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-I-45607	- Inspection Equipment, Acquisition, Maintenance and Disposition of

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-636	- Visual Inspection Standards for Small Arms Ammunition Through Caliber .50
MIL-STD-644	- Visual Inspection Standards and Inspection Procedures for Inspection of Packaging, Packing and Marking of Small Arms Ammunition
MIL-STD-1168	- Lot Numbering of Ammunition

DRAWINGS

Munitions Command

C10534359	- Cartridge, Caliber .45 Tracer, M26
C7636733	- Cartridge, Caliber .45 Tracer, M26 (Steel Case)
C7643674	- Classification of Cartridge Case Defects
D7553728	- Packing and Marking, Cartridges, Caliber .45, Cartons; Box, Ammunition, M2A1; Box, Wirebound

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

2.1 (Cont'd)

PUBLICATIONS

Munitions Command
AMCR 715-505, Vol. 5 - Ammunitions Ballistic Acceptance Test Methods, Volume 5, Test Procedures for Caliber .45 Cartridges

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained form the procuring activity or as directed by the contracting officer.)

2.2 Other Publications
ASTM Standards - American Society for Testing and Materials

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Phila., Pa. 19103.)

3. REQUIREMENTS

3.1 General. - The cartridge shall comply with Drawing C10534359 or C7636733 as applicable and as specified herein (See 6.12).

3.2 Bullet extraction. - The force required to extract the bullet from the cartridge case shall be not less than 40 pounds.

3.3 Residual stress. - (Brass case cartridges) The cartridge case shall not split when subjected to a 1% mercurous nitrate solution for 15 minutes.

3.4 Airtightness of base closure seal. - The bullet shall not release more than one bubble of air under application of a pressure differential of two pounds per square inch (psi) for 5 seconds.

3.5 Waterproof. - The cartridge shall not release more than one bubble of air when subjected to a pressure differential of 5 psi for 15 seconds.

3.6 Salt spray. - (Steel case cartridges) No steel case shall show any corrosion products after the cartridge has been subjected to a 5% salt spray for five hours.

3.7 Accuracy. - The average of the diagonals (D) of all targets of the sample cartridges, fired at 50 yards, shall not exceed 18.75 inches.

3.8 Trace. - The bullet of the cartridge shall exhibit a visible trace from a point not greater than 15 yards from the muzzle of the weapon to a point not less than 150 yards from the muzzle.

3.9 Velocity. - The average velocity of the sample cartridges, conditioned at $70^{\circ} \pm 2^{\circ}$ Fahrenheit (F), shall be 885 feet per second (ft/sec) plus or minus 25 ft/sec, at 25.5 feet from the muzzle of the weapon. The standard deviation of the velocities shall not exceed 27 ft/sec.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

3.10 Chamber pressure. - The average chamber pressure of the sample cartridges, conditioned at 70° ± 2° F, shall not exceed 19,000 pounds per square inch (psi).

3.11 Function and casualty. - The cartridge shall function without casualty.

3.12 Workmanship. - The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.12.1 Metal defects. - The cartridge shall be free of wrinkles, deep draw scratches, scaly metal, dents and other defects.

3.12.2 Foreign matter. - The cartridge shall be free of corrosion, stains, discolorations, dirt, oil, and smears of lacquer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions. - Reference shall be made to Standard MIL-STD-109 for definition of quality assurance terms.

4.2 First article sample.

4.2.1 Initial production sample. - At the beginning of regular production, a sample shall be submitted in accordance with contractual requirements and shall consist of 1700 cartridges. The sample shall be manufactured in the same manner, using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and test. - After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Initial production sample failure. - Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval. Determination as to acceptability of any initial production sample shall be based upon results of initial tests only, and no second tests shall be permitted on that initial production sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product. - The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Lot identification. - Each lot of ammunition shall be identified as to type, caliber and model, as well as with a lot number in accordance with MIL-STD-1168. Each lot shall be further identified by a Federal Stock Number assigned by the procuring activity.

4.3.2 Examination. - One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a class basis in accordance with the classification of defects, Table I, using applicable sampling plans and acceptance criteria of MIL-STD-105. The acceptable quality level (AQL) for the major class shall be 0.25 percent and the AQL for the minor class shall be 1.50 percent. All non-conforming cartridges shall be rejected.

4.3.2.1 Classification of defects. - The classification of defects shall be as specified in Table I.

Table I

No.	Defect and Method of Inspection Visual 1/	Critical	Major	Minor	Major or Minor
	Cartridge				
1	Discolored, dirty, oily, smeared			X	
2	Corroded or stained, if etched		X		
	Case				
4	Round head		X		
5	Dent				X
6	Split case				
	in K, L, or M location	X			
	in I, S, or J location		X		
7	Perforated case	X			
8	Draw scratch				X
9	Scratch			X	
10	Beveled underside of head		X		
11	Scaly metal				X
12	No chamfer or head (rim)				X
13	Wrinkle			X	
14	Bulge			X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

Table I (Cont'd)

No.	Defect and Method of Inspection	Critical	Major	Minor	Major or Minor
	Visual 1/				
15	Illegible or missing head stamp			X	
16	Defective head			X	
17	Defective mouth			X	
17a	Defective protective finish (Steel Case)			X	
	Bullet				
18	Dent			X	
19	Scratch			X	
20	Split bullet jacket		X		
21	Loose bullet		X		
22	Scaly metal (bullet)				X
23	Upset (crooked) point			X	
24	Exposed steel (clad jacket)			X	
25	Flat point			X	
	Primer				
26	No primer	X			
27	Cocked primer	X			
28	Inverted primer	X			
29	Loose primer		X		
30	Nicked or dented primer			X	
31	No waterproofing material (primer pocket joint)			X	
	Gaging				
32	Cartridge profile failure (requiring more than 10 lbs dead weight to insert in profile and alignment gage)		X		
33	Diameter of extractor groove			X	
34	Diameter of head			X	
35	Thickness of head, max.			X	
36	Thickness of head, min.		X		
37	Case length		X		
38	Total length		X		
39	Depth of primer		X		

1/ Refer to Standard MIL-STD-636 for visual defect standards for defects 1 through 31. In the event of conflict between Table I of this specification and MIL-STD-636, as to defect classification, the classification specified in Table I shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

4.3.3 Tests. - The tests listed in Table II shall be conducted in accordance with the methods and procedures specified in 4.4.

4.3.3.1 Test samples. - The quantities for the various tests shall be as specified in Table II. Only cartridges having met the visual, and dimensional requirements shall be used in the ballistic tests, and shall have been selected in such a manner that the sample is representative of the entire lot. The cartridges shall be throughly mixed before being divided into samples for the various tests.

Table II

Test	Number of Cartridges	Requirement Paragraph
Bullet extraction 1/	25	3.2
Residual stress (Mercurous nitrate) 1/	20	3.3
Airtightness of base closure seal 2/	—	3.4
Waterproof 3/	20	3.5
Salt spray (Steel only) 4/	20	3.6
Accuracy 4/	90	3.7
Trace 5/	100	3.8
Velocity 4/		3.9
Chamber pressure 4/	20	3.10
Function & casualty 6/	—	3.11
Pistol automatic, cal. .45, M1911A1	294	
Gun, submachine, cal. .45, M3A1	900	

1/ Failure of two or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If one cartridge fails in the first test, a second sample consisting of double the number of cartridges in the first sample shall be tested. If any failing cartridges are found in the second sample, the lot shall be rejected.

2/ The bullets, extracted from the cartridges in the bullet extraction test. shall be used in this test. Failure of seven or more bullets to comply with the applicable requirement shall be cause for rejection of the lot. If more than three but less than seven bullets fail in the first test, a second sample consisting of double the number of bullets in the first sample shall be tested. The lot shall be rejected if, in the combined first and second sample, seven or more bullets fail to comply with the applicable requirement.

3/ Failure of nine or more cartridges to comply with the applicable requirements shall be cause for rejection of the lot. If more than four, but less than nine cartridges fail in the first test, a second

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

4.3.3.1 (Cont'd)

sample consisting of double the number of cartridges in the first sample shall be tested. The lot shall be rejected if, in the combined first and second sample, nine or more cartridges fail to comply with the applicable requirement.

4/ Failure of the cartridges to comply with the applicable requirement shall be cause for rejection of the lot subject to testing of a second sample consisting of double the quantity of cartridges used in the first test. Failure of the cartridges in the second sample to comply with the applicable requirement shall be cause for rejection of the lot. Chamber pressure and velocity shall be obtained simultaneously.

5/ The lot shall be rejected if more than ten (10) shots fail to comply with the applicable requirements. No second sample permitted.

6/ The lot shall be rejected when function and casualty defects plus firing defects observed in all other firing tests exceed the acceptance number for the cumulative sample in Table III. If the number of defects found in the first tests exceeds the acceptance number for the first sample, but is equal to or less than the acceptance number for the cumulative sample, a second sample, consisting of double the quantities specified under function and casualty test, shall be fired in the service weapon specified therfor. This procedure shall apply regardless of the weapon or weapons in which the firing defects occurred in the first test. If the total number of defects in the combined first and second sample exceeds the acceptance number for the cumulative sample, the lot shall be rejected. If, in testing a second sample, defects other than those for which the second sample is being tested should occur to the extent that they exceed the acceptance number for the cumulative sample, the lot shall be rejected.

4.3.3.2 Firing defects.-Firing defects and acceptance numbers shall be as specified in Table III.

Table III

Defects	Acceptance Number First Sample	Acceptance Number Cumulative (1st & 2nd Sample)
1. Misfire 5/		
a. No vent hole or obstruction in vent area	0	-
b. Other	1	2

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

4.3.3.2 (Cont'd)

Table III (Cont'd)

Defects	Acceptance Number First Sample	Acceptance Number Cumulative (1st & 2nd Sample)
2. Bullet remaining in bore 1/	0	-
3. Primer leak		
a. Perforation in firing pin indent in primer cup		
(1) Submachine gun	14	41
(2) Automatic pistol	1	3
b. Escape of gas around primer cup 2/	15	39
c. Primer remains in pocket but is physically loose	2	4
d. Blown primer	0	1
e. Primer falls out of pocket on retraction of bolt	0	1
4. Case casualties		
a. Longitudinal split 3/		
(1) Mouth (I)	28	77
(2) Body (J)	8	20
(3) Body (K)	1	2
(4) To head (L)	0	1
(5) Through head (M)	0	1
b. Circumferential rupture 3/		
(1) Partial (J)	6	15
(2) Partial, body (K)	0	1
(3) Partial, head (L)	0	1
(4) Complete	0	1
5. Failure to extract	0	1
6. Weapons stoppage 4/	0	1

1/ No second sample permitted. Lot shall be rejected.

2/ Gas escapes around more than 50% of periphery of cup.

3/ For location of defects indicated by letters in parentheses, see drawing C7643674.

4/ All stoppages attributable to the ammunition, with the exception of misfire, complete rupture or failure to extract, observed in all tests shall be included.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

4.3.3.2 (Cont'd)

5/ Each cartridge that misfires shall be disassembled and examined for presence of a vent hole in the primer pocket, or any obstruction in the vent hole area of the primer pocket that can be assignable as the cause for misfire. If the vent hole is missing or obstructed, the lot shall be rejected with no second sample permitted.

4.3.4 Packaging, packing and marking inspection. - During or immediately prior to the packaging operation, 100% examination of the cartridges shall be performed to ascertain that the cartridge type conforms to the drawing. Occurrence of a high pressure test, dummy or blank cartridge shall be classed as a critical defect. Occurrence of any type other than those listed shall be classed as a major defect. All nonconforming cartridges shall be rejected. Inspection for packaging, packing and marking shall be in accordance with Standard MIL-STD-644 as applicable to the drawing.

4.3.5 Inspection equipment. - Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-I-45607.

4.4 Test methods and procedures.

4.4.1 Bullet extraction. - The cartridges shall be tested in an approved bullet extractor machine. The rate of travel of the test head shall be not less than three or more than six inches per minute. The test shall be conducted in accordance with AMCR 715-505, Volume 5.

4.4.2 Residual stress (mercurous nitrate). - The test shall be conducted in accordance with AMCR 715-505, Volume 5.

4.4.3 Airtightness of the base closure seal. - The bullets shall be placed base up under approximately 1.5 inch head of freshly boiled water in a vacuum desiccator or vacuum jar test unit. The desiccator or jar shall be evacuated to a pressure two pounds per square inch (four inches of mercury) below atmospheric pressure and held at that pressure for five seconds. The number of bubbles liberated from each bullet shall be observed.

4.4.4 Waterproof. - The test shall be conducted in accordance with AMCR 715-505, Volume 5. The container shall be evacuated to a pressure of 5 pounds per square inch (10 inches of mercury) below atmospheric pressure, and held at that pressure for 15 seconds.

4.4.5 Salt spray. - Steel case cartridges shall be subjected to the salt spray test conducted in accordance with ASTM-Method B117.

4.4.6 Accuracy. - The test shall be conducted in accordance with AMCR 715-505, Volume 5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

4.4.7 Trace. - The test shall be conducted in accordance with AMCR 715-505, Volume 5, and the following: Observation for trace performance shall be conducted on a range of at least 150 yards length. Observation for trace performance shall be made at the weapon and at points 15 yards and 150 yards beyond the muzzle of the gun. The observer at the weapon shall observe for any abnormal behavior as an informational check only. Record shall be made of erratic flight, bursting bullets, muzzle flash of obviously greater intensity than that produced by other bullets in the sample or such other behavior as may be considered abnormal by the observer.

4.4.8 Velocity. - The test shall be conducted in accordance with AMCR 715-505, Volume 5 and shall be conducted simultaneously with the chamber pressure test.

4.4.9 Chamber pressure. - The test shall be conducted in accordance with AMCR 715-505, Volume 5.

4.4.10 Function and casualty. - The test shall be conducted in accordance with AMCR 715-505, Volume 5, in the quantities listed below. The weapons shall be at room temperature at the beginning of test.

a. Pistol Automatic, Caliber .45, M1911A1:

One hundred and forty-seven cartridges (twenty-one magazines seven cartridges each) in each of two pistols.

b. Gun, Submachine, Caliber .45, M3A1:

Three hundred cartridges (ten magazines, thirty cartridges each) in each of three guns.

4.4.11 Defect penalty. - In any ballistic test, except function and casualty, in which the occurence of a firing defect listed in Table III prevents the obtaining of a reliable result for the characteristic being tested, an additional shot shall be fired. That particular test shall not be penalized, but the acceptance or initial production sample shall be penalized for such defects in accordance with Table III.

5. PREPARATION FOR DELIVERY

5.1 Packing. - Level A (Worldwide shipment) - The cartridges shall be packed in accordance with drawing D7553728.

5.2 Marking and labeling. - Packing boxes shall be marked and labeled in accordance with the applicable drawing cited in 5.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. - Invitations for bids and contracts or orders will specify the following:

6.1.1 Title, number and date of this specification.

6.1.2 Applicable cartridge drawing number (See 3.1).

6.1.3 Type and level of packing.

6.1.4 Provision for the supply, maintenance and disposition of mandatory ballistic test equipment for acceptance inspection purposes.

6.1.5 Provision for the submission of acceptance inspection reports containing final inspection results for each lot of ammunition presented to the Government.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1305-A740

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-C-1314B(MU) Cartridge, Caliber .45, Tracer, M26

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF [illegible] WHICH IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2026-10-16T15:09Z
Check the source to verify that this is the current version before use.