MIL-C-1316A
27 November 1967
SUPERSEDING
MIL-C-1316
3 August 1949

MILITARY SPECIFICATION
CARTRIDGE, CALIBER .50, INCENDIARY, M23

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers Cartridge, Caliber .50, Incendiary M23 for use in Caliber .50 weapons.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-636	- Visual Inspection Standards for Small Arms Ammunition through Caliber .50
MIL-STD-644	- Visual Inspection Standards and Inspection Procedures for Inspection of Packaging, Packing and Marking of Small Arms Ammunition

DRAWINGS

Munitions Command

C7673512	- Cartridge, Caliber .50, Incendiary, M23
C7643674	- Classification of Cartridge Case Defects
D7553346	- Packing and Marking, Cartridges, Cal. .50; Linked; Box, Ammunition, M2A1; Box, Wirebound

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

2.1 DRAWINGS (Cont'd)

Munitions Command

D7553544	- Packing and Marking, Cartridges, Cal. .50; Bulk; Box, Ammunition, M2A1; Box, Wirebound
F8596993	- Packing and Marking; Cartridges, Caliber .50; Linked, M15A2; Box, Ammunition M2A1; Box, Wirebound
D7692129	- Incendiary Flash Standards for Small Arms Ammunition
D44021	- Target, Incendiary
IEL-7673512	- Inspection Equipment List for Cartridge Caliber .50, Incendiary, M23

PUBLICATIONS

AMCR 715-505, Volume 3	- Ammunition Ballistic Acceptance Methods and Procedures for 7.62mm Cartridges
TECP 700-700, Vol. III	- Manual of Test Methods for Small Arms Ammunition

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- The cartridge shall comply with requirements specified on Drawing C7673512 as specified by the contract, referenced specifications and the following:

3.2 Bullet extraction.- The force required to extract the bullet from the cartridge case shall be not less than 200 pounds.

3.3 Residual stress.- The cartridge case shall not split when subjected to a one percent mercurous nitrate solution for 15 minutes.

3.4 Waterproof.- The cartridge shall not release more than one bubble of air when subjected to a pressure differential of $7\frac{1}{2}$ pounds per square inch (psi) for 30 seconds.

3.5 Accuracy.- The average of the mean radii of all targets of the sample cartridges at 600 yards shall be not greater than 12.0 inches.

3.6 Action time.- The action time (overall primer ignition, propellant burning and bullet-barrel time) of the cartridge shall not exceed 4 milliseconds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

3.7 Velocity.- The average velocity of the sample cartridges, conditioned at 68° to 72° Fahrenheit (F), shall be 3400 feet per second (ft/sec) plus or minus 30 ft/sec. The standard deviation of the velocities shall not exceed 36 ft/sec.

3.8 Chamber pressure.- The average chamber pressure of the sample cartridges conditioned at 68° to 72°F. shall not exceed 58,000 psi.

3.9 Incendiary flash.- The incendiary composition of bullets of the sample cartridges shall ignite and produce an incandescent flash upon impact against an aluminum target (Drawing D4402) at 175 yards. The flash shall be sufficiently intense and sustained to cause combustion of flammable liquids having a flash point not less than 100°F.

3.10 Function and casualty.- The cartridge shall function without casualty.

3.11 Workmanship.- The requirement for workmanship is as specified on the applicable drawings, referenced specifications and the following:

3.11.1 Metal defects.- The cartridge shall be free of folds, wrinkles, deep draw scratches, scaly metal, dents and other defects.

3.11.2 Foreign matter.- The cartridge shall be free of corrosion, stains, discolorations, oil and smears of lacquer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 for definition of quality assurance terms.

4.2 First article sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4.2.1 Initial production sample.- At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 2000 cartridges. The sample shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials, including packaging and packing shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and test.- After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a government laboratory or such other facility specified in the contract.

4.2.1.2 Initial production sample failure.- Failure of the sample to comply with requirements shall result in sample disapproval.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Lot identification.- Each lot of ammunition shall be identified as to type, caliber and model, as well as with a lot number and the supplier's identification as assigned by the procuring activity. Each lot shall be further identified by a Federal Stock Number assigned by the procuring activity.

4.3.2 Examination.- One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a class basis in accordance with the classification of defects, Table I, using applicable sampling plans and acceptance criteria of MIL-STD-105. The AQL for Major Class shall be 0.25 percent and the AQL for the Minor Class shall be 1.50 percent.

4.3.2.1 Classification of defects.- The classification of defects shall be as specified in Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

TABLE I

No.	Defect and Method of Inspection	Critical	Major	Minor	Major or Minor
	Visual 1/				
	Cartridge				
1.	Discolored, dirty, oily, smeared			X	
2.	Corroded, or stained, if etched		X		
	Case				
4.	Round head		X		
5.	Dent				X
6.	Split case				
	in K, L or M location	X			
	in I, S or J location		X		
7.	Perforated case	X			
8.	Draw scratch				X
9.	Scratch			X	
10.	Beveled underside of head		X		
11.	Case mouth not crimped in cannelure		X		
12.	Scale metal				X
13.	No chamfer on head (rim)		X		
14.	Fold			X	
15.	Wrinkle			X	
16.	Buckle			X	
17.	Bulge			X	
18.	Illegible or missing head stamp			X	
19.	Defective head			X	
20.	Defective mouth			X	
21.	No visible evidence of mouth anneal		X		
	Bullet				
22.	Dent			X	
23.	Scratch			X	
24.	Split bullet jacket		X		
25.	Loose bullet		X		
26.	Missing cannelure		X		
27.	Scaly metal				X
28.	Upset (crooked) point			X	
29.	Exposed steel (clad jacket)			X	
30.	Blunt point			X	
31.	Defective cannelure			X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

TABLE I (Cont'd)

No.	Defect and Method of Inspection	Critical	Major	Minor	Major or Minor
	Visual 1/				
	Primer				
32.	No primer	X			
33.	Cocked primer	X			
34.	Inverted primer	X			
35.	Loose primer		X		
36.	Nicked or dented primer			X	
37.	No waterproofing material (primer pocket joint)			X	
38.	Defective crimp			X	
	Gaging				
39.	Total length		X		
40.	Cartridge profile failure (requiring more than 80 lbs. dead weight to insert in profile and alignment gage)		X		
41.	Diameter of extractor groove, max.		X		
42.	Diameter of extractor groove, min.			X	
43.	Diameter of head		X		
44.	Thickness of head		X		
45.	Length to shoulder datum		X		
46.	Depth of primer		X		
	Weighing				
47.	Weight, min. 2/	X			

1/ Refer to MIL-STD-636 for visual defects standards for defects 1 through 38.

2/ Each lightweight cartridge shall be disassembled and the propellant weighed. Each such cartridge found to contain 100 grains or more of propellant shall be classed as a major defect. Any cartridge containing less than 100 grains of propellant shall be classed as a critical defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4.3.3 Tests.- The tests listed in Table II shall be conducted in accordance with the methods and procedures specified in 4.4.

4.3.3.1 Test samples.- The quantities for the various tests shall be as specified in Table II. Only cartridges having met the visual, dimensional and weight requirements shall be used in the ballistic tests and shall have been selected in such a manner that the sample is representative of the entire lot. The cartridges shall be thoroughly mixed before being divided into samples for the various tests.

TABLE II

Test	Number of Cartridges	Requirement Paragraph
Bullet extraction 1/	25	3.2
Residual stress (Mercurous Nitrate) 1/	50	3.3
Waterproof 2/	20	3.4
Accuracy 4/	90	3.5
Action time 1/	50	3.6
Velocity 3/	20	3.7
Chamber pressure 3/	20	3.8
Incendiary flash 5/	20	3.9
Function and casualty 6/	--	3.10
Gun, Machine Cal. .50 Browning M2, HB (Turret Type)	300	
Gun, Machine Cal. .50 Browning M2, HB (Flexible Type)	300	
Gun, Machine Cal. .50 M85 (Fixed Type)	300	
Gun, Machine Cal. .50 AN-M3 Aircraft (Basic)	300	

1/ Failure of two or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If one cartridge fails in the first test, a second sample consisting of double the number of cartridges in the first sample shall be tested. If any failing cartridges are found in the second sample, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4.3.3.1 (Cont'd)

2/ Failure of nine or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If more than four but less than nine cartridges fail in the first test, a second sample consisting of double the number of cartridges in the first sample shall be tested. The lot shall be rejected if in the combined first and second sample, nine or more cartridges fail to comply with the applicable requirement.

3/ Failure of the cartridges to comply with the applicable requirement shall be cause for rejection of the lot, subject to testing a second sample consisting of double the quantity of cartridges used in the initial test. Failure of the cartridges in the second sample to comply with the applicable requirement shall be cause for rejection of the lot.

4/ Failure of three (3) or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If two cartridges fail in the first test, a second sample consisting of double the number of cartridges in the first sample shall be tested. If any failing cartridges are found in the second sample,the lot shall be rejected.

5/ The lot shall be rejected when upon completion of the test the films showing the flash of the bullets under test are compared with the flash standards (Drawing 7692129) are less than 80 out of a possible score of 100. No second sample is permitted.

6/ The lot shall be rejected when function and casualty defects plus firing defects observed in all other firing tests exceed the acceptance number for the cumulative sample in Table III. If the number of defects found in the first test exceeds the acceptance number for the first sample, but is equal to or less than the acceptance number for the cumulative sample, a second sample, consisting of double the quantities specified under function and casualty test, shall be fired in all the service weapons specified therefor. This procedure shall apply regardless of the weapon or weapons in which the firing defects occurred in the first test. If the total number of defects in the combined first and second sample exceeds the acceptance number for the cumulative sample, the lot shall be rejected. If, in testing a second sample, defects other than those for which the second sample is being tested should occur to the extent that they exceed the acceptance number for the cumulative sample, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4.3.3.2 Firing defects.- Firing defects and acceptance numbers shall be as specified in Table III.

TABLE III

Defects	Acceptance First Sample	Acceptance Cumulative (1st & 2nd Sample)
1. Misfire	1	2
2. Bullet remaining in bore 1/	0	-
3. Primer leak		
a. Perforation in firing pin indent in primer cup, Machine Guns	24	60
b. Escape of gas through primer cup other than 3a.	7	15
c. Escape of gas around primer cup more than 50% of periphery	14	30
d. Blown primer or primer falls out of pocket on retraction of bolt	0	1
4. Case casualties		
a. Longitudinal split 2/		
(1) Neck and shoulder (I or S)	27	65
(2) Body (J)	7	15
(3) Body (K)	1	2
(4) To head (L)	0	1
(5) Through head (M)	0	1
b. Circumferential rupture 2/		
(1) Partial, shoulder or body (J or S)	2	4
(2) Partial body (K)	0	1
(3) Partial head (L)	0	1
(4) Complete	0	1
5. Failure to extract	0	1
6. Weapon stoppage 3/	0	1
7. Bullet bursting before striking terminal or target 4/	0	1

1/ No second sample permitted. Lot shall be rejected.

2/ For location of defects indicated by letters in parentheses, see Drawing C7643674.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4.3.3.2 (Cont'd)

3/ All stoppages attributable to the ammunition, with the exception of misfire, complete rupture or failure to extract, observed in all tests shall be included.

4/ This defect shall be counted in the incendiary flash test only.

4.3.4 Packaging, packing and marking inspection.- During or immediately prior to the packaging operation, 100 percent examination of the cartridges shall be performed to ascertain that the cartridge type conforms to the drawing. Occurrence of a high pressure test, dummy or blank cartridge shall be classed as a critical defect. Occurrence of any incorrect type other than those listed shall be classed as a major defect. All nonconforming cartridges shall be rejected. Inspection for packaging, packing and marking shall be in accordance with MIL-STD-644 as applicable to the drawing.

4.3.5 Inspection equipment.- The examination and tests shall be made using the equipment listed on IEL-7673512.

4.4 Test methods and procedures.

4.4.1 Bullet extraction.- The cartridges shall be tested in an approved bullet extractor machine. The rate of travel of the test head shall be not less than three or more than six inches per minute.

4.4.2 Residual stress (Mercurous nitrate).- The test shall be conducted in accordance with TECP 700-700, Vol. III.

4.4.3 Waterproof.- The cartridges (not exceeding five at one time) shall be placed horizontally under a 2 to $2\frac{1}{2}$ inch head of freshly boiled water in a glass container and the container shall be evacuated to a pressure of $7\frac{1}{2}$ pounds per square inch (15 inches of mercury) below atmospheric pressure and held at that pressure for 30 seconds. The number of bubbles liberated from the mouth or primer or both of each cartridge shall be observed.

4.4.4 Accuracy.- The test shall be conducted in accordance with TECP 700-700, Vol. III.

4.4.5 Action time.- The test shall be conducted in accordance with methods and procedures of AMCR 715-505, Volume 3, using equipment listed in IEL-7673512.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4.4.6 Velocity.- The test shall be conducted in accordance with TECP 700-700, Vol. III.

4.4.7 Chamber pressure.- The test shall be conducted in accordance with TECP 700-700, Vol. III.

4.4.8 Incendiary flash.- The test shall be conducted in accordance with TECP 700-700, Vol. III. During the performance of this test, observation shall also be made for "bullet bursting before striking terminal or target".

4.4.9 Function and casualty.- In these firings, the weapons shall be at room temperature at the beginning of the test, and the machine guns shall be cooled between bursts. The number of cartridges to be fired shall be as specified in Table II. The test shall be conducted in accordance with TECP 700-700, Vol. III and as indicated below:

a. Gun, Machine, Caliber .50, Browning, M2 HB (Turret Type) - Fire in bursts of 100 cartridges.

b. Gun, Machine, Caliber .50, Browning, M2 HB (Flexible Type) - Fire in bursts of 100 cartridges.

c. Gun, Machine, Caliber .50, Tank, M85 (Fixed) - Fire in bursts of 100 cartridges.

d. Gun, Machine, Caliber .50, AN-M3, Aircraft (Basic) - Fire in bursts of 100 cartridges.

4.4.10 Defect penalty.- In any ballistic test except function and casualty, in which the occurrence of a firing defect listed in Table III prevents the obtaining of a reliable result for the characteristic being tested, an additional shot shall be fired. That particular test shall not be penalized, but the total ballistic sample shall be penalized for such defects in accordance with Table III.

5. PREPARATION FOR DELIVERY

5.1 Packing, Level A.- (Worldwide shipment).- The cartridge shall be packed in accordance with Drawing D7553346, D7553544 or F8596993.

5.2 Marking and labeling.- Packing boxes shall be marked and labeled in accordance with applicable drawings cited in 5.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data.- Invitations for bids and contracts or orders will specify the following:

6.1.1 Title, number and date of this specification.

6.1.2 Type and level of packing.

6.1.3 Provision for the supply, maintenance and disposition of mandatory ballistic test equipment for acceptance inspection purposes.

6.1.4 Provision for the submission of acceptance inspection reports containing final inspection results for each lot of ammunition presented to the Government.

6.1.5 Requirements for contractor to provide and maintain an inspection system in accordance with MIL-I-45208, Inspection System Requirements.

Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:

Army - MU

Air Force - 70

User activity:

Air Force 26

Review activities:

Army - MU

Air Force - 70

Preparing activity:

Army - MU

Project No. 1305-0503

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.