MIL-C-1317E
18 February 1972
SUPERSEDING
MIL-C-1317D
28 October 1966

MILITARY SPECIFICATION
CARTRIDGE, CALIBER .30, TRACER, M25

This specification is mandatory for use by all Department and Agencies of Department of Defense.

1. SCOPE

1.1 This specification covers Cartridge, Caliber .30, Tracer, M25 for use in Caliber .30 Weapons.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-I-45607 - Inspection Equipment, Acquisition, Maintenance and Disposition of

STANDARDS

Military

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-636 - Visual Inspection Standards for Small Arms Ammunition Through Caliber .50
MIL-STD-644 - Visual Inspection Standards and Inspection Procedures for Inspection of Packaging, Packing and Marking of Small Arms Ammunition
MIL-STD-1168 - Lot Numbering of Ammunition

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

DRAWINGS

Munitions Command

C7640667 - Cartridge, Caliber .30, Tracer, M25
C7643674 - Classification of Cartridge Case Defects
F7553807 - Packing and Marking for Cartridges, Caliber .30, in Cartons, in Box, Ammunition, M2A1 in Box, Wirebound
D7553510 - Packing and Marking for Cartridges, Caliber .30, Linked in Box, Ammunition, M19A1, in Box, Wirebound
D7553698 - Packing and Marking for Cartridges, Caliber .30 in 8RD Clips in Bandoleers, in Box, Ammunition, M19A1, in Box Wirebound
F10533838 - Packing and Marking, Cartridges, Caliber .30, 8RD Clips, Bandoleers, Box Ammunition, M2A1; Box Wirebound

PUBLICATIONS

Munitions Command

AMCR 715-505, Vol. 3 - Ammunition Ballistic Acceptance Test Methods and Procedures for 7.62mm Cartridges
TECP 700-700, Vol 3 - Manual of Test Methods for Small Arms Ammunition

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.-The cartridge shall comply with Drawing C7640667, referenced specification and the following:

3.2 Bullet extraction.-The force required to extract the bullet from the cartridge case shall be not less than 45 pounds.

3.3 Airtightness of base closure seal.-The bullet shall not release more than one bubble of air under application of a pressure differential of 2 pounds per square inch for 5 seconds.

3.4 Residual stress.-The cartridge case shall not split when subjected to a one percent mercurous nitrate solution for 15 minutes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

3.5 Waterproof.-The cartridge shall not release more than one bubble of air when subjected to a pressure differential of 5 pounds per square inch (psi) for 15 seconds.

3.6 Accuracy.-The average of the mean radii of all targets at 600 yards shall be not greater than 18.0 inches.

3.7 Trace.-When viewed at night from a line parallel to the plane of the trajectory, with the line of sight perpendicular to the plane of the trajectory at each point of observation, the bullet of the tracer cartridge shall exhibit a visible trace of full luminosity from a point not greater than 100 yards from the muzzle of the weapon to a point not less than 900 yards from the muzzle. The trace shall be of a level below full luminosity, and prefereably invisible, from the muzzle of the weapon to a point at least 15 yards from the muzzle.

3.8 Action time.-The action time (overall primer ignition, propellant burning and bullet-barrel time) of the cartridge shall not exceed 4 milliseconds.

3.9 Velocity.-The average velocity of the sample cartridges conditioned at 68° to 72° Fahrenheit (F) shall be 2665 feet per second (ft/sec) plus or minus 30 ft/sec at 78 feet from the muzzle. The standard deviation of the velocities shall not exceed 32 feet ft/sec.

3.10 Chamber pressure.-The average chamber pressure of the sample cartridges, conditioned at 68° to 72°F shall not exceed 50,000 psi.

3.11 Function and casualty.-The cartridge shall function without casualty.

3.12 Bullet integrity.-The bullet of the cartridge shall not burst either in its passage through the barrel or in flight; neither shall the jacket of the bullet or any part thereof strip from the slug when the cartridge is fired.

3.13 Workmanship.-The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.13.1 Metal defects.-The cartridge shall be free of folds, wrinkles, deep draw scratches, scaly metal, dents and other defects.

3.13.2 Foreign matter.-The cartridge shall be free of corrosion, stains, discolorations, dirt, oil and smears of lacquer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.-Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.2 First article sample.

4.2.1 Initial production sample.-At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 2500 cartridges. The sample shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same sources of supply.

4.2.1.1 Examination and test.-After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Initial production sample failure.-Failure of the sample to comply with requirements of the drawings and specifications shall result in sample disapproval. Determination as to acceptability of any initial production sample shall be based upon results of initial tests only, and no second tests shall be permitted on that initial production sample.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.-The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Lot identification.-Each lot of ammunition shall be identified as to type, caliber, and model as well as with a lot number in accordance with MIL-STD-1168. Each lot shall be further identified by a Federal Stock Number assigned by the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4.3.2 Examination.-One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a class basis in accordance with the classification of defects, Table I, using applicable sampling plans and acceptance criteria of MIL-STD-105. The Acceptable Quality Level (AQL) for the major class shall be 0.25 percent and the AQL for the minor class shall be 1.50 percent. All non-conforming cartridges shall be rejected.

4.3.2.1 Classification of defects.-The classification of defects shall be as specified in Table I.

Table I

No.	Defect and Method of Inspection	Critical	Major	Minor	Major or Minor
	Visual 1/				
	Cartridge				
1	Discolored, dirty, oily, smeared			X	
2	Corroded or stained, if etched		X		
	Case				
4	Round head		X		
5	Dent				X
6	Split case				
	in K, L or M location	X			
	in I, S or J location		X		
7	Perforated case	X			
8	Draw scratch				X
9	Scratch			X	
10	Beveled underside of head		X		
11	Case mouth not crimped in cannelure		X		
12	Scaly metal				X
13	No chamfer on head (rim)		X		
14	Fold			X	
15	Wrinkle			X	
16	Buckle			X	
17	Bulge			X	
18	Illegible or missing head stamp			X	
19	Defective head			X	
20	Defective mouth			X	
21	No visible evidence of mouth anneal		X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

Table I (cont'd)

No.	Defect and Method Of Inspection	Critical	Major	Minor	Major or Minor
	Visual 1/				
	Bullet				
22	Dent			X	
23	Scratch			X	
24	Split bullet jacket		X		
25	Loose bullet		X		
26	Missing cannelure		X		
27	Scaly metal (bullet)			X	
28	Upset (crooked) point			X	
29	Exposed steel (clad jacket)			X	
30	Blunt point			X	
31	Defective cannelure			X	
	Primer				
32	No primer	X			
33	Cocked primer	X			
34	Inverted primer	X			
35	Loose primer		X		
36	Nicked or dented primer			X	
37	No waterproofing material (primer pocket joint)			X	
38	Defective crimp			X	
	Gaging				
39	Total length		X		
40	Cartridge profile failure (requiring more than 20 lbs dead weight to insert in profile and alignment gage)		X		
41	Diameter of extractor groove, max.		X		
42	Diameter of extractor groove, min.			X	
43	Diameter of head		X		
44	Thickness of head		X		
45	Length to shoulder datum		X		
46	Depth of primer		X		
	Weighing				
47	Weight, min. 2/	X			

1/ Refer to MIL-STD-636 for visual defect standards for defect 1 through 38.

2/ Each lightweight cartridge shall be disassembled and the propellant weighed. Each such cartridge found to contain 25 grains or more of propellant shall be classed as a major defect. Any cartridge containing less than 25 grains of propellant shall be classed as a critical defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4.3.3 Tests.-The tests listed in Table II shall be conducted in accordance with the methods and procedures specified in 4.4.

4.3.3.1 Test samples.-The quantities for the various tests shall be as specified in table II. Only cartridges having met the visual, dimensional and weight requirements shall be used in the ballistic tests, and shall have been selected in such a manner that the sample is representative of the entire lot. The cartridges shall be thoroughly mixed before being divided into samples for the various tests.

Table II

Test	Number of Cartridges	Requirement Paragraph
Bullet Extraction 1/	25	3.2
Airtightness of base closure seal 2/		3.3
Residual stress (Mercurous Nitrate) 1/	50	3.4
Waterproof 3/	20	3.5
Accuracy 4/	90	3.6
Trace 5/	100	3.7
Action time 1/	50	3.8
Velocity 4/	20	3.9
Chamber pressure 4/	20	3.10
Function & casualty 6/		3.11
Gun, Machine, Cal. .30, M37 (Tank) or Alternate Gun, Machine Cal. .30, Browning, M1919A4	300	
Gun, Machine, Cal. .30, Browning, M1919A6	300	
Rifle, U.S. Cal. .30, M1	208	
Bullet integrity 7/	-	3.12

1/ Failure of two or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If one cartridge fails in the first test, a second sample consisting of double the number of cartridges in the first sample shall be tested. If any failing cartridges are found in the second sample, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

Table II (Cont'd)

2/ The bullets extracted from the cartridges in the bullet extraction test shall be used in this test. Failure of seven or more bullets to comply with the applicable requirement shall be cause for rejection of the lot. If more than three but less than seven bullets fail in the first test a second sample consisting of double the number of bullets in the first sample shall be tested. The lot shall be rejected if, in the combined first and second sample, seven or more bullets fail to comply with the applicable requirement.

3/ Failure of nine or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If more than four, but less than nine cartridges fail in the first test, a second sample consisting of double the number of cartridges in the first sample shall be tested. The lot shall be rejected if, in the combined first and second sample, nine or more cartridges fail to comply with the applicable requirement.

4/ Failure of the cartridges to comply with the applicable requirement shall be cause for rejection of the lot subject to testing of a second sample consisting of double the quantity of cartridges used in the first test. Failure of the cartridges in the second sample to comply with the applicable requirement shall be cause for rejection of the lot.

5/ The lot shall be rejected if more than twenty (20) shots fail to comply with the applicable requirements. No second sample permitted.

6/ The lot shall be rejected when function and casualty defects plus firing defects observed in all other firing tests exceed the acceptance number for the cumulative sample in Table III. If the number of defects found in the first test exceeds the acceptance number for the first sample but is equal to or less than the acceptance number for the cumulative sample, a second sample consisting of double the quantities specified under function and casualty test shall be fired in all the service weapons specified therefor. This procedure shall apply regardless of the weapon or weapons in which the firing defects occurred in the first tests. If the total number of defects in the combined first and second sample exceeds the acceptance number for the cumulative sample, the lot shall be rejected. If, in testing a second sample, defects other than those for which the second sample is being tested should occur to the extent that they exceed the acceptance number for the cumulative sample, the lot shall be rejected.

7/ This test shall be performed in conjunction with the "Trace Test", failure of any cartridge to comply with the applicable requirement shall be cause for rejection of the lot. No second sample permitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4.3.3.2 Firing defects.-Firing defects and acceptance numbers shall be as specified in Table III.

Table III

Defects	Acceptance Number: First Sample	Acceptance Number: Cumulative (First & Second Sample).
1. Misfire 4/		
a. No venthole or obstruction in vent area	0	-
b. Other	1	?
2. Bullet remaining in bore 1/	0	-
3. Primer leak		
a. Perforation in firing pin indent in primer cup		
(1) Machine guns	12	28
(2) Rifle	1	?
b. Escape of gas through primer cup other than 3a.	1	?
c. Escape of gas around primer cup more than 50% of periphery	10	20
d. Blown primer	0	1
e. Primers falls out of pocket on retraction of bolt	0	1
f. Primer remains in pocket but is physically loose	3	6
4. Case casualties		
a. Longitudinal split 2/		
(1) Neck and shoulder (I&S)	20	42
(2) Body (J)	3	6
(3) Body (K)	0	1
(4) To head (L)	0	1
(5) Through head (M)	0	1
b. Circumferential rupture 2/		
(1) Partial, shoulder or body (J or S)	1	2
(2) Partial, body (K)	0	1
(3) Partial, head (L)	0	1
(4) Complete	0	1
5. Failure to extract	0	1
6. Weapon stoppage 3/	0	1

1/ No second sample permitted. Lot shall be rejected.

2/ For location of defects indicated by letters in parentheses, see drawing C7643674.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

Table III (Cont'd)

3/ All stoppage attributable to the ammunition, with the exception of misfire, complete rupture or failure to extract observed in all tests shall be included.

4/ Each cartridge that misfires shall be disassembled and examined for presence of a vent hole in primer pocket, or any obstruction in the vent hole area of the primer pocket that can be assignable as the cause for misfire. If the vent hole is missing or obstructed, the lot shall be rejected with no second sample permitted.

4.3.4 Packaging, packing, and marking inspection.-During or immediately prior to the packaging operation, 100% examination of the cartridges shall be performed to ascertain that the cartridge type conforms to the drawing. Occurrence of a high pressure test, dummy, grenade or blank cartridge shall be classed as a critical defect. Occurrence of any incorrect type other than those listed shall be classed as a major defect. All non-conforming cartridges shall be rejected. Inspection for packaging, packing, and marking shall be in accordance with MIL-STD-644 as applicable to the drawing.

4.3.5 Inspection equipment.-Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-I-45607. The reference cartridge to be used shall be loaded with propellant of the same type as the propellant loaded into the production cartridge. Simulated assessment of reference cartridge shall be in accordance with TECP 700-700, Vol. III.

4.4 Test Methods and Procedures.

4.4.1 Bullet extraction.-The cartridges shall be tested in an approved bullet extractor machine. The rate of travel of the test head shall be not less than three nor more than six inches per minute.

4.4.2 Residual Stress (Mercurous Nitrate).-Tests shall be conducted in accordance with TECP 700-700, Vol. III.

4.4.3 Waterproof.-The ammunition to be tested, not to exceed five cartridges at one time, shall be placed horizontally on a perforated tray. The tray shall be placed in a desiccator containing sufficient quantity of freshly boiled water to maintain a head of 2 to 2-1/2 inches. The desiccator shall be evacuated to a pressure of 5 pounds per square inch (10 inches of mercury) below atmospheric pressure and held at that pressure for 15 seconds. The number of bubbles liberated from the mouth or primer of each cartridge shall be observed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4.4.5 Chamber pressure.-The cartridges shall be drilled, using the specified equipment, and the drilled hole shall be covered with a half inch square of tape. The test shall be conducted in accordance with TECP 700-700 Vol. III.

4.4.6 Accuracy.-The test shall be conducted in accordance with TECP 700-700, Vol. III, utilizing the longest range available up to 600 yards. Ranges shorter than 200 yards shall not be used. When accuracy testing is conducted on ranges shorter than 600 yards, the average of the mean radii of the targets shall be multiplied by the applicable conversion factor given below:

Range (yards)	200	300	400	500
Factor	3.40	2.23	1.68	1.35

4.4.7 Trace.-Observation for trace performance shall be conducted on a range of at least 900 yards length. All trace testing shall be performed at night. The cartridges shall be fired in a gun assembled with a barrel which has not previously been fired more than 6000 times. Observation for trace performance shall be made at the weapon and at points 15 yards, 100 yards and 900 yards beyond the muzzle of the gun on a line parallel to and approximately 75 yards from the plane of the trajectory. Lights or other suitable visible markers shall be placed opposite the 15,100, and 900 yard observing points to insure a line of sight from each point perpendicular to the plane of the trajectory. The ammunition shall not be conditioned to temperature but shall be fired under existing conditions. Three cartridges shall be fired to sight, warm and foul the weapon prior to the test. The sample cartridges shall be fired in regular sequence permitting sufficient time between shots for each observer to record trace characteristics at each observation point. Each cartridge shall be considered as a defective only once in the event it fails at more than one observation point.

Observations for trace performance shall be as follows:

a. Observation at weapon position.-The observer at this point shall observe for any abnormal behavior as an information check only. Record shall be made of erratic flight, bursting bullets, muzzle flash of obviously greater intensity than that produced by other bullets in the sample, or such other behavior as may be considered abnormal by the observer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4.4.7 (Cont'd)

b. Observation at 15 yard position.-The observer, with line of sight established perpendicular to the trajectory by the light or visible marker, shall note the trace performance of the bullet from each sample cartridge. Trace of low level luminosity or absence of trace extending for at least 15 yards from the muzzle shall be considered acceptable. The cartridge shall be considered defective if the trace reaches full luminosity during the first 15 yards of the trajectory.

c. Observation at 100 yard position.-The observer, with line of sight established perpendicular to the trajectory by the light or visible marker, shall note the trace performance of the bullet from each sample cartridge. A trace which has attained full luminosity prior to 100 yards range shall be considered acceptable. The cartridge shall be considered defective when the bullet exhibits a low level luminosity trace or no trace.

d. Observation at the 900 yard position.-The observer, with line or sight established perpendicular to the trajectory by the light or visible marker, shall note the trace performance of the bullet from each sample cartridge. A trace of full luminosity extending to 900 yards range or beyond shall be considered acceptable. The cartridge shall be considered defective if the bullet exhibits a trace of low level luminosity or no trace.

e. "Full luminosity" is defined as the maximum level of sustained luminosity.

f. "Low level of luminosity" is a level obviously lower in intensity than full luminosity.

4.4.8 Airtightness of the Base Closure Seal.-The bullets shall be placed base up under approximately 1.5 inch head of freshly boiled water in a vacuum desiccator or vacuum jar test unit. The desiccator or jar shall be evacuated to a pressure 2 pounds per square inch (4 inches of mercury) below atmospheric pressure and held at that pressure for 5 seconds. The number of bubbles liberated from each bullet shall be observed.

4.4.9 Action time.-The test shall be conducted in accordance with the methods and procedures of AMCR 715-505, Vol. 3.

4.4.10 Function and casualty.-In these firings the weapon shall be at room temperature at the beginning of the test and the machine guns shall be cooled between bursts. The number of cartridges to be fired shall be as specified in table II. The test shall be conducted in accordance with TECP 700-70C, Vol. III and as indicated below:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

4.4.10 (Cont'd)

a. Gun, Machine, Caliber .30, M37 (Tank) or Alternate Gun Machine, Caliber .30, Browning, M1919A4 - Fire in bursts of 100 cartridges.

b. Gun, Machine, Caliber .30, Browning, M1919A6 - Fire in bursts of 100 cartridges.

c. Rifle, U.S., Caliber .30, M1 - Fire 8 cartridges (one clip) rapid fire, with intervals of not more than ½ minute between clips. The weapon shall be cooled after firing the first 48 cartridges (6 clips). Two rifles shall be used and 104 cartridges shall be fired in each rifle.

4.4.11 Defect penalty.-In any ballistic test, except function and casualty, in which the occurrence of firing defect listed in Table III prevents the obtaining of a reliable result for the characteristic being tested, an additional shot shall be fired. That particular test shall not be penalized, but the total ballistic sample shall be penalized for such defects in accordance with Table III.

4.4.12 Velocity.-The test shall be conducted in accordance with TECP 700-700, Vol. III.

4.4.13 Bullet integrity.-The test shall be conducted in accordance with Appendix "A". Any bullet recorded as a "Blind" by down range observers either by absence of trace or absence of noise of passing bullet and accompanied by either detection of an abnormally loud report and bright flash by the observer at the gun position or by the presence of any irregulary shaped hole in the screen, shall be considered as a bursting or stripped bullet.

5. PREPARATION FOR DELIVERY

5.1 Packing Level A (Worldwide Shipment).-The cartridges shall be packed in accordance with drawings D7553807, D7553510, D7553698 or F10533838.

5.2 Marking and labeling.-Packing boxes shall be marked and labeled in accordance with the applicable drawings cited in 5.1.

6. NOTES

6.1 Ordering data.-Invitations for bids and contracts or orders should specify the following:

6.1.1 Title, number, and date of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

6.1.2 Type and level of packing.

6.1.3 Provisions for the supply, maintenance and disposition of mandatory ballistic test equipment for acceptance inspection purposes.

6.1.4 Provision for the submission of acceptance inspection reports containing final inspection results for each lot of ammunition presented to the Government.

6.1.5 Requirement for contractor to provide and maintain an inspection system in accordance with MIL-I-45208, Inspection System Requirements.

6.2 Hazard notice. The cartridge described herein and certain of its components are flammable and/or explosive and consequently present hazards in manufacture, handling, storage and shipment. The contractor should recognize these hazards and take appropriate measures to guard and protect against fire, explosion, adverse environment, corrosive atmosphere, rough handling and electrically induced incidents.

Custodian:

Army - MU

User Activity:

Navy - MC

Preparing Activity:

Army - MU(FA)
Project No. 1305-0696

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

APPENDIX "A"

Bullet Integrity Test Procedure

1.0 Equipment

1.1 Equipment listed in the Trace section of the Inspection Equipment List shall be used.

1.2 Target screen, 6' x 6', shall be placed 50 feet from the muzzle of the gun, in the line of fire.

2.0 Observation Points

2.1 The three observers used for the Trace test shall also observe for the Bullet Integrity Test.

3.0 Test Procedure

3.1 Preparation for firing

3.1.1 Preparation for firing shall be in accordance with AMCR 715-505, Volume 3, Chapter 1, Section 17.

3.1.2 Prior to each test, the gun to be used for the test shall be inspected. The gun shall be clean, including the chamber and bore of the barrel.

3.1.3 Target screen, referenced in para. 1.2, shall be placed in specified position, so that bullets pass through the screen at its center.

3.2 Firing the test..

3.2.1 Test shall be fired in accordance with AMCR 715-505, Volume 3, Chapter 1, Section 17.

3.2.2 Each observer shall keep a shot-by-shot record. In addition to recording trace performance of each bullet, observers shall also record any abnormalities observed, e.g., large flash, loud report, erratic flight, absence of noise of passing bullet at terminal point, etc. Observers shall record performance of each bullet in order to compare records upon completion of the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

Appendix A (Cont'd)

3.2.3 The target screen shall be examined after each series of 20 rounds or anytime a suspect bursting or stripped bullet is encountered. Screen shall be renewed as often as is necessary to assure positive identification of bursting or stripped bullets.

4.0 Recording of data.

4.1 Upon completion of the test, the observers shall check their respective observations together, shot by shot. All observations shall be reported.

4.1.1 Suspect shots shall be reported by each observer, as follows:

a. Loud report
b. Large flash
c. Lack of trace
d. Erratic flight
e. Shot number

4.1.2 Target screen observations shall be reported as follows:

a. Number of holes
b. Location of holes
c. Type of holes

4.1.3 The test results are reported as follows:

a. Number of cartridges fired
b. Number and type of defects
c. Number and type of case casulties

4.1.4 The following test weapon data shall be recorded on the test sheet:

a. Receiver number
b. Barrel number
c. Total number of cartridges fired in barrel prior to test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

YES NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Print or typed name and activity - Optional)*

DATE

DD FORM 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:10Z
Check the source to verify that this is the current version before use.