MIL-C-1312C(Ord)

8 July 1960

SUPERSEDING
MIL-C-1312B
22 Oct 1954

MILITARY SPECIFICATION
CARTRIDGE, CALIBER .30, BLANK, M1909

1. SCOPE

1.1 This specification covers a cartridge intended for saluting and training purposes.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitations for bids form a part of this specification to the extent specified herein.

SPECIFICATION

Military

MIL-A-625	-	Ammunition, Small Arms, General Specification for

STANDARDS

Military

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	-	Inspection Terms and Definitions
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-636	-	Visual Inspection Standards for Small Arms Ammunition through Caliber .50

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

2.1 (cont.)

DRAWINGS

Ordnance Corps

C-6006152	-	Cartridge, Blank, Cal. .30, M1909
B-7643674	-	Classification of Cartridge Case Defects
D-7553502	-	Packing and Marking for Cartridges, Blank, Cal. .30, M1909; Linked; Box, Ammunition M19A1; Box, Wirebound
D-7553654	-	Packing and Marking for Cartridges, Blank, Cal. .30, M1909; Cartons (Auto. Pack); Box, Ammunition M2A1; Box, Wirebound
D-7553659	-	Packing and Marking for Cartridges, Blank, M1909 and Rifle Grenade, Cal. .30, M3; Cartons (Hand Pack); Box, Ammunition M2A1; Box, Wirebound
D-7553734	-	Packing and Marking for Cartridges, Blank, Cal. .30, M1909; 8-Rd Clips; Bandoleers; Box, Ammunition M2A1; Box, Wirebound
D-7553891	-	Packing and Marking for Cartridges, Blank, Cal. .30, M1909; Containers; Box, Ammunition M2A1; Box, Wirebound
D-7553897	-	Packing and Marking for Cartridges, Blank, Cal. .30, M1909; 5-Rd Clips; Bandoleers; Box, Ammunition M2A1; Box, Wirebound
D-8595241	-	Packing and Marking for Cartridges, Blank, Cal. .30, M1909; 8-Rd Clips; Bandoleers; Box, Ammunition M19A1; Box, Wirebound
IEL-6006152	-	List of Inspection Equipment for Assembled Cartridge

PUBLICATIONS

Department of the Army

SM9-5-1305	-	Department of the Army Supply Manual Ammunition and Explosives Ammunition, through 30mm

Ordnance Corps

ORD-M608-PM, Vol. III	-	Manual of Test Methods for Small Arms Ammunition
ORD-SIP-S324	-	Standard Inspection Procedure for Packing of Small Arms Ammunition

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

2.2 Other Publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

INTERSTATE COMMERCE COMMISSION - 49 CFR 71-78

Interstate Commerce Commission Rules and Regulations for the Transportation of Explosives and Other Dangerous Articles. (The Interstate Commerce Commission regulations are now a part of the Code of Federal Regulations available from the Superintendent of Documents, Government Printing Office, Washington 25, D. C. Orders for the above publication should cite "49 CFR 71-78".)

3. REQUIREMENTS

3.1 General.- The cartridge shall comply with the requirements specified on Drawing C-6006152, referenced specifications and the following:

3.2 Preproduction Sample.- Unless otherwise directed by the contracting officer, a preproduction sample shall be required.

3.3 Case.- Use of cases not suitable for combat type cartridges (including cases obtained from pulldown of Grade 3 ammunition), fired cases, reworked cases or both, shall be permitted.

3.4 Screen Perforation.- The wad of the cartridge shall not perforate a paper screen placed 15 feet from the muzzle of the gun.

3.5 Function and Casualty.- The cartridge shall function without casualty at ambient temperatures, at minus 40 degrees to minus 45 degrees Fahrenheit (F) and at plus 125 degrees to plus 130 degrees (F).

3.6 Workmanship.- Workmanship shall be in accordance with Specification MIL-A-625.

4. QUALITY ASSURANCE PROVISIONS

4.1 General Quality Assurance Provisions.- The quality assurance provisions in this section and other documents referenced in this specification are applicable to inspection performed by or for the Government. Reference shall be made to Standard MIL-STD-109 to define the inspection terms used. Inspection shall be in accordance with Specification MIL-A-625 except as specified herein.

4.1.1 Contractor Inspection.- The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

4.1.1 (cont.)

shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.2 Contractor Quality Assurance System.- The contractor shall provide and maintain an adequate quality assurance system, acceptable to the Government, covering the supplies under the contract. A current written description of the system shall be submitted to the contracting officer prior to initiation of production. The written description will be considered acceptable when, as a minimum, it provides the quality assurance required by this specification and other applicable documents referenced in this specification. The contractor shall notify the Government of and obtain approval for any change to the written procedure that might affect the degree of assurance required by this specification or other applicable documents referenced herein.

4.1.3 Government Verification.- All quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of (a) surveillance of the operations to determine that practices, methods, and procedures of the written inspection plan are being properly applied, and (b) Government product inspection to measure quality of product offered for acceptance. Deviations from the prescribed or agreed upon procedures or instances of poor practices which might have a detrimental effect upon the quality of the product will be immediately called to the attention of the contractor. Failure of the contractor to promptly correct deficiencies discovered will be cause for suspension of acceptance until correction has been made or until conformance of product to prescribed criteria has been demonstrated. To avoid interference with operations, the contractor shall designate a responsible official or officials to whom the Government inspector will report such instances.

4.2 Preproduction Inspection

4.2.1 Preproduction Sample.- Prior to the start of regular production, the contractor shall submit a preproduction sample to a Government approved facility for evaluation. The sample shall consist of 900 cartridges from the contractor's initial production, manufactured in the same manner, using the same materials, equipment, processes and procedures as will be used in regular production, and packaged and packed in accordance with the requirements of the contract. The contracting officer will furnish instructions for shipment of the sample to a designated facility for examination and tests. Any production under the contract prior to approval of the preproduction sample shall be at the risk of the contractor. After the start of production, additional preproduction samples shall be submitted for approval immediately subsequent to each major change in material or manufacturing process as determined by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

4.2.2 Inspection.- The preproduction sample shall be examined and tested for all requirements of the drawings and specifications including all those characteristics listed in 4.3.2 and 4.3.3. All testing shall be conducted in accordance with 4.4. The Government reserves the right to require additional preproduction samples until such time as an acceptable sample is submitted.

4.3 Inspection Provisions.- Alternative inspection procedures and inspection equipment may be used by the contractor when such procedures and equipment provide, as a minimum, the quality assurance required in the contractual documents. The inspection procedures or equipment specified in this specification and referenced documents will prevail in case of dispute. However, in all firing tests, the use of the equipment specified and the methods of test prescribed in this specification and other documents referenced herein shall be mandatory.

4.3.1 Lot.

4.3.1.1 Submittal of Product.- The contractor shall submit the product in accordance with Standard MIL-STD-105.

4.3.1.2 Size of Lot.- The ammunition lot size shall be as agreed upon between the contractor and the contracting officer provided the formation of the lot is in accordance with Standard MIL-STD-105.

4.3.1.3 Lot Identification.- Each lot of ammunition shall be identified in accordance with Specification MIL-A-625. Each lot shall be further identified by a Federal Stock Number assigned by the procuring agency in accordance with Publication SM9-5-1305.

4.3.2 Examination.- Examination shall be performed as indicated below:

4.3.2.1 Critical Defects.- One hundred percent examination shall be performed for critical defects. All critically defective cartridges shall be rejected.

4.3.2.2 Major and Minor Defects.- Examination for major and minor defects shall be performed on a class basis in accordance with the classification of defects, Table I, using applicable sampling plans of Standard MIL-STD-105. If the number of defective cartridges is equal to or greater than the applicable rejection number, the lot shall be rejected subject to reinspection in accordance with Specification MIL-A-625.

4.3.2.3 Acceptable Quality Levels.- The acceptable quality levels with respect to visual and dimensional defects shall be as follows:

Defect	Percent
Major	0.65
Minor	2.50

4.3.2.4 Classification of Defects.- The visual and dimensional defects shall be classified as specified in Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

TABLE I

No.	Defect	Critical	Major	Minor
	Visual 1/			
2	Corroded or stained, if etched			x
3	Mixed ammunition types			
	a. Dummy, Grenade			x
	b. All others not included in a.	x		
7	Perforated case 2/		x	
12	Scaly metal			x
14	Fold			x
19	Defective head			x
32	No primer		x	
33	Cocked primer		x	
34	Inverted primer		x	
35	Loose primer		x	
39	Split case between head and rear face of wad 2/		x	
40	Split case between mouth and rear face of wad			x
41	Joint between case neck and wad not covered by lacquer			x
42	Joint between case neck and wad covered by lacquer but wad not completely covered by lacquer			x
43	Opening between wad and case wall 2/		x	
	Gaging			
44	Failure to chamber in M1 Rifle 3/		x	
45	High primer		x	

1/ Refer to Caliber .30 section of Standard MIL-STD-636 for definite classification of defects 2 through 35. In the event of conflict between Table I of this specification and MIL-STD-636 as to defect classification, the classification specified in Table I shall apply.

2/ To be counted as a minor defect if no propellant can be shaken from the case.

3/ The cartridge shall be inserted into a Rifle, U.S. Cal. .30, M1, with minimum chamber and minimum headspace, and the bolt shall be allowed to close by spring pressure. If the cartridge fails to chamber completely or results in a failure of the weapon to lock completely, it shall be considered defective. Preliminary gaging may be performed in the maximum profile and alignment gage, and only those cartridges failing to conform shall be required to be gaged in the rifle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

4.3.3 Tests.- The following tests shall be conducted in accordance with the methods and procedures specified in 4.4.

4.3.3.1 Firing Tests.- The quantities for these tests shall be as specified in Table II. Only cartridges having met the visual and dimensional requirements shall be used in the firing tests, and shall have been selected in such a manner that the sample is representative of the entire lot. The cartridges selected shall be thoroughly mixed before being divided into test samples.

TABLE II

Test	Number of Cartridges Temperatures			Requirement Paragraph
	Ambient	Low	High	
Screen Perforation 1/	200			3.4
Function and Casualty 2/	400	100	100	3.5

1/ The lot shall be rejected if more than three cartridges fail to comply with the applicable requirement. Retest may be conducted with double the test sample, provided that no more than eight cartridges fail to comply with the requirement in the initial test. The lot shall be rejected if, in the combined test and retest, nine or more cartridges fail to comply with the applicable requirement.

2/ The lot shall be rejected when function and casualty defects plus other firing test defects exceed the number permitted for the initial test in Table III. Retest may be conducted in accordance with 4.3.3.3 provided that the number of defects found in the initial test does not exceed the number permitted for the cumulative sample (test plus retest). If the total number of defects in the combined test and retest exceeds the number permitted for the cumulative sample, the lot shall be rejected.

4.3.3.2 Firing Defects.- Firing defects and number permitted in a sample shall be as specified in Table III.

TABLE III

Defects	No. of Defects Permitted	
	Initial Test	Cumulative (Test plus Retest)
Primer:		
Escape of gas through primer cup	40	100
Loose primer 1/	2	5
Blown primer 2/	0	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

TABLE III (cont.)

Defects	No. of Defects Permitted	
	Initial Test	Cumulative (Test plus Retest)
Case:		
Splits, neck, shoulder or mouth	40	100
Splits, body	7	17
Splits, through head	1	3
Complete rupture 3/	1	3
Partial rupture	2	5
Detached metal 3/	0	1
Gun stoppage 4/	20	50

1/ Primer falls out of pocket on retraction of bolt after firing. If the primer remains in the pocket but is physically loose, the defect shall be reported for information, with no limit specified.

2/ Primer not in pocket after firing and both head of cartridge case and primer pocket enlarged and distorted, (determined visually).

3/ Any particle of metal which becomes separated from the case between the mouth and the juncture of the shoulder and neck shall be classified as detached metal. A complete rupture at this location on the case shall be classed as detached metal.

4/ Gun stoppages, including misfire, observed in all tests shall be included.

4.3.3.3 Retests.- Retests, when permissible, will be conducted at the request of the contractor. Retest for failure due to excessive firing defects (Table III) shall be made by firing double the quantities specified in Table II under function and casualty test in the service weapon specified therefor. This procedure for retest shall apply regardless of the weapon or weapons in which the firing defects occurred during the initial tests.

4.3.4 Packaging, Packing and Marking Inspection.

4.3.4.1 Level A.- Inspection for packaging, packing and marking shall be in accordance with Specification MIL-A-625 and Publication ORD-SIP-S324. Sampling shall be in accordance with Inspection Level I of Standard MIL-STD-105.

4.3.4.2 Level C.- When standard commercial containers are contractually required by the procuring activity, inspection for packaging, packing and marking shall be as required by the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

4.3.5 Inspection Equipment.- The examination and tests shall be made using equipment listed on IEL-6006152 except as provided in 4.3. The Government will determine by means of its monitoring program that the contractor has available and correctly utilizes gaging, measuring and test equipment of required accuracy and precision and that the instruments are of proper type and range to make measurements of the required accuracy. The contractor shall have available a set of master gages, standards and other appropriate instruments for regularly scheduled calibration of his inspection equipment. Records of such regularly scheduled calibration shall be maintained by the contractor and made available to the Government for review. The calibration of gages, standards and instruments will be periodically checked by authorized Government personnel.

4.4 Test Methods and Procedures.

4.4.1 Screen Perforation.- The test shall be conducted in accordance with Publication ORD-M608-PM, Vol. III.

4.4.2 Function and Casualty.- In these firings, the weapon shall be at room temperature at the beginning of the test. Two machine guns shall be used, and one-half the quantities specified in Table II shall be fired in each gun. The machine gun shall be fired in bursts of 100 cartridges for the ambient temperature test and in bursts of 50 cartridges each for the low and high temperature tests. The gun shall be cooled between bursts. The test shall be conducted in accordance with Publication ORD-M608-PM, Vol. III.

4.4.2.1 Low Temperature Test.- The ammunition for the low temperature test shall be placed in a controlled temperature box in such a manner that all cartridges are subjected to a uniform temperature, cooled to a temperature of minus 40 to minus 45 degrees (F) and held thereat for a minimum of four hours immediately before firing. The controlled temperature box shall be of sufficient capacity to permit cooling of the ammunition to the desired temperature, and to allow free circulation of air. The ammunition shall be fired immediately upon removal from the cold box in the specified weapon which shall be at ambient temperature. If the weapon is not convenient to the controlled temperature box, the ammunition shall be placed in an insulated chest which has been cooled to a temperature of minus 40 to minus 45 degrees (F), transported to the weapon and fired immediately upon removal.

4.4.2.2 High Temperature Test.- The ammunition for this test shall be stored, conditioned and fired in the same manner as that prescribed for the low temperature test except that the temperature at which the ammunition is conditioned shall be plus 125 to plus 130 degrees (F).

4.4.3 Defect Penalty.- In any firing test, except function and casualty, in which the occurrence of a firing defect prevents the obtaining of a reliable result for the characteristic being tested, an additional shot shall be fired. That particular test shall not be penalized, but the acceptance sample shall be penalized for such defects in accordance with Table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packing Level A.- The cartridge shall be packed in accordance with Drawing D-7553659, D-7553734, D-7553897, D-8595241, D-7553654, D-7553502 or D-7553891 as stipulated in the contract.

5.1.1 Level C.- When specified by the procuring activity, the cartridges shall be packed in standard commercial containers so as to insure acceptance by common or other carrier for safe transportation, at the lowest rate to the point of delivery.

5.1.2 Reclaimed clips with adequate surface finish may be used, provided no defects are present which could interfere with the proper functioning of the weapon

5.2 Marking and Labeling.- Packing boxes shall be marked and labeled in accordance with the applicable drawings cited in 5.1, Standard MIL-STD-129 and Publication SM9-5-1305.

5.3 Delivery.- A lot which has been officially accepted by the Government inspector shall be considered as delivered when the cartridges are packed, the ammunition packing boxes sealed and marked as required by applicable drawings, and the packed ammunition has been accepted. After delivery has been accomplished as specified herein, the lot shall be either shipped or stored, in accordance with the terms of the contract as may be directed by the contracting officer. When the contract provides for delivery f.o.b. cars at the place of manufacture, the ammunition shall be packed and properly secured in accordance with Interstate Commerce Commission regulations as listed in 2.2.

6. NOTES

None

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

CUSTODIAN:
Army - Ordnance Corps

PREPARING ACTIVITY:
Army - Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.