MIL-C-1312D(MU)
26 December 1962
SUPERSEDING
MIL-C-1312C(Ord)
8 July 1960

MILITARY SPECIFICATION
CARTRIDGE, CALIBER .30, BLANK, M1909

1. SCOPE

1.1 This specification covers a cartridge intended for saluting and training purposes.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-I-45208	- Inspection Requirements, General Specification for

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-636	- Visual Inspection Standards for Small Arms Ammunition through Caliber .50

DRAWINGS

Munitions Command

C6006152	- Cartridge, Cal. .30, Blank, M1909
B7643674	- Classification of Cartridge Case Defects
D7553502	- Packing and Marking for Cartridges, Blank, Cal. .30, M1909; Linked; Box, Ammunition M19A1; Box, Wirebound
D7553654	- Packing and Marking for Cartridges, Blank, Cal. .30, M1909; Cartons (Auto. Pack); Box, Ammunition M2A1; Box, Wirebound

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

2.1 (Cont.)

D7553659	- Packing and Marking for Cartridges, Blank, M1909 and Rifle Grenade, Cal. .30, M3; Cartons (Hand Pack); Box, Ammunition M2A1; Box, Wirebound
D7553734	- Packing and Marking for Cartridges, Blank, Cal. .30, M1909; 8-Rd Clips; Bandoleers; Box, Ammunition M2A1; Box, Wirebound
D7553891	- Packing and Marking for Cartridges, Blank, Cal. .30, M1909; Containers; Box, Ammunition M2A1; Box, Wirebound
D7553897	- Packing and Marking for Cartridges, Blank, Cal. .30, M1909; 5-Rd Clips; Bandoleers; Box, Ammunition M2A1; Box, Wirebound
D8595241	- Packing and Marking for Cartridges, Blank, Cal. .30, M1909; 8-Rd Clips; Bandoleers; Box, Ammunition M19A1; Box, Wirebound
IEL-6006152	- Inspection Equipment List for Cartridge, Cal. .30, Blank, M1909

PUBLICATIONS

Munitions Command

ORD-M608-PM, Vol. III	- Manual of Test Methods for Small Arms Ammunition
ORD-SIP-S324	- Standard Inspection Procedure for Packing of Small Arms Ammunition

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- The cartridge shall comply with the requirements specified on Drawing C6006152, referenced specifications and the following:

3.2 Initial production sample.- Unless otherwise directed by the contracting officer, an initial production sample shall be required.

3.3 Case.- Use of cases not suitable for combat type cartridges (including cases obtained from pulldown of Grade 3 ammunition), fired cases, reworked cases or both, shall be permitted.

3.4 Primer sensitivity.- The energy imparted by a steel ball (3.94 $\pm$ .02 ounces) falling 15 inches shall cause initiation of the primer. The energy imparted by a steel ball (3.94 $\pm$ .02 ounces) falling 2½ inches shall not cause initiation of the primer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

3.5 Screen perforation.- The cartridge, when fired, shall not cause perforations of 0.1 inch or greater in diameter in a paper screen placed 15 feet from the muzzle of the gun.

3.6 Function and casualty.- The cartridge shall function without casualty.

3.7 Workmanship.- The cartridge shall comply with the applicable drawings and shall be free of folds, scaly metal, splits, corrosion, stains if etched and other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to Standard MIL-STD-109 to define the quality assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with Specification MIL-I-45208, except as specified herein.

4.2 Initial production sample.- Prior to the initiation of regular production, the contractor shall submit an initial production sample to a designated Government approved facility for evaluation. The sample shall consist of 1500 cartridges from the contractor's initial production, manufactured in the same manner, using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials, including packaging and packing, must be the same as will be used in regular production and shall be obtained from the same source of supply. The contractor shall inspect the same in accordance with his inspection system and other inspection requirements of Specification MIL-I-45208. After inspection and acceptance at source, the initial production sample shall be inspected at the Government approved facility for all requirements of the drawings and specifications. The Government reserves the right to require new initial production samples until such time as an acceptable sample is submitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

4.3 Inspection provisions.- Use of alternative inspection procedures and inspection equipment shall be in accordance with Specification MIL-I-45208, except that in all ballistic testing, the use of equipment specified and the methods of test prescribed in this specification and other documents referenced herein shall be mandatory.

4.3.1 Lot.

4.3.1.1 Presentation of lots.- The product shall be presented in accordance with Standard MIL-STD-105.

4.3.1.2 Size of lot.- The ammunition lot size shall be as agreed upon between the contractor and the contracting officer, provided the formation of the lot is in accordance with Standard MIL-STD-105.

4.3.1.3 Lot identification.- Each lot of ammunition shall be identified as to type, caliber and model as well as with a lot number and the manufacturer's identification as assigned by the procuring agency. Each lot shall be further identified by a Federal Stock Number assigned by the procuring agency.

4.3.2 Examination.- Examination shall be performed as indicated below:

4.3.2.1 Major and minor defects.- Examination for major and minor defects shall be performed on a class basis in accordance with the classification of defects, Table I, using applicable sampling plans of Standard MIL-STD-105.

4.3.2.2 Acceptable quality levels.- The acceptable quality levels with respect to visual and dimensional defects shall be as follows:

Defect Class	Percent
Major	0.65
Minor	2.50

4.3.2.3 Classification of defects.- The visual and dimensional defects shall be classified as specified in Table I.

Table I

No.	Defect and Method of Inspection	Major	Minor
	Visual 1/		
2	Corroded or stained, if etched		X
7	Perforated case 2/	X	
12	Scaly metal		X
14	Fold		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

Table I (Cont.)

No.	Defect and Method of Inspection	Major	Minor
19	Defective head		X
32	No primer	X	
33	Cocked primer	X	
34	Inverted primer	X	
35	Loose primer	X	
39	Split case 2/	X	
40	Missing or loose wad	X	
41	Wad and joint between neck and wad not completely covered by lacquer		X
42	Opening between wad and case wall	X	
	Gaging		
43	Cartridge profile failure	X	
44	High primer	X	

1/ Refer to Caliber .30 section of Standard MIL-STD-636 for visual classification of defects 2 through 35. In the event of conflict between Table I of this specification and Standard MIL-STD-636 as to defect classification, the specification specified in Table I shall apply.

2/ To be counted as a minor defect if no propellant can be shaken from the case.

4.3.3 Tests.- The following tests shall be conducted in accordance with the methods and procedures specified in 4.4.

4.3.3.1 Firing tests.- The quantities for these tests shall be as specified in Table II. Only cartridges having met the visual and dimensional requirements shall be used in the firing tests, and shall have been selected in such a manner that the sample is representative of the entire lot. The cartridges selected shall be thoroughly mixed before being divided into test samples.

Table II

Test	Number of Cartridges	Requirement Paragraph
Primer sensitivity 1/	600	3.4
Screen perforation 2/	200	3.5
Function and casualty 3/	400	3.6

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

1/ If the average critical height ($\bar{H}$) plus 5 standard deviations (5s) exceeds 15 inches or if the average critical height ($\bar{H}$) minus 2 standard deviations (2s) is less than 2½ inches, the lot of cartridges shall be rejected subject to the testing of a second sample of double the quantity of cartridges used in the initial test. Failure of the second sample to comply with the above criteria shall be cause for rejection of the lot of cartridges.

2/ Failure of nine or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If more than three but less than nine cartridges fail in the initial test, a second sample consisting of double the number of cartridges in the first sample may be tested. The lot shall be rejected if, in the combined first and second sample, nine or more cartridges fail to comply with the applicable requirement.

3/ The lot shall be rejected when function and casualty defects plus all other firing test defects exceed the acceptance number for the cumulative sample of Table III. If the number of defects found in the initial test exceeds the acceptance number for the first sample (Table III), but is equal to or less than the acceptance number for the cumulative sample (Table III), a second sample consisting of double the quantities specified under function and casualty test, shall be fired in the service weapons specified therefor. This procedure shall apply regardless of the weapon or weapons in which the firing defects occurred in the initial test. If the total number of defects in the combined first and second samples exceed the acceptance number for the cumulative sample, the lot shall be rejected. If, in testing the second sample, defects other than those for which the second sample is being tested should occur to the extent that they exceed the acceptance for the cumulative sample, the lot shall be rejected.

4.3.3.2 Firing defects.- Firing defects and acceptance numbers shall be as specified in Table III.

Table III

Defects	Acceptance Numbers (First Sample)	Acceptance Numbers Cumulative (First & Second Sample)
1. Primer		
Escape of gas through or around primer cup	30	80
Blown primer or primer falls out of pocket on retraction of bolt	0	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

Table III (Cont.)

Defects	Acceptance Numbers (First Sample)	Cumulative (First & Second Sample)
2. Case		
Splits, neck, shoulder or mouth	30	80
Splits, body	5	14
Splits, through head	1	3
Complete rupture 1/	1	3
Partial rupture	2	5
Detached metal 1/	0	1
3. Weapon stoppage 2/	11	29
4. Misfire	5	12

1/ Any particle of metal which becomes separated from the case between the mouth and the juncture of the shoulder and neck shall be classified as detached metal. A complete rupture at this location on the case shall be classed as detached metal.

2/ All stoppages attributable to the ammunition with the exception of misfire or complete rupture, observed in all tests shall be included.

4.3.4 Packaging, packing and marking inspection.- Inspection for packaging, packing and marking shall be in accordance with Publication ORD-SIP-S324 as applicable to the drawing (or as required by the contract) using the following AQL's:

	AQL Major Percent	AQL Minor Percent
a. Contents of Container		
Type of Pack		
Carton packs	1.0	2.5
Clip packs	1.0	2.5
Bandoleer packs	1.0	2.5
Metallic linked belt packs	1.0	2.5
b. Packed and Sealed Containers		
Gasket sealed container		
Physical characteristics, paint, markings	1.0	2.5
Gasket sealing	1.0	---
c. Overpacks and Overpack Contents		
Wirebound boxes (crates)	1.5	6.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

4.3.5 Inspection equipment.- The examination and tests shall be made using equipment listed on IEL-6006152, except as provided in 4.3.

4.4 Test methods and procedures.

4.4.1 Primer sensitivity.- After removal of the propellant from the cartridges, the method and procedure for conducting the test shall be in accordance with ORD-M608-PM, Vol. III. In testing a second sample, 100 cartridges shall be tested at each height.

4.4.2 Screen perforation.- The test shall be conducted in accordance with Publication ORD-M608-PM, Vol. III.

4.4.3 Function and casualty.- In these firings, the weapon shall be at room temperature at the beginning of the test. Two machine guns shall be used, and one-half the quantities specified in Table II shall be fired in each gun. The machine gun shall be fired in bursts of 100 cartridges. The gun shall be cooled between bursts. The test shall be conducted in accordance with Publication ORD-M608-PM, Vol. III.

4.4.4 Defect penalty.- In any firing test, except function and casualty, in which the occurrence of a firing defect prevents the obtaining of a reliable result for the characteristic being tested, an additional shot shall be fired. That particular test shall not be penalized, but the acceptance sample shall be penalized for such defects in accordance with Table III.

5. PREPARATION FOR DELIVERY

5.1 Packing.- Level A (Worldwide Shipment). The cartridge shall be packed in accordance with Drawing D7553502, D7553654, D7553659, D7553734, D7553891, D7553897 or D8595241 as stipulated in the contract.

5.1.1 Level C.- (Domestic Shipment). When specified by the procuring activity, the cartridges shall be packed in standard commercial containers so as to insure acceptance by common or other carrier for safe transportation, at the lowest rate to the point of delivery.

5.2 Marking and labeling.- Level A. Packing boxes shall be marked and labeled in accordance with the applicable drawings cited in 5.1.

5.2.1 Level C.- Containers shall be marked and labeled in accordance with Standard MIL-STD-129.

6. NOTES

6.1 Ordering data.- Invitations for bids and contracts or orders will specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

6.1.1 Title, number and date of this specification.

6.1.2 Type and level of packing.

6.1.3 Provision for the supply, maintenance and disposition of mandatory ballistic test equipment for acceptance inspection purposes.

6.1.4 Provision for the submission of acceptance inspection reports containing final inspection results for each lot of ammunition presented to the Government.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1305-A220

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.