MIL-C-1312E(MU)
15 March 1967
SUPERSEDING
MIL-C-1312D(MU)
26 December 1962

MILITARY SPECIFICATION
CARTRIDGE, CALIBER .30, BLANK, M1909

1. SCOPE

1.1 This specification covers a cartridge intended for saluting and training purposes.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-636	- Visual Inspection Standards for Small Arms Ammunition through Caliber .50
* MIL-STD-644	- Visual Inspection Standards and Inspection Procedures for Inspection of Packaging, Packing and Marking of Small Arms Ammunition

DRAWINGS

Munitions Command

C6006152	- Cartridge, Cal. .30, Blank, M1909
C7643674	- Classification of Cartridge Case Defects
D7553502	- Packing and Marking for Cartridges, Blank, Cal. .30, M1909; Linked; Box, Ammunition M19A1; Box, Wirebound
D7553654	- Packing and Marking for Cartridges, Blank, Cal. .30, M1909; Cartons (Auto. Pack); Box, Ammunition M2A1; Box, Wirebound

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

2.1 (Cont'd)

DRAWINGS (Cont'd)

D7553659	- Packing and Marking for Cartridges, Blank, M1909 and Rifle Grenade, Cal. .30, M3; Cartons (Hand Pack); Box, Ammunition M2A1; Box, Wirebound
D7553734	- Packing and Marking for Cartridges, Blank, Cal. .30, M1909; 8-Rd Clips; Bandoleers, Box, Ammunition M2A1; Box, Wirebound
D7553891	- Packing and Marking for Cartridges, Blank, Cal. .30, M1909; Containers, Box, Ammunition M2A1; Box, Wirebound
D7553897	- Packing and Marking for Cartridges, Blank, Cal. .30, M1909; 5-Rd Clips; Bandoleers; Box, Ammunition M2A1; Box, Wirebound
D8595241	- Packing and Marking for Cartridges, Blank, Cal. .30, M1909; 8-Rd Clips; Bandoleers, Box, Ammunition M19A1; Box, Wirebound
IEL-6006152	- Inspection Equipment List for Cartridge, Cal. .30, Blank, M1909

PUBLICATIONS

TECP 700-700, Vol. III - Manual of Test Methods for Small Arms Ammunition

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- The cartridge shall comply with the requirements specified on Drawing C6006152, referenced specifications and the following:

3.2 Case.- Use of cases not suitable for combat type cartridges (including cases obtained from pulldown of Grade 3 ammunition), fired cases, reworked cases or both, shall be permitted.

3.3 Screen perforation.- The cartridge, when fired, shall not cause perforations of 0.1 inch or greater in diameter in a paper screen placed 15 feet from the muzzle of the gun.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

3.4 Function and casualty.- The cartridge shall function without casualty.

3.5 Workmanship.- The cartridge shall comply with the applicable drawings and shall be free of folds, scaly metal, splits, corrosion, stains if etched and other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 for definition of quality assurance terms.

* 4.2 First article sample.

* 4.2.1 Initial production sample.- At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 1500 cartridges. The sample shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials, including packaging and packing shall be the same as used for regular production and shall be obtained from the same source of supply.

* 4.2.1.1 Examination and test.- After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a government laboratory or such other facility specified in the contract.

* 4.2.1.2 Initial production sample failure.- Failure of the sample to comply with requirements of the drawings and specifications shall result in sample disapproval.

* 4.3 Inspection provisions.

4.3.1 Lot.

* 4.3.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

* 4.3.1.2 Lot identification.- Each lot of ammunition shall be identified as to type, caliber, and model, as well as with a lot number and the manufacturer's identification as assigned by the procuring activity. Each lot shall be further identified by a federal stock number assigned by the procuring activity.

* 4.3.2 Examination.- Examination for major and minor defects shall be performed on a class basis in accordance with the classification of defects, Table I, using applicable sampling plans and acceptance criteria of MIL-STD-105. The acceptable quality level (AQL) for the major class shall be 0.65 percent and the AQL for the minor class shall be 2.50 percent. All non-conforming cartridges shall be rejected.

4.3.2.1 Classification of defects.- The classification of defects shall be as specified in Table I.

TABLE I

No.	Defect and Method of Inspection	Major	Minor
	Visual 1/		
2	Corroded or stained, if etched		X
7	Perforated case 2/	X	
12	Scaly metal		X
14	Fold		X
19	Defective head		X
32	No primer	X	
33	Cocked primer	X	
34	Inverted primer	X	
35	Loose primer	X	
39	Split case 2/	X	
40	Missing or loose wad	X	
41	Wad and joint between neck and wad not completely covered by lacquer		X
42	Opening between wad and case wall	X	
	Gaging		
43	Cartridge profile failure	X	
44	High primer	X	

1/ Refer to Caliber .30 section of MIL-STD-636 for visual classification of defects 2 through 35. In the event of conflict between Table I of this specification and MIL-STD-636 as to defect classification, the specification specified in Table I shall apply.

2/ To be counted as a minor defect if no propellant can be shaken from the case.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

* 4.3.3 Tests.- The tests listed in Table II shall be conducted in accordance with the methods and procedures specified in 4.4.

* 4.3.3.1 Test samples.- The quantities for the various tests shall be as specified in Table II. Only cartridges having met the visual, dimensional and weight requirements shall be used in the ballistic tests, and shall have been selected in such a manner that the sample is representative of the entire lot. The cartridges shall be thoroughly mixed before being divided into samples for the various tests.

* TABLE II

Test	Number of Cartridges	Requirement Paragraph
Screen perforation 1/	200	3.3
Function and casualty 2/	400	3.4

1/ Failure of nine or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If more than three but less than nine cartridges fail in the initial test, a second sample consisting of double the number of cartridges in the first sample may be tested. The lot shall be rejected if, in the combined first and second sample, nine or more cartridges fail to comply with the applicable requirement.

2/ The lot shall be rejected when function and casualty defects plus all other firing test defects exceed the acceptance number for the cumulative sample of Table III. If the number of defects found in the initial test exceeds the acceptance number for the first sample (Table III), but is equal to or less than the acceptance number for the cumulative sample (Table III), a second sample consisting of double the quantities specified under function and casualty test, shall be fired in the service weapons specified therefor. This procedure shall apply regardless of the weapon or weapons in which the firing defects occurred in the initial test. If the total number of defects in the combined first and second samples exceed the acceptance number for the cumulative sample, the lot shall be rejected. If, in testing the second sample, defects other than those for which the second sample is being tested should occur to the extent that they exceed the acceptance for the cumulative sample, the lot shall be rejected.

4.3.3.2 Firing defects.- Firing defects and acceptance numbers shall be as specified in Table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

4.3.3.2 (Cont'd)

TABLE III

Defects	Acceptance Numbers (First Sample)	Cumulative (First & Second Sample)
1. Primer		
Escape of gas through or around primer cup	30	80
Blown primer or primer falls out of pocket on retraction of bolt	0	1
2. Case		
Splits, neck, shoulder or mouth	30	80
Splits, body	5	14
Splits, through head	1	3
Complete rupture 1/	1	3
Partial rupture	2	5
Detached metal 1/	0	1
3. Weapon stoppage 2/	11	29
4. Misfire	5	12

1/ Any particle of metal which becomes separated from the case between the mouth and the juncture of the shoulder and neck shall be classified as detached metal. A complete rupture at this location on the case shall be classed as detached metal.

2/ All stoppages attributable to the ammunition with the exception of misfire or complete rupture, observed in all tests shall be included.

* 4.3.4 Packaging, packing and marking inspection.- During or immediately prior to the packaging operation, 100% examination of the cartridges shall be performed to ascertain that that the cartridge type conforms to the drawing. Occurrence of another model blank cartridge or a dummy cartridge shall be classed as a major defect. Occurrence of any type other than those listed shall be classed as a critical defect. All nonconforming cartridges shall be rejected. Inspection for packaging, packing and marking shall be in accordance with MIL-STD-644 as applicable to the drawing.

4.3.5 Inspection equipment.- The examination and tests shall be made using equipment listed on IEL-6006152, except as provided in 4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

4.4 Test methods and procedures.

* 4.4.1 Screen perforation.- The test shall be conducted in accordance with TECP 700-700, Vol. III.

* 4.4.2 Function and casualty.- In these firings, the weapon shall be at room temperature at the beginning of the test. Two machine guns shall be used, and one-half the quantities specified in Table II shall be fired in each gun. The machine gun shall be fired in bursts of 100 cartridges. The gun shall be cooled between bursts. The test shall be conducted in accordance with TECP 700-700, Vol. III.

4.4.3 Defect penalty.- In any firing test, except function and casualty, in which the occurrence of a firing defect prevents the obtaining of a reliable result for the characteristic being tested, an additional shot shall be fired. That particular test shall not be penalized, but the acceptance sample shall be penalized for such defects in accordance with Table III.

5. PREPARATION FOR DELIVERY

5.1 Packing.- Level A (Worldwide Shipment).- The cartridge shall be packed in accordance with Drawing D7553502, D7553654, D7553659, D7553734, D7553891, D7553897 or D8595241.

* 5.2 Marking and Labeling.- Packing boxes shall be marked and labeled in accordance with the applicable drawings cited in 5.1.

6. NOTES

6.1 Ordering data.- Invitations for bids and contracts or orders will specify the following:

6.1.1 Title, number and date of this specification.

6.1.2 Type and level of packing.

6.1.3 Provision for the supply, maintenance and disposition of mandatory ballistic test equipment for acceptance inspection purposes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.

6.1.4 Provision for the submission of acceptance inspection reports containing final inspection results for each lot of ammunition presented to the Government.

6.1.5 Requirement for contractor to provide and maintain an inspection system in accordance with MIL-I-45208, Inspection System Requirement.

* The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - MU

User Activity:

Air Force - 70

Preparing activity:

Army - MU

Project No. 1305-A375

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:09Z
Check the source to verify that this is the current version before use.