MILITARY SPECIFICATION

CARTRIDGE, CALIBER .50, TRACER, M17

This Admendment forms a part of Military Specification MIL-C-1318B, dated 3 April 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.5: Delete "cartridge" and substitute "cartridges".

3.6: Delete in its entirety and substitute:

"3.6 Accuracy: The average of the mean radii of all targets of the sample cartridges, fired at 600 yards, shall not exceed 20.0 inches or, when fired at 200 yards, shall not exceed 6.25 inches. The test shall be performed as specified in 4.5.5."

PAGE 5

4.3.1: Delete "Ctg Cal .50, Ball, M33" and substitute "Ctg, Cal .50 Tracer, M17"

4.3.1: Delete "5/machine or tool" and substitute "5/tool/machine" in five places.

PAGE 6

Table I: Add:

"8. Cyclic rate	0	2/

2/ If any burst fails to meet the cyclic rate requirement specified in 3.10, the first article sample shall be rejected."

FSC 1305

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:11Z
Check the source to verify that this is the current version before use.

PAGE 7

Table II, NO. OF SAMPLE UNITS: Delete "5" and substitute "5/tool/machine" in five places.

PAGE 9

4.4.1.2 a thru d: Delete in its entirety and substitute:

"a. Cartridge cases from one unchanged process and from one manufacturer.
b. Bullets from one unchanged process and from one manufacturer.
c. Primers from one lot interfix number and from one manufacturer
d. Propellant from no more than two lot numbers and from one manufacturer."

PAGE 18

Table III: Add:

"8. Cyclic rate	0	5/	Major"

PAGE 19

Table III, Notes: Add the following:

"5/ Failure of any burst to comply with the applicable requirement shall be cause for rejection of the lot subject to the testing of a second sample consisting of double the number of cartridges in the first sample. Failure of any burst in the second sample to comply with the applicable requirement shall be cause for rejection of the lot. The second sample, if required, shall only be fired in the weapon type in which the failure occurred."

PAGE 20

4.5.5: Add: " The size of the target shall be adjusted to suit the target range (200 or 600 yards)."

4.5.7: Add: "Prior to this test the cartridge shall be temperature conditioned in accordance with 4.5.12."

4.5.9: Change "revised" to "reused"

Custodian:
Army-AR
Air Force-70

Preparing activity:
Army-AR

(Project 1305-0B47

Review activities:
Army-AR
Air Force-70

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:11Z
Check the source to verify that this is the current version before use.